

Appendix D
Groundwater Resources Impact Assessment

REPORT

Groundwater Resources Impact Assessments, Coburn Mineral Sand Project

Prepared for


Gunson Resources Limited

Level 2, 33 Richardson Street
West Perth WA, 6872


May 2005

42905541/ 609-F6616.2

URS

Project Manager: 


for Robert Wallis
Associate Hydrogeologist

Project Director: 

Ian Brunner
Senior Principal Hydrogeologist

Author: 

Ian Brunner
Senior Principal Hydrogeologist



for Robert Wallis
Associate Hydrogeologist

URS Australia Pty Ltd
Level 3, The Hyatt Centre
20 Terrace Road
East Perth, WA 6004 Australia
Tel: 61 8 9221 1630
Fax: 61 8 9221 1639

Date: May 2005
Reference: 42905541/609-F6616.2
Status: Final

| | | |
|----------|--|------------|
| 1 | Introduction ----- | 1-1 |
| 1.1 | Project Description | 1-1 |
| 1.2 | Forecast Groundwater Resources Issues | 1-2 |
| 1.3 | Scope of Work | 1-3 |
| 2 | Physiography ----- | 2-1 |
| 2.1 | Local Climate | 2-1 |
| 2.2 | Geomorphology and Hydrology | 2-2 |
| 2.3 | Geology | 2-2 |
| 2.4 | Stratigraphy | 2-3 |
| 2.5 | Nilemah Embayment and Hamelin Pool | 2-7 |
| 3 | Site Investigations ----- | 3-1 |
| 3.1 | Superficial Formations Investigations | 3-1 |
| 3.1.1 | Superficial Formations Drilling Results | 3-2 |
| 3.1.2 | Superficial Formations and Toolonga Calcilitite Aquifer Testing | 3-4 |
| 3.1.3 | Shallow Groundwater Quality Analyses | 3-6 |
| 3.2 | Confined Aquifer Investigations | 3-7 |
| 3.2.1 | Confined Aquifer Drilling Results | 3-8 |
| 3.2.2 | Confined Aquifer Test Results | 3-9 |
| 3.2.3 | Confined Aquifer Groundwater Quality Analyses | 3-11 |
| 3.3 | Bore Census Findings | 3-12 |
| 4 | Hydrogeology ----- | 4-1 |
| 4.1 | Background | 4-1 |
| 4.2 | Superficial Formations Aquifer Systems | 4-2 |
| 4.2.1 | Aquifer Profiles | 4-2 |
| 4.2.2 | Groundwater Levels | 4-3 |
| 4.2.3 | Aquifer Parameters | 4-4 |
| 4.2.4 | Shallow Groundwater Quality | 4-5 |
| 4.2.5 | Superficial Formations Conceptual Hydrogeological Model | 4-6 |
| 4.3 | Confined Aquifer Systems | 4-8 |
| 4.3.1 | Aquifer Profiles | 4-8 |
| 4.3.2 | Potentiometric Levels | 4-10 |
| 4.3.3 | Aquifer Characteristics | 4-10 |
| 4.3.4 | Confined Aquifer Groundwater Quality | 4-11 |
| 4.3.5 | Confined Aquifer Conceptual Hydrogeological Model | 4-13 |
| 4.4 | Groundwater Management | 4-15 |
| 5 | Predicted Impacts of Mining on the Superficial Formations ----- | 5-1 |
| 5.1 | Superficial Formations Groundwater Flow Modelling | 5-1 |
| 5.1.1 | Model Code | 5-1 |
| 5.1.2 | Generic Model Domains | 5-1 |
| 5.1.3 | Boundary Conditions | 5-2 |
| 5.1.4 | Hydraulic Parameters | 5-2 |
| 5.2 | Predicted Sand Tailings Water Recovery | 5-2 |
| 5.2.1 | Controls on Sand Tailings Water Recovery | 5-3 |
| 5.2.2 | Characterisation of Sand Tailings Water Recovery | 5-5 |

| | | |
|-----------|---|-------------|
| 5.2.3 | Predicted Sand Tailings Water Recovery for Six Drains | 5-7 |
| 5.2.4 | Predicted Sand Tailings Water Recovery for Two Drains | 5-9 |
| 5.3 | Water Recovery from Slimes Tailings | 5-10 |
| 5.4 | Estimated Consumptive Groundwater Use | 5-10 |
| 5.5 | Predicted Extents of Water Table Mounding During Mining | 5-14 |
| 5.5.1 | Southern Pit Areas | 5-14 |
| 5.5.2 | Northern Pit Areas | 5-16 |
| 5.6 | Predicted Fates of Tailings Waters | 5-18 |
| 5.6.1 | Southern Project Areas | 5-19 |
| | Northern Project Areas | 5-20 |
| 5.7 | Predicted Pit Dewatering Requirements | 5-21 |
| 5.8 | Mine Water Salinity Issues | 5-22 |
| 5.9 | Summary of Predicted Impacts on Flora and Fauna | 5-23 |
| 6 | Predicted Impacts of Large-Scale Process Water Supply Abstractions ----- | 6-1 |
| 6.1 | Confined Aquifer Groundwater Flow Modelling | 6-1 |
| 6.1.1 | Model Code | 6-1 |
| 6.1.2 | Model Domain and Form | 6-1 |
| 6.1.3 | Boundary Conditions | 6-2 |
| 6.1.4 | Hydraulic Parameters | 6-3 |
| 6.1.5 | Model Calibration | 6-4 |
| 6.2 | Simulated Large-Scale Abstraction | 6-4 |
| 6.3 | Extent of Predicted Drawdowns | 6-7 |
| 6.3.1 | Abstraction of 11 GL/annum | 6-7 |
| 6.3.2 | Abstraction of 15 GL/annum | 6-8 |
| 6.4 | Predicted Impacts on Private Bores | 6-9 |
| 6.5 | Aquifer Recovery After Cessation of Abstraction | 6-13 |
| 6.6 | Sustainability of Large-Scale Abstractions | 6-14 |
| 6.7 | Summary of Predicted Environmental Impacts | 6-15 |
| 7 | Borefield Management and Monitoring----- | 7-1 |
| 7.1 | Operating Strategy | 7-2 |
| 7.1.1 | Monitoring and Management of Groundwater Resources | 7-2 |
| 7.1.2 | Local Superficial Formations Multipiezometers | 7-4 |
| 7.1.3 | Regional Piezometers and Private Bores | 7-6 |
| 7.1.4 | Production Bores and In-Pit Sump Pumping | 7-7 |
| 7.1.5 | Water Resources Monitoring Programme | 7-8 |
| 8 | Conclusions ----- | 8-1 |
| 9 | Recommendations----- | 9-1 |
| 10 | References ----- | 10-1 |
| 11 | Limitations ----- | 11-1 |

List of Tables, Figures & Appendices

Tables

| | | |
|----------|---|------|
| Table 1 | Climatic Averages for Hamelin Station..... | 2-1 |
| Table 2 | Summary of Local Stratigraphy | 2-4 |
| Table 3 | Summary of Superficial Formations Site Investigations | 3-3 |
| Table 4 | Results of Aquifer Tests in SMB2..... | 3-4 |
| Table 5 | Results of Aquifer Tests in SMB3 and STB3..... | 3-5 |
| Table 6 | Results of Aquifer Tests in SMB4..... | 3-6 |
| Table 7 | Summary of Confined Aquifer Site Investigations | 3-8 |
| Table 8 | Stratigraphy In DTB1 | 3-9 |
| Table 9 | Results of Aquifer Tests in DTB1 and DMB1 | 3-10 |
| Table 10 | Typical Particle Size Distribution of the Amy Zone | 4-2 |
| Table 11 | Interpreted Superficial Formations and Shallow Toolonga Calcilutite Aquifer Parameters | 4-4 |
| Table 12 | Summary of Shallow Groundwater Quality | 4-5 |
| Table 13 | Confined Aquifers Hydraulic Parameters..... | 4-11 |
| Table 14 | Summary of Interpreted Regional Groundwater Salinities | 4-11 |
| Table 15 | Summary of Confined Aquifers Groundwater Quality | 4-12 |
| Table 16 | Simulated Peron Sandstone Hydraulic Parameters..... | 5-2 |
| Table 17 | Sand Tailings Water Recovery – Constraints and Variables..... | 5-2 |
| Table 18 | Simulated Sand-Stacker Operating Settings..... | 5-5 |
| Table 19 | Predicted Rates of Sand Tailings Water Recovery for Six Drains | 5-8 |
| Table 20 | Predicted Rates of Sand Tailings Water Recovery for Two Drains | 5-9 |
| Table 21 | Estimates of Annual Consumptive Water Use Based on a 68% Tailings Water Recovery Rate | 5-12 |
| Table 22 | Estimates of Annual Consumptive Water Use Based on a 43% Tailings Water Recovery Rate | 5-13 |
| Table 23 | Estimated Mound Heights at the Shark Bay World Heritage Property Boundary ... | 5-15 |
| Table 24 | Northern Pit Model Form and Hydraulic Parameters..... | 5-16 |
| Table 25 | Forecast Salinity of Process Water..... | 5-22 |
| Table 26 | Layered Form of the Confined Aquifer Model..... | 6-2 |
| Table 27 | Confined Aquifer Model Hydraulic Parameters..... | 6-3 |
| Table 25 | Design Production Bore Locations..... | 6-5 |
| Table 29 | Simulated Schedule for Abstraction of 11 GL/annum | 6-6 |

List of Tables, Figures & Appendices

| | | |
|----------|---|------|
| Table 30 | Simulated Schedule for Abstraction of 15 GL/annum | 6-7 |
| Table 31 | Predicted Drawdown Impacts of 11 GL/annum Abstraction on Private Bores..... | 6-10 |
| Table 32 | Objectives of Monitoring Programmes | 7-3 |
| Table 33 | Locations of Additional Superficial Formations Multipiezometers | 7-5 |
| Table 34 | Locations of Existing Regional Confined Aquifer Monitoring Bores..... | 7-6 |
| Table 35 | Locations of Additional Regional Confined Aquifer and Confining Layer Multipiezometers | 7-7 |
| Table 36 | Monitoring Programme | 7-8 |

Figures

| | |
|-----------|---|
| Figure 1 | Regional Setting |
| Figure 2 | Coburn Mineral Sand Project Area |
| Figure 3 | Proximity of Nilemah Embayment and Hamelin Pool |
| Figure 4 | Planned Mine Layout |
| Figure 5 | Proposed Operational Layout |
| Figure 6 | Meteorological Data |
| Figure 7 | Local Geological Cross-Section of the Superficial Formations |
| Figure 8 | Gascoyne Platform Stratigraphic Profile (a) West to East (b) South to North |
| Figure 9 | Locations of Site Investigation Bores |
| Figure 10 | Completion Details SMB2 |
| Figure 11 | Completion Details SMB3 |
| Figure 12 | Completion Details SMB4 |
| Figure 13 | Completion Details STB3 |
| Figure 14 | SMB2d Pumping Test Results |
| Figure 15 | SMB2s and SMB2d Falling-Head Tests |
| Figure 16 | STB3 Pumping Tests, Drawdown in STB3 and SMB3d |

List of Tables, Figures & Appendices

- Figure 17 SMB3s and SMB3d Falling-Head Tests
- Figure 18 SMB4d Pumping Test Results
- Figure 19 SMB4s and SMB4d Falling-Head Tests
- Figure 20 Completion Details DTB1
- Figure 21 Completion Details DMB1
- Figure 22 Geophysical Log Correlations, DTB1, DMB1 and Coburn1
- Figure 23 DTB1 Step and Constant-Rate Pumping Test
- (a) Drawdown in DTB1
 - (b) Drawdown in DMB1b and DMB1k
- Figure 24 DTB1 Recovery Test
- (a) Residual Drawdown in DTB1
 - (b) Residual Drawdown in DMB1b and DMB1k
- Figure 25 Regional Private Bore Locality Map
- Figure 26 Interpreted Basal Elevations of the Superficial Formations
- Figure 27 Baseline Superficial Formations and Toolonga Calcilutite Water Table Elevations
- Figure 28 Saturated Areas of Superficial Formation In Context with Regional Flow
- Figure 29 Water Table Elevations In Cross-Section
- Figure 30 Piper Diagram of Groundwater Chemistry
- Figure 31 Superficial Formations Conceptual Hydrogeological Model
- Figure 32 Interpreted Groundwater Levels Windalia Sand Member
- Figure 33 Interpreted Groundwater Levels Birdrong Sandstone
- Figure 34 Confined Aquifers Conceptual Hydrogeological Model
- Figure 35 Generic Model Domains for Sand-Stacker Advances
- (a) 5m/day, 10m/day and 15m/day
 - (b) 35m/day, 55m/day and 80m/day
- Figure 36 Typical Mine Profile Within the Superficial Formations

List of Tables, Figures & Appendices

- Figure 37 Development of the Conceptual Sand Tailings Water Recovery Systems
- (a) Initial Plan
 - (b) Second Plan
- Figure 38 Final Conceptual Sand Tailings Water Recovery Plan
- (a) Start of Pit
 - (b) Middle of Sand-Stacker Traverse
 - (c) Sand-Stacker Changeover
 - (d) End of Pit
- Figure 39 Simulated Mounding: 5 m/day Sand-Stacker Advance and No Sand Beneath Pit Floor
- Figure 40 Recovery Rate Calculations: 5 m/day Sand-Stacker Advance and 2 m Sand Beneath Pit Floor
- Figure 41 Simulated Upper-Bound Tailings Water Recovery Rates
- (a) 5 to 15 m/day Advance Rate With All Active Drains
 - (b) 35 to 80 m/day Advance Rate With All Active Drains
- Figure 42 Alternative Conceptual Sand Tailings Water Recovery Plan – 2 Drains Only
- Figure 43 Simulated Lower-Bound Tailings Water Recovery Rates
- (a) 5 to 15 m/day Advance Rate, With 2 Active Drains
 - (b) 35 to 80 m/day Advance Rate, With 2 Active Drains
- Figure 44 Simulated Lower-Bound Mounding With 0, 2, 5, 10m Sand Beneath Pit Floor
- (a) at 5 m/day Advance Rate
 - (b) at 10 m/ day Advance Rate
 - (c) at 15 m/ day Advance Rate
 - (d) at 35 m/ day Advance Rate
 - (e) at 55 m/ day Advance Rate
 - (f) at 80 m/ day Advance Rate
- Figure 45 Simulated Upper-Bound Mounding With 0, 2, 5 and 10 m Sand Beneath Pit Floor
- (a) at 5 m/ day Advance Rate

List of Tables, Figures & Appendices

- (b) at 10 m/ day Advance Rate
 - (c) at 15 m/ day Advance Rate
 - (d) at 35 m/ day Advance Rate
 - (e) at 55 m/ day Advance Rate
 - (f) at 80 m/ day Advance Rate
- Figure 46 Areas of Potential Risk Due To Mounding Encroachment Within Vegetation Root Zones
- Figure 47 Northern Pit Model Domain
- Figure 48 Form of the Northern Pit Model
- (a) Plan View of Sub-Crop Geology
 - (b) North-South Section View
 - (c) East-West Section View Through the Mine
 - (d) East-West Section View Through Hamelin Pool
- Figure 49 Simulated Water Table Environments
- (a) Plan View
 - (b) North-South Section View
 - (c) Depths To Water Table
 - (d) Saturated Thickness of the Superficial Formations
- Figure 50 Predicted Northern Pit Water Table Mounding
- (a) After 374 Days of Mining
 - (b) After 748 Days of Mining
 - (c) After 1105 Days of Mining
- Figure 51 Simulated Southern Project Area Transient Mound Distributions
- (a) 5 to 20 Years After Mining
 - (b) 25 to 50 Years After Mining
- Figure 52 Predicted Mounded Water Table Profiles Beneath The Shark Bay World Heritage Property
- (a) Data Used To Define

List of Tables, Figures & Appendices

- (b) Section View Of
- Figure 53 Plan Views of Predicted Northern Pit Residual Water Table Mounding
 - (a) 1 Year After Mining
 - (b) 5 Years After Mining
 - (c) 10 Years After Mining
 - (d) 15 Years After Mining
 - (e) 20 Years After Mining
 - (f) 30 Years After Mining
 - (g) 40 Years After Mining
 - (h) 50 Years After Mining
- Figure 54 Section Views of Predicted Northern Pit Residual Water Table Mounding
 - (a) 1 Year After Mining
 - (b) 50 Years After Mining
 - (c) Transient Groundwater Flow Fluxes
- Figure 55 Confined Aquifer Model Domain
- Figure 56 Form of the Confined Aquifer Model
- Figure 57 Confined Aquifer Model Boundary Conditions
- Figure 58 Simulated Steady-State Potentiometric Levels
 - (a) Windalia Radiolarite
 - (b) Windalia Sand Member
 - (c) Birdrong Sandstone
 - (d) Kopke Sandstone
- Figure 59 Simulated Confined Aquifer South to North Flow Paths
 - (a) Potentiometric Levels
 - (b) Flow Vectors
- Figure 60 Simulated Confined Aquifer East to West Flow Paths

List of Tables, Figures & Appendices

- (a) Potentiometric Levels
 - (b) Flow Vectors
- Figure 61 Conceptual Layout of Process Water Supply Borefield
- Figure 62 Predicted Regional Drawdowns In Windalia Radiolarite
- (a) After One Year of 11 GL/Annum Abstraction
 - (b) After Two Years of 11 GL/Annum Abstraction
 - (c) After Five Years of 11 GL/Annum Abstraction
 - (d) After Ten Years of 11 GL/Annum Abstraction
 - (e) After Twenty Years of 11 GL/Annum Abstraction
- Figure 63 Predicted Regional Drawdowns In Windalia Sand Member
- (a) After One Year of 11 GL/Annum Abstraction
 - (b) After Two Years of 11 GL/Annum Abstraction
 - (c) After Five Years of 11 GL/Annum Abstraction
 - (d) After Ten Years of 11 GL/Annum Abstraction
 - (e) After Twenty Years of 11 GL/Annum Abstraction
- Figure 64 Predicted Regional Drawdowns In Birdrong Sandstone
- (a) After One Year of 11 GL/Annum Abstraction
 - (b) After Two Years of 11 GL/Annum Abstraction
 - (c) After Five Years of 11 GL/Annum Abstraction
 - (d) After Ten Years of 11 GL/Annum Abstraction
 - (e) After Twenty Years of 11 GL/Annum Abstraction
- Figure 65 Predicted Regional Drawdowns In Kopke Sandstone
- (a) After One Year of 11 GL/Annum Abstraction
 - (b) After Two Years of 11 GL/Annum Abstraction
 - (c) After Five Years of 11 GL/Annum Abstraction
 - (d) After Ten Years of 11 GL/Annum Abstraction

List of Tables, Figures & Appendices

- (e) Twenty Years of 11 GL/Annum Abstraction
- Figure 66 Predicted Regional Drawdowns After 20 Years of 11 GL/Annum Abstraction
 - (a) Alinga Formation
 - (b) Toolonga Calcilutite
 - (c) Superficial Formations
- Figure 67 Predicted Regional Drawdowns In Windalia Radiolarite
 - (a) After One Year of 15 GL/Annum Abstraction
 - (b) After Two Years of 15 GL/Annum Abstraction
 - (c) After Five Years of 15 GL/Annum Abstraction
 - (d) After Ten Years of 15 GL/Annum Abstraction
 - (e) After 20 Years of 15 GL/Annum Abstraction
- Figure 68 Predicted Regional Drawdowns In Windalia Sand Member
 - (a) After One Year of 15 GL/Annum Abstraction
 - (b) After Two Years of 15 GL/Annum Abstraction
 - (c) After Five Years of 15 GL/Annum Abstraction
 - (d) After Ten Years of 15 GL/Annum Abstraction
 - (e) After 20 Years of 15 GL/Annum Abstraction
- Figure 69 Predicted Regional Drawdowns In Birdrong Sandstone
 - (a) After One Year of 15 GL/Annum Abstraction
 - (b) After Two Years of 15 GL/Annum Abstraction
 - (c) After Five Years of 15 GL/Annum Abstraction
 - (d) After Ten Years of 15 GL/Annum Abstraction
 - (e) After 20 Years of 15 GL/Annum Abstraction
- Figure 70 Predicted Regional Drawdown In Kopke Sandstone
 - (a) After One Year of 15 GL/Annum Abstraction
 - (b) After Two Years of 15 GL/Annum Abstraction

List of Tables, Figures & Appendices

(c) After Five Years of 15 GL/Annum Abstraction

(d) After Ten Years of 15 GL/Annum Abstraction

(e) After 20 Years of 15 GL/Annum Abstraction

Figure 71 Predicted Drawdown Impacts of 11 GL/Annum Abstraction

(a) Nanga Resort, Carbla Station and Sweeny Mia 2001 Bores

(b) Northern Hamelin Station, Telegraph Station and Overlander Roadhouse Bores

(c) Southern Hamelin and Coburn Station Bores

(d) Eastern Hamelin, Meadow and Nerren Nerren Stations and Billabong Roadhouse Bores

Figure 72 Predicted Drawdown Impacts of 15 GL/Annum Abstraction

(a) Nanga Resort, Carbla Station and Sweeny Mia 2001 Bores

(b) Northern Hamelin Station, Telegraph Station and Overlander Roadhouse Bores

(c) Southern Hamelin and Coburn Station Bores

(e) Eastern Hamelin, Meadow and Nerren Nerren Stations and Billabong Roadhouse Bores

Figure 73 Predicted Residual Drawdowns In Windalia Radiolarite

(a) One Year After Abstraction of 11 GL/Annum

(b) Two Years After Abstraction of 11 GL/Annum

(c) Five Years After Abstraction of 11 GL/Annum

(d) Ten Years After Abstraction of 11 GL/Annum

Figure 74 Predicted Residual Drawdowns In Windalia Sand Member

(a) One Year After Abstraction of 11 GL/Annum

(b) Two Years After Abstraction of 11 GL/Annum

(c) Five Years After Abstraction of 11 GL/Annum

(d) Ten Years After Abstraction of 11 GL/Annum

Figure 75 Predicted Residual Drawdowns in Birdrong Sandstone

(a) One Year After Abstraction of 11 GL/Annum

List of Tables, Figures & Appendices

- (b) Two Years After Abstraction of 11 GL/Annum
 - (c) Five Years After Abstraction of 11 GL/Annum
 - (d) Ten Years After Abstraction of 11 GL/Annum
- Figure 76 Predicted Residual Drawdowns in Kopke Sandstone
- (a) One Year After Abstraction of 11 GL/Annum
 - (b) Two Years After Abstraction of 11 GL/Annum
 - (c) Five Years After Abstraction of 11 GL/Annum
 - (d) Ten Years After Abstraction of 11 GL/Annum
- Figure 77 Predicted Transient Residual Drawdowns After Abstraction of 11 GL/Annum
- (a) Nanga Resort, Carbla Station and Sweeny Mia 2001 Bores
 - (b) Northern Hamelin Station, Telegraph Station and Overlander Roadhouse Bores
 - (c) Southern Hamelin and Coburn Station Bores
 - (d) Eastern Hamelin, Meadow and Nerren Nerren Stations and Billabong Roadhouse Bores
- Figure 78 Locations of Additional Superficial Formations Multipiezometers
- (a) Southern Project Area
 - (b) Northern Mine and Nilemah Embayment Areas
- Figure 79 Locations of Confined Aquifer Multipiezometers

Appendices

- Appendix A Copy of Licence to Construct or Alter Well Nos. CAW155919(1) & CAW155924(1)
- Appendix B Summary of Aquifer Testing and Calculated Parameters
- Appendix C Laboratory Certificates and Chemical Analyses of Regional (Private) Bores
- Appendix D Results of Bore Census
- Appendix E Mine Water Balance Detail

Gunson Resources Limited proposes to develop the Coburn Mineral Sand Project; a deposit rich in zircon, located near Shark Bay (Figure 1). It is proposed to mine the mineralised Amy Zone over a 20-year period, commencing at the southern end of the deposit on Coburn Station, and finishing about 35 kilometres to the north on Hamelin Station (Figure 2). The eastern limits of the Shark Bay World Heritage Property occur adjacent to the western and northern project areas. Nilemah Embayment and Hamelin Pool, with associated algal mats and stromatolites, occur about 4 and 12 km north of the project area (Figure 3). Mining is proposed to take place using a conventional dry strip mining method, with the primary concentrators located alongside the pits. Both mining and the concentrators will progressively moved northwards at rates dependent on the volume of ore to be processed. The Heavy Mineral Concentrate (HMC) will be transported to Geraldton.

The Amy Zone consists of mostly dry sand (i.e. above the water table), being only partly saturated in localised areas in the north. The Amy Zone is a low-grade mineral sand resource lying within re-worked deposits of the Peron Sandstone, overlying the Toolonga Calcilutite. The mineral sands would be separated from the host quartz sands using banks of spiral concentrators, achieving HMC containing more than 90% heavy minerals.

Depending on the efficiency of the water recovery system the concentrators will use process water at a rate of between 0.4 and 0.6 kilolitre (kL) per tonne of ore. The concentrators are planned to derive make-up supplies from regional confined aquifer systems formed by the Birdrong Sandstone and Kopke Sandstone beneath the project area. The groundwater would be abstracted to replace process water losses incurred through wetting of the mined ore, tailings seepage and evaporation. The Birdrong Sandstone and Kopke Sandstone are regional aquifers found across most of the Gascoyne Platform. The Birdrong Formation is commonly used for pastoral and industrial water supplies in the central Gascoyne Platform whereas the Kopke Formation is more commonly utilised in northern Gascoyne Platform, due to its larger thickness and better groundwater quality. In the Shark Bay area, the Windalia Sand Member is preferentially used by pastoralists and other bore-owners because it occurs at comparatively shallow depths.

This report presents an assessment of local and regional groundwater resources, pit dewatering and tailings water management issues relating to the mining development of the Amy Zone. The report is intended to support environmental impact assessments in the Public Environmental Review for the Coburn Mineral Sand Project and applications for licensing of the groundwater abstractions.

1.1 Project Description

The mineral sand ore is to be mined by bucket-wheel excavators and processed by water-based gravity separation methods. Mining is planned to be continuous maintaining an overall 85% availability. The proposed pits follow defined ore strands within the superficial formations and will generally be linear features aligned north to south (Figure 4). The proposed operation is shown on Figure 5 and will follow a continuous cycle comprising:

-
- Existing vegetation and topsoil removal and immediate relocation to rehabilitated areas behind the active pit.
 - Sub-soil removal and stockpile beside the mine path.
 - Overburden removal and placement on the pit floor.
 - Ore excavation and screening on the pit floor,
 - Mixing the screened ore with water and pumping the slurry to a concentrator. The concentrator may be up to 1 km from the active pit.
 - Backfilling the pit with the tailings being deposited on top of the overburden stockpiles. The sand tailings slurry is partly dewatered using two sand-stacker units which are relocated as required to build the final land profiles.
 - Fine clay will be settled in trenches constructed along the eastern side of the pit.
 - Tailings contoured and covered with sub-soil from stockpiles.
 - Placement of topsoil and vegetation over sub-soil.
 - Rehabilitation of the disturbed area.

It is proposed that the mining infrastructure be progressively relocated as mining advances at one to two kilometres per annum. From year three onwards, the entire mining system would be duplicated, providing a total processing rate of 4,600 tph to the end of the 20-year mine life.

1.2 Forecast Groundwater Resources Issues

The known groundwater resources issues (URS, 2004) linked to the proposed mining developments include:

- Recovery and reuse of process water from the tailings and slimes settling areas thereby, limiting consumptive groundwater use.
- Mounding of the water table in the superficial formations to within the root zones of vegetation.
- The dispersion within the superficial formations of process waters not recovered, given that the water table aquifer would discharge in part into Nilemah Embayment and Hamelin Pool.
- Salinisation of the process water supplies due to recycling and cumulative effects of evaporative losses.
- Drawdown impacts within the superficial formations should pit dewatering be required in the northern project area.

-
- Drawdown impacts within the regional confined aquifer systems due to abstractions from the Birdrong Sandstone and Kopke Sandstone for process water supplies.
 - Potentials for propagation of drawdown impacts from the regional confined aquifer systems vertically upwards into the water table aquifer.
 - Removal from storage of groundwater in the regional confined aquifer systems due to forecast abstractions exceeding the estimated recharge and throughflow beneath the project area.

The proximity of the Shark Bay World Heritage Property heightens the potential risks linked to these issues. This aspect lends itself to precautionary and conservative approaches to project development and associated protocols for the mitigation of risk.

1.3 Scope of Work

Three separate site investigation programmes have been completed to investigate the forecast groundwater resources issues linked to the proposed mining developments. These programmes comprised:

- A superficial formations drilling programme that comprised construction of multipiezometers and test production bore at three separate sites, with associated groundwater sampling and hydraulic tests.
- A confined aquifer drilling programme, including the construction and test pumping of a production bore screened in the Birdrong Sandstone and Kopke Sandstone and construction of one multipiezometer to provide hydrogeological data for the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone.
- A bore census that comprised the collection of historical data on existing bore locations and construction and groundwater levels and quality. The historical data were obtained from published government records and through discussions with the bore owners. The groundwater level and quality parameters were measured during site visits.

The specific parameters determined during the site investigations include:

- Determining the baseline hydrogeological characteristics of the water table aquifer in the superficial formations and underlying confined aquifer systems formed by the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone.
- Determining the likely yields from dewatering the superficial formations and impacts of mining on the water table environment.
- Determining the yields from the Birdrong Sandstone and Kopke Sandstone, and likely impacts of process water abstractions on other groundwater users in a local and regional context.

-
- Evaluation of the hydraulic properties of the superficial formations, Birdrong Sandstone and Kopke Sandstone.

Assessments of the various impacts of mine development on the local and regional groundwater environment have been undertaken using a series of predictive groundwater flow models. The models have been applied to predict transient water table mounding of, or drawdowns in each aquifer during the life of the mine. The results were used to determine the impacts of the mining operations on the local environment and existing groundwater users. Subsequently, the model results were used to develop strategies for mitigation of adverse impacts, groundwater resources conservation and environmental management.

2.1 Local Climate

The climate of the project area is characterised by mild winters and hot, dry summers. The average annual rainfall is about 210 mm with most rain falling between May and August. Rain can, however, fall during the other months, with a highly variable intensity. Heavier, more intense rainfall events outside the winter months are commonly associated with the passage of cyclonic and more localised thunderstorm activity.

Evaporation in the project area typically exceeds the monthly rainfall totals by factors between 2 and 160. The lowest evaporation and highest rainfall occur in the winter months, with the reverse to a greater degree in the summer months. The project area typically has average wind speeds of about 12 and 20 km/hr in the winter and summer months respectively. The wind conditions have a strong bearing on the evaporation rates.

The local climate averages for the project area are summarised in Table 1 and presented graphically on Figure 6.

**Table 1
Climatic Averages for Hamelin Station**

| Month | Mean Monthly Rainfall (mm) | Mean Daily Maximum Temperature (deg C) | Mean Daily Minimum Temperature (deg C) | Mean Daily Evaporation (mm) | Mean Monthly Evaporation (mm) | Mean Wind Speed (km/h) | Mean Relative Humidity (%) |
|--------|----------------------------|--|--|-----------------------------|-------------------------------|------------------------|----------------------------|
| Jan | 7.6 | 36.9 | 20.5 | 13.4 | 415.4 | 18.1 | 39.5 |
| Feb | 13.1 | 36.7 | 21.2 | 13.9 | 392.7 | 17.8 | 42.5 |
| Mar | 15.7 | 34.9 | 20.1 | 11.6 | 359.6 | 16.5 | 43.0 |
| Apr | 13.7 | 30.3 | 17.0 | 7.1 | 213.0 | 14.7 | 48.0 |
| May | 33.1 | 25.2 | 13.2 | 5.2 | 161.2 | 13.4 | 54.0 |
| Jun | 47.7 | 21.5 | 10.6 | 3.4 | 102.0 | 12.2 | 63.5 |
| Jul | 40.2 | 20.7 | 9.2 | 3.4 | 105.4 | 13.3 | 62.5 |
| Aug | 21.5 | 22.2 | 9.4 | 4.7 | 145.7 | 14.4 | 55.0 |
| Sep | 8.1 | 25.4 | 11.1 | 6.5 | 195.0 | 17.5 | 46.5 |
| Oct | 5.2 | 28.2 | 13.0 | 10.0 | 310.0 | 19.2 | 42.0 |
| Nov | 3.7 | 31.8 | 15.8 | 11.0 | 330.0 | 19.6 | 39.0 |
| Dec | 2.4 | 34.8 | 18.3 | 12.5 | 387.5 | 18.5 | 39.0 |
| Annual | 211.9 | - | - | - | 3,117.5 | - | - |
| Daily | - | 29.1 | 15.0 | 8.7 | - | 16.3 | 47.5 |

Note: Hamelin Station – Bureau of Meteorology Station No. 006025

2.2 Geomorphology and Hydrology

The project area lies mainly within the Victoria Sand Plain District. It fringes the Carbla Plateau at the northernmost end (Payne *et al*, 1987). The Victoria Sand Plain District is characterised by undulating sand plains with isolated low coastal dunes. The Carbla Plateau typically has a well developed duricrust of calcrete, ferricrete and silcrete that generally overlies the areas of Toolonga Calcilutite subcrop.

Most of the project area is traversed by sand dunes. The dunal system exhibits an apparent interference form, with cross-patterned dune alignments that have produced many isolated swales (Figure 2). The dune flanks and swales are typically covered with shrub-heath and tree-heath, dominated by proteaceous and myrtaceous species in the south and scattered or clumped mallee and tree-form eucalyptus over waynu-dominated tall shrubland in the north (Payne *et al*, 1987).

There are few drainage features within the Victoria Sand Plains District, due to the extent and characteristics of the dunal systems. Small, localised drainages occasionally occur in some of the swales where the soils are slightly silty and constrain infiltration.

In the northern project area the superficial formations thin and become intermittent between outcrops of duricrust. The Amy Zone does not extend onto the Carbla Plateau as the mineralisation is confined to the superficial formations. Surface drainages become more apparent as the topography becomes increasingly dominated by the duricrust to the northeast and east. Overall, these drainages trend northwards towards Hamelin Pool (Figure 2).

North of the project area, the foreshore and nearshore areas of Hamelin Pool and the Nilemah Embayment are characterised by small dunal ridges of shell coquina and shell sand, with salina occupying intradunal swales and depressions (Figure 3). These areas appear to have internal drainage, with the low elevation salinas forming surface water and groundwater receptors.

2.3 Geology

The project area is situated within the Gascoyne Platform of the southern Carnarvon Basin. The Carnarvon Basin is an extensive sedimentary structure that extends along and off the coast of Western Australia and comprises numerous sub-basins, shelves and platforms. On a local scale, the geology of the superficial formations has been specifically investigated within the Nilemah Embayment and foreshore areas of Hamelin Pool during a geo-biology study (BMR, 1990) on the stromatolites and algal mats. On a region scale, the basin and sub-basin boundaries have been defined by fault and basement ridge structures. The geology of the Carnarvon Basin is also defined at regional scale by seismic and drilling investigations for petroleum exploration and limited exposure mapping. Consequently, the available information on many of the Carnarvon Basin sedimentary units has been derived from lithological and palynological logging of the petroleum exploration drilling. A comprehensive list of references to these studies is given in Iasky *et al*, (2003).

The regional geology of the southern Carnarvon Basin and specifically the Gascoyne Platform has been interpreted several times during the past 30 to 40 years. The most recent interpretation is published by Iasky *et al* (2003). Stratigraphic units in the southern Carnarvon Basin sometimes differ slightly to the northern basin due to structural controls and lithological variations resulting from different depositional settings. The stratigraphic nomenclature within and between the sub-basins has changed over the past few decades as more data have become available. For example, the Gearle Siltstone and Alinga Formation are used to represent the same stratigraphic unit in the northern and southern Carnarvon Basin.

Within the southern Carnarvon Basin, some of the geological units have lateral equivalents that probably represent facies changes. In the Gascoyne Platform, the Windalia Radiolarite and Windalia Sand Member are defined as different formations but are interpreted to represent a facies change from distal chemical deposits to proximal clastic deposits.

A local geology cross-section of the superficial formations in the vicinity of Nilemah Embayment and Hamelin Pool is shown on Figure 7. This section is predominantly based on the collation of the findings of the geo-biology study (BMR, 1990) and resource drilling to define the Amy Zone. The section shows a marked transition in the superficial formations geology profile from the dunal domains of Peron Sandstone to the marine setting of Hamelin Pool.

Regional geology cross-sections from west to east and south to north are shown on Figure 8 (a and b). The regional sections are simplified and do not show small-scale faulting or folding, the evidence of which is shown by detailed offshore seismic mapping (Iasky *et al*, 2003). The Ordovician to Devonian successions generally dip to the west, northwest and possibly north-northwest, with steeper dips near the southern and eastern margins of the Gascoyne Platform. The Cretaceous successions generally dip westwards, over an erosional unconformity that removed most of the formations above the Kopke Sandstone. This unconformity is widespread within the Carnarvon Basin and is covered by a transgressional sedimentary sequence of sandstones and shales.

2.4 Stratigraphy

The Carnarvon Basin extends between Kalbarri in the south and Dampier in the north and is underlain by Precambrian crystalline basement. This basement also forms a fault-bounded margin to the Gascoyne Platform, with the Hardabut Fault against the Northampton Complex and the Ajana Fault against the Ajana Ridge. The Ajana Ridge separates the Gascoyne Platform from the Coolcalalaya Sub-Basin to the east. However, the stratigraphic successions of the Gascoyne Platform and Coolcalalaya Sub-Basin may be hydraulically connected by a thick sequence of Tumblagooda Sandstone. The Coolcalalaya Sub-Basin is interpreted to contain elements of both the Carnarvon Basin (including the basal Tumblagooda Sandstone and possibly Kopke Sandstone) and various northern Perth Basin successions of Permian age (Mory *et al*, 1998).

The interpreted stratigraphic succession in the Gascoyne Platform region of the southern Carnarvon Basin is shown in Table 2.

Table 2
Summary of Local Stratigraphy

| Age | | Stratigraphy | |
|---------------------------|------------------------|--|-------------------|
| Quaternary & Tertiary | | Superficial Formations including marine clay, shell coquina, salina, Peron Sandstone, Bibra Limestone and Dampier Limestone. | |
| <i>Unconformity</i> | | | |
| Cretaceous | Late | Toolonga Calcilutite | |
| | Early | Alinga Formation | Winning Group |
| | | Winalia Radiolarite | |
| | | Winalia Sand Member | |
| | | Muderong Shale Formation | |
| Birdrong Sandstone | | | |
| <i>Major Unconformity</i> | | | |
| Devonian | Early | Sweeney Mia Formation | |
| | | Kopke Sandstone | |
| | | Faure Formation | |
| Silurian | Late | Coburn Formation | Dirk Hartog Group |
| | Early | Yaringa Formation | |
| Ordovician | Ajana Formation | | |
| | Marron Member | | |
| | Tumblagooda Sandstone | | |
| Pre-Ordovician? | Unnamed Sandstone Unit | | |
| <i>Major Unconformity</i> | | | |
| Archaean-Proterozoic | | Crystalline Bedrock | |

A brief discussion of the sedimentary successions beneath the project area is provided below:

Superficial Formations comprise Tertiary and Quaternary deposits that occur in the project area as well as in and around Hamelin Pool to the north. The Quaternary dune sand deposits in the Nanga and Peron Station areas have been described as the **Peron Sandstone** (BMR, 1990 and Hocking *et al.*, 1987). Quaternary shallow marine, shell coquina and salina deposits have also been described in the Nilemah Embayment during a geo-biology study on the stromatolites and algal mats in Hamelin Pool (BMR, 1990). The shallow marine and salina deposits may form elements of Bibra Limestone and Dampier Limestone that onlap and possibly interfinger with the Peron Sandstone (Figure 7). The shell coquina deposits that have formed along the present-day shoreline of Hamelin Pool are known as the Hamelin Coquina. Coquina consists almost entirely of shells of *Fragum erugatum* that is weakly cemented in

ridges up to 3 m high. Older Tertiary limestone and calcareous coquina deposits are described in several places around Hamelin Pool, but do not occur in the project area.

The superficial formations in the project area contain the Amy Zone. These deposits are of Quaternary age and predominantly comprise medium to fine-grained quartz sand (re-worked Peron Sandstone), with minor calcareous (calcrete) bands representing cemented fossil soil (palaeosol) profiles. Occasional silty and / or clayey lenses are present.

The superficial formations form a thinning sequence to the east, that onlaps calcrete and silcrete-capped Toolonga Calcilutite outcrop areas that typify the Carbla Plateau. The Amy Zone deposits represent a palaeo-coastline dune system that is aligned approximately north to south (Figure 1).

Toolonga Calcilutite is widespread within the Carnarvon Basin, including the Gascoyne Platform west of the Ajana Ridge, and disconformably overlies the Winning Group sediments. The unit is described as a calcilutite and calcisiltite, deposited in a low-energy marine environment (Iasky *et al.*, 2003). The unit thickness increases to the northwest from the project area, to reach over 300 m beneath the northern half of Shark Bay. Further north, this formation grades into the Korojon Calcarenite.

In Coburn 1, the Toolonga Calcilutite is 57 m thick Figures 7 (a and b). Drillers logs typically describe this formation as blue-grey, greenish-grey or white clay, chalk or shale (DoE, 2004). The Toolonga Calcilutite forms the local basement below the Amy Zone. Locally, the upper successions of this formation are re-worked into sandy or silty clay beds.

Alinga Formation is referred to as the Gearle Siltstone in northern and middle parts of the Gascoyne Platform (McWhae, 1958), and as the Alinga Formation in the southern area (Yasin and Mory, 1999). The presence of radiolaria in both units that have similarities with the Windalia Radiolarite suggests there is a close relationship between these units separated by facies-controlled transgressive environments.

In Coburn 1, the Alinga Formation consists of three sub-intervals; (i) a basal pebbly, glauconitic medium-grained sandstone that is overlain by (ii) black siltstone with abundant mica, pyrite and radiolaria, and an upper unit (iii) of black carbonaceous glauconitic sandstone (Yasin and Mory, 1999).

Windalia Radiolarite overlies the Muderong Shale and is commonly described as a black, hard, cherty or flinty-shale that is also pyritic. This formation is encountered over a wide area of the Carnarvon Basin and is believed to be an accumulation of siliceous ooze on the sea floor (Wills and Dogramaci, 2000). The radiolarite does not occur below or to the east of the project area, but has been described in logs from artesian bores to the north and west, beneath the Tamala, Nilemah and Nanga stations (Playford and Chase, 1955; Kempin and Fujioka, 1973).

Windalia Sand Member (of the Muderong Shale) is distinguished by grain size, but restricted to the southeastern part of the Gascoyne Platform in the vicinity of the Coburn, Hamelin and Meadow stations. It was deposited in a moderate-energy, very shallow marine environment (Wills and Dogramaci, 2000). Historically, this unit was informally combined with the Birdrong Sandstone and referred to as the Hamelin Beds (McWhae, 1958).

Locally, this unit consists of grey, medium-grained quartz sandstone with common wood fragments (Yasin and Mory, 1999). The sand member is typically 20 m thick, but thins to the north, south and west of a “lobe-type” structure beneath the Coburn, Hamelin and Meadow stations and appears to occur exclusively in the absence of the Windalia Radiolarite. The Windalia Radiolarite and Windalia Sand Member do not occur in the same vertical successions and as such are interpreted to represent an east to west facies change in depositional environment.

Muderong Shale Formation comprises a basal mudstone/shale and in the Shark Bay area an overlying sandstone (Windalia Sand Member). The shale unit was deposited in a low-energy marine environment (Iasky *et al.*, 2003). In Coburn 1, the shale forms a 5.5 m thick interval comprising dark grey, pyritic mudstone with a thin, medium-grained sandstone bed in the middle.

Birdrong Sandstone represents a basal transgressive sequence, deposited during the break-up of continental Australia from Greater India (Wills and Dogramaci, 2000). It is the lowest of several formations within the Winning Group. The formation is typically about 20 to 30 m thick and covers an unconformity throughout most of the Carnarvon Basin. Beds generally dip west and north. The lithology typically comprises pale grey to white friable sandstone and silty sandstone that is commonly glauconitic and contains wood fragments.

In Coburn 1, the Birdrong Sandstone is grey, fine grained, coarsening upwards to medium to coarse grained sandstone with common mudstone drapes (Yasin and Mory, 1999). The Birdrong Sandstone was deposited in a high-energy, near-shore, marine environment.

Kopke Sandstone conformably overlies the Faure Formation where they are both present. This formation is only present in the central to southern part of the Gascoyne Platform, with a maximum known thickness of 496 m in petroleum exploration hole Yaringa No. 1. The Kopke Sandstone has been eroded in the very southern part of the Gascoyne Platform, where it sub-crops below the Birdrong Sandstone. It is interpreted to be juxtaposed against the Tumblagooda Sandstone on the Ajana Fault (Wills & Dogramaci, 2000). In the project area, the 320 m thick succession of Kopke Sandstone was fully cored in Coburn 1 and described by Yasin and Mory, (1999).

The Kopke Sandstone comprises an upward-coarsening sequence of red to reddish-brown sandstone with minor siltstone and dolostone. The sandstone succession in Coburn 1 presents evidence of deposition in a mixed very shallow marine, fluvial to deltaic, lacustrine and eolian environment (Yasin and Mory, 1999). The coarsening-upwards sequence is associated with geological uplift of the hinterland during deposition.

Dirk Hartog Group and Faure Formation overly the Tumblagooda Sandstone over much of the Carnarvon Basin, except within the very southern part of the Gascoyne Platform, where they appear to have been eroded. The Dirk Hartog Group is subdivided into four units; namely the Ajana, Yaringa and Coburn Formations and basal Marron Member. The Dirk Hartog Group and Faure Formation are predominantly formed of shale, mudstone, dolostone and various evaporitic rocks (Iasky *et al.*, 2003). In Coburn 1, these units are present between about -415 and -884 m AHD (Yasin and Mory, 1999).

Tumblagooda Sandstone was named by Clarke and Teichert in 1948 and is widespread throughout the Carnarvon Basin. A detailed account of the formation at a type section in the lower reaches of the

Murchison River is provided by Hocking *et al.* (1987). The formation is almost entirely sandstone, ranging from very fine-grained to very coarse-grained and pebbly. It is a classical “red-bed” sequence and contains characteristics of a braided fluvial to coastal depositional environment. It has been assigned various ages extending between Cambrian to Early Ordovician. Previous interpretations have placed this unit at the base of the sedimentary sequence, but more recently, another unassigned unit has been identified (mainly by seismic exploration) beneath the Tumblagooda Sandstone and overlying the granitic basement (Iasky *et al.*, 2003).

Near the project area, the Tumblagooda Sandstone is present in Coburn 1 below -884 m AHD and was not fully penetrated at -1,000 m AHD. This sequence comprised light grey to reddish-grey fine to coarse-grained sandstone, sometimes pebbly, with cross-bedding and cross-laminations of very fine sandstone to siltstone (Yasin and Mory, 1999).

2.5 Nilemah Embayment and Hamelin Pool

The Nilemah Embayment and Hamelin Pool are significant physiographic features near Shark Bay (Figure 3). Hamelin Pool is a unique hypersaline marine environment with a restricted tidal interconnection, through the Faure Sill with the outer reaches of Shark Bay. Hypersaline conditions are the result of this restricted throughflow and high evaporation rates. Hamelin Pool is fringed by extensive sublittoral and intertidal platforms that are subjected to relatively small tidal fluctuations, and shell coquina beach ridges.

A number of studies of Hamelin Pool environment were completed between 1983 and 1989 by the Baas Becking Geobiological Laboratory and Bureau of Mineral Research (BMR, 1990). The predominant focus of these studies was to determine the environmental settings contributing to sulphide mineralisation of carbonate rich sediments. Significant data were collected on the geology, biology and chemistry of the existing environments in Hamelin Pool. Several sites on the fringes of Hamelin Pool, including the Nilemah Embayment in the south, and transects that include the stromatolites near the old Hamelin Telegraph Station, are included in the database.

Geological data indicate that the Nilemah Embayment is underlain by a succession of marine sand and clay beds. Some of these beds are correlated to the Bibra Limestone and Dampier Limestone Formations as described in Hocking *et al.* (1987). Marine clay beds underlie the coastal beach ridge of shell coquina dunes and intertidal zone, and overlie marine equivalents of the land-based Peron Sandstone. The clay sub-crops or outcrops beneath the salinas and topographic depressions on the landward side of the beach ridge within the Nilemah Embayment. The clays form a physical and evaporative barrier in the water table aquifer and shallow groundwater environment.

The water table environment in these areas comprises of a mixture of evaporated meteoric water and seawater that is responsible for the “*reasonably homogenous brine at depth*” (BMR, 1990). Local groundwater of meteoric origin would be derived from aquifers in the superficial formations surrounding the embayment. The BMR study data suggests that the shallow groundwater becomes increasingly saline from about 65,000 mg/L TDS south of the Denham Road to about 200,000 mg/L beneath clay pans and associated salinas in the embayment.

Field work undertaken in 1983 utilised piezometric and salinity measurements to specifically investigate the hydrology of the intertidal and sub-tidal zones in the Nilemah Embayment. This work indicated tidal influences extend inland several hundred metres from the beach. Quality data indicate that shallow carbonate-rich brackish to saline groundwater discharges from below the high-tide mark during low tide. These groundwaters are of meteoric origin entering the flow system through the shell coquina beach ridges, and mix in the marine environment beneath the beach. The carbonate derived from the beach ridges precipitates as aragonite when it mixes in the presence of algae with marine waters. Field data also determined that hypersaline groundwater of salinities between 100,000 and 200,000 mg/L TDS occurs at shallow depth below the water table.

The shallow groundwater flow system described for the Nilemah Embayment is repeated along the coast to the northeast. Where stromatolites occur, carbonate-rich shallow groundwater discharges from the base of the shell coquina beach ridges at low tide and following heavy rain. In these areas, the beach ridges are underlain by either Bibra Limestone or caprock overlying the Toolonga Calcilutite. The stromatolites occur in groundwater discharge zones (extract Burne, R.V. and James N.P., 1986 in BMR, 1990).

The stromatolites near the old Hamelin Telegraph Station occur within a different catchment than the project area and Nilemah Embayment.

Site investigations have been completed that characterise both the shallow groundwater environment and the predominant confined aquifer systems. The site investigations also provide a baseline assessment of current groundwater uses.

The site investigations have focussed on developing an understanding of the local aquifer systems and groundwater environments, enabling informed assessments of the potential impacts associated with the proposed mining of the Amy Zone.

Three discrete site investigation programmes have been completed. These programmes involved:

- A superficial formations drilling programme that comprised construction of multipiezometers and test production bore at three separate sites, with groundwater sampling and hydraulic tests at each site (Figure 9).
- A confined aquifer drilling programme, including the construction and test pumping of a production bore screened in the Birdrong Sandstone and Kopke Sandstone and construction of a multipiezometer to provide hydrogeological data on the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone (Figure 9).
- A bore census that comprised the collection of historical data on existing bore locations, construction, groundwater levels and groundwater quality. The historical data were obtained from published government records and through discussions with the bore owners. The groundwater level and quality parameters were measured during site visits.

The site investigations have been supported by research of available geological, hydrogeological and petroleum exploration references. These include the findings of a geo-biology study on the stromatolites and algal mats in Hamelin Pool (BMR, 1990). Importantly, this study characterises the shallow formations and water table environment within the Nilemah Embayment and foreshore areas of Hamelin Pool.

3.1 Superficial Formations Investigations

The superficial formations and uppermost interval of the Toolonga Calcilutite were investigated. The investigation programme consisted of airlift development of an existing production bore (STB1), drilling three multipiezometers (SMB2, SMB3 and SMB4) and one test production bore (STB3). Several existing piezometers (installed as part of the BMR (1990) geo-biology studies associated with Hamelin Pool and herein termed SMB1a, SMB1b and SMB1c) in the vicinity of the project area were also included, providing groundwater level and quality data. Prior to drilling, the investigation sites were pegged and surveyed by MHR Surveys using a differential GPS.

The superficial formations drilling programme was undertaken by Aquatech Drilling between 28th July and 5th August 2004. All investigation bores were drilled using mud-rotary techniques. Multipiezometers SMB2, SMB3 and SMB4 are constructed using 50 mm nominal diameter Class 9 uPVC, with separate standpipes screened against the upper 10 to 15 m of the Toolonga Calcilutite and lower-most 6 m of the

superficial formations. Screen intervals are gravel-packed using 2.0 to 3.6 mm graded quartz sand and hydraulically separated using bentonite-cement grout. The shallow standpipes are denoted with an “s” suffix, while the deep standpipes have a “d” suffix.

STB3 is constructed in the northern-most project area, near SMB3, to determine the hydraulic conductivity of the Toolonga Calcilutite and saturated interval of the superficial formations. STB3 is constructed of 155 mm nominal diameter Class 9 uPVC, screened against both potential aquifer intervals. The casing is centralised in the bore and gravel-packed using 2.0 to 3.6 mm graded quartz sand.

Each investigation bore was tested and sampled to determine hydraulic parameters and baseline groundwater quality data.

3.1.1 Superficial Formations Drilling Results

The superficial formations site investigation bores are summarised in Table 5 and on Figures 10 to 13. Details (where available) for the existing bores are also included in Table 3.

Table 3
Summary of Superficial Formations Site Investigations

| Bore | MGA North (m) | MGA East (m) | Datum Elevation (m AHD) | Ref. Point Height (m agl) | Static Water Level (Oct 2004) | | Depth (mbgl) | Saturated Thickness (m) | Slotted Interval (mbgl) | Lithology | Salinity (mg/L TDS) | Field pH | Comments |
|-------|---------------|--------------|-------------------------|---------------------------|-------------------------------|---------|--------------|-------------------------|-------------------------|-----------------------------|---------------------|----------|-----------------------|
| | | | | | (m brp) | (m AHD) | | | | | | | |
| SMB1a | 7,067,820.8 | 210,581.7 | 4.07 | 0.36 | 3.38 | 0.69 | 7.3 | 3.9 | n.d. | Superficial marine deposits | - | - | Installed by BMR 1984 |
| SMB1b | 7,067,639.1 | 210,586.0 | 4.27 | 0.55 | 3.49 | 0.78 | 4.2 | 0.7 | n.d. | Superficial marine deposits | - | - | Installed by BMR 1984 |
| SMB1c | 7,067,169.9 | 210,612.8 | 12.50 | 0.00 | 11.35 | 1.15 | 13.3 | 1.9 | n.d. | Superficial marine deposits | - | - | Installed by BMR 1984 |
| SMB2s | 7,060,717.6 | 211,125.6 | 41.71 | 0.51 | 23.88 | 17.83 | 24.0 | 0.1 | 18.0-24.0 | Superficial Formations | 14,000 | 6.3 | |
| SMB2d | 7,060,717.6 | 211,125.6 | 41.71 | 0.51 | 23.68 | 18.03 | 40.0 | 16.3 | 34.0-40.0 | Toolonga Calcilutite | 25,000 | 6.7 | |
| SMB3s | 7,065,001.0 | 208,683.0 | 33.50 | 0.49 | >30.2 | <3.30 | 30.0 | 0.0 | 24.0-30.0 | Superficial Formations | - | - | Dry |
| SMB3d | 7,065,001.0 | 208,683.0 | 33.50 | 0.49 | 30.12 | 3.38 | 43.0 | 12.9 | 37.0-43.0 | Toolonga Calcilutite | - | - | |
| SMB4s | 7,055,527.1 | 212,594.5 | 67.22 | 0.54 | >30.0 | >30.0 | 30.0 | 0.0 | 24.0-30.0 | Superficial Formations | - | - | Dry |
| SMB4d | 7,055,527.1 | 212,594.5 | 67.22 | 0.54 | 37.65 | 29.57 | 42.0 | 4.4 | 36.0-42.0 | Toolonga Calcilutite | 11,000 | 6.2 | |
| STB1 | 7,067,732.8 | 210,581.0 | 4.20 | 0.40 | 3.45 | 0.75 | 7.0 | 3.6 | n.d. | Superficial marine deposits | 68,000 | 6.6 | Installed by BMR 1984 |
| STB3 | 7,065,001.4 | 208,698.7 | 33.76 | 0.41 | 30.63 | 3.13 | 43.0 | 12.4 | 16.0-43.0 | Toolonga Calcilutite | 34,000 | 6.2 | |

Abbreviations: m AHD - metres above the Australian Height Datum
 m bgl - metres below ground level
 m agl - metres above ground level

m brp - metres below the reference point (usually top of bore casing)
 n.d. - Not Determined
 mg/L TDS - milligrams per Litre Total Dissolved Solids

The shallow standpipes in SMB3 and SMB4 are dry; that is the water table is below the base of the superficial formations. SMB2s has about 0.7 m of groundwater at the base of the superficial formations. Groundwater was intersected in the deep standpipes in SMB2, SMB3 and SMB4. STB3 intersected the water table in the upper section of the Toolonga Calcilutite, just below the base of the superficial formations.

No aquifer tests were conducted in the existing shallow bores located north of the project area as they had been scheduled for stygofauna sampling.

3.1.2 Superficial Formations and Toolonga Calcilutite Aquifer Testing

Aquifer tests were completed in SMB2 to SMB4 and STB3 to characterise the hydraulic conductivity of the superficial formations and shallow Toolonga Calcilutite. The test methods varied to cater for differences in the saturated thickness of the Peron Sandstone and lithology of the shallow Toolonga Calcilutite. Preferentially, aquifer tests in standpipes with sufficient submergence beneath the water table were conducted by pumping and measurement of drawdown responses. Elsewhere, where submergence of the standpipes is limited, the aquifer testing involved injection and falling-head methods.

Testing in SMB2

As discussed, SMB2 has groundwater in both the shallow and deep standpipes. The superficial formations standpipe does not contain sufficient groundwater for Grundfos MP1 submergence so it was sampled using an environmental bailer. The sandy interval in the Toolonga Calcilutite intersected by the deep standpipe was pumped for 40 minutes at 13.8 kL/day, resulting in a drawdown of 3.4 m (Figure 14).

The groundwater levels are essentially the same in the SMB2 standpipes, indicating locally there is a 0.2 m vertical head difference between the superficial formations and shallow Toolonga Calcilutite. This difference implies an upward potentiometric head from the Toolonga Calcilutite. After the standpipes were pumped or bailed, they were subjected to an inflow test and falling-head test (Figure 15).

The results of the aquifer testing in SMB2s and SMB2d are summarised in Table 4 and presented in Appendix B.

Table 4
Results of Aquifer Tests in SMB2

| Standpipe | Static Water Level (m brp) | Pumping Rate (kL/day) | Hydraulic Conductivity (m/day) | Comments |
|-----------|----------------------------|-----------------------|--------------------------------|--|
| SMB2s | 23.88 | Bailed | >13 | Test section includes mostly unsaturated sand. |
| SMB2d | 23.68 | 13.8 | 0.1 | Aquifer is a sandy layer 5m below top of Toolonga Calcilutite. |

Note: m brp = metres below reference point (top of bore casing)

Testing in SMB3 and STB3

Both SMB3 and STB3 encountered groundwater only in the Toolonga Calcilutite; the water table at this site being 2 m below the base of the superficial formations (Figure 13). The shallow Toolonga Calcilutite was tested in STB3 by pumping at a rate of 7.5 kL/day for 180 minutes after which time the groundwater level had been drawn down to the pump inlet. Constant-head and falling-head tests were completed in the SMB3 standpipes. A groundwater sample was obtained only from STB3 after 180 minutes of pumping.

The results of the hydraulic testing in SMB3 and STB3 are summarised in Table 5, on Figures 16 and 17 and in Appendix B.

**Table 5
Results of Aquifer Tests in SMB3 and STB3**

| Standpipe | Static Water Level (m brp) | Pumping Rate (kL/day) | Hydraulic Conductivity (m/d) | Comments |
|-----------|----------------------------|-----------------------|------------------------------|---|
| SMB3s | >30.2 | Dry | 5.6 | Test section includes mostly unsaturated sand. |
| SMB3d | 30.2 | N.D. | 0.1 | Storativity of Toolonga Calcilutite measured from pumping = 2.2×10^{-5} (dimensionless). |
| STB3 | 30.22 | 7.5 | 0.2 | Aquifer is a sandy layer in upper 2 m of Toolonga Calcilutite. |

Note: m brp = metres below reference point (top of bore casing)

Testing in SMB4

SMB4 encountered groundwater only in the shallow Toolonga Calcilutite. The water table is about 7 m below the superficial formations at this location (Figure 12). The constant-rate pumping test conducted in SMB4d lasted 14 minutes before the groundwater level was drawn below sandy beds in the Toolonga Calcilutite. Evidently, the pumping rate of 2.4 kL/day exceeded the groundwater supply capability of these beds. While drilling, an interval of lost-circulation was encountered in the unsaturated Toolonga Calcilutite. This interval accepted all of the water introduced for the constant-head test and is evidently comparatively transmissive.

The results of the aquifer testing conducted in SMB4s are summarised in Table 6, shown on Figures 18 and 19 and presented in Appendix B.

Table 6
Results of Aquifer Tests in SMB4

| Standpipe | Static Water Level (m brp) | Pumping Rate (kL/day) | Hydraulic Conductivity (m/day) | Comments |
|-----------|----------------------------|-----------------------|--------------------------------|--|
| SMB4s | >30.0 | Dry | >5 | Test section includes mostly unsaturated sand. |
| SMB4d | 37.63 | 2.4 | 0.05 – 2.0 | Aquifer is a slightly sandy layer within clay. The higher hydraulic conductivity result is due to an unsaturated transmissive zone accepting the introduced water during the constant head test. |

Note: m brp = metres below reference point (top of bore casing)

3.1.3 Shallow Groundwater Quality Analyses

Sampling was undertaken using either an environmental bailer or a Grundfos MP1 electric submersible pump. The testing was conducted according to the following schedule:

Multipiezometers: Measured static groundwater levels.

Bailed or pumped a representative groundwater sample after purging.

In low-yielding standpipes, hydraulic tests consisting of a constant-head test followed by a falling-head test.

For high-yielding standpipes, pumping tests with drawdown observations in the pumped and other standpipe.

STB3: Measurement of a static water level.

Pumping for hydraulic response analysis in STB3 and nearby SMB3.

Groundwater samples were taken from all standpipes except SMB3s, SMB3d and SMB4s. Both SMB3s and SMB4s are dry. The sampling included a bailed sample from STB1 a week after airlift development. The samples were filtered, preserved and dispatched according to the following schedule:

- STB1 and SMB2s were purged and sampled by bailing, due to low-yield or limited saturated thickness.
- SMB2d, STB3, and SMB4d were purged and sampled using a Grundfos MP1.
- One unfiltered sample was taken from each site for major ions, pH, salinity (by evaporation) and electrical conductivity.
- One filtered sample (to 0.45 µm) was taken for dissolved metals; preserved with nitric acid.

-
- One filtered sample (to 0.45 µm) was taken for dissolved mercury; acid/potassium dichromate preservative.
 - One filtered sample (pre-filter only) was taken for radionuclide analysis; using acid-washed sample bottles.

The samples were stored on ice in the field and refrigerated until transported to SGS laboratories by commercial courier. SGS Laboratories received the samples within 3 or 4 days of sampling. The radionuclide samples were submitted to Genalysis within 5 or 6 days of sampling.

Laboratory analysis reports are provided in Appendix C. The results of the radionuclide analyses are reported separately by Radiation Advice & Solutions Pty Ltd.

3.2 Confined Aquifer Investigations

The confined aquifer investigations consisted of one test-production bore (DTB1) screened within the Birdrong Sandstone and Kopke Sandstone and a multipiezometer (DMB1), with separate standpipes screened within the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone. Both investigation holes were drilled by Drilling Contractors of Australia (DCA). DTB1 was drilled using an ADS1500 rig, while DMB1 was drilled and constructed using a Midway rig.

The drill sites are located so the constructed bores could be incorporated into the operating borefield in the southern part of the project area. They were also selected on the basis of reasonable access and where the collars were at relatively low elevations. All of the drilling was conducted using mud-rotary techniques; both holes were geophysically logged by Westlog Wireline Services once the pilot-holes reached their target depths. Drilling water was derived from Coburn No. 9, located about 10 km to the northeast. The existing pastoral Mono-pump was temporarily replaced with a 100 mm electric submersible pump. The supply from Coburn No. 9 was limited to three loads per day plus minor stock water requirements. This limited the rate of progress, particularly during periods of lost circulation (in several zones in the Toolonga Calcilutite and Windalia Sand Member) as well as in the initial stages of bore development.

Once completed, DTB1 was developed by jetting the screens, using proprietary-branded break-back additives, followed by extensive airlifting and surging to reduce the returned sand content. Groundwater airlifted from the DTB1 was directed into mud pits and then to a sump where it was temporarily contained before being lost due to infiltration. Finally, DTB1 was treated with sodium hypochlorite for disinfection against microbacteria, such as iron-reducing bacteria. The standpipes in DMB1 were also developed by airlifting and surging until the abstracted groundwater was clean and free of sand. The groundwater was disposed initially to the mud pits, then into a small trench until lost by infiltration.

Following development, an electric submersible pump was installed in DTB1 to a depth of 86 m. Subsequently, DTB1 was subjected to step-rate pumping consisting of three one-hour steps and one five-hour step at increasing pumping rates of 5,620, 6,480, 7,340 and 8,640 kL/day. Pumping water levels were measured in DTB1 to determine bore efficiency characteristics and a suitable pumping rate for the

constant-rate test. The constant-rate test occurred over a duration of 41-hours pumping at 7,780 kL/day, following-on immediately from the step-rate tests. Groundwater levels were measured in DTB1 and DMB1, located 1,040 m apart.

The abstracted groundwater was discharged to the mud pits and allowed to overflow to the sump for infiltration. Some of the groundwater was also diverted into adjoining areas, including a swale near DMB1, for infiltration as the constant-rate pumping could not be entirely accommodated by the sump. During the test, the groundwater was monitored for clarity, salinity, pH and temperature. Groundwater samples were taken for chemical analysis after one hour of pumping and at the end of the constant-rate test. A separate sample was taken for dissolved metals. This sample was filtered to 0.45 µm on site and acidified to pH 2. Non-preserved samples were also taken for major ion, physio-chemical analyses, and radionuclides. Samples were also collected from DMB1 at the end of the development. All samples were taken according to AS5667.1:1998 and analysed at the NATA-registered SGS Laboratories (major & minor chemistry) and Genalysis (radionuclides).

3.2.1 Confined Aquifer Drilling Results

Details of the DTB1 and DMB1 constructions are presented in Table 7 and on Figures 20 and 21.

Table 7
Summary of Confined Aquifer Site Investigations

| Bore No. | MGA North (m) | MGA East (m) | Datum Elevation (m AHD) | Ref. Point Height (m agl) | Static Water Level (Oct 2004) | | Depth (m bgl) | Slotted Interval (m bgl) | Formation | Salinity (mg/L TDS) |
|----------|---------------|--------------|-------------------------|---------------------------|-------------------------------|---------|---------------|--------------------------|---------------------------------------|---------------------|
| | | | | | (m brp) | (m AHD) | | | | |
| DMB1 | 7,042,678.0 | 216,734.1 | 85.41 | 0.20 | 36.4 | 49.0 | 400.0 | 190.0-196.0 | Windalia Sand Member | 9,100 |
| | | | | | 36.2 | 49.2 | | 211.0-217.0 | Birdrong Sandstone | 7,750 |
| | | | | | 35.7 | 49.7 | | 394.0-400.0 | Kopke Sandstone | 12,000 |
| DTB1 | 7,041,723.0 | 216,318.0 | 85.85 | 0.25 | 38.52 | 47.33 | 425.0 | 206.0-400.0 | Birdrong Sandstone Kopke Sandstone | 8,900 |

Abbreviations: m AHD - metres above the Australian Height Datum
m bgl - metres below ground level
m agl - metres above ground level

m brp - metres below the reference point (usually top of bore casing)
n.d. - Not Determined
mg/L TDS - milligrams per litre Total Dissolved Solids

The construction of DTB1 provides for the isolation of both the Toolonga Calcilutite, which occasionally contains thin sand beds, and Windalia Sand Member, which is utilised by many of the local pastoralists. The pilot-hole was drilled to 485 m depth and geophysically logged (Figure 20). The formations intersected correlate with the Coburn 1 log (Figure 22) with distinctive responses for both the natural gamma and resistivity logs. The caliper log of the Windalia Sand Member and Birdrong Sandstone indicates these formations are poorly lithified, in sections, with some washouts evident in the hole diameter. The simplified stratigraphy intersected in DTB1 is shown in Table 8.

Table 8
Stratigraphy In DTB1

| Formation | Depth (m bgl) | | Depth (m AHD) | |
|---------------------------|---------------|--------|---------------|---------|
| | Top | Bottom | Top | Bottom |
| Superficial Formations | 0.0 | 21.0 | 85.9 | 64.9 |
| Toolonga Calcilutite | 21.0 | 122.0 | 64.9 | -36.1 |
| Alinga Formation | 122.0 | 170.0 | -36.1 | -84.1 |
| Windalia Sandstone Member | 170.0 | 197.5 | -84.1 | -111.6 |
| Muderong Shale Formation | 197.5 | 205.0 | -111.6 | -119.1 |
| Birdrong Sandstone | 205.0 | 229.0 | -119.1 | -143.1 |
| Kopke Sandstone | 229.0 | >485 | -143.1 | >-399.1 |

DTB1 is constructed with two mild steel casings that are pressure cement-grouted within the superficial formations, Toolonga Calcilutite, Alinga Formation and Muderong Shale Formation. The upper casing, of 457 mm ND low-carbon mild steel, extends to 132 m depth, 38 m below the top of the Alinga Formation. The second casing is 132 m of 300 mm ND steel fitted with a further 73 m of 250 mm ND mild steel, which extends to 205 m, at the base of the Muderong Shale Formation. The production assembly consists of (from the bottom) a blank stainless steel baseplate, stainless steel wire-wound 0.5 mm aperture screens and an inflatable packer on a 6 m blank extension to seal against the base of the 250 mm ND casing.

The construction of DMB1 isolates the superficial formations Toolonga Calcilutite, and Alinga Formation using 200 mm ND mild steel casing installed to 132 m depth. The pilot-hole was then drilled to 400 m depth and geophysically logged (Figure 21). The stratigraphy in DMB1 is very similar to that in DTB1 with only about 3 m difference in the distribution of the stratigraphic successions above the Birdrong Sandstone.

DMB1 is constructed with three standpipe piezometers of 40 mm ND, 0.5 mm aperture stainless steel screens at 184-190 m, 210-216 m and 392-398 m within the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone. Six metre cement-grout seals are placed at 197-203 m and 227-233 m depth to seal against the Muderong Shale and Birdrong Sandstone/Kopke Sandstone boundaries. The remainder of the annulus is backfilled with 1.6 to 3.2 mm graded gravel pack.

3.2.2 Confined Aquifer Test Results

The aquifer test in DTB1 test was conducted as a single composite pumping test of the following sequence:

- Step 1 – One hour at 5,616 kL/day.
- Step 2 – One hour at 6,480 L/day.
- Step 3 – One hour at 7,344 L/day.

- Step 4 – Five hours at 8,640 L/day.
- Constant-Rate Test – Forty one hours at 7,776 L/day.

The results of the aquifer tests in DTB1 are presented in Table 9, on Figure 23 (a and b), and on Figure 24 (a and b).

Shortly after start-up, the abstracted groundwater became grey-coloured and slightly sandy as some of the Birdrong Sandstone was drawn through the screens due to the initial hydraulic shock. After about 8 minutes, the ingress of sand diminished to normal levels. After about 13 minutes, the pumping discharge became black and very sandy, probably due to some residual mud cake entering the bore. This occurrence continued for about 12 minutes before the groundwater began to clear. A minor increase in sand content was noted after one hour of pumping but cleared to become sand-free after three hours.

At 5,616 kL/day, the pumping water level in DTB1 was rapidly drawn down about 16 m in the first minute, and subsequently significantly fluctuated for about 10 minutes because the pumping rate was variable. Subsequent rate-steps were generally more controlled and hence, the corrected drawdowns follow more linear trends. The drawdown after 60 minutes of pumping at 5,616 kL/day was 18.1 m. Corrected 60-minute drawdowns for each of the subsequent steps were 23.4, 26.6 and 30.9 m with the latter step reaching a drawdown of 31.9 m after 240 minutes. After 240 minutes at 8,640 kL/day, the rate was reduced to 7,776 kL/day to allow groundwater disposal to be managed. The test was completed at 7,776 kL/day for an additional 41 hours, for a total duration of 49 hours pumping. After the 8,640 kL/day step, the pumping water level declined at an average rate of 1.5 m per log cycle until about 1800 minutes, after which the pumping rate slowly drifted from 7,776 to 8,035 kL/day. After the pumping rate was corrected, the pumping water level rose immediately by 0.71 m and then resumed a slow decline of about 1.5 m per log cycle (Figure 23a).

Table 9
Results of Aquifer Tests in DTB1 and DMB1

| Bore | Aquifer | Transmissivity (m ² /day) | Hydraulic Conductivity (m/day) | Storativity (dimensionless) | Specific Storage (1/m) | Interpretation Method |
|---------|--|--------------------------------------|--------------------------------|-----------------------------|------------------------|-----------------------|
| DTB1 | Birdrong Sandstone and Kopke Sandstone | 931 | 4.8 | - | - | Jacob (CRT) |
| | | 579 | 2.9 | - | - | Theis Semi-log (Rec) |
| DMB1(b) | Birdrong Sandstone | 402 | 13 | 0.00058 | 0.000019 | Jacob (CRT) |
| | | 216 | 7.2 | - | - | Theis Semi-log (Rec) |
| DMB1(k) | Kopke Sandstone | 308 | 1.9 | 0.00016 | 0.000001 | Jacob (CRT) |

Note: CRT = Constant Rate Test; Rec = Recovery Test

Groundwater levels in DMB1 responded as expected (Figure 23b). The Windalia Sand Member did not respond to pumping from DTB1. The largest drawdown response was from the Birdrong Sandstone, with a final drawdown of 2.2 m. A smaller response of 0.75 m occurred in the Kopke Sandstone. Groundwater levels in the Birdrong Sandstone in DMB1 responded after 80 minutes of pumping. The Kopke Sandstone in DMB1 responded after 300 minutes of pumping. Both the Birdrong Sandstone and Kopke Sandstone drawdown responses are steepening trends that become linear on semi-log scale after about 1,700 minutes. The Birdrong Sandstone drawdown trend after 1,700 minutes declined at an average rate of 2.50 m/log cycle, while that for the Kopke Sandstone declined at 1.63 m/log cycle.

After the constant-rate test, recoveries were monitored for two days in DTB1 and DMB1. The results of these measurements are presented on Figure 24 (a and b). Groundwater levels in DTB1 recovered quickly from a maximum drawdown of 31.4 m to a residual drawdown of 8.63 m after one minute ($t/t' = 2941$). The recovery followed a linear trend for the first 150 minutes ($t/t' = 21$) and then steepened towards a 97% recovery after 3015 minutes ($t/t' = 2.0$). In DMB1 groundwater levels did not start to recover in the Birdrong Sandstone and the Kopke Sandstone until after 70 minutes and about 1,000 minutes.

To analyse the aquifer responses, it is necessary to assign a proportion of the total pumping rate to each aquifer interval. This was achieved by solving the laboratory-derived salinity from DTB1 against the individual piezometer salinities using the electrical resistivity logs on Figures 20 and 21. These derivations are included in Appendix B. By characterising the Formation Factors and long-normal resistivity results, it is calculated that about 46% of the abstractions (3,580 kL/day) were derived from the Birdrong Sandstone and 54% (4,204 kL/day) from the Kopke Sandstone.

The interpretations from the piezometers are considered the most representative and indicate the Birdrong Sandstone has a hydraulic conductivity of between 7 and 13 m/day, with the lower part of the Kopke Sandstone being about 2 m/day. The Kopke Sandstone is a coarsening-up sequence (DMB1 log, Figure 21). As such, it is likely that the effective hydraulic conductivity of the screened Kopke Sandstone will be higher than interpreted in DMB1(k), which is screened within an interbedded sandstone and siltstone sequence. The lithological logs from Coburn 1 and DTB1 indicate the Kopke Sandstone is predominantly a sandstone formation and that DMB1(k) intersects atypical intervals of argillaceous lithologies. An analysis of the recovery in DMB1(k) (Kopke Sandstone) is not presented, as this interval had not recovered sufficiently after two days. Evidently, the lower interval screened has a restricted hydraulic connection to the interval pumped in DTB1.

3.2.3 Confined Aquifer Groundwater Quality Analyses

The results of groundwater analyses from DTB1 and DMB1 samples and those earlier (August 2003) on samples from the nearby Coburn No. 7 and Spinifex No. 2 are presented in Appendix C.

The field-measured salinities of groundwater from DMB1 decreased from 8,660 mg/L in the Windalia Sand Member, to 6,880 mg/L in the Birdrong Sandstone and increased to 11,370 mg/L in the Kopke Sandstone. The lab-measured salinities show a similar trend with concentrations of 9,100, 7,750 and

12,000 mg/L TDS in the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone. A combined salinity of 8,900 mg/L TDS is determined from DTB1. Based on a correlation between the measured salinities from DMB1 and the resistivity logs (Figures 20 and 21), it is likely that about 46% of the groundwater abstraction from DTB1 is from the Birdrong Sandstone and 54% from the Kopke Sandstone (Appendix B). The salinities measured in groundwater from DMB1(k) may not be representative of the sandier more transmissive beds of the Kopke Sandstone. The screen interval in DMB1(k) is within interbedded argillaceous sediments that might be expected to transect groundwater of comparatively high salinity.

3.3 Bore Census Findings

A comprehensive census of 58 local bores has been undertaken. The census determines the existing bore network in the region. Initially, the census extended out to a nominal 50 km radius from the project site, but later included bores from Pastoral Stations further afield to address concerns from the pastoralists.

The census was initiated by collating available data from the WINS database held by the DoE. Additional details were also derived from reports by Playford and Chase, (1955) and McWhae (1958). Two separate field visits were conducted to gather the following statistics:

- Current status of the bores (i.e. whether they are still operational or have recently been replaced).
- Measurement of a static water level (where possible).
- Determination of groundwater salinity and pH - collected directly from the outlet where possible.
- Visual inspection and photographs of the bores to record the current headworks and overall condition.
- Discussion with the bore owners to determine historical details, including the installed pumping equipment and intake depths where known.
- Discussion with the owners to determine (or estimate) the usage pattern of each bore where this is possible.

The locations of the bores are shown on Figure 25. The detailed results of the census are presented in Appendix D.

The findings of the census are as follows:

- There are eight artesian bores within the census area: Nanga View Homestead, Nilemah Artesian No. 1A, Hamelin Pool Telegraph Station Caravan Park, Hamelin Homestead No 2, Spinifex Bore (including 2 old bores), Sweeney Mia Bore, Carbla Homestead and Six Mile Well.
- Nilemah Artesian No. 1A is used occasionally for road-maintenance by the Shark Bay Shire. Groundwater from the Hamelin Pool Telegraph Station Caravan Park and Carbla Homestead bores is used semi-continuously for domestic purposes. Groundwater from Hamelin Homestead No. 2 is

used continuously for generating a domestic electricity supply (via a small turbine). The groundwater is subsequently used for domestic, stock and maintenance of a nearby small artificial wetland. The Sweeney Mia, Spinifex, Carbla Homestead and Six Mile bores are used by Hamelin and Carbla stations, through reticulated pipe networks, to provide stock water. A new domestic water bore is planned in the near future by a land developer near the Nanga Resort to provide a shared supply with nearby property owners.

- With the exception of Spinifex Bore, the artesian bores have hydraulic pressures ranging from about 24 to 42 m above the boreheads. Spinifex Bore flows intermittently, at low pressures, due to the elevation of the borehead and either variations in the confined aquifers or regional drawdown effects from other bores.
- Outside the nominal census range are existing artesian bores at Eagle Bluff, on the old Peron Pastoral Station, and at Denham township, about 90 km and 60 km north-northwest of the project area. The Eagle Bluff bore supplies groundwater for road maintenance.
- A new bore on the old Nanga Station, south of Useless Loop Road near the Nanga-Tamala Station boundary, is also planned to provide a road maintenance supply. This bore is planned to be installed in 2005 and is expected to provide a low-pressure artesian supply (Harold Crawford, pers. comm.)
- The closest non-artesian bores to the project area provide stock water on Hamelin and Coburn stations. Those on Hamelin Station are operated by windmills, while those on the Coburn Station are equipped with diesel-driven Mono (shaft-turbine) pumps. Some groundwater is reticulated across these stations, particularly at Coburn where all of the southern bores have been decommissioned, and groundwater is now diverted from the northern bores via pipelines and diesel-driven booster pumps. Coburn Station sources their domestic supplies on an as-needed basis from a superficial (soak) bore adjacent to the homestead.
- The bores operated by the Billabong and Overlander roadhouses and Billabong Hotel all use electric-submersible pumps. A portion of the supply is desalinated for potable use; the remainder is reticulated for non-potable domestic uses.
- All the bores on Carbla and Meadow stations are operated by windmills on an as-needed basis. Bores on Woodleigh and Nerren-Nerren stations use a mixture of windmills, Mono and electric-submersible pumps. The pump inlets for the windmills are generally about 4.6 or 6 m below the water table.
- Shallow bores are used on Tamala Station for stock and domestic supply purposes, abstracting brackish groundwater from the Tamala Limestone. Several old shallow bores (referred to as soaks) were once present on the old Cooloomia Station, south of Coburn Station, but are now all decommissioned. They derived groundwater from localised unconfined aquifers not connected to the confined regional aquifer systems.

-
- It is difficult in many bores to determine from which confined aquifer system groundwater is being abstracted. Most of the bores were not rigorously lithologically or geophysically logged when they were constructed. Lithological details are often incomplete and do not allow accurate correlation with the regional geology. Some sources are readily determined, where sufficient data are available, or have been previously interpreted by Wills and Dogramaci, (2000). The aquifer intercepts by the remaining bores have been interpreted as shown in Appendix D.

4.1 Background

The understanding of the hydrogeology of the Gascoyne Platform has been developing for over a number of decades, driven by the needs for groundwater supplies from production bores and the interpretation of structure and stratigraphy in petroleum exploration. Many of the existing production bores have been constructed based on groundwater quality and yield, rather than targeting specific aquifer systems. Lithological data collected by drillers are typically very brief. As a result, these data are often ambiguous and provide incomplete records.

Several studies collate the results of (mainly pastoral) drilling in the onshore Gascoyne Platform. The definition and interpreted distribution of the main aquifers, their flow-paths and salinity distributions are developed based on the groundwater data collected from groundwater bores and petroleum exploration. An initial study conducted by Playford and Chase (1955) for Australian Petroleum Pty Ltd collated the geological and hydrogeological data collected over the previous 50 years. Subsequently, a study by McWhae (1958), investigated the salinity and hydrodynamics of the main aquifers in the Carnarvon Basin utilising the results of Playford and Chase, and others, with the benefit of (then) recent petroleum exploration drilling.

More recently, Wills and Dogramaci (2000) updated the hydrogeological database utilising the results of nearly one hundred years of drilling in the Carnarvon Basin. This study, other studies regarding petroleum prospects and regional structural investigations by Iasky *et al.*, (2001 and 2003) form the basis of the current understanding of the confined aquifer hydrogeology of the Gascoyne Platform. Work has also been undertaken using geochemical and stable-isotope analyses, but findings have been limited by the distribution of bores and lack of confidence of the stratigraphic interval being sampled.

It is generally accepted that groundwater recharge is entering the confined aquifer systems where these formations outcrop or sub-crop along the Ajana Ridge. It is also understood that recharge to and the available groundwater resources in the Birdrong Sandstone and Kopke Sandstone aquifers is poorly defined (Wills and Dogramaci, 2000). Therefore, there is uncertainty regarding the rates of sustainable abstraction.

Current estimates indicate the groundwater recharge may be in the order of 0.5% of annual rainfall (Wills and Dogramaci, 2000), but may have changed historically. Lower salinity groundwater at depth in the stratigraphic profile may be the result of higher recharge rates during historical wetter climates.

Estimates of the groundwater through-flow rates in the Carnarvon Basin have generally been calculated by application Darcy's Law at a regional scale, using generalised hydraulic gradients and cross-sectional area (Allen, 1987). However, the interpretations of groundwater levels are uncertain due to bore construction (or condition) and the occurrence of structural constraints on groundwater flow. The estimated through-flow (and recharge) rates are therefore semi-quantitative. Recent studies by Hiller *et al.*, (2002) using stable-isotopes did not produce conclusively-supporting results on the flow direction and recharge rates through the Kopke Sandstone, for the same reasons that limited the reliability of earlier studies. This work, based on the extent of the Windalia Radiolarite and Birdrong Sandstone in the area between Shark Bay and Carnarvon, provided recharge estimates of 4.5 GL/annum.

The above descriptions indicate that the knowledge and understanding of the regional Carnarvon Basin hydrogeology is comparatively limited. The groundwater flow systems, rates of recharge, throughflow and discharge mechanisms are only defined in conceptual and semi-quantitative terms. The limited available relevant data will continue to restrict the understanding of the regional aquifer systems until more definitive data are available. In the meantime, the hydrogeology assessments are strongly interpretive and incorporate uncertainty.

4.2 Superficial Formations Aquifer Systems

4.2.1 Aquifer Profiles

The superficial formations beneath the project area are predominantly formed of sands of the reworked Peron Sandstone. The sand is typically medium to fine grained as shown in Table 10. The particle size distribution indicates that the sand is predominantly between 180 and 500 μm and clean, with a slimes fraction ($< 45 \mu\text{m}$) comprising 0.3 % by weight. Several calcrete bands are present in the upper sand profile representing palaeo-sols, some of which are covered by recent dunes.

Soil salinities between 120 and 800 mg/L TDS were recorded during a recent landform survey and indicate there is naturally stored salt in the soil profile (Blandford, 2004). This is probably the result of high rates of evaporation and infiltration of wind-borne salt.

Table 10
Typical Particle Size Distribution of the Amy Zone

| Fraction (μm) | Weight (%) | Cumulative Weight (%) |
|----------------------------|------------|-----------------------|
| 5,000 | 1.6 | 1.6 |
| 1,980 | 1.0 | 2.5 |
| 1,500 | 0.2 | 2.7 |
| 1,000 | 0.3 | 3.0 |
| 710 | 0.6 | 3.6 |
| 500 | 0.1 | 3.7 |
| 400 | 31.5 | 35.2 |
| 250 | 39.8 | 75.0 |
| 180 | 15.1 | 90.1 |
| 125 | 6.5 | 96.5 |
| 90 | 2.1 | 98.7 |
| 63 | 0.5 | 99.1 |
| 45 | 0.6 | 99.7 |
| -45 | 0.3 | 100.0 |
| Total | 100.0 | |

Source: Gunson Resources Limited.

Thin sandy beds are also present in the upper three to nine metres of the Toolonga Calcilutite. These sandy beds typically occur below clay beds. Mineral resource drillhole logs characterise the top of the Toolonga Calcilutite as predominantly sandy or silty clay. As such, the Toolonga Calcilutite is interpreted to typically form a confining layer.

Beneath the northern project area, erosion of the upper Toolonga Calcilutite has formed a shallow palaeodrainage surface. The palaeodrainage surface is interpreted from the mineral resource drilling. Figure 26 shows the interpreted basal elevation of the superficial formations and evidence of a palaeodrainage surface. Based on this interpretation, the roof structures of the Toolonga Calcilutite form groundwater divides that potentially control local groundwater flows. The roof structures dip to the west and northwest beneath the southern and northern project areas. The southern area may have localised depressions in the Toolonga Calcilutite that also control flow, but these are evidently not as well developed as in the north. Recharge from rainfall infiltration that reaches the Toolonga Calcilutite might be diverted laterally along the contact.

To the north of the project area, the Peron Sandstone is predominantly removed by erosion, has no surface expression, dips below and is interbedded with marine clay deposits (Figure 7). In this setting aquifer systems exist both in shell coquina beach ridge and estuarine to shallow marine deposits in foreshore areas of and beneath Hamelin Pool. Thin, perched groundwater lenses in the shell coquina beach ridges are recharged by direct rainfall and locally may contain fresh groundwater resources. The groundwater systems in foreshore areas of the Hamelin Pool are recharged by rainfall (meteoric), with occasional inundations by hypersaline seawater (BMR, 1990).

Superficial formations aquifers in the Shark Bay area also exist in several other settings:

- Shallow groundwater (up to about 30 m depth) utilised by Tamala Station for stock water. This groundwater resource is probably restricted to fresh to brackish water lenses overlying saline groundwater within the Tamala Limestone.
- Unconfined (or semi-confined) groundwater in recharge areas where the Windalia Sand Member and Birdrong Sandstone overly Tumblagooda Sandstone on the Ajana Ridge.
- Small-scale brackish groundwater resources in low-lying areas where the superficial formations cover depressions in the Toolonga Calcilutite. Several soaks, which possibly fall in this category, exist at the Coburn Homestead and probably existed on the now derelict Cooloomia Station. These aquifers are probably localised features that are physically separated from the Birdrong Sandstone and Kopke Sandstone by aquitards such as the Toolonga Calcilutite and Alinga Formation.

4.2.2 Groundwater Levels

The superficial formations beneath the project area are dry (above the water table) except for thin, saturated zones in depressions within the Toolonga Calcilutite.

Within SMB2, there is a vertically upward groundwater flow gradient from the Toolonga Calcilutite to the superficial formations. Based on these data, it is interpreted that the Toolonga Calcilutite and

potentially the underlying confined aquifer systems are discharging into the superficial formations beneath the northern project area and Hamelin Pool.

Interpreted baseline water table elevations in the superficial formations and Toolonga Calcilutite are shown on Figure 27. These interpretations have been expanded on Figure 28 (plan view) and Figure 29 (section view) to describe areas where the superficial formations are saturated and to indicate in a more regional context the flow paths and discharge to Nilemah Embayment and Hamelin Pool.

The water table is recharged by both rainfall infiltration and upward leakage from the Toolonga Calcilutite. Most rainfall probably does not reach the water table, but is lost to evaporation and evapotranspiration. Rainfall recharge that does pass through the soil profile is probably brackish due to the mobilisation of the stored soil salts and becomes saline as it flows down gradient towards Hamelin Pool. Groundwater level data from the site investigations show water table elevations in the range from 0.7 to 29.6 m AHD. The water table occurs within the Toolonga Calcilutite beneath most of the project area and within the superficial formations only beneath the northern project area. Groundwater flow is to the northwest and Hamelin Pool under a hydraulic gradient of about 0.002 (dimensionless). The superficial formations aquifer systems discharge into Nilemah Embayment and Hamelin Pool.

Figure 29 shows that in nearshore areas marine clay deposits control the local groundwater flow systems. The presence of the marine clays is interpreted to be linked to the salina occurrences and the predominant isolation of the water table environment beneath shell coquina dunes on the fringe of Hamelin Pool. The salinas appear to form in depressions above the water table, being basins for surface water flows and seasonal groundwater discharge by capillary rise and evaporation. The marine clay also constrains discharge from the Peron Sandstone into Hamelin Pool.

Throughflow of groundwater in the superficial formations is expected to be small-scale given the known hydraulic gradient and limited saturated thickness of the reworked Peron Sandstone.

4.2.3 Aquifer Parameters

The hydraulic characteristics of the superficial formations and water table environment have been interpreted from the aquifer tests in SMB2, SMB3 and SMB4 are summarised in Table 11.

Table 11
Interpreted Superficial Formations and Shallow Toolonga Calcilutite Aquifer Parameters

| Aquifer System | Hydraulic Conductivity (m/day) | | Storativity (dimensionless) |
|---|--------------------------------|---------|-----------------------------|
| | Range | Average | |
| Superficial Formations ¹ | 5 – 15 | 10 | Not Determined |
| Shallow Toolonga Calcilutite – Clay Beds | 0.1 | 0.1 | 2.2 x 10 ⁻⁵ |
| Shallow Toolonga Calcilutite – Sandy Beds | 0.05 – 2.0 | 0.6 | Not Determined |

Note: 1 The superficial formations test sections are predominantly unsaturated sands.

Based on the interpreted aquifer parameters, the superficial formations are comparatively homogeneous and transmissive in saturated profiles.

4.2.4 Shallow Groundwater Quality

The sampled groundwater is saline, slightly acidic with pH 6.2 to 6.7 and a sodium-chloride type. The groundwater becomes hypersaline further down gradient in the Nilemah Embayment. Salinities increase from about 11,000 mg/L TDS near SMB4 to greater than 67,000 mg/L in Nilemah Embayment (near STB1). Pore water salinities greater than 200,000 mg/L are reported (BMR, 1990) beneath clay pan areas of the salina.

The results of the superficial formations and shallow Toolonga Calcilutite groundwater quality analyses are summarised in Table 12. These quality data are also plotted on a Piper Diagram on Figure 30.

Table 12
Summary of Shallow Groundwater Quality

| Sample | Units | STB1 | SMB2s | SMB2d | STB3 | SMB4d |
|---|----------|-----------|-----------|-----------|-----------|-----------|
| Date Sampled | | 13-Aug-04 | 13-Aug-04 | 12-Aug-04 | 12-Aug-04 | 12-Aug-04 |
| Physio-chemical Parameters | | | | | | |
| Lab pH | pH Units | 6.6 | 6.3 | 6.7 | 6.2 | 6.2 |
| Field pH | pH Units | - | 5.9 | 7 | 6.6 | - |
| Electrical Conductivity | μS/cm | 91,500 | 17,600 | 34,500 | 47,000 | 17,400 |
| Total Dissolved Solids (grav.) | mg/L | 67,840 | 14,052 | 25,388 | 34,476 | 11,172 |
| Sum of Ions (calc.) | mg/L | 67,072 | 11,516 | 25,041 | 30,543 | 10,295 |
| Alkalinity (Total) as CaCO ₃ | mg/L | 228 | 750 | 265 | 129 | 285 |
| Colour (True) | PCU | 10 | 60 | 10 | 10 | 35 |
| Hardness (Total) by Calculation | mg/L | 12,000 | 430 | 4,300 | 6,000 | 880 |
| Major Ions | | | | | | |
| Sodium | mg/L | 21,000 | 4,200 | 8,100 | 10,000 | 3,700 |
| Potassium | mg/L | 560 | 72 | 210 | 280 | 99 |
| Calcium | mg/L | 1,200 | 56 | 420 | 590 | 88 |
| Magnesium | mg/L | 2,200 | 72 | 780 | 1,100 | 160 |
| Chloride | mg/L | 37,000 | 5,100 | 13,000 | 17,000 | 4,900 |
| Carbonate | mg/L | <1 | <1 | <1 | <1 | <1 |
| Bicarbonate | mg/L | 278 | 915 | 324 | 158 | 348 |
| Sulphate | mg/L | 4,800 | 1,100 | 2,200 | 1,400 | 1,000 |
| Nitrate | mg/L | 34 | 0.99 | 6.88 | 15 | <0.2 |
| Nitrite | mg/L | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 |
| Fluoride | mg/L | 0.62 | 0.46 | 0.64 | 0.98 | 0.14 |
| Silica (as SiO ₂) | mg/L | 21 | 193 | 41 | 60 | 140 |
| Cation anion balance | % | 0.86 | 3.06 | 2.89 | 4.71 | 4.71 |

Table 12 (continued)

| Sample | Units | STB1 | SMB2s | SMB2d | STB3 | SMB4d |
|-----------------------------|-------|-----------|-----------|-----------|-----------|-----------|
| Date Sampled | | 13-Aug-04 | 13-Aug-04 | 12-Aug-04 | 12-Aug-04 | 12-Aug-04 |
| Minor and Trace Ions | | | | | | |
| Aluminium | mg/L | <0.1 | 12 | <0.1 | 0.2 | 4.4 |
| Arsenic | mg/L | <0.005 | 0.089 | 0.007 | 0.008 | 0.063 |
| Cadmium | mg/L | <0.001 | <0.001 | <0.001 | <0.001 | <0.001 |
| Copper | mg/L | <0.5 | <0.05 | <0.05 | 0.05 | <0.05 |
| Iron – Total | mg/L | 0.1 | 8.6 | 0.23 | 0.15 | 10 |
| Manganese | mg/L | <0.5 | 0.5 | 0.85 | 0.1 | 1.1 |
| Mercury | mg/L | <0.0005 | <0.0005 | <0.0005 | <0.0005 | <0.0005 |
| Lead | mg/L | <0.005 | <0.005 | <0.005 | <0.005 | <0.005 |
| Selenium | mg/L | <0.01 | <0.01 | <0.01 | <0.01 | <0.01 |
| Zinc | mg/L | <0.5 | 0.1 | 0.05 | 0.1 | 0.05 |

The groundwater in SMB2s and SMB4d has higher proportions of chloride and lower sulphate than in other samples. They also have higher proportions of sodium and lower magnesium than in other samples. It is apparent that the higher salinity sources may become slightly enriched in magnesium and depleted of sulphate over time.

Variable concentrations of nitrate are detected in the samples, the lowest being in groundwater from SMB2s and SMB4d, which also have the lowest salinities. Variable concentrations of iron and aluminium are detected. As the analysis of total iron was conducted on unfiltered samples, this variation may be due to the presence of particulate matter. Other minor and trace metals were close to or below the Limit of Reporting.

Stable isotope investigations of groundwater in the Nilemah Embayment (BMR, 1990) conclude that the primary recharge source is from water of meteoric origin. Shallow groundwater in the Nilemah Embayment apparently receives very little input from Hamelin Pool and only responds to tidal influences close to the shoreline.

4.2.5 Superficial Formations Conceptual Hydrogeological Model

The conceptual hydrogeological model of the superficial formations has been developed primarily to determine the likely effects of mine dewatering and disposal of tailings as a slurry on the local environment. Details of the conceptual hydrogeological model are predominantly based on:

- Data from mineral resource drilling by Gunson Resources;
- hydrogeological investigations in the project area; and
- the findings of a geo-biology study (BMR, 1990) within Hamelin Pool and surrounds.

The conceptual hydrogeological model of the superficial formations and water table environment is shown on Figure 31. Key elements of the conceptual hydrogeological model include:

- Reworked deposits of Peron Sandstone predominantly form the superficial formations within the project area.
- Thin saturated intervals of the reworked Peron Sandstone only occur within the northern project area. Elsewhere, the superficial formations are dry.
- In areas where the superficial formations are dry, the water table occurs in the underlying Toolonga Calcilutite. Upper beds of the Toolonga Calcilutite are characterised by sandy or silty clay, with irregular thin sandy interbeds.
- Where the superficial formations are saturated, the water table is recharged by both rainfall infiltration and upward leakage from the regional confined aquifer systems through the Toolonga Calcilutite. Most rainfall is anticipated not to reach the water table, being lost to evaporation and evapotranspiration.
- Where saturated, the superficial formations are comparatively homogeneous and have interpreted average hydraulic conductivity of about 10 m/day.
- The upper Toolonga Calcilutite typically forms a low-transmissivity, low-storage groundwater environment. The range of interpreted hydraulic conductivity for the shallow Toolonga Calcilutite is 0.05 to 2.0 m/day, average 0.6 m/day. Groundwater flow would occur in the upper sandy beds but is expected to be small-scale.
- Groundwater flow is towards the northwest and Hamelin Pool under a hydraulic gradient of 0.002 (dimensionless). Groundwater flow within the superficial formations is locally controlled and constrained by:
 - small-scale palaeodrainage features on the Toolonga Calcilutite contact; and
 - marine clay deposits in foreshore areas of Hamelin Pool.

Both of these aspects influence the location of and mechanisms for discharge into Hamelin Pool.

- Both the superficial formations and Toolonga Calcilutite discharge into Hamelin Pool. The discharge occurs by upward leakage through overlying marine clay deposits.
- Marine clay outcrops or subcrops in the Nilemah Embayment are characterised by topographic depressions, clay pans and salina. The salina areas overlie a shallow water table, hypersaline groundwater and are interpreted to form groundwater discharge zones. The groundwater discharge is understood to be predominantly from evaporation losses; the water table occurs beneath the ground surface.

-
- Shell coquina beach ridges that overlie marine clay deposits on the fringe of Hamelin Pool form discrete catchment zones wherein direct infiltration of rainfall leads to local lenses of fresh groundwater and discharge occurs locally at low tide.
 - Groundwater in the superficial formations and shallow Toolonga Calcilutite is saline to hypersaline, slightly acidic and a sodium-chloride type. Salinities increase along the flow paths in the measured range from 11,000 to 67,000 mg/L TDS. Salinities within the Peron Sandstone and salina areas become increasingly hypersaline nearer Hamelin Pool and associated salina discharge areas.

4.3 Confined Aquifer Systems

4.3.1 Aquifer Profiles

There are five significant confined aquifers in the Gascoyne Platform:

1. Windalia Radiolarite
2. Windalia Sand Member
3. Birdrong Sandstone
4. Kopke Sandstone
5. Tumblagooda Sandstone

Windalia Radiolarite is interpreted to be present beneath the northern project area. Where present, this aquifer yields significant supplies, presumably from secondary porosity (i.e. fracturing) in the siliceous, cherty or flinty beds. Very strong anisotropy of the hydraulic conductivity has been observed from bores drilled into this formation; usually in old bores that were drilled using cable-tool methods. Upwards heads of between 7 and 22 m have been recorded during the drilling of Yaringa No. 5 and Yaringa No. 15, with further head rises after the deeper Birdrong Sandstone was intersected. The upward head distributions may indicate that vertical flow between these aquifer systems is limited. Locally, Spinifex Bore exhibited upward heads of about 20 m while drilling through the Windalia Radiolarite between 125 and 128 m depth (Playford & Chase, 1955).

Spinifex Bore 2 and Nilemah Artesian No. 1A source groundwater from the Windalia Radiolarite nearest the project area, although there is doubt whether abstraction is only from this aquifer system.

The Windalia Radiolarite is typically about 15 m thick, but probably thins towards the areas where the Windalia Sand Member is present. There are no aquifer parameters available in either the literature or bore completion reports.

Windalia Sand Member is restricted to the southern Gascoyne Platform, beneath Coburn, Hamelin, Meadow and possibly Nerren Nerren stations. This aquifer system overlies the Birdrong Sandstone and is utilised by many of the pastoralists east of the project area as it provides adequate groundwater

supplies of acceptable quality. Where the supply is inadequate or the groundwater quality exceeds stock limits for salinity, pastoral bores have been extended down into the Birdrong Sandstone.

The Windalia Sand Member is typically in excess of 20 m thick, but thins towards the west (near Spinifex Bore, Nilemah Artesian No. 1A), and to the north (near Hamelin No. 5 and Kevin's Bore). In Coburn 1, this formation is 32 m thick. Groundwater levels are typically lower than in the Birdrong Sandstone and Kopke Sandstone, indicating upward hydraulic heads due to the presence of Muderong Shale or intrinsic transmissivity anisotropy within the sedimentary bedding. The aquifer properties of the Windalia Sand Member are not known precisely; they have not been measured or published.

Birdrong Sandstone is the most commonly used aquifer in the Carnarvon Basin due to its regional distribution and capability to yield large groundwater supplies.

Typically, the hydraulic conductivity of the Birdrong Sandstone is between about 5 and 10 m/day. There are no published storage coefficients for this aquifer. Static groundwater level measurements in non-flowing bores reported by McWhae, (1958) indicate the Birdrong Sandstone has a westerly-dipping hydraulic gradient of about 5×10^{-4} (dimensionless).

Kopke Sandstone is probably the second most important groundwater source in the middle and southern Gascoyne Platform. Where the formation is shallow, it is utilised as a lower salinity groundwater source in preference to the Birdrong Sandstone. In more westerly parts, the Kopke Sandstone is generally too deep (greater than 300 to 500 m) for widespread use. Apart from the large volume of groundwater in storage in the Kopke Sandstone, it is possible that this formation is in hydraulic connection with the Tumblagooda Sandstone beneath the Ajana Ridge.

This formation has been investigated during petroleum exploration drilling programmes. Porosities of 23 to 28% have been reported from Yaringa 1, Yaringa 1 East and Coburn 1 (Wills and Dogramaci, 2000) with hydraulic conductivities of about 4 m/day. The hydraulic gradient is in the order of 1×10^{-4} (dimensionless) to the west.

The age and flow direction of groundwater in the Kopke Sandstone was examined by Hiller *et al.*, (2002) using analyses of stable isotopes and their ratios. The bores they tested on Carbla and Yaringa stations suggested the groundwater probably entered the formation during wetter climatic conditions and subsequently has had low rates of throughflow. They inferred that this historical recharge and low rates of throughflow have resulted in lower salinities in this aquifer as a whole.

Tumblagooda Sandstone is a large regional aquifer. This formation is generally too deep to be significantly exploited to date, except in areas on the eastern and southern margins of the Carnarvon Basin. Presently, the only significant abstraction from the Tumblagooda Sandstone is in the Kalbarri region, where it outcrops. The formation has been investigated in petroleum exploration activities.

A summary of the hydraulic parameters derived from petroleum exploration work is presented by Wills and Dogramaci (2000). In general, the Tumblagooda Sandstone is described as having a porosity of about 22 % and a hydraulic conductivity of about 1 m/day. Hydraulic gradients in this formation are

unknown. At depths less than 1,000 m, this formation is generally of lower transmissivity due to pore space clogging by silica overgrowths and kaolinitic clay (Wills and Dogramaci, 2000).

4.3.2 Potentiometric Levels

Few reliable Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone groundwater level data are available. The absence of reliable groundwater level data constrains knowledge of the regional groundwater flow systems, both in terms of the individual aquifers and the confined aquifer systems as a whole. At present, the groundwater flow systems are characterised only in conceptual terms. There is a comparatively poor understanding of recharge and discharge flow paths, vertical flow gradients and leakage between the confined aquifers and, drawdown responses to large-scale historical abstraction.

The groundwater levels from bores with reasonably reliable stratigraphic determinations are shown on Figure 32 (Windalia Sand Member) and Figure 33 (Birdrong Sandstone). In a regional context, the interpreted groundwater level contours show westerly hydraulic gradients and groundwater flow, with discharge offshore beneath the Indian Ocean. Local gradients show northwest and southwest groundwater flow aspects. Within the Windalia Sand Member, comparatively high groundwater levels are aligned with the mapped distribution of sand beds: the groundwater levels decline near the interpreted facies change to the Windalia Radiolarite.

Regional groundwater flow gradients of 10^{-3} to 10^{-4} (dimensionless) to the west are interpreted in the Birdrong Sandstone. Groundwater throughflow, based on these hydraulic gradients and average hydraulic conductivities, has a regional average of about 3 m/annum per unit cross-sectional area or 2.7 GL/annum beneath the 33 km length of the project area. No through-flow rates are interpreted for the Kopke Sandstone.

Large upward hydraulic gradients occur within the Windalia Radiolarite, interpreted to be linked to strong vertical anisotropy in the transmissivity of fractured flint beds. Upward hydraulic gradients are also extrapolated within and between the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone. These upward hydraulic gradients indicate vertical discharge into the overlying confining layers formed by the Alinga Formation and Toolonga Calcilutite and also the superficial formations.

4.3.3 Aquifer Characteristics

Data on the hydraulic characteristics of the regional confined aquifer systems are available from petroleum exploration activities and the findings of the completed site investigations. A summary of the available aquifer parameters data is provided in Table 13.

Table 13
Confined Aquifers Hydraulic Parameters

| Aquifer System | Hydraulic Conductivity (m/day) | | Storativity (dimensionless) | |
|-----------------------|--------------------------------|---------------------|-----------------------------|----------------------|
| | Research References | Site Investigations | Research References | Site Investigations |
| Windalia Radiolarite | No Record | No Record | No Record | No Record |
| Windalia Sand Member | No Record | No Record | No Record | No Record |
| Birdrong Sandstone | 5 – 10 | 7 – 13 | No Record | 5.8×10^{-4} |
| Kopke Sandstone | 4 | 2 | No Record | 1.6×10^{-4} |
| Tumblagooda Sandstone | 1 | No Record | No Record | No Record |

The interpretations from the site investigations are compatible with those from research literature.

The Toolonga Calcilutite, Alinga Formation, Faure Formation and Dirk Hartog Group form thick successions of predominantly argillaceous and/or chemical sediments that are interpreted to characterised by low-transmissivity. These successions confine the regional aquifer systems, constraining vertical groundwater flow. There are no data on the hydraulic conductivity of these formations. Interpreted lateral and vertical hydraulic conductivities range from 1×10^{-2} to 1×10^{-4} m/day and 1×10^{-3} to 1×10^{-5} m/day.

4.3.4 Confined Aquifer Groundwater Quality

Generally, the salinities of the regional confined aquifers are interpreted to decrease with depth as described in Table 14. Variations in quality of the confined aquifer groundwater resources have historically been the driving factor for deeper drilling for groundwater supplies and hence the occurrence of more Kopke Sandstone than Birdrong Sandstone intersections in some areas.

Table 14
Summary of Interpreted Regional Groundwater Salinities

| Formation | Typical Salinity Range (mg/L TDS) |
|------------------------|--|
| Superficial Formations | 14,000 (on site) >60,000 (Marine Deposits in Nilemah Embayment) |
| Toolonga Calcilutite | 11,200 – 34,400 (on site) |
| Windalia Sand Member | 5,000 – 9,000 |
| Birdrong Sandstone | 3,500 – 8,000 |
| Kopke Sandstone | 1,500 – 12,000 |
| Tumblagooda Sandstone | <1,000 |

Mention is made in the literature of heterogeneity in the groundwater quality within the main aquifers such as the Kopke Sandstone (Wills and Dogramaci, 2000). Many of the bores in the Carnarvon Basin have dissimilar salinities to neighbouring bores and are not easily correlated to groundwater level maps that attempt to differentiate the confined aquifers. In general, however, the trends given in Table 14 are a reasonable indicator of the groundwater source quality, except where a bore is screened within (or corroded through to) multiple aquifers.

Beneath the project area, the groundwater from the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone is near neutral to weakly alkaline, brackish to saline and of a sodium-chloride type. The results of the site investigation sampling and groundwater quality analyses are summarised in Table 15. These quality data are also plotted on a Piper Diagram on Figure 30.

Table 15
Summary of Confined Aquifers Groundwater Quality

| Sample | Units | Spinifex 2 ¹ | Coburn 7 ² | DMB1(k) | DMB1(b) | DMB1(w) | DTB1 |
|---|----------|-------------------------|-----------------------|----------|----------|----------|-----------|
| Date Sampled | | 21-Aug-03 | 21-Aug-03 | 8-Dec-04 | 7-Dec-04 | 6-Dec-04 | 17-Jan-05 |
| Physio-chemical Parameters | | | | | | | |
| Lab pH | pH Units | 7.15 | 8.0 | 7.3 | 7.7 | 7.9 | 7.3 |
| Field pH | pH Units | - | - | 7.0 | 6.8 | 7.0 | 7.0 |
| Electrical Conductivity | µS/cm | 11,000 | 15,000 | 17,000 | 11,000 | 14,000 | 15,000 |
| Total Dissolved Solids (grav.) | mg/L | 7,300 | 10,000 | 12,000 | 7,750 | 9,100 | 8,900 |
| Sum of Ions (calc.) | mg/L | 7,166 | 10,021 | 11,091 | 6,647 | 8,166 | 9,898 |
| Alkalinity (Total) as CaCO ₃ | mg/L | - | - | 300 | 350 | 300 | 140 |
| Hardness (Total) by Calculation | mg/L | 1,200 | 1,900 | 2,200 | 1,280 | 1,420 | 2,300 |
| Major Ions | | | | | | | |
| Sodium | mg/L | 2,100 | 2,900 | 3,280 | 1,960 | 2,480 | 3,000 |
| Potassium | mg/L | 92 | 120 | 135 | 99 | 105 | 120 |
| Calcium | mg/L | 160 | 200 | 360 | 220 | 200 | 330 |
| Magnesium | mg/L | 210 | 340 | 320 | 180 | 220 | 350 |
| Chloride | mg/L | 3,600 | 5,200 | 5,540 | 3,210 | 4,080 | 4,900 |
| Carbonate | mg/L | <1 | <1 | <1 | <1 | <1 | <1 |
| Bicarbonate | mg/L | 230 | 310 | 371 | 425 | 371 | 160 |
| Sulphate | mg/L | 880 | 1,100 | 1,270 | 765 | 895 | 1,100 |
| Nitrate (as Nitrate) | mg/L | 0.8 | <0.1 | 0.33 | <0.05 | <0.05 | 0.2 |
| Nitrite | mg/L | <0.1 | <0.1 | - | - | - | <0.2 |
| Fluoride | mg/L | - | - | 0.6 | 0.8 | 0.7 | 0.5 |
| Silica (as SiO ₂) | mg/L | 8 | 6 | - | - | - | 17 |

Table 15 (continued)

| Sample | Units | Spinifex 2 ¹ | Coburn 7 ² | DMB1(k) | DMB1(b) | DMB1(w) | DTB1 |
|-----------------------------|-------|-------------------------|-----------------------|----------|----------|----------|-----------|
| Date Sampled | | 21-Aug-03 | 21-Aug-03 | 8-Dec-04 | 7-Dec-04 | 6-Dec-04 | 17-Jan-05 |
| Minor and Trace Ions | | | | | | | |
| Aluminium | mg/L | - | - | - | - | - | <0.1 |
| Arsenic | mg/L | - | - | - | - | - | <0.005 |
| Cadmium | mg/L | - | - | - | - | - | <0.005 |
| Copper | mg/L | - | - | - | - | - | <0.05 |
| Iron - Total | mg/L | <0.01 | <0.01 | - | - | - | 3.0 |
| Manganese | mg/L | <0.01 | 0.12 | - | - | - | 0.3 |
| Mercury | mg/L | - | - | - | - | - | <0.0005 |
| Lead | mg/L | - | - | - | - | - | <0.05 |
| Selenium | mg/L | - | - | - | - | - | <0.005 |
| Zinc | mg/L | - | - | - | - | - | 0.05 |

Notes: 1 - Sample derived from tank at Hamelin No. 22
 2 - Sample derived from tank beside Coburn No. 7
 DMB1(k) - Kopke Sandstone
 DMB1(b) - Birdrong Sandstone
 DMB1(w) - Windalia Sand Member
 DTB1 – Birdrong Sandstone and Kopke Sandstone combined

The salinities have similar discrepancies between the values determined by evaporation and sum of ions as reported by Wills and Dogramaci, 2000. Typically, the sum of ions values are lower than that determined by evaporation.

Minor ion and trace metals analyses (Table 15) show only iron and manganese were detected at concentrations 3.0 and 0.3 mg/L. A concentration of 0.05 mg/L for zinc is at the Limit of Reporting.

4.3.5 Confined Aquifer Conceptual Hydrogeological Model

The conceptual hydrogeological model of the confined regional aquifer systems is based on published regional geology and hydrogeology and results of site investigations. The conceptual hydrogeological model of the confined aquifer systems is shown on Figure 34.

Key elements of the confined aquifer conceptual hydrogeological model include:

- Main aquifers in the southern Gascoyne Platform being:
 - Windalia Radiolarite
 - Windalia Sand Member
 - Birdrong Sandstone
 - Kopke Sandstone

-
- Tumblagooda Sandstone
 - The relationship of the Windalia Radiolarite and Windalia Sand Member is interpreted as a facies change from east to west.
 - The Muderong Shale Formation is probably discontinuous, particularly in the eastern regions of the study area. Continuous intersections have been recorded in western and far-northern parts of the Shark Bay area, but not in the eastern parts of Hamelin and Coburn stations as well as Meadow Station.
 - There are no conclusive indications of an aquitard between the Birdrong Sandstone and Kopke Sandstone. However, groundwater level and salinity differences are apparent, suggesting both structural and stratigraphic influences on recharge zones and groundwater flow.
 - The confined aquifers are recharged where they outcrop (or sub-crop below superficial cover) along the Ajana Ridge and to south and southeast (near the old Murchison House Station area). The southern recharge area extends to the groundwater divide with the Murchison River catchment.
 - Potentially, there is a regional groundwater resource in the Tumblagooda Sandstone that recharges the Kopke Sandstone beneath the Ajana Ridge.
 - Regional groundwater flow is westward under hydraulic gradients of 1×10^{-3} to 1×10^{-4} (dimensionless), with discharge into the Indian Ocean. On a local scale flow is also to the northwest, with discharge into Hamelin Pool.
 - Upward hydraulic gradients are interpreted between most of the confined aquifers in the western groundwater flow domains. As such, the confined aquifers discharge through the Alinga Formation and Toolonga Calcilutite in the vicinity of the project area and Hamelin Pool.
 - The aquifers formed by the Birdrong Sandstone and Kopke Sandstone are characterised by hydraulic conductivities in the range from 5 to 13 and 2 to 4 m/day. Confined storage coefficients of 5.8×10^{-4} and 1.6×10^{-4} have been interpreted from results of site investigations.
 - Groundwater resources of the confined aquifer systems are brackish to saline, with TDS concentrations of 1,000 to 35,000 mg/L. In a regional context, the salinity is interpreted to progressively decrease with depth.
 - Groundwater in the confined aquifers beneath the project area is brackish to saline (TDS 6,650 to 11,100 mg/L), weakly alkaline and a sodium-chloride type. The lowest and highest salinity groundwater occurs in the Birdrong Sandstone and underlying Kopke Sandstone.
 - Regional groundwater chemistry and ionic ratios indicate that the lower salinities in the confined aquifers are probably the result of higher recharge rates in the past, when the climate was wetter. Higher salinities in shallow formations near recharge areas overlying the Ajana Ridge, suggest that recharge rates are presently about 0.5% of total annual rainfall. Recharge to the Windalia Radiolarite

and Birdrong Sandstone is estimated at 4.5 GL/annum based on the distribution of these aquifer systems in the area between Shark Bay and Carnarvon.

- The large losses of groundwater from the Gascoyne Platform aquifer systems (through uncontrolled flow from artesian bores) may be above the natural recharge rate.

4.4 Groundwater Management

The DoE manages the groundwater resources in the Carnarvon Basin, although many of the pastoral bores drawing from the confined aquifers are unlicensed. Either plugging for abandonment or re-lining and re-capping has recently rehabilitated many of the older bores that were flowing uncontrollably under artesian conditions. This programme has involved several bores in the Shark Bay area, but is incomplete. Near the project area, uncontrolled artesian bores still remain on Hamelin Station (Spinifex Bore Nos. 1 and 2), Six Mile Well on Carbla Station and possibly also old Nanga Station (Nilemah No. 2). These bores may be rehabilitated in the future.

Prior to the recent rehabilitation programme, it was estimated that of the approximately 140 artesian bores have been drilled within the Carnarvon Basin since the early 1900s and only 40 still have substantial uncontrolled flows. The remainder have either stopped flowing or flows were reduced to a trickle (Astill *et al.* 2002). From these 40 bores, it is estimated that about 15 GL/annum is currently being lost to seepage and evaporation.

Several superficial formations groundwater flow models have been developed to assess sand tailings water recovery concepts, mounding of the water table due to tailings disposal, consumptive process water demand, the potential fate of tailings waters that are not recovered and pit dewatering. One set of models is generic, simulating the sand-stacker operations in a suite of variable pit settings. The other model is specific to sand-stacker operations in the proposed northern mining developments, predicting the impacts of tailings waters that are not recovered. The northern pit is specifically investigated due to its setting, including proximity to outcrops of Toolonga Calcilutite and discharge zones of the superficial formations within Hamelin Pool.

5.1 Superficial Formations Groundwater Flow Modelling

The generic set of models is simple, with only one active layer that represents the superficial formations. The northern pit model conforms to the conceptual hydrogeological model. The simulated superficial formations are isotropic, homogeneous and transmissive. The models have a base representing the low-transmissivity and low-storage domain formed by the Toolonga Calcilutite. Sandy and silty intervals within the upper Toolonga Calcilutite are not represented.

In all generic model simulations the superficial formations are dry but being recharged locally in domains compatible with the sand-stacker operations and traverses. Initially, the ground-surface topography and roof structure of Toolonga Calcilutite were incorporated into the groundwater flow models. It was found, however, that this caused unnecessary complications for the assessment of sand tailings water recovery and pit dewatering, and made an insignificant difference to the outcomes. Subsequent models use a flat basement and surface topography.

The model of the northern pit incorporates all of the key characteristics of the generic model. The primary difference is that it is site-specific in terms of topography and Toolonga Calcilutite occurrence with the northern pit. It also simulates dual sand-stacker operations (four sand-stackers) with comparatively long traverses.

5.1.1 Model Code

The models are developed in MODFLOW-SURFACT, which is a three-dimensional block-centred finite-difference code developed by the USGS. This code allows groundwater flow within saturated and unsaturated media. This aspect is critical for the re-wetting of the superficial formations due to sand tailings disposal and subsequent drainage and groundwater recovery aspects. Visual MODFLOW from Waterloo Hydrogeologic Inc. is used as the pre- and post-processor.

5.1.2 Generic Model Domains

The generic sets of models consist of 254 by 132 rows and columns forming matrices of 33,528 cells. The dimensions of the rows were varied between the models to allow for sand-stacker advance rates of 5, 10, 15, 35, 55 and 80 m/day across increasingly wider pits, Figure 35 (a and b).

5.1.3 Boundary Conditions

The models are sized such that the boundaries occur beyond the forecast extent of any significant impacts due to mining. Several separate models have been developed to simulate different rates of tailing and in all cases the boundaries are set to general no-flow conditions/characteristics.

The models do not include rainfall recharge.

5.1.4 Hydraulic Parameters

The hydraulic characteristics of the generic superficial formations groundwater flow models are shown in Table 16. They are based on the results of the site investigation and typical values for well-sorted medium to fine-grained sands.

Table 16
Simulated Peron Sandstone Hydraulic Parameters

| Model Layer | Formation | Hydraulic Conductivity (m/day) | | | Specific Yield (dimensionless) |
|-------------|-----------------|--------------------------------|----------------|----------------|--------------------------------|
| | | K _x | K _y | K _z | |
| 1 | Peron Sandstone | 10 | 10 | 10 | 0.2 |

5.2 Predicted Sand Tailings Water Recovery

To determine practical and reasonable strategies for recovery of groundwater from the disposed sand tailings, the operational aspects of the mining and tailings processes have been considered. These aspects include materials handling, pit dimensions, sand-stacker operations and local aquifer setting. Some of these aspects are constant and others are variable, as shown in Table 17. The typical mine profile within the superficial formations (Figure 36) is also considered.

Table 17
Sand Tailings Water Recovery – Constraints and Variables

| Variables | Constants |
|---|---------------------------------|
| Pit width, depth and length | Ore processing rate |
| Pit shape | Ore processing time |
| Mining rate | Sand tailings disposal rates |
| Thickness of sand beneath the pit floor | Specific yield of sand tailings |
| Number of plants operating per pit | Plant water throughput rate |

The developed sand tailings water recovery concepts are compatible with the mine plans and schedules, and have been iterated several times to refine the developed strategies and optimise water recovery. The predominant theme behind the water recovery concepts is the minimisation of the flow paths for release of water from the disposed sand tailings. Successive developments of the conceptual mine water recovery strategies are shown on Figures 37 (a and b) and 38 (a to d).

1. The initial concept on Figure 37a uses open drains, corresponding to low areas on the pit floor, to recover water from the advancing front of disposed sand tailings. An underdrain along one side of the pit captures water from the slimes disposal area. This strategy is adequate for narrow pits, but not for wide pit areas.
2. The second concept (Figure 37b) is based on the sand-stackers traversing the pits and using the bottoms of the swales between overburden stockpiles as open lateral drains. Longitudinal drains would also be maintained along the sides of the pits to collect residual seepage from previous sand-stacker traverses and from the slimes disposal area. This concept assumes that two sand-stackers would each backfill half of the pits. Variations on this theme were also assessed using sand-stackers traversing inwards from the outside of the pit, outwards from the centre of the pit, or from one side to another.
3. The third concept adopts most of the ideas from the second, but assumes that two sand-stackers traverse the entire pit area in tandem Figure 38 (a to d). Open drains would also be present on both (western and eastern) sides of the pit, with one underdrain also collecting seepage from beneath the slimes disposal areas. Open drains would be maintained where possible behind the operating sand-stackers to collect residual water. Control of the slimes content in the process water stream would be maintained by periodically and temporarily diverting some of the return water through the slimes disposal areas for settlement.

5.2.1 Controls on Sand Tailings Water Recovery

Findings of the iterative development of sand tailings water recovery concepts indicate that numerous factors control water recovery. These factors include:

- Number of drains.
- Drain efficiency (conductance) - 1,000 m²/day.
- Drain spacing – variable, see model domains on Figure 37 (a and b).
- Sand thicknesses beneath the pit floor of 0, 2, 5, and 10 m.
- Sand-stacker advance rate of 5, 10, 15, 35, 55 or 80 m/day laterally across the pit.
- Sand-stacker cyclone underflow density of 65 % solids (i.e. 35% water).
- Discharge rate (water fraction of sand tailings) of 28,130 kL/day.

Numerous versions of the generic models have been applied to predict tailings water recovery rates and potential impacts of artificial recharge and water table mounding. Notwithstanding, it is understood that the key variables that will influence rates of tailings water recovery include the rate of sand-stacker advance and the thickness of undisturbed sand beneath the pit floor. As such, each model version simulates a different rate of sand-stacking traverses within the pit, reflecting different pit dimensions and rates of mining advances. These models were then used to simulate the rate of tailings water recovery and extent of water table mounding within the superficial formations due to variations in the thickness of sand beneath the pit floor.

The conceptual sand tailings water recovery plan shown on Figure 38 (a to d) with the preferred typical drain configurations at four stages of pit development:

- (a) The beginning of the pit with no trailing lateral drain behind the first sand-stacker traverse.
- (b) The middle of a typical sand-stacker traverse, with all drains active.
- (c) The change-over from one sand-stacker traverse to the next, with significant residual flows from the previous traverse and full flows at the start of the new sand-stacker traverse.
- (d) The end of the pit with no facing lateral drain in front of the last sand-stacker traverse.

The generic set of models incorporate the following features:

- Two sand-stackers operating in tandem at a rate of advance dictated by pit depth and overall mine advancement rate.
- Each traverse by the sand-stackers would backfill the pit (on top of the overburden) to a height compatible with rehabilitation requirements.
- Tailings water disposal from the sand-stackers is simulated using recharge cells, with rates of recharge compatible with the forecast underflow characteristics of the sand-stackers.
- Steady and constant operation of the sand-stackers has been simulated, but in practice, the units are forecast to operate for only about 81% of the time.
- Lateral (across the pit) and longitudinal (along the western and eastern sides of the pit) drains are simulated using rows or columns of drain cells. The base of each drain cell is set to the base of the pit floor, except in the trailing lateral drain that is set 5 m higher to simulate partial backfilling. The drain conductance is maintained at 1,000 m²/day.
- Lateral drains are in-filled once sand is stacked over them. As such, these drains progressively lose their functionality and are deactivated once the sand-stacker passes-by.
- The longitudinal drains remain open for at least one sand-stacker traverse, or long enough to collect residual seepage from the previous sand-stacker traverse.

- Of the three lateral drains in front of the sand-stacker, the trailing lateral drain is assumed to be partially backfilled (by about 5 m) with sand from the previous sand-stacker traverse.

The variable sand-stacker operating settings are outlined in Table 18.

Table 18
Simulated Sand-Stacker Operating Settings

| Model Setting | Sand-Stacker Advance Rate (m/day) | Sand Thickness (m, below pit-floor) |
|---------------|-----------------------------------|-------------------------------------|
| 1 | 5 | 0 |
| 2 | 5 | 2 |
| 3 | 5 | 5 |
| 4 | 5 | 10 |
| 5 | 10 | 0 |
| 6 | 10 | 2 |
| 7 | 10 | 5 |
| 8 | 10 | 10 |
| 9 | 15 | 0 |
| 10 | 15 | 2 |
| 11 | 15 | 5 |
| 12 | 15 | 10 |
| 13 | 35 | 0 |
| 14 | 35 | 2 |
| 15 | 35 | 5 |
| 16 | 35 | 10 |
| 17 | 55 | 0 |
| 18 | 55 | 2 |
| 19 | 55 | 5 |
| 20 | 55 | 10 |
| 21 | 80 | 0 |
| 22 | 80 | 2 |
| 23 | 80 | 5 |
| 24 | 80 | 10 |

5.2.2 Characterisation of Sand Tailings Water Recovery

In all settings, the sand-stacker operations result in temporary mounding of the water table within the superficial formations. The mounding distributions, and magnitudes are constrained by the lateral and longitudinal drains. The predicted build-up of the mound during the first 20 days of operation is shown

on Figure 39 for a sand-stacker advance rate of 5 m/day and no sand beneath the pit floor. As there is no trailing lateral drain in the first sand-stacker traverse, some tailings water is lost to storage beyond the pit perimeter. The mound grows in height to about 18 m beneath the sand-stackers, after 20 days operation (Figure 39).

Tailings water recovery rates are calculated using zone budget data from the predictive generic set of models. There are four components to the zone budgets:

1. Rate of tailings water use (A, constant at 28,130 kL/day) based on a maximum throughput rate of 2,200 tph. Actual rates of tailing water use will vary depending on throughput rates, cyclone underflow densities, slimes contents and slurry densities.
2. Water accumulation in aquifer storage (B) due to mounding of the water table within the superficial formations.
3. Water captured by the drains (C) from direct disposal (A) and release from storage (B).
4. Net tailings water recovery (D).

The tailings water recovery rate (as a percentage) is calculated as follows:

$$\text{Tailings Water Recovery Rate (D)} = \frac{\text{Tailings water disposal rate (A)}}{\text{Tailings water captured by the drains (C)}} \times 100$$

A graphical representation of the predicted zone budget where there is 2 m of sand below the pit floor during six traverses of the sand-stackers is shown on Figure 40. A plan view snapshot of the water mound after one sand-stacker traverse is also provided on Figure 40.

The following description broadly frames the transient zone budgets for a pit area characterised by a sand-stacker advance rate of 5m/day and a 2 m thickness of sand beneath the pit floor.

1. **Start of Pit, Days 1 to 10.** The rate of tailings water lost into aquifer storage is initially about 2,500 kL/day, and rises to about 4,200 kL/day after 7 to 10 days. In these earliest stages, the tailings water is predominantly released directly into the drains, resulting in a recovery rate of about 91%. The remaining tailings water is lost to aquifer storage, saturating the 2 m thickness of sand beneath the pit floor in the vicinity of the sand-stacker. The rate of tailings water recovered by the drains begins to stabilise after 7 to 10 days, as the mound builds sufficiently to promote flow from storage to the drains. The recovery rate at this stage has dropped to about 85%. After about 10 days, the mound height is sufficient to enable flow from storage to the drains.
2. **Days 10 to 100.** After about 10 to 15 days, the contribution of tailings water lost to aquifer storage has nearly stabilised. During this period, the recovery of tailings water steadily increases as the mound intersects more drains. The recovery rate increases from 85% to about 90%. After 100 days, the rate of flow from aquifer storage into the drains has increased to about 2,000 kL/day, and the amount being lost to storage has stabilised at about 4,750 kL/day.

3. **Days 100 to 150.** As the sand-stacker traverse approaches the far side of the pit, the longitudinal drain on the pit-edge begins to intercept and recover tailings water. The quantity of water going into storage decreases. The contour plan shown on Figure 40 shows the residual mound left after the first sand-stacker traverse.
4. **Days 150 to 151.** One sand-stacker traversal of the pit will take 150 days. One day later, the sand-stacker is relocated back at the start, to commence tailings disposal beside the first longitudinal drain. This movement sees mound developments beneath the relocated sand-stacker. At this stage, the tailings water is mostly collected by the drains on three sides. Also, water is still being released from the mound on the far side of the pit. The net result is a brief period where the recovery rates are more than 100% of the sand-stacker rate.
5. **Day 150 onwards.** The second sand-stacker traverse will develop a mound of residual tailings water that is superimposed on the residual mound from the initial sand-stacker traverse. This cumulative impact results in a slightly higher overall recovery rate as the hydraulic gradients within the sand tailings steepen and stabilise at a faster rate. This response is more prominent in the faster mining rates.
6. **End of Pit.** As the sand-stackers reach the final traverse across the end of the pit, the recovery rates begin to fall. This is a function of fewer drains near the operating sand-stacker and losses to aquifer storage beyond the end of the pit. The graph on Figure 40 indicates the reduced rates of recovery are predominantly linked to extra losses of water into aquifer storage.

The characterisation of the sand tailings water recovery has been applied to predict the most effective drainage system that would promote water use efficiency. It is understood that recovery efficiencies are improved by:

- limiting of the length of the flow paths to the drains: and
- retention of drains, where practical, on all perimeters of the sand-stackers.

Conversely, the water use efficiency is diminished if the length of flow path is increased and the number of drains is decreased.

Predictive simulations that explore these aspects and associated variation in sand tailings water recovery are outlined below.

5.2.3 Predicted Sand Tailings Water Recovery for Six Drains

The predicted net recovery rates for the simulated sand-stacker operating with six drains are summarised in Table 19 and on Figure 41 (a to b). The six active floor drains include the four oriented laterally and longitudinally as shown on Figure 38 (a to c). Similar overall recovery patterns are depicted for each setting, with lower recoveries at the start of each pit cycle and generally higher recovery rates during the middle and end stages of each pit development. Comparatively high rates of recovery are also observed during each turn-around stage of the sand-stackers.

Table 19
Predicted Rates of Sand Tailings Water Recovery for Six Drains

| Model Setting | Sand-Stacker Advance Rate (m/day) | Sand Thickness (m, below pit-floor) | Predicted Tailings Water Recovery (%) | | | |
|---------------|-----------------------------------|-------------------------------------|--|--|---|--------------------------|
| | | | First Sand-Stacker Traverse (Start of Pit) | Normal Sand-Stacker Traverse (Middle of Pit) | Last Sand-Stacker Traverse (End of Pit) | Overall Weighted Average |
| 1 | 5 | 0 | 87 | 92 | 95 | 93 |
| 2 | 5 | 2 | 85 | 90 | 94 | 92 |
| 3 | 5 | 5 | 80 | 86 | 91 | 88 |
| 4 | 5 | 10 | 70 | 76 | 84 | 79 |
| 5 | 10 | 0 | 81 | 88 | 91 | 89 |
| 6 | 10 | 2 | 78 | 85 | 90 | 87 |
| 7 | 10 | 5 | 71 | 78 | 85 | 81 |
| 8 | 10 | 10 | 58 | 65 | 76 | 70 |
| 9 | 15 | 0 | 76 | 84 | 88 | 85 |
| 10 | 15 | 2 | 72 | 80 | 85 | 82 |
| 11 | 15 | 5 | 63 | 70 | 79 | 74 |
| 12 | 15 | 10 | 48 | 55 | 67 | 60 |
| 13 | 35 | 0 | 61 | 71 | 75 | 73 |
| 14 | 35 | 2 | 53 | 63 | 71 | 67 |
| 15 | 35 | 5 | 37 | 45 | 59 | 51 |
| 16 | 35 | 10 | 16 | 22 | 36 | 28 |
| 17 | 55 | 0 | 51 | 63 | 68 | 65 |
| 18 | 55 | 2 | 40 | 51 | 61 | 56 |
| 19 | 55 | 5 | 18 | 26 | 43 | 34 |
| 20 | 55 | 10 | 3 | 5 | 15 | 9 |
| 21 | 80 | 0 | 43 | 57 | 63 | 59 |
| 22 | 80 | 2 | 27 | 39 | 53 | 46 |
| 23 | 80 | 5 | 3 | 10 | 29 | 19 |
| 24 | 80 | 10 | 0 | 0 | 2 | 1 |

The simulations indicate an average recovery rate of 68%. Tailings water losses will generally be greatest during the first traverse in each pit. Higher recoveries will result where mining is continuous. High recovery rates are also expected where rates of sand-stacker advance are less than about 15 m/day and there is less than 2 m of sand beneath the pit floor. The predicted recovery rates decrease significantly where faster sand-stacking rates (>35 m/day) and greater sand thicknesses (>5 m) occur. The results indicate there would be limited sand tailings water recovery in areas where sand thicknesses of 5 to 10 m beneath the pit-floor are linked to rates of sand-stacker advance of 55 to 80 m/day.

5.2.4 Predicted Sand Tailings Water Recovery for Two Drains

To test the sensitivity of the simulated tailings water recovery strategies, the generic models were reconfigured with only two lateral drains in front of the sand-stacker units, as shown on Figure 42. A reduced drain configuration comprising only two lateral drains is simulated to predict sand tailings water recoveries under less efficient conditions.

The lower-bound net recovery rates for the simulated sand-stacker operating settings are summarised in Table 20 and on Figure 43 (a and b). These simulations indicate an average recovery rate of about 43%.

Table 20
Predicted Rates of Sand Tailings Water Recovery for Two Drains

| Model Setting | Sand-Stacker Advance Rate (m/day) | Sand Thickness (m, below pit-floor) | Predicted Tailings Water Recovery (%) | | | |
|---------------|-----------------------------------|-------------------------------------|--|--|---|--------------------------|
| | | | First Sand-Stacker Traverse (Start of Pit) | Normal Sand-Stacker Traverse (Middle of Pit) | Last Sand-Stacker Traverse (End of Pit) | Overall Weighted Average |
| 1 | 5 | 0 | 71 | 79 | 85 | 81 |
| 2 | 5 | 2 | 70 | 78 | 84 | 80 |
| 3 | 5 | 5 | 67 | 75 | 82 | 77 |
| 4 | 5 | 10 | 62 | 69 | 76 | 71 |
| 5 | 10 | 0 | 60 | 70 | 79 | 73 |
| 6 | 10 | 2 | 58 | 68 | 78 | 71 |
| 7 | 10 | 5 | 55 | 64 | 74 | 68 |
| 8 | 10 | 10 | 42 | 48 | 59 | 52 |
| 9 | 15 | 0 | 49 | 62 | 73 | 65 |
| 10 | 15 | 2 | 47 | 59 | 71 | 63 |
| 11 | 15 | 5 | 44 | 53 | 67 | 58 |
| 12 | 15 | 10 | 37 | 43 | 56 | 48 |
| 13 | 35 | 0 | 16 | 35 | 55 | 42 |
| 14 | 35 | 2 | 14 | 30 | 51 | 38 |
| 15 | 35 | 5 | 10 | 18 | 41 | 28 |
| 16 | 35 | 10 | 4 | 7 | 21 | 12 |
| 17 | 55 | 0 | 4 | 25 | 47 | 33 |
| 18 | 55 | 2 | 1 | 17 | 41 | 26 |
| 19 | 55 | 5 | 0 | 3 | 26 | 13 |
| 20 | 55 | 10 | 0 | 0 | 3 | 1 |
| 21 | 80 | 0 | 1 | 22 | 44 | 30 |
| 22 | 80 | 2 | 0 | 12 | 35 | 21 |
| 23 | 80 | 5 | 0 | 0 | 15 | 6 |
| 24 | 80 | 10 | 0 | 0 | 0 | 0 |

5.3 Water Recovery from Slimes Tailings

Water recovery from the slimes disposal trench and associated underdrain has not been simulated. Actual water recovery from the disposed slimes tailings will be controlled by operational practises, concentrations of fines, rates of seepage into the adjoining sand tailings, clogging of adjoining sand tailings and evaporation. These aspects are largely uncertain and consequently difficult to adequately frame in a predictive groundwater flow model.

Conservatively low recovery of waters from slimes tailings has been estimated and used in the assessments of consumptive water requirements (Appendix E). The estimates incorporate:

- Evaporation losses over the design slimes settling areas of about 27,000 kL/annum.
- Seepage losses into the superficial formations, Toolonga Calcilutite and sand tailings backfill that amount to about 1.6 GL/annum. This estimate is based on the loss of 80% of the water from the slimes settling area.

The aggregate estimated loss is about 1.63 GL/annum.

Actual water losses from slimes settling are anticipated to be less than those estimated. Seepage losses would be intercepted in part by the in-pit drains used to recover the sand tailings waters.

5.4 Estimated Consumptive Groundwater Use

In the predictive modelling, the rates of tailings water recovery from the sand-stacker operations is predominantly shown to be dependent on the rates of sand-stacker advance and the thickness of sand beneath the pit floor.

In order to estimate consumptive groundwater use, the mining schedule for the first 10 years of the project has been reviewed in context of these controls. The mining schedule (Appendix E) for the first ten years comprises the following:

- Mining from 7,033,000 to 7,050,250 m N with the following milestones:
 1. End of year one at about 7,035,625 m N
 2. End of year two at about 7,036,375 m N
 3. End of year three at about 7,037,000 m N
 4. End of year four at about 7,037,750 m N
 5. End of year five at about 7,039,625 m N
 6. End of year six at about 7,040,875 m N
 7. End of year seven at about 7,043,000 m N

-
8. End of year eight at about 7,048,000 m N
 9. End of year nine at about 7,049,250 m N
 10. End of year ten at about 7,050,250m N
- Northern mining advance rate of between 0.4 and 40 m/day (averaging 7 m/day).
 - Rate of sand-stacker advance between 2.5 and 95 m/day (averaging 27 m/day).
 - Pit floor elevation ranging from 55 and 86 m AHD, generally becoming lower to the north.
 - Pit width ranging from about 70 to 2,700 m.
 - Sand thickness below the pit floor ranging between 0 and 9 m.

Based on the findings of the predictive groundwater flow modelling, key elements of the estimated consumptive groundwater use include:

- Average annual rates of sand tailings water recovery range from 53 to 78%, with a long-term average of 68%.
- With only one concentrator operating during the first two years of mining, the annual water losses from the disposal of sand tailings are estimated to range between 2.0 and 2.3 GL/year, averaging 2.2 GL/year.
- With two concentrators operating, the annual water losses from sand tailings disposal are estimated to range between 2.9 to 5.9 GL/year, with a long-term average of 3.6 GL/year.
- The estimated sand tailings water recovery rates range from about 1,400 to 33,700 kL/day, averaging 11,200 kL/day.

Other variables used in estimates of consumptive water use include:

- Water In:
 - a) Recharge from an annual mean rainfall of 112 mm on dams and active tailings operations of 50 ha in area.
- Water Out:
 - a) Losses associated with the sand-stacker operations. This loss will only occur for the times (about 80%) that the sand-stackers are operational. On a gross scale, this loss is likely to average about 32% of the cyclone underflow volume.
 - b) Losses from water retention by and seepage from disposed slimes. It is assumed that about 20% of this water will be recovered, primarily by decantation. These estimates are anticipated to be conservatively low.

- c) Evaporation losses from process water dams (about 10 ha), slimes settling areas totalling 1.2 ha, stacked sand tailings (0.5 ha), and dust suppression over roads areas of 30 ha.
- d) A small proportion of the confined aquifer supply will be used for a camp water supply, sourced from a dedicated bore near the camp site. It is estimated that about 270 kL/day will be required during construction to feed a reverse osmosis plant. The requirement is expected to drop to about 200 kL/day during normal operations.

Estimates of the annual consumptive water use based on an average tailings water recovery rate of 68% are provided in Table 21 and Appendix E. These estimates are expected to broadly frame the lower-bound consumptive water use.

The annualised water balance indicates that during first two years of operation, a minimum make-up supply of about 5.9 GL/year is required. Once two concentrators are operational, a minimum make-up supply range of between 9.9 and 11.3 GL/year is required for a long-term average of 10.4 GL/year.

Table 21
Estimates of Annual Consumptive Water Use Based on a 68% Tailings Water Recovery Rate

| Year | Water Budget | | Annual Make-Up Requirements (kL) |
|---|--------------|--------------|----------------------------------|
| | Inputs (kL) | Outputs (kL) | |
| 1 | 10,595 | 5,942,564 | 5,931,969 |
| 2 | 10,595 | 5,942,564 | 5,931,969 |
| 3 | 10,595 | 9,917,228 | 9,906,633 |
| 4 | 10,595 | 9,917,228 | 9,906,633 |
| 5 | 10,595 | 11,267,228 | 11,256,633 |
| 5 to 10 | 52,975 | 53,185,085 | 10,626,422 |
| 10 to 15 | 52,975 | 52,285,085 | 10,446,422 |
| 15 to 20 | 52,975 | 51,385,085 | 10,266,422 |
| Average Water Requirement (1 concentrator) | | | 5,931,969 |
| Average Water Requirement (2 concentrators) | | | 10,401,528 |

There are uncertainties in the estimates of consumptive groundwater uses. There are numerous factors and variables that will determine actual consumptive groundwater use. Variables that will control the actual consumptive groundwater use include:

- Operational practises, including:
 - water contents of disposed sand tailings;
 - sand-stacker operating strategies;

-
- dust suppression requirements;
 - slimes tailings strategies;
 - in-pit water management;
 - capacity of the water storage dam(s); and
 - lining of the water storage dam(s).
- Hydraulic conductivity of both the disposed sand tailings and *in-situ* superficial formations.
 - Hydraulic conductivity of the shallow Toolonga Calcilutite.
 - Structure and form of the Toolonga Calcilutite contact with the superficial formations
 - Climatic factors (rainfall and evaporation).
 - Fines contents of the disposed sand tailings.
 - Distributions of overburden in the backfill and sand tailings profile.

Results of the predictive sand tailings water recovery modelling have been applied to frame estimates of consumptive water use based on a sub-optimal average tailings water recovery rate of 43%. These estimates are shown in Table 22.

Table 22

Estimates of Annual Consumptive Water Use Based on a 43% Tailings Water Recovery Rate

| Year | Water Budget | | Annual Bore Confined Aquifer Make-Up (kL) |
|--|--------------|--------------|---|
| | Inputs (kL) | Outputs (kL) | |
| 1 | 10,595 | 7,856,440 | 7,845,845 |
| 2 | 10,595 | 7,856,440 | 7,845,845 |
| 3 | 10,595 | 13,744,980 | 13,734,385 |
| 4 | 10,595 | 13,744,980 | 13,734,385 |
| 5 | 10,595 | 15,094,980 | 15,084,385 |
| 5 to 10 | 52,975 | 72,323,845 | 14,454,174 |
| 10 to 15 | 52,975 | 71,423,845 | 14,274,174 |
| 15 to 20 | 52,975 | 70,523,845 | 14,094,174 |
| Average Water Requirement (1 concentrator) | | | 7,845,845 |
| Average Water Requirement (2 concentrator) | | | 14,229,280 |

These estimates might be exceeded under some operational settings. Based on the long-term average consumptive uses for the 43 and 68 % tailings water recoveries, it is estimated that a minimum long-term average tailings water recovery rate in the order of 30% may arise. For two concentrators, this would lead to a maximum consumptive water use of 18 GL/year

5.5 Predicted Extents of Water Table Mounding During Mining

The height and extent of water table mounding beneath individual southern dry pits has been predicted for each of the operational sand-stacker settings described in Table 18. The predictions are focussed on the period of mining, intending to show the short-term mounding distributions. The predictions are intended to represent upper-bound mound heights, assuming the mounding would progressively decay once sand-stacker operations cease in respective pits. Mounding in the vicinity of the northern-most pit is separately assessed due to shallowing depths of the proposed mining and consequent increased potentials for impacts on near-surface and surface environments.

5.5.1 Southern Pit Areas

The current mine plans typically have pit developments with less than 2 m of sand below the pit floor. Under these conditions, it is expected that the mounding may typically reach heights of about 11 m beneath the sand-stackers. The simulated mounds would propagate about 800 to 900 m behind the initial pit area and about 500 m beyond the pit sides as mining advances. The mounding is also estimated to extend about 400 m beyond the end of individual pits.

Mounds accumulated in aquifer storage for the typical case of a 5 m/day sand-stacker advance at several sand thicknesses below the pit floor are shown on Figure 44a. Differences in the mounding caused by rates of sand-stacker advance up to 80 m/day and range of sand thicknesses are shown on Figure 44 (b to f) for the optimum drain configuration.

Under circumstances where only two drains are operating and the sand tailings water recovery is comparatively inefficient, the mounding is of greater magnitude, as shown on Figure 45 (a to f).

In all cases, the outer portions of the mounds are predicted to be less than 2 m in height. Mounding of this magnitude locally poses potential risks if the water table propagates into the root zone of the overlying vegetation. This may occur in areas adjacent to the mining operations where the thickness of the superficial formations is less than 10 m. These areas are described on Figure 46 and shown to be predominantly aligned both west and east of the southern pits and to the north of the northern pit. The western and northern areas occur within the Shark Bay World Heritage Property.

Pits occur within several hundred metres of the Shark Bay World Heritage Property in four places along the western and northern project area boundaries. In these areas, the mine plans (Appendix E) indicate sand-stacker rates of advance between 4 and 60 m/day and sand thicknesses below the pit floor of up to 4 m. Predicted mounding during the development of these pits may extend up to 400 m inside the Shark Bay World Heritage Property. Predicted water table mounding during mining in proximity to the Shark Bay World Heritage Property is summarised in Table 23.

Table 23

Estimated Mound Heights at the Shark Bay World Heritage Property Boundary

| Domain | Sand-Stacker Advance Rate (m/day) | Pit Floor Sand Thickness (m) | Model Setting | Predicted Mound Extent | | Mound Height at SBWHP Boundary (m) |
|------------------------|-----------------------------------|------------------------------|---------------|------------------------|----------------|------------------------------------|
| | | | | Lateral (m) | Into SBWHP (m) | |
| 7,032,800 to 7,034,800 | 35 | 0 | 13 | 400 | 300 | 2.0 |
| 7,036,000 to 7,038,500 | 30 | 0 – 1 | 13 - 14 | 400-500 | 300-400 | 2.0 – 2.5 |
| 7,044,500 to 7,050,000 | 24 | 0 – 4 | 10 & 14 | 400-500 | 200-400 | 2.0 – 2.5 |

Note: SBWHP - Shark Bay World Heritage Property

Importantly, the actual thickness of the superficial formations is unknown outside of the Amy Zone. Also, the accuracy of the ground surface topography is constrained by poor access and limited resolution of photogrammetry mapping. As such, errors of 5 m or more might be manifest in the superficial formations thickness isopachs. Consequently, the potential risks to vegetation can only be framed in semi-quantitative terms.

The mitigation of potential risk to stands of vegetation in perimeter areas of the proposed pits should be approached in a staged manner that enables collection of additional data and informed decision-making on actual risks. The staged approach includes:

- mapping of any currently unmapped areas of susceptible vegetation and investigation of typical depths of root penetration;
- the installation of multipiezometers in specific locations to characterise the ground surface elevation, thickness of the superficial formations, shallow Toolonga Calcilutite lithologies and water table elevations;
- enhancement of the Digital Terrain Model and topographic elevations;
- use of the additional data to refine the potential risks;
- monitoring of actual water table mounding; and
- where appropriate, maintain active drains in the pit(s) adjacent to areas at risk in order to intercept and abstract tailings waters locally contributing to the mounding.

The mitigation of all risks associated with mounding of the water table beneath shrubland areas is considered to be best and most practicably achieved through the localised use of drains in the developed pits. As shown on Figure 39 and Figure 40 the drains do effectively limit the transmission of tailings waters by locally dewatering to the pit-floor elevation. To be effective, such drains would need to be installed as early as practical during pit development and operated for the duration of subsequent mining in respective pits.

The drawdown impacts on the mounded water table might also be controlled in-part by variations in drain length and excavation of the drain beneath the pit floor. Longer and deeper drains would be more

effective than shorter and shallower drains. These additional controls may be important in areas where the thickness of the superficial formations beneath the pit floor exceeds several metres.

5.5.2 Northern Pit Areas

The model of the northern pit conforms to the conceptual hydrogeological model, incorporating the interpreted Peron Sandstone, marine clay and Toolonga Calcilutite distributions. Also included in the model are:

- Surface topography and bottom elevations of the superficial formations compatible with the digital terrain model.
- Four layers that discretely represent:
 - Peron Sandstone and foreshore shell coquina dunal terrain;
 - marine clay beds;
 - Peron Sandstone; and
 - Toolonga Calcilutite.
- Hamelin Pool, as a suite of fixed-head cells.
- Hydraulic parameters for Peron Sandstone that are compatible with those in the generic models.

Hydraulic parameters applied in the model are outlined in Table 24. Both the marine clay and Toolonga Calcilutite are represented as low transmissivity domains.

Table 24
Northern Pit Model Form and Hydraulic Parameters

| Model Layer | Formation | Hydraulic Conductivity | | | Specific Yield (dimensionless) |
|-------------|-------------------------------|------------------------|---------------|---------------|--------------------------------|
| | | k_x (m/day) | K_y (m/day) | K_z (m/day) | |
| 1 | Peron Sandstone/Shell Coquina | 10 | 10 | 10 | 0.2 |
| 2 | Marine Clay | 0.001 | 0.001 | 0.001 | 0.3 |
| 3 | Peron Sandstone | 10 | 10 | 10 | 0.2 |
| 4 | Toolonga Calcilutite | 0.0001 | 0.0001 | 0.0001 | 0.00001 |

The domain and form of the model are described on Figure 47 and Figure 48.

Simulated groundwater levels (Figure 49) are broadly compatible with those interpreted and shown on Figure 27 and Figure 31. Lateral variations in fixed-head boundary conditions have been applied to enable the simulated water table elevations to conform to those interpreted.

Subsequent to calibration, the northern pit model has been applied to evaluate the impacts during mining of water table mounding due to disposal of sand tailings. The predictive simulations were undertaken in three stages, using previous outputs as impacts to consecutive stages. Sand tailing is simulated as in the generic models, but rates of recharge are doubled to represent four sand-stacker units operating together.

Importantly, the simulations provide for pit development from the north to south (the opposite from all southern pits) and east to west. This development approach is intended to:

- Provide temporary drains along the northern pit floor, with the drains operating for periods compatible with mining in adjacent areas. In the east, the initial northern drain remains operating for 374 days.
- Limit the mounding that occurs in the north and east.
- Enable the focussing of residual mounding in western pit areas, where the water table occurs within the superficial formations and consequently provides higher transmissivity profiles within which the mound tailings waters would more readily dissipate.

Also, several areas north and east of the northern mining limits are characterised by interpreted depths to the water table of <1.0 to 3.0 m. These areas reflect a change in geomorphology from the Victoria Sand Plains to Carbla Plateau, and associated subcrop or outcrop of Toolonga Calcilutite. They also reflect the topography sloping towards Nilemah Embayment and the occurrence of intradunal swales where the thickness of the superficial formations is constrained.

The predictive findings for the northern pit areas are shown on Figure 50 (a to c) for incremental periods during the mining. These predictive findings show:

- The progressive development of a west to east elongate mound that is about 10 m and 3 m in height within the western and eastern pit areas at the end of mining.
- In the eastern areas, the mound distribution and height steadily increases during the period of mining, despite mining having previously retreated from these areas. This characteristic shows preferential re-wetting of and flow within the deposited sand tailings. This aspect is interpreted to be linked to the comparatively high transmissivity of the saturated sand tailings as opposed to that of the dry superficial formations or saturated shallow Toolonga Calcilutite.
- The mounding during mining encroaches on areas to the north and east of the pit where the interpreted water table occurs at depths of <1.0 to 3.0 m. This encroachment is predicted to cause shallowing of the water table to depths of <1.0 m in two local settings, perhaps to within the root zones of the vegetation stands. These settings occur outside of the Shark Bay World Heritage Property.
- Beneath the western pit limits and adjoining Shark Bay World Heritage Property areas in the northwest, the mounding typically occurs in settings where the superficial formations are thickening and depths to the water table predominantly exceed 15 m. Mounding propagates distance up to

about 500 m into the domain of the Shark Bay World Heritage Property, with heights of up to about 5 m.

As for the southern project areas, the mitigation of potential risks to stands of vegetation should be approached in a staged manner involving the investigation of any currently unmapped areas of susceptible vegetation, typical depths of root penetration, installation of multipiezometers to accurately define the local water table environment and monitoring of actual water table mounding. Where appropriate, active remediation would involve the retention of active drains in northern pit areas to intercept and enhance recovery of the tailings waters. Based on the predictive simulations, the potential risks linked to water table mounding would be mitigated by the retention of active drains within the eastern half of the pit coupled with a north to south spur drain that evenly subdivides the pit. These drains would be installed as early as practicable and maintained in operation for the duration of mining.

5.6 Predicted Fates of Tailings Waters

The estimates of tailings water recovery and consumptive water uses indicate that large volumes of groundwater are residual within tailings profiles and the adjoining superficial formations after development of individual pits. The residual volumes and associated water table mounds would dissipate over time, along subsurface flow paths towards the Indian Ocean, Freycinet Reach and Hamelin Pool controlled by the regional water table.

The water table mounds in each pit would decay in height after the removal of the sand-stackers. Subsequently the residual mound would migrate down gradient, progressively dissipating within the water table environment. These aspects have been investigated using one of the developed generic models and the northern pit model of the sand-stacker operations and sand tailings water recovery.

The simulations are intended to broadly frame:

- the rate of decay of the height of the mound;
- rate and distance that the leading edge of the mound propagates;
- dissipation of the mound;
- influences on the mound and its decay imposed by the structure of the Toolonga Calcilutite contact;
- fate of the residual waters; and
- potential environmental impacts, if any, due to encroachment of the mound within the root zones of vegetation and outcrop of the water table in discharge zones.

The predictive results of the modelling are semi-quantitative. They are intended to broadly characterise potential environmental risks linked to the migration of the tailings waters. It is anticipated that the models represent a worst case, understanding that actual rates of mound dissipations would be enhanced by:

-
- downward leakage to the regional water table within the Toolonga Calcilutite;
 - the dipping surface of the Toolonga Calcilutite and associated palaeovalleys that would control groundwater flow directions; and
 - occurrence of preferred groundwater flow paths in the shallow Toolonga Calcilutite.

5.6.1 Southern Project Areas

The generic model selected for use is characterised by 2 m of superficial formations beneath the pit floor and a 15 m/day rate of sand-stacker advance, conditions that broadly typify most pits. Each model has been applied to predictive simulations that commence upon cessation of sand-stacker operations and continue for a period of 50 years.

The predictive results from the generic model are shown on:

- Figure 51 (a and b), outlining the incremental changes in mound distribution over a period of 50 years; and
- Figure 52 (a and b) outlining the potential transient mound distributions on four transects to the west of the proposed pits and beneath the Shark Bay World Heritage Property.

The predicted results for the southern project areas show:

- The distributions of the mounds are constrained by the structure contours of the Toolonga Calcilutite.
- Dissipation of the mounded waters in the immediate pit areas and on the boundary of the Shark Bay World Heritage Property takes time. On the four sections shown on Figure 52b, the height of the mound on the boundary of the Shark Bay World Heritage Property diminishes by about 1.5 m over a 50-year period after mining of the local pit.
- The mounds propagate laterally distances in the order of 1,000 m during the initial five years after cessation of local mining.
- After 50 years, the leading edges of the mounds occur at distances up to 2,000 m from the local pits. Heights of the mounding at distances of 1,000 to 2,000 m from the pits are typically less than 1.0 m.
- The mounding is small-scale compared to the interpreted thickness of the superficial formations and typically would occur at least 10 m below the ground surface. Beneath intradunal swales the mounding would be closest to the ground surface. Projections of the predicted mounding onto cross-sections beneath the Shark Bay World Heritage Property, shown on Figure 52, indicate a minimum depth to the water table of about 4 m at one location.

Based on the outlined predictive findings, it is interpreted there would be low environmental risks associated with the long-term transport and fate of the tailings waters from the southern project areas. That said, it needs to be recognised that these findings are semi-quantitative, due to constraints imposed

by the available data (as per Section 5.6.1), and need to be re-appraised in an operational environment based on a staged approach to mapping of vegetation, determining typical depths of root penetration, installation of multipiezometers and monitoring of actual water table mounding.

As discussed earlier, the mitigation of all risks associated with mounding of the water table beneath shrubland areas is considered to best and most practicably achieved through the localised use of drains in the developed pits. The recovery of tailings water locally during mining operations would reduce the mound dimensions and volumes. This approach is directed at source removal and avoidance of access and intrusive activities within the Shark Bay World Heritage Property.

Northern Project Areas

The northern pit model is characterised by regional flow towards the Nilemah Embayment and Hamelin Pool. The water table environment naturally shallows as the topography slopes towards the Nilemah Embayment and associated groundwater discharge zones. The predictive results from the northern pit model are shown on Figure 53 (a to h) and Figure 54 (a to c). Results of the predictive simulations show:

- Residual mound heights within the pit area progressively decay from 3 to 10 m at the end of mining to a maximum of 3 m after 10 years. Subsequently, the residual mound becomes increasingly segregated. After 50 years the mounding has a 2 m peak, is widely distributed and has entered groundwater discharge zones formed by salina landscapes within the Nilemah Embayment.
- Residual tailings waters in the mound progressively migrate to the north. After 10 years the leading edge of the mound has reached salinas within the Nilemah Embayment at distances up to 1.8 km from the northern pit crest. The mound propagates faster in areas where the thickness of the saturated superficial formations is greatest. This occurs to the northwest rather than northeast of the pit.

In the northwest, beneath the Shark Bay World Heritage Property, the mound is simulated to reach a quasi steady-state distribution after about 20 years. Thereafter, the mounding magnitude and distribution does not significantly change.

In the northeast, the mounding continues to propagate over the 50-year post-mining period. The rates of propagation are comparatively slow because the superficial formations locally are thin and predominantly dry.

- The mounding propagates beneath both dunal terrain and salina areas where the interpreted water table occurs at depths of <1.0 to 3.0 m. The predicted rises in the water table elevations in these areas would be to within 1 m of the ground surface. The simulations do not show discharge of groundwater onto the ground surface.

Potential impacts in terms of invasion of vegetation root zones and groundwater discharge would be linked to intradunal swales and the southern perimeter of the salinas, along the fringe of the dunal terrain.

-
- Rates of increased groundwater throughflow into the salina areas due to the presence of the residual mounding (Figure 54c) are predicted to peak in the order of 185 kL/day, about 17% above that simulated during baseline conditions. A throughflow increase of this magnitude may be predominantly intercepted by evaporation in fringe areas of or within the salinas. Evaporation losses would locally increase the salt loadings within the shallow water table environment and shallow soils.

The predictive simulations have investigated several mining and sand tailings water recovery scenarios. These scenarios incorporate drains along the northern wall of the pit and vary regarding lengths of and periods of operations for the drain systems. All of the predictive simulations show that the practical variations in drain lengths and operating periods do not substantially reduce the height of the residual mound where the interpreted water table occurs at depths of <1.0 to 3.0m. These outcomes reflect the local environment where residual mounding of 0.5 to 1.0m poses potential risks.

The predictive simulations broadly characterise the northern pit and Nilemah Embayment hydrogeology. However, the simulations do not incorporate evaporation losses and consequently do not replicate potential groundwater discharge within the salina environment. As such, the simulations might overestimate the heights of the residual mounds that propagate into areas of shallow depths to the water table. Notwithstanding, additional investigations are required in the northern pit areas and Nilemah Embayment to characterise the vegetation and water table environments. These investigations should include vegetation mapping, quantifying the typical depths of root penetration, installation of multipiezometers (within the superficial formations, marine clay and Toolonga Calcilutite) and aquifer testing. These investigations should be coupled with reviews of the northern pit mining plans. To mitigate environmental risks linked to the development of the northern pit, there is a potential need to reduce the rate of mining, limit the number of sand-stackers in operations and reduce the residual mound height.

5.7 Predicted Pit Dewatering Requirements

The proposed northern pits would intersect the water table within the reworked successions of the Peron Sandstone. Typically, the saturated thickness of the profile to be mined is less than one to two metres, thus representing a low-transmissivity, limited-extent aquifer setting. Nevertheless, groundwater abstraction will accompany the northern pit mining developments.

The northern pit dewatering requirements have been assessed using the conceptual hydrogeological model. Based on this assessment, the effects of dewatering to provide comparatively dry mining conditions are considered to be negligible because:

- The water table is generally about 30m below ground surface in the immediate vicinity of the northern Amy Zone.
- The local aquifer is of limited extent and of low-transmissivity.
- Groundwater abstractions required to dewater to the pit-floor elevation are expected to be of small-scale, predicted to be less than 500 kL/day for a period of about one year.

- Drawdown of the water table beyond the pit limits would be of small-scale due to the limited thickness of the saturated profile and its low-transmissivity.

In addition to these aspects, it is expected that the water table is not supporting any dependent ecosystems (due to the depth and known salinity of the shallow groundwater resources) and artificial recharge of the water table by water from the sand tailings would predominantly offset any drawdown impacts.

5.8 Mine Water Salinity Issues

The salinity of the mixed groundwater abstracted from Birdrong Sandstone and Kopke Sandstone in DTB1 is 8,900 mg/L TDS. Once the abstracted groundwater enters the processing circuit, the salinity is expected to progressively increase due to evaporative effects both in the process water dam(s), sand-stacker operations, slimes tailings disposal and tailings water recovery drains. It is also likely that comparatively small concentrations of salt would be mobilised from the parent sandstone.

An assessment of forecast increases in salinity of the process water due to evaporation is presented in Table 25. This assessment is predominantly based on potential water losses from the process water dam(s) and sand-stacker traverses.

Table 25
Forecast Salinity of Process Water

| Year | Raw Water Salinity (mg/L TDS) | Raw Water Abstraction (kL) | Total Evaporative Losses ¹ (kL) | Salinity Multiplier ² | Process Water Salinity ³ (mg/L TDS) | Cumulative Salinity Increase ⁴ (%) |
|------|-------------------------------|----------------------------|--|----------------------------------|--|---|
| 1 | 8,900 | 4,568,742 | 30,302 | 0.00663 | 8,959 | 0.7 |
| 2 | 8,900 | 4,568,742 | 30,302 | 0.00663 | 9,018 | 1.3 |
| 3 | 8,900 | 9,727,870 | 49,381 | 0.00508 | 9,063 | 1.8 |
| 4 | 8,900 | 9,729,622 | 49,381 | 0.00508 | 9,108 | 2.3 |
| 5 | 8,900 | 9,727,870 | 49,381 | 0.00508 | 9,154 | 2.8 |
| 10 | 8,900 | 9,565,372 | 246,904 | 0.02581 | 10,302 | 16 |
| 15 | 8,900 | 9,729,622 | 246,904 | 0.02538 | 11,431 | 28 |
| 20 | 8,900 | 9,729,622 | 246,904 | 0.02538 | 12,561 | 41 |

- Notes:
- 1 These calculations are based on recirculating the same process water stream for the entire mine life. Evaporation is assumed to be from active process water dams, slimes settling trench and sand-stacker sites.
 - 2 Salinity Multiplier = Evaporation Losses divided by Abstraction
 - 3 Forecast Process Water Salinity = Raw Water Salinity + (previous forecast process water salinity x salinity multiplier)
 - 4 Actual salinities will be lower if the process water circuit is purged between concentrator relocations.

The completed assessment indicates that salinity increases due to evaporation in the first five years are likely to be insignificant. This is due to the relatively large volume of make-up water used compared to that evaporated. The actual salinity increases may be higher than indicated in Table 25 due to the addition of stored soil salt from the processed ore. The increases in salinity from 8,900 to 12,600 mg/L TDS are not significant in context to the local groundwater environment or potential impacts.

5.9 Summary of Predicted Impacts on Flora and Fauna

The findings of the groundwater resources impact assessments indicate that the predominant environmental issues and potential risks within the superficial formations linked to the Amy Zone development include:

- recovery of sand tailings waters and limiting the potentials for mounding of the water table, within both the southern and northern project areas, propagating into the root zones of vegetation stands;
- potentials for discharge from the northern water table mounds into salina domains within the Nilemah Embayment and the Shark Bay World Heritage Property.

These assessments also indicate that the potentials for adverse environmental impacts linked to the outlined issues is low and broadly acceptable in the south, but medium in the north and requiring the identification of further risk reduction options. Within the superficial formations, the predictive modelling results show that:

- water table mounding within the southern project areas that potentially threatens vegetation root zones can be mitigated by the dedicated operation of in-pit trench drains that intercept and enhance recovery of tailings waters;
- water table mounding within the northern project areas that potentially threatens vegetation root zones can be mitigated by refining knowledge of salina water table and groundwater discharge environments and reviewing mining plans to reduce the rate of northern pit development, the number of sand-stackers in operation and the magnitudes of the residual mounds; and
- the simulated mounds do not actually have a surface expression within the salinas.

Studies of the local fauna, flora and stygofauna undertaken during environmental impact assessments include:

- Flora studies by Mattiske Consulting (Mattiske, 2005).
- Stygofauna studies by the University of Western Australia (UWA, 2005).
- Vertebrate fauna studies by Ninnox Environmental Services (Ninox, 2005).

No groundwater-dependent flora or fauna are known in the project area. No stygofauna were found following a survey conducted on shallow groundwater bores in and near the project area (UWA, 2005).

The proposed mining developments would temporarily alter the water table environment. In several areas along the flanks of the Amy Zone in the south, and beyond the northern boundary of the northern pit, within Nilemah Embayment, there may be insufficient thickness of the superficial formations to prevent potential interaction between the mounded water table and vegetation root zones. Residual tailings waters may rise close to the surface near the base of the Peron Sandstone dunes around the fringes of the Nilemah Embayment. The residual water table mounding due to sand tailings disposal is predicted to

remain within about 3 km of the project area. Throughflow would be towards the Nilemah Embayment, with discharge being controlled in part by evaporation-dominated hydro-cycle in salinas, presence of marine clay beds and rates of groundwater throughflow.

The nearest groundwater dependent ecosystem is likely to be the salina and estuarine ecology associated with the Nilemah Embayment and Hamelin Pool. Both are groundwater discharge areas.

The stromatolites along the shoreline of Hamelin Pool, near the old Hamelin Telegraph Station, are located in groundwater discharge zones about 12 km from the northern project area. The groundwater discharge is from a different catchment than the project area and Nilemah Embayment. There are no predicted impacts on the Hamelin Pool ecosystem due to occurrence of residual tailings waters in the superficial formations and water table environment.

Additional investigations are required to refine the understanding of the local vegetation systems and water table environment. Results of these investigations would be applied to refine the potential environmental risks and develop appropriate and practical mitigation strategies.

These aspects might be aligned with reviews of the mine plans for the northern pit that consider options for scheduling and/or staging of the developments to lengthen the mining period, minimise the number of sand-stackers in use and consequently reduce the volumes of tailings waters in residual mounds.

Based on the assessments of sand tailings water recovery and consumptive water use forecasts it is evident that large-scale groundwater abstractions would be required to meet process water supply demands. These abstractions are proposed to be sourced from the regional confined aquifers formed by the Birdrong Sandstone and Kopke Sandstone. Predictive assessments of the potential impacts of the forecast large-scale process water supply abstractions are outlined below.

6.1 Confined Aquifer Groundwater Flow Modelling

A groundwater flow model of the confined aquifer systems has been developed to predict the impacts of large-scale abstractions for make-up of process water supplies.

The simulated southern Carnarvon Basin structure is derived from that interpreted by Wills and Dogramaci (2000); original bore logs are used to interpolate between areas of higher confidence. Most stratigraphic units are simulated as separate hydrogeological domains and assigned hydraulic parameters that correspond with the findings of the site investigations, published data or assumed values.

6.1.1 Model Code

The confined aquifer model is developed in MODFLOW. MODFLOW is a three-dimensional block-centred finite-difference code developed by the USGS to simulate groundwater flow in the saturated subsurface. Visual MODFLOW from Waterloo Hydrogeologic Inc. is used as the pre- and post-processor.

6.1.2 Model Domain and Form

Surface topography is derived either from a local domain model in the project area or digitised spot heights from published 1: 100,000 scale topographic maps. Coastlines are set to have a sea level elevation with fixed-head cells set to a similar level offshore. The model domain encompasses an area of 175 by 280 km centred on the project site (Figure 55). The developed model incorporates 12 layers compatible with the stratigraphy as shown in Table 26. The structure of the confined aquifer model is shown in cross sectional form on Figure 56.

Table 26

Layered Form of the Confined Aquifer Model

| Layer | Description |
|-------|--------------------------|
| 1 | Superficial Formations |
| 2 | Toolonga Calcilutite |
| 3 | Alinga Formation |
| 4 | Windalia Radiolarite |
| 5 | Windalia Sand Member |
| 6 | Muderong Shale Formation |
| 7 | Birdrong Sandstone |
| 8 | Kopke Sandstone |
| 9 | Sweeney Mia Formation |
| 10 | Faure Formation |
| 11 | Dirk Hartog Group |
| 12 | Tumblagooda Sandstone |

Several layers are sub-divided to assist with the simulation of vertical groundwater level distributions within the confined aquifer systems.

6.1.3 Boundary Conditions

Boundary conditions are broadly configured to simulate the interpreted groundwater levels and throughflow dynamics of the confined aquifer systems. Where possible, the model boundaries correspond with regional structural or geological boundaries such as:

- Ajana Ridge and Hardabut Fault (eastern and southeastern boundaries).
- Tectonic faults evident in seismic interpretations (western boundary).
- Pinching-out of the Kopke Sandstone to the west.
- Groundwater divides interpreted from surface drainage catchments.

The northern boundary of the model is chosen on the basis of its physical remoteness from the project area.

Boundary types used by the model include:

- Fixed-head in east, to simulate regional throughflow from the Ajana Ridge.
- Fixed-head corresponding to the Murchison River catchment divides in the south and local unconfined groundwater levels.

- Fixed-head river cells in the west and northwest, representing sea level. These cells enable groundwater to enter or leave the Gascoyne Platform at a controlled rate, thus allowing the observed regional gradients to be broadly simulated under steady-state conditions.
- No-flow in the north.

The river cells in MODFLOW act as groundwater sinks when the specified river cell elevations are below the water table. By setting the river cell drain elevations to sea level, the model removes groundwater that is above this elevation in each river cell. Inclusive in the river cell specification is the conductance, which can be used to retard flow into the drain cell. The river cell conductance was iterated during the steady-state simulations, arriving at values typically between 1×10^{-2} and 1×10^{-8} m²/day to simulate the interpreted regional groundwater levels and both lateral and vertical groundwater flow gradients.

The simulated boundary conditions are described on Figure 57.

6.1.4 Hydraulic Parameters

The hydraulic parameters applied in the model are shown in Table 27.

Table 27
Confined Aquifer Model Hydraulic Parameters

| Model Layer | Formation | Hydraulic Conductivity | | | Specific Storage (1/m) | Specific Yield (dimensionless) |
|-------------|---------------------------|------------------------|------------------------|------------------------|------------------------|--------------------------------|
| | | K _x (m/day) | K _y (m/day) | K _z (m/day) | | |
| 1 | Superficial Formations | 10 | 10 | 10 | 1x10 ⁻⁵ | 0.2 |
| 2 | Toolonga Calcilutite | 0.0001 | 0.0001 | 0.00001 | 1x10 ⁻⁵ | 0.01 |
| 3 | Alinga Formation | 0.001 | 0.001 | 0.0001 | 1x10 ⁻⁵ | 0.005 |
| 4 | Windalia Radiolarite | 1 | 1 | 0.0001 | 1x10 ⁻⁵ | 0.01 |
| 5 | Windalia Sand Member | 2 | 2 | 0.2 | 1x10 ⁻⁵ | 0.1 |
| 6 | Muderong Shale Formations | 0.0001 | 0.0001 | 0.00001 | 1x10 ⁻⁵ | 0.005 |
| 7 | Birdrong Sandstone | 13 | 13 | 1.3 | 1x10 ⁻⁵ | 0.1 |
| 8 | Kopke Sandstone | 1.9 | 1.9 | 0.19 | 1x10 ⁻⁵ | 0.1 |
| 9 | Sweeney Mia Formation | 0.01 | 0.01 | 0.001 | 1x10 ⁻⁵ | 0.01 |
| 10 | Faure Formation | 0.01 | 0.01 | 0.001 | 1x10 ⁻⁵ | 0.005 |
| 11 | Dirk Hartog Group | 0.001 | 0.001 | 0.0001 | 1x10 ⁻⁵ | 0.005 |
| 12 | Tumblagooda Sandstone | 1 | 1 | 0.1 | 1x10 ⁻⁵ | 0.05 |

Uniform horizontal hydraulic conductivities are assigned to all layers. Generally, the vertical hydraulic conductivity is one order of magnitude below the horizontal value, to take into account normal differences observed in sedimentary aquifers. Several of the aquitard formations and the Windalia Radiolarite have been assigned stronger horizontal to vertical anisotropy, to simulate observed relatively large groundwater level differences over small vertical depths.

6.1.5 Model Calibration

The purpose of calibration is to establish that the model can reproduce observed groundwater levels, hydraulic gradients and regional flow paths. Calibration of the model comprised three stages. Firstly, a series of steady-state simulations were conducted to establish the regional groundwater flow, hydraulic gradients and groundwater elevations near the project area. Subsequently, the model was applied in transient mode, using the steady-state groundwater levels as the initial conditions.

The calibration process involved adjusting the boundary positions, conditions and hydraulic parameters, within realistic ranges, so that the simulated groundwater levels in each of the main aquifers broadly matched those interpreted.

The final calibration stage involved simulation of the local aquifer responses to test pumping in DTB1.

The simulated steady-state groundwater levels in the Windalia Radiolarite, Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone are shown on Figure 58 (a to d).

Groundwater throughflow mechanisms from recharge to discharge zones are shown on south to north and east to west section views on Figure 59 (a and b) and Figure 60 (a and b). These figures show both simulated potentiometric levels and flow vectors in profile.

The figures show a predominance of vertical upward groundwater flow throughout the stratigraphic profile, with discharge into the Alinga Formation, Toolonga Calcilutite and the superficial formations. Potentiometric levels in the stratigraphic profile and rates of discharge are predominantly controlled by the simulated vertical hydraulic conductivity of the Muderong Shale Formation, Alinga Formation and Toolonga Calcilutite. Outcomes of the predictive modelling are sensitive to these hydraulic conductivity values. Notwithstanding the vertical upward groundwater flow characteristics are compatible with the conceptual hydrogeological model of the confined aquifer systems.

No allowance has been made in the model calibration of regional impacts resulting from the long-term abstraction of groundwater from uncontrolled artesian and non-artesian bores. There is insufficient evidence available to determine the impacts of such abstractions, either before or after the recent bore rehabilitation programme. If the groundwater system has been historically depressurised, any recent recovery linked to the bore-rehabilitation programme would tend to reduce the predicted drawdowns.

6.2 Simulated Large-Scale Abstraction

The confined aquifer predictive simulations are based on the estimates of annual consumptive groundwater use of 11 and 15 GL/annum, assuming make-up supply demands would be met by abstractions from the Birdrong Sandstone and Kopke Sandstone. These simulations have been applied to enable predictive determinations of:

- Locations of the production bores and overall borefield layout, cognisant of drawdown interference effects that may influence production bore designs.

- Local and regional drawdown distributions due to the forecast abstraction.
- Potential drawdown impacts on private bores.
- To assess the impact of the forecast abstraction on the regional groundwater flow budget.

The design production bores are nominally spaced 3 km apart along the eastern perimeter of the Amy Zone, as shown in Table 28 and on Figure 61. This spacing is based on a cost-benefit analysis incorporating the predicted drawdown interference. Actual production bore spacings may vary depending on location of suitable drilling sites, distances to the nearest power source and actual consumptive water use. In practice, all production bores would preferentially be located adjacent to the access road that is planned to run the length of the mine site.

Table 25
Design Production Bore Locations

| Production Bore | Location (m MGA) | |
|-----------------|------------------|-----------|
| | Eastings | Northings |
| CPB1 | 216,200 | 7,036,100 |
| CPB2 | 216,150 | 7,039,100 |
| CPB3 (DTB1) | 216,318 | 7,041,723 |
| CPB4 | 215,050 | 7,044,300 |
| CPB5 | 215,200 | 7,047,500 |
| CPB6 | 215,300 | 7,050,950 |
| CPB7 | 214,750 | 7,053,850 |
| CPB8 | 214,200 | 7,055,900 |
| CPB9 | 212,350 | 7,058,700 |
| CPB10 | 211,700 | 7,061,700 |
| CPB11 | 212,300 | 7,063,700 |
| CPB12 | 213,625 | 7,065,000 |
| CPB13 | 220,340 | 7,034,250 |

The large-scale abstraction simulations are based on each of the production bores pumping at the same rate. In reality, some production bores would operate continuously, whilst others would be used as required or be on standby. Short-term variations in supply demand would be offset where practicable by storage capacity in the process water dam(s). On a short-term basis, water demands are expected to peak:

- when sand tailings disposal has commenced in a new pit and initial tailings water volumes are lost to storage;
- when the rate of sand-stacker advance exceeds 15 m/day;
- when the sand-stackers are operating in areas where thick intervals of sand occur beneath the pit floor; and

- where the pit-floor drains have become backfilled, in part, by overburden or tailings.

The simulated production bores abstracted groundwater from both the Birdrong Sandstone and Kopke Sandstone, as in DTB1. They are activated and deactivated at selected times, to retain the concentrators near the centre of the borefield to minimise infrastructure and operating costs.

The simulated borefield operations include:

Abstraction of 11 GL/annum:

- Three production bores operating, with an aggregate pumping rate of 15,060 kL/day for one concentrator.
- The pumping rate is increased to an aggregate of 30,140 kL/day, from four production bores, with two concentrators operating after two years.
- Recovery of the aquifer systems after 20 years of abstraction.

The simulated schedule for abstractions of 11 GL/annum from individual production bores is provided in Table 29.

Table 29
Simulated Schedule for Abstraction of 11 GL/annum

| Production Bore | Production Bore Commissioning (Year) | Production Bore Decommissioning (Year) | Operating Period (Years) | Individual Production Bore Abstraction (kL/day) | |
|-----------------|--------------------------------------|--|--------------------------|---|---------------|
| | | | | Years 1 and 2 | After 2 Years |
| CPB1 | 0 | 7 | 7 | 5,022 | 7,534 |
| CPB2 | 0 | 10 | 10 | 5,022 | 7,534 |
| CPB3 (DTB1) | 0 | 12 | 12 | 5,022 | 7,534 |
| CPB4 | 3 | 13 | 10 | 0 | 7,534 |
| CPB5 | 7 | 15 | 8 | 0 | 7,534 |
| CPB6 | 10 | 17 | 7 | 0 | 7,534 |
| CPB7 | 12 | 17 | 5 | 0 | 7,534 |
| CPB8 | 13 | 17 | 4 | 0 | 7,534 |
| CPB9 | 15 | 21 | 6 | 0 | 7,534 |
| CPB10 | 17 | 21 | 4 | 0 | 7,534 |
| CPB11 | 17 | 21 | 4 | 0 | 7,534 |
| CPB12 | 17 | 21 | 4 | 0 | 7,534 |

Abstraction of 15 GL/annum

- Three production bores operating, with an aggregate pumping rate of 18,500 kL/day for one concentrator.
- The pumping rate is increased to an aggregate of 41,120 kL/day from four production bores, with two concentrators operating after two years.

- Recovery of the aquifer systems after 20 years of abstraction.

The simulated schedule for abstractions of 15 GL/annum from individual production bores is provided in Table 30.

Table 30
Simulated Schedule for Abstraction of 15 GL/annum

| Production Bore | Production Bore Commissioning (Year) | Production Bore Decommissioning (Year) | Operating Period (Years) | Individual Production Bore Abstraction (kL/day) | |
|-----------------|--------------------------------------|--|--------------------------|---|---------------|
| | | | | Years 1 and 2 | After 2 Years |
| CPB1 | 0 | 7 | 7 | 7,300 | 10,280 |
| CPB2 | 0 | 10 | 10 | 7,300 | 10,280 |
| CPB3 (DTB1) | 0 | 12 | 12 | 7,300 | 10,280 |
| CPB4 | 3 | 13 | 10 | 0 | 10,280 |
| CPB5 | 7 | 15 | 8 | 0 | 10,280 |
| CPB6 | 10 | 17 | 7 | 0 | 10,280 |
| CPB7 | 12 | 17 | 5 | 0 | 10,280 |
| CPB8 | 13 | 17 | 4 | 0 | 10,280 |
| CPB9 | 15 | 21 | 6 | 0 | 10,280 |
| CPB10 | 17 | 21 | 4 | 0 | 10,280 |
| CPB11 | 17 | 21 | 4 | 0 | 10,280 |
| CPB12 | 17 | 21 | 4 | 0 | 10,280 |

6.3 Extent of Predicted Drawdowns

6.3.1 Abstraction of 11 GL/annum

The predictive simulations show that drawdowns in the Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone will propagate outwards from the project area in a semi-radial pattern. The outer limit of measurable drawdowns is likely to extend 60 to 75 km from the project area.

The predicted drawdowns in Windalia Radiolarite, Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone after 1, 2, 5 10 and 20 years of 11 GL/annum abstraction are shown on Figures 62 to 65. The predicted drawdown also propagate vertically upwards in the stratigraphic profile, being manifest in decreasing magnitudes in the Alinga Formation, Toolonga Calcilutite and superficial formations, as shown on Figure 66 (a to c).

Drawdowns in the *Windalia Radiolarite* have been filtered to remove data from areas where this formation is absent. The drawdowns are predicted to propagate radially outwards from the borefield as shown on Figure 62 (a to e). The predicted 1 m drawdown contour propagates radial distances of 30, 40, 55, 65 and 75 km after 1, 2, 5, 10 and 20 years of abstraction. Where the Windalia Radiolarite and the

Windalia Sand Member coalesce, drawdowns of about 5 m are predicted after 20 years. The Nilemah No. 1A, Caravan Park and Hamelin Homestead bores lie between the 5 and 6 m drawdown contours after 20 years of abstraction.

Predicted drawdowns in the *Windalia Sand Member* shown on Figures 63 (a to e) have also been filtered to remove regions where this formation is absent. Drawdowns are predicted to propagate outwards from the southern project area to distances of 30, 35, 40, 50 and 55 km after 1, 2, 5, 10 and 20 years of abstraction. The northern, western and southern margins of the predicted drawdown cone on Figure 63 are truncated, but it is assumed there is sufficient aquifer continuity with the adjoining Windalia Radiolarite to limit any significant effects of aquifer discontinuity.

Radial drawdowns for the *Birdrong Sandstone* are shown on Figure 64 (a to e). The predicted drawdowns extend to distances of 30, 35, 50, 60 and 65 km after 1, 2, 5, 10 and 20 years of abstraction. The nearest artesian bores, including Nilemah No. 1A, Caravan Park and Hamelin Homestead, are approximately positioned on the 6 m drawdown contour after 20 years of abstraction. Nanga Resort and Sweeney Mia bores are located near the 2 m and 4 m drawdown contours. Drawdowns of about 15 m are predicted within the area traversed by the planned process water supply borefield between the 5 and 20-year periods.

Within the *Kopke Sandstone*, the predicted drawdown distribution is generally radial, except where the aquifer system is juxtaposed the Tumblagooda Sandstone along the Ajana Fault. Drawdowns are predicted to propagate distances of 30, 40, 55, 60 and 65 km after 1, 2, 5, 10 and 20 years of abstraction, as shown on Figures 65 (a to e).

6.3.2 Abstraction of 15 GL/annum

The predicted drawdowns due to aggregate abstractions of 15 GL/year over the period of mining are of about 1.0 to 3.0 m greater magnitude than those associated with abstraction of 11 GL/year. Predicted drawdown impacts are shown on Figures 67 to 70 for the Windalia Radiolarite, Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone.

The shape of the predicted drawdown cone resulting from 15 GL/year are very similar to the 11 GL/year case. Although slightly larger, the predicted drawdowns resulting from 15 GL/year are not likely to cause significant impacts over that predicted from 11 GL/year. Predicted drawdowns after 20 years in the Windalia Sand Member at 50 km distance are about 0.5 m larger from 15 GL/year, while at 25 km they are only about 1 m larger. Similar trends are apparent within the other aquifers between the two abstraction rates.

Impacts of pumping 15 GL/year on the confining and superficial layers such as the Alinga Formation, Toolonga Calcilutite and superficial formations are expected to be similar to 11 GL/year. Propagation of the additional potentiometric head vertically through the Alinga Formation and lower sections of the Toolonga Calcilutite may only be measurable within 25 km of the mine and have no net impact on either the resource or other groundwater users.

6.4 Predicted Impacts on Private Bores

Drawdown impacts on private bores are likely to vary depending on the aquifer zones that they intersect and the local characteristics of vertical hydraulic connections with the Birdrong Sandstone and Kopke Sandstone. The predicted drawdown impacts on selected private bores are shown in Table 31 and on Figures 71 (a to d) and 72 (a to d), for abstractions of 11 and 15 GL/annum. The magnitude of drawdown impacts in bores that intersect only the Windalia Radiolarite or Windalia Sand Member are expected to be less than those intersecting the Birdrong Sandstone and Kopke Sandstone. Actual drawdown impacts will depend on the local and regional characteristics of vertical hydraulic connections between the Windalia Sand Member and the Birdrong Sandstone.

Predicted Impacts of Large-Scale Process Water Supply Abstractions

SECTION 6

Table 31

Predicted Drawdown Impacts of 11 GL/annum Abstraction on Private Bores

| Name / No. | Predicted Maximum Drawdown (m) | Predicted Time for Recovery to < 0.5 m (years) | Predicted Adverse Impacts | Equipped With | Proposed Remediation (if required) |
|---|--------------------------------|--|-------------------------------------|--------------------------|--------------------------------------|
| Hamelin Station | | | | | |
| Hamelin Homestead No.3 | 6.28 | 6.0 | Lower pressure for power generation | Artesian Headworks | |
| Hamelin No. 4 | <u>2</u> | <u>4.5</u> | Deeper pumping water level | Windmill | Lower pump inlet |
| Hamelin No. 5 | <u>5.5</u> | <u>5.5</u> | Deeper pumping water level | Windmill | Lower pump inlet / Upgrade windmill |
| Outcamp Bore | <u>2</u> | <u>4.5</u> | Deeper pumping water level | Windmill | Lower pump inlet |
| Hamelin No. 8 | 5.61 | 6 | Deeper pumping water level | Windmill | Lower pump inlet / Upgrade windmill |
| Hamelin No 9 | 3.00 | 5.50 | Deeper pumping water level | Windmill | Lower pump inlet |
| Hamelin No. 11 | <u>3.8</u> | <u>5.5</u> | Deeper pumping water level | Windmill | Lower pump inlet |
| Hamelin No. 13 | <u>1.4</u> | <u>4</u> | None | Windmill | |
| Hamelin No. 14 | <u>2</u> | <u>5</u> | Deeper pumping water level | Windmill | Lower pump inlet |
| Hamelin No. 16 | 1.34 | 4 | None | Windmill | |
| Hamelin No. 17 New | <u>4.5</u> | <u>6.5</u> | Deeper pumping water level | Not Equipped | Lower pump inlet |
| Hamelin No. 18 | <u>2.1</u> | <u>5</u> | Deeper pumping water level | Windmill | Lower pump inlet |
| Hamelin No. 20B | 1.32 | 4 | None | Windmill | |
| Hamelin No. 23 | <u>4.2</u> | <u>6</u> | Deeper pumping water level | Windmill | Lower pump inlet / Upgrade windmill |
| Hamelin No. 24 | <u>1.5</u> | <u>4</u> | None | Not Equipped | |
| Hamelin No 26 | <u>1.2</u> | <u>3.5</u> | None | Not Equipped | |
| Hamelin Spinifex 1 | <u>8.9</u> | <u>6</u> | As for Spinifex 2 | Flowing | As for Spinifex 2 |
| Hamelin Spinifex 2 | 8.86 | 6 | May stop flowing | Flowing | Provide alternative external source. |
| Hamelin Kevins Bore | 3.26 | 5.5 | Deeper pumping water level | Windmill | Lower pump inlet |
| Hamelin Five Mile Bore | <u>4.8</u> | <u>5.5</u> | Deeper pumping water level | Windmill | Lower pump inlet / Upgrade windmill |
| Hamelin Ten Mile Bore | 3.26 | 5 | Deeper pumping water level | Windmill | Lower pump inlet |
| Sweeney Mia Bore 2001 | 3.68 | 5 | Lower flow pressure | Nil - Artesian Headworks | |
| Coburn Station | | | | | |
| Coburn No. 7 | 7.72 | 6 | Deeper pumping water level | Mono Pump 54.8m | Lower pump inlet |
| Coburn No. 8 | 3.52 | 7 | Deeper pumping water level | Mono Pump 60.96m | Lower pump inlet |
| Coburn No. 9 B | 8.16 | 7 | Deeper pumping water level | Mono Pump 60.96m | Lower pump inlet |
| Coburn No. 11 B | <u>2.5</u> | <u>5.5</u> | Deeper pumping water level | Mono Pump 60.96m | Lower pump inlet |
| Coburn No. 14 | 5.54 | 7 | Deeper pumping water level | Mono Pump 60.96m | Lower pump inlet |
| Overlander Roadhouse (Main Roads Bore) | | | | | |
| Overlander Roadhouse | 2.27 | 5 | Deeper pumping water level | Electric Submersible | Lower pump inlet |
| Billabong Roadhouse | | | | | |
| Billabong Roadhouse | 0.93 | 3 | None | Electric Submersible | |

Predicted Impacts of Large-Scale Process Water Supply Abstractions

SECTION 6

Table 31 (continued)

| Name / No. | Predicted Maximum Drawdown (m) | Predicted Time for Recovery to < 0.5 m (years) | Predicted Adverse Impacts | Equipped With | Proposed Remediation (if required) |
|---|--------------------------------|--|----------------------------|---------------------------------|------------------------------------|
| Hamelin Telegraph Station & Caravan park | | | | | |
| Hamelin Telegraph Station | 5.88 | 6 | Lower flow pressure | Nil - Artesian Headworks | |
| Meadow Station | | | | | |
| Meadow No. 1 | 1.15 | 3.5 | None | Mono Pump | |
| Meadow No. 3 | 0.96 | 3 | None | Electric Submersible | |
| Meadow No. 4 | <u>0.5</u> | <u>3</u> | None | Windmill | |
| Meadow No. 5 | <u>0.5</u> | <u>3</u> | None | Windmill | |
| Meadow No. 6 | <u>0.5</u> | <u>3</u> | None | Mono Pump | |
| Meadow No. 7 | <u>1.2</u> | <u>3.5</u> | None | Windmill | |
| Meadow No. 8 (New) | <u>1.7</u> | <u>4.5</u> | None | Not Equipped | |
| Nerren Nerren Station | | | | | |
| Nerren Nerren 1A | 1.03 | 3 | None | Mono Pump | |
| Nerren Nerren 5A | <0.5 | <3 | None | Mono Pump | |
| Carbla Station | | | | | |
| Carbla Homestead | <u>3.3</u> | <u>5</u> | None | Artesian Headworks | |
| Carbla No. 12 | <u>2.5</u> | <u>5</u> | Deeper pumping water level | Windmill | Lower pump inlet |
| Carbla No. 13 | 3.07 | 5 | Deeper pumping water level | Windmill | Lower pump inlet |
| Carbla No. 14 | 1.9 | 4.5 | None | Windmill | |
| Carbla No. 16 | 2.47 | 4.5 | Deeper pumping water level | Windmill | Lower pump inlet |
| Carbla No. 17 | <u>2.2</u> | <u>4.5</u> | Deeper pumping water level | Windmill | Lower pump inlet |
| Six Mile Well | 1.67 | 4 | None | Leaking Artesian Headworks | |
| SEC Bore | <u>2.5</u> | <u>4.5</u> | None | Windmill | Lower pump inlet |
| Nanga Station | | | | | |
| Nanga Homestead | 2.15 | 4 | Lower flow pressure | Artesian Headworks | |
| Nilemah Artesian No. 1A | 6.32 | 6 | Lower flow pressure | Nil - Artesian Headworks | |
| Tamala Station | | | | | |
| Cape Well Bore | <u>None</u> | <u>N/A</u> | None | Mono Pump | |
| Beethen Outcamp Well | <u>None</u> | <u>N/A</u> | None | Mono Pump & Windmill | |
| Natta Outcamp Bore | <u>None</u> | <u>N/A</u> | None | Windmill & Electric Submersible | |
| Woodleigh Station | | | | | |
| Woodleigh No 10C | <u>1.5</u> | <u>3.5</u> | None | Electric Submersible | |
| Woodleigh No 11 | <u>2.0</u> | <u>4.5</u> | Deeper pumping water level | Windmill | Lower pump inlet |
| Woodleigh No 22 | <u>1.0</u> | <u>3.5</u> | None | Electric Submersible | |
| Woodleigh No 25 | <u>1.0</u> | <u>3.5</u> | None | Electric Submersible | |
| Toolonga Station | | | | | |
| SB2 | <0.5 | <3.0 | None | Not Equipped | |

Note: Italicised and underlined data has been interpolated between modelled observation points.

Predicted impacts due to abstraction of 11 GL/annum include:

- Drawdowns at the Nanga Resort are predicted to reach 2 m after 20 years of abstraction (Figure 71a).
- Drawdowns on all three of the Carbla Stations bores are likely to increase as mining advances northwards. Predicted drawdowns include 1.7 m at Six Mile Bore and about 2.5 m in Carbla No. 16 (Figure 71a).
- The predicted responses in the Hamelin Station bores vary with distance from the mine as shown on Figures 71 (b to d).
 - Drawdowns of about 9 m in Spinifex Bore after about 20 years of pumping (Figure 71b). It is likely that Spinifex Bore will cease to flow after about 1 to 2 years of pumping from the southern project area. This bore is barely flowing at present due to its elevation and possibly poor condition.
 - Hamelin Nos. 16 and 20 are predicted to have drawdowns of about 1.2 m after about 14 to 16 years of abstraction (Figure 71d).
 - The Hamelin Homestead Bore is predicted to experience slowly increasing drawdowns during the life of the project. Drawdowns of up to 6.1 m are predicted after about 20 years of pumping. This bore is not expected to cease flowing; the artesian head would temporarily decline from 22 to 16 m.
- Both the Nilemah No. 1A and Hamelin Telegraph Station bores are expected to be affected by drawdowns after about two years of abstraction (Figure 71b). These drawdowns are expected to slowly increase as the mine advances northwards, to peak at about 6.2 m after 20 years of abstraction. Neither bore is expected to cease flowing; artesian heads of about 34 m are predicted near the end of the mining.
- On Coburn Station (Figure 71c), drawdowns of 8 m are predicted in Coburn No. 7 and Coburn No. 9, about 5.5 m in Coburn No. 14 and 3.5 m in Coburn No. 8.
- Bores at Billabong and Overlander roadhouses are predicted to experience drawdowns of 0.8 and 2.3 m (Figures 71b and d). The drawdowns at Billabong Roadhouse are predicted to stabilise after 10 to 13 years of abstraction, as the mining moves north from this location. Drawdowns at the Overlander Roadhouse are predicted to slowly increase as the mining moves northwards.
- The Nerren Nerren and Meadow Station bores are predicted to experience up to about 1.0 m of drawdown after about 10 to 13 years of abstraction (Figure 71d). The drawdowns are expected to stabilise as the mine advances to the north.

Predicted drawdowns resulting from large-scale abstractions range between < 0.5 m at distant sites and 8.9 m in proximal sites. If depletion of the existing supply results from the predicted drawdowns, remediation should generally require the lowering of the pump inlets by several meters to maintain sufficient submergence and available drawdown. Proposed remediation measures to overcome the predicted impacts are presented in Table 31.

In the closest bores, the pumping infrastructure may also require upgrading as a result of the increased pumping heads. Further away, most of the bores have potential for lowering the pump inlets, but as the impacts are less, few would require any further action. Adjusting the pump inlets in some of the older bores may pose problems due to the effects of corrosion on casing and pump conditions.

The bores located over the Ajana Ridge to the east should experience < 0.5 to about 1 m of drawdown, particularly in areas where the aquifers are unconfined. Some of these bores only penetrate the unconfined aquifers sufficiently to provide the required supply, so the pump inlets are close to, or within the aquifer intervals. It is unlikely that these bores will experience a depletion or loss of supply, but it is recognised that remediation measures may be required for relatively small drawdowns.

None of the artesian bores are expected to stop flowing, except Spinifex Bore. It is likely that relatively small pressures deliver groundwater to the header tank at the Nanga Resort. The predicted 2.1 m drawdown may decrease the supply available at the header tank and it could require a booster pump from lower level (i.e. near the borehead) if this occurs. A cessation of artesian flows at Spinifex Bore (including both holes) is likely. An alternative supply will need to be sourced when this occurs.

A decrease in the artesian pressure at the Hamelin Homestead may have a significant impact on the ability of the existing equipment to generate a local electricity supply. Further research should be undertaken to derive an equitable solution in the early stages of the mine development and prior to any impacts reaching this bore.

6.5 Aquifer Recovery After Cessation of Abstraction

After pumping has ceased, the aquifer systems will progressively recover. Predictive simulations indicate that the inner part of the drawdown cone will contract rapidly at first, with the regional drawdowns remaining after 2 years. Almost complete recovery is predicted within five years of the cessation of large-scale abstraction. Results of the predictive recovery simulations are shown for the Windalia Radiolarite, Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone on Figures 73 to 76 at period 1, 2, 5 and 10 years after the cessation of 11 GL/annum abstractions. Specific recovery trends in selected private bores are shown on Figure 77 (a to d).

Recoveries in all private bores are predicted to be relatively rapid in the initial 3 to 5 years after the cessation of abstraction, most private bores are predicted to fully recover (less than 0.5 m drawdown) four to six years after the completion of mining. Bores that are closer to the project are predicted to recover at the fastest rates.

6.6 Sustainability of Large-Scale Abstractions

Recharge to the Windalia Radiolarite and Birdrong Sandstone is estimated to be 4.5 GL/annum in the area between Shark Bay and Carnarvon (Hillier *et al.*, 2002). This is a reasonable estimate for the domain of these aquifers in the hinterland of the project area. Historically, large-scale uncontrolled abstractions are understood to have exceeded the rates of annual recharge. The completed bore rehabilitation programmes have reduced abstractions, but currently there may remain a deficit between abstraction and recharge.

Using the available hydrogeological data, the rate of through-flow within the Birdrong Sandstone and Kopke Sandstone beneath the project area is estimated to be in the order of 4.5 GL/annum. This estimate is based on a flow path width of 33 km, thickness of the Birdrong Sandstone and Kopke Sandstone being 25 and 270 m and hydraulic conductivity of these aquifer systems being 13.0 and 1.9 m/day.

In a regional context, the aggregate recharge over a 20-year period is 90 GL and the proposed abstraction is up to 360 GL, equating to a 270 GL temporary deficit in available groundwater resources. This temporary deficit would be enlarged, by continuance of uncontrolled abstractions from artesian bores and pastoral uses, perhaps by another 100 GL. As such, an aggregate temporary deficit in the order of 370 GL might be expected during the project duration.

Groundwater volumes in storage in the regional confined aquifers, excluding the Tumblagooda Sandstone, have been estimated using the developed groundwater flow model.

The estimates include:

| | |
|------------------------|--------------|
| • Windalia Radiolarite | 9,980 GL |
| • Windalia Sand Member | 30,120 GL |
| • Birdrong Sandstone | 189,400 GL |
| • Kopke Sandstone | 1,185,000 GL |
| | _____ |
| Total | 1,414,600 GL |
| | _____ |

The aggregate 20-year deficit of abstraction compared to recharge is interpreted to represent less than 0.03% of the estimates of groundwater volumes in storage within the Birdrong Sandstone and Kopke Sandstone.

The deficit in recharge compared to abstraction would be predominantly manifest as drawdown of the water table in areas where the regional aquifers are unconfined or semi-confined. These areas occur tens of kilometres to the east and south of the project area.

6.7 Summary of Predicted Environmental Impacts

The findings of the groundwater resources impact assessments indicate that the predominant environmental issues and potential risks linked to the large-scale abstractions from the confined aquifer systems for process water supplies include:

- potential for propagation of drawdown impacts from the regional confined aquifer systems into the water table aquifer systems; and
- temporary deficits in recharge compared to abstraction and consequent removal of groundwater from storage in unconfined zones of the regional aquifer systems.

These assessments also indicate that the potentials for adverse environmental impacts linked to the outlined issues are low. For the confined aquifer systems, the predictive simulations show drawdowns of up to 4.0 m within the Toolonga Calcilutite and that the superficial formations are not affected. Also, there are no known adverse impacts from long-term deficits in recharge compared to abstraction due the uncontrolled flows from artesian bores.

Notwithstanding these predictive outcomes, there is uncertainty in the understanding of the regional hydrogeology and confined aquifer flow systems and, the environmental impacts already imposed on both local and regional groundwater resources by uncontrolled artesian abstractions. As such, the conceptual hydrogeological model of the confined aquifer systems and predictive drawdown outcomes due to long term abstraction need to be validated during the early operational phase of the project and the potential environmental risks refined.

The findings of the groundwater resources impact assessments indicate that the predominant environmental issues and potential risks linked to the Amy Zone development include:

- recovery of sand tailings waters and limiting the potentials for mounding of the water table to propagate into the root zones of vegetation stands;
- potential for discharge from the northern water table mounds into salina domain in foreshore areas of Hamelin Pool;
- potential for propagation of drawdown impacts from the regional confined aquifer systems into the water table aquifer systems; and
- temporary deficits in recharge compared to abstraction and consequent removal of groundwater from storage in unconfined zones of the regional aquifer systems.

These assessments also indicate that the potential for adverse environmental impacts linked to the outlined issues is low if managed effectively. Within the superficial formations, the predictive modelling results show that:

- water table mounding within the southern project areas that potentially threatens vegetation root zones can be mitigated by the dedicated operation of in-pit trench drains that intercept and enhance recovery of tailings waters;
- water table mounding within the northern project areas that potentially threatens vegetation root zones can be mitigated by refining knowledge of salina water table and groundwater discharge environments and reviewing mining plans to reduce the rate of northern pit development and reduce the magnitudes of the residual mounds; and
- the simulated mounds do not actually have a surface expression within the salinas.

For the confined aquifer systems, the predictive simulations show drawdowns of up to 4.0 m within the Toolonga Calcilutite and that the superficial formations are not affected. Also, there are no known adverse impacts from long-term deficits in recharge compared to abstraction due to uncontrolled flows from artesian bores.

Notwithstanding the predictive outcomes, there is uncertainty in the hydrogeological interpretations and predictive findings. As such, these issues and potential risks need to be monitored and appropriately managed. It is important that these impacts are quantified so that they can be appropriately managed based on:

- ecological and environmental considerations; and
- the rights of other users of the local groundwater resources.

Regulatory authorisation of groundwater abstraction from the confined aquifers for process water supply should be sought through application for a Licence to Take Water from the DoE. This application should be supported by the technical content of this report and the monitoring and management protocols that

form the Operating Strategy. Authorisation from the DoE should also be sought for abstractions linked to local dewatering of the superficial formations in the northern pit.

7.1 Operating Strategy

The Operating Strategy pertains to the Licence to Take Water for the provision of process water supply from a dedicated borefield and later by dewatering of the superficial formations during mining. It is anticipated that the licences would predominantly relate to the operation of a number of production bores for provision of secure process supplies and sump-pumping to dewater the northern pit. In some pits other dewatering infrastructure such as trenches, well points or production bores may also be used to increase the recovery of tailings water, improve mining conditions and promote water use efficiency. All abstracted groundwater would be used for the process water supply, camp water supply or dust suppression. No excess water will be produced by this operation that will need to be disposed.

7.1.1 Monitoring and Management of Groundwater Resources

Groundwater monitoring programmes have been developed to enable assessment and management of the shallow aquifers due to mine dewatering, residual mounding of the water table in the superficial formations and drawdown in the confined aquifers due to process water supply abstraction. The key objectives of the monitoring programmes are shown in Table 32. The monitoring programmes would involve both quantitative and qualitative measurements of the groundwater resources in:

- Multipiezometers in the superficial formations and shallow Toolonga Calcilutite including the following aspects:
 - Close to and within the active pits to characterise the shallow Toolonga Calcilutite natural water table environment and subsequent mounding magnitudes and distributions due to residual tailings waters for optimisation of mine water recovery.
 - Near the active pits, in areas identified with potential risk to vegetation root zones, to determine the water table setting, actual thickness of the superficial formations and transient data on the residual water table mounding.
 - Within the Nilemah Embayment and environs, to characterise the hydrogeology, lateral and vertical groundwater flow paths and water table environment.
- A regional confined aquifer and confining layer multipiezometer network including the following aspects:
 - Within the local and regional Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone aquifer systems to improve the baseline groundwater level interpretations and provide data on transient drawdown impacts.

- Within the local and regional Alinga Formation, Toolonga Calcilutite and superficial formations to characterise baseline vertical flow gradients and transient drawdown impacts.
- Selected private bores in the region.
- In-pit sumps and sump-pumps.
- The process water supply production bores abstracting drawing groundwater from the confined aquifers.

The monitoring programmes should be reviewed annually and revised as appropriate to remain compatible with the needs of the operating and receiving environments.

Table 32
Objectives of Monitoring Programmes

| Objective | Key Items | Outcomes |
|---|---|--|
| 1. Definition of natural and seasonal baseline conditions – before the commencement of mining | <ul style="list-style-type: none"> • Groundwater level monitoring in all existing and proposed multipiezometers to define seasonal and other transient changes in superficial formations, Toolonga Calcilutite, Alinga Formation, Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone. • Sampling of all multipiezometers to define hydrochemistry parameters and seasonal changes in the superficial formations, Toolonga Calcilutite, Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone. • Quantifying the private water use demands on the confined aquifer groundwater resources. • Installation of the superficial formations and confined aquifer/aquitard multipiezometer networks would be undertaken either 1 year in advance of mining or out to a distance of 20 km from the active process water supply borefield location. | <ul style="list-style-type: none"> • Baseline data for quantitative and qualitative assessments of impacts. |
| 2. Assessment of the impacts of process water supply, pit dewatering abstraction and residual water table mounding. | <ul style="list-style-type: none"> • Measurement of cumulative pumping volumes from all production bores and aggregate monthly totals of in-pit sump-pumps. • Measurement of groundwater levels in local superficial formations and regional confined aquifer/aquitard multipiezometers, production bores and selected private bores. • Sampling and basic analysis of selected superficial formations multipiezometers, private bores and process water supply bores to provide transient quality data for the key aquifers. • Regular assessment and reporting on the impacts of the process water supply, mounding of the water table, pit dewatering and groundwater resource management issues. | <ul style="list-style-type: none"> • To develop an understanding of the impacts of mining on the groundwater resources. • To provide data to appropriately define and manage any adverse impacts from process water supply abstraction, mounding of the water table within the superficial formations and pit dewatering. • To provide sufficient data to define and manage potential adverse impacts on vegetation and other biota in the vicinity of the project. |

Table 32 (continued)

| Objective | Key Items | Outcomes |
|--|--|---|
| 3. Provision of data for refinement of the groundwater flow models | <ul style="list-style-type: none"> As per the Key Items for Objectives 1 and 2 above. Refinement of model parameters based on findings of programmes to construct the process water supply production bores and local and regional multipiezometers. Refinement of model parameters and predictive outcomes if appropriate to enhance management objectives. | <ul style="list-style-type: none"> Increase confidence in the model and predictive outcomes. |
| 4. Meeting reporting requirements of the regulators | <ul style="list-style-type: none"> Annual reporting on forecasts of consumptive water uses. This reporting would be framed on the sand-stacker and slimes trench tailings water recovery strategies, measured tailings water recoveries measured distributions of the water table mounding and refined site water balance estimates. Annual reporting of groundwater abstraction volumes and measured impacts of the abstraction. Review of management protocols to ensure they remain effective. | <ul style="list-style-type: none"> Compliance with the terms, limitations and conditions of the Licence to Take Water. |

An important component of the monitoring programme will be a database that allows efficient entry and collation of data. It is recommended that a monitoring database is developed to provide:

- hydrographs for the multipiezometers and piezometers;
- graphs of monthly and cumulative groundwater abstraction; and
- groundwater quality parameters.

7.1.2 Local Superficial Formations Multipiezometers

The additional multipiezometers should be constructed to independently monitor the superficial formations, shallow Toolonga Calcilutite marine clays and/or shell coquina beach ridge deposits depending on location. Design additional multipiezometers are outlined in Table 33 and locations are shown on Figure 78 (a and b).

Table 33
Locations of Additional Superficial Formations Multipiezometers

| Proposed Multipiezometer | Approximate MGA Co-ordinates | | Purpose |
|-------------------------------------|------------------------------|-----------|---|
| | mE | mN | |
| Nilemah Embayment Monitoring | | | |
| NMB1 | 206,080 | 7,064,620 | Up gradient of Nilemah Embayment on SBWHAP Boundary |
| NMB2 | 207,420 | 7,064,750 | |
| NMB3 | 210,530 | 7,066,850 | Lower reaches of Peron Sandstone |
| NMB4 | 208,730 | 7,067,190 | Back Flats South of Denham Road |
| NMB5 | 209,730 | 7,067,320 | Back Flats South of Denham Road |
| NMB6 | 210,560 | 7,067,710 | Replacement of STB1 |
| NMB7 | 208,330 | 7,068,050 | Denham Road – west |
| NMB8 | 211,520 | 7,068,220 | Denham Road – east |
| NMB9 | 210,460 | 7,068,360 | Nilemah Salina |
| NMB10 | 208,980 | 7,068,540 | Nilemah Salina |
| NMB11 | 210,420 | 7,068,990 | Nilemah Salina |
| NMB12 | 209,820 | 7,069,220 | Nilemah Salina |
| NMB13 | 210,390 | 7,069,610 | Nilemah Salina |
| Vegetation Risk Monitoring | | | |
| VMB1 | 214,340 | 7,032,600 | South end of Amy Zone |
| VMB2 | 212,420 | 7,032,630 | South end of Amy Zone |
| VMB3 | 215,130 | 7,032,930 | South end of Amy Zone |
| VMB4 | 212,370 | 7,033,530 | Southwest of Amy Zone |
| VMB5 | 215,360 | 7,033,690 | Southeast of Amy Zone |
| VMB6 | 212,390 | 7,033,920 | Southwest of Amy Zone |
| VMB7 | 212,380 | 7,034,410 | South west of Amy Zone |
| VMB8 | 215,350 | 7,034,670 | Southeast of Amy Zone |
| VMB9 | 215,400 | 7,035,460 | Southeast of Amy Zone |
| VMB10 | 212,240 | 7,038,840 | West of Amy Zone |
| VMB11 | 212,250 | 7,039,370 | West of Amy Zone |
| VMB12 | 215,450 | 7,043,080 | East of Amy Zone |
| VMB13 | 212,010 | 7,045,970 | West of Amy Zone |
| VMB14 | 215,150 | 7,049,360 | East of Amy Zone |
| VMB15 | 215,010 | 7,050,060 | East of Amy Zone |
| VMB16 | 214,120 | 7,065,070 | Northeast of Amy Zone |
| VMB17 | 210,560 | 7,065,610 | North of Amy Zone |
| VMB18 | 212,390 | 7,066,040 | North of Amy Zone |
| VMB19 | 210,530 | 7,066,250 | North of Amy Zone |

Table 33 (continued)

| Proposed Multipiezometer | Approximate MGA Co-ordinates | | Purpose |
|--------------------------------------|------------------------------|-----------|-----------------------|
| | mE | mN | |
| Long Term Pit Perimeter Areas | | | |
| SMB5 | 212,380 | 7,033,930 | Southwestern Amy Zone |
| SMB6 | 212,240 | 7,038,850 | Western Amy Zone |
| SMB7 | 212,240 | 7,042,950 | Western Amy Zone |
| SMB8 | 212,100 | 7,047,840 | Western Amy Zone |
| SMB9 | 211,100 | 7,052,950 | Western Amy Zone |
| SMB10 | 209,600 | 7,057,830 | Western Amy Zone |
| SMB11 | 208,030 | 7,063,250 | Northwestern Amy Zone |
| SMB12 | 212,000 | 7,066,050 | Northeastern Amy Zone |

These multipiezometers would provide data on the drawdown and mounding impacts within the superficial formations and upper Toolonga Calcilutite in the vicinity of the Shark Bay World Heritage Property to the west and north of the Amy Zone. Additional piezometers will need to be installed within the Amy Zone to establish data on the residual water table mounds. The number and locations of these piezometers will be dependent on access and pit dimensions. Piezometer locations for the first three years are shown on Figure 78a in the southern Amy Zone. Locations of nominal sites for superficial formations multipiezometers in the Nilemah Embayment and environs are shown on Figure 78b.

7.1.3 Regional Piezometers and Private Bores

The existing confined aquifer piezometers, multipiezometers and private bores are valuable facilities providing both historical/baseline hydrogeological data and enabling future access to the groundwater environments for quantitative and qualitative assessments of impacts due to mine development. Regional piezometers and private bores incorporated within the developed monitoring programmes include SMB1 (a to c), STB1, Nilemah Artesian No.1A, Coburn No.4, Hamelin MRD Bore, Hamelin 26 (SB1), and Meadow 5(old), as shown in Table 34 and on Figure 79.

Table 34
Locations of Existing Regional Confined Aquifer Monitoring Bores

| Bore | MGA Co-ordinates | | Interpreted Formation |
|------------------------|------------------|-----------|---|
| | mE | mN | |
| Nilemah Artesian No 1A | 205,888 | 7,073,900 | Windalia Radiolarite/ Birdrong Sandstone – artesian |
| Coburn No. 4 | 249,216 | 7,045,002 | Windalia Sand Member |
| Hamelin MRD Bore | 253,842 | 7,056,239 | Windalia Sand Member |
| Hamelin No. 26 (SB1) | 266,050 | 7,051,196 | Windalia Sand Member or Tumblagooda Sandstone |
| Meadow No. 5 (Old) | 267,779 | 7,038,527 | Windalia Sand Member or Tumblagooda Sandstone |

Additional regional multipiezometers are also proposed to provide specific information relevant to the confined aquifers and confining layers between the planned process water supply borefield and existing artesian bores and other private bores. The planned additional regional confined aquifer and confining layers multipiezometers sites are outlined in Table 35 and also shown on Figure 79.

These multipiezometers should ideally be installed up to a year in advance of mining to provide data on seasonal piezometric level fluctuations and indicative trends. The confining layers (IMB-series) would provide a measure of vertical hydraulic gradients between the confined and unconfined aquifer systems.

Table 35

Locations of Additional Regional Confined Aquifer and Confining Layer Multipiezometers

| Proposed Multipiezometer | Approximate MGA Co-ordinates | | Purpose |
|------------------------------------|------------------------------|-----------|---|
| | mE | mN | |
| Confined Aquifer Monitoring | | | |
| DMB2 | 216,520 | 7,049,880 | Borefield Groundwater Level Monitoring |
| DMB3 | 215,548 | 7,058,265 | Borefield Groundwater Level Monitoring |
| DMB4 | 217,656 | 7,070,673 | Northern Region Groundwater Level Monitoring |
| DMB5 | 235,131 | 7,067,854 | Northeastern Region Groundwater Level Monitoring |
| DMB6 | 236,821 | 7,052,766 | Eastern Region Water Level Monitoring |
| DMB7 | 237,392 | 7,037,272 | Southeastern Region Water Level Monitoring |
| Confining Layer Monitoring | | | |
| IMB1 | 217,880 | 7,033,890 | Confining Layer Multipiezometer in The Southeastern Region of The Project |
| IMB2 | 216,440 | 7,049,890 | Confining Layer Multipiezometer in The Northeastern Region of The Project |
| IMB3 | 211,880 | 7,066,070 | Confining Layer Multipiezometer in The Eastern Region of The Project |
| IMB4 | 217,480 | 7,074,880 | Confining Layer Multipiezometer in The Hamelin Pool Region |

7.1.4 Production Bores and In-Pit Sump Pumping

The production bores associated with process water supply and in-pit sump-pumps for tailings water recovery and pit dewatering would be included in the monitoring programme. To accommodate the defined monitoring requirements, the individual production bores and individual sump-pumps or combined sump-pumping systems should be equipped with flow meter(s) to define instantaneous and cumulative groundwater abstraction and tailings water recovery rates. Pumping water levels in each production bore should also be regularly measured to enable assessments of pumping performance and sustainable yields.

7.1.5 Water Resources Monitoring Programme

A monitoring programme appropriate for the assessments of the impacts of mining on the shallow groundwater and surface water resources is outlined in Table 36. This programme should be reviewed on an annual basis as part of the annual reporting requirements.

**Table 36
Monitoring Programme**

| Monitoring | Parameters | Monitoring Frequency |
|--|---|--|
| BASELINE SAMPLING | | |
| Local Superficial Formations Multipiezometers <ul style="list-style-type: none"> • SMB2 to SMB4. • Additional Multipiezometers SMB5 to SMB12 • Additional Vegetation Monitoring Multipiezometers VMB1 to VMB19 Adjacent to The Active Pits. • Nilemah Embayment Monitoring Multipiezometers NMB1 to NMB13 to the north of the project area | Groundwater Levels Groundwater Quality: pH, EC, TDS. Groundwater Quality: pH, EC, TDS, Total Alkalinity, Total Hardness, Cl, CO ₃ /HCO ₃ , SO ₄ , NO ₃ , NO ₂ , Na, K, Ca, Mg, Fe, SiO ₂ , Al, Mn, As, Cd, Cu, Pb, Se and Zn. | Monthly Quarterly Annually |
| Regional Piezometers <ul style="list-style-type: none"> • Existing/Nilemah Artesian No.1A, Coburn No.4, Hamelin MRD Bore, Hamelin 26 (SB1), and Meadow 5(old), and DMB1 • Additional Multipiezometers DMB2 to DMB7 and IMB1 to IMB4 | Groundwater Levels or Pressures (artesian bores) Groundwater Quality: pH, EC, TDS (artesian bores) | Monthly. |
| DURING MINING SAMPLING | | |
| Local Superficial Formations Multipiezometers <ul style="list-style-type: none"> • SMB2 to SMB4. • Additional Multipiezometers SMB5 to SMB12 • Additional Vegetation Monitoring Multipiezometers VMB1 to VMB19 Adjacent to The Active Pits. • Nilemah Embayment Monitoring Multipiezometers NMB1 to NMB13 to the north of the project area | Groundwater Levels Groundwater Quality: pH, EC, TDS. Groundwater Quality: pH, EC, TDS, Total Alkalinity, Total Hardness, Cl, CO ₃ /HCO ₃ , SO ₄ , NO ₃ , NO ₂ , Na, K, Ca, Mg, Fe, SiO ₂ , Al, Mn, As, Cd, Cu, Pb, Se and Zn. | Monthly Quarterly Annually |
| Regional Piezometers <ul style="list-style-type: none"> • Existing/Nilemah Artesian No.1A, Coburn No.4, Hamelin MRD Bore, Hamelin 26 (SB1), and Meadow 5(old), and DMB1 • Additional Multipiezometers DMB2 to DMB7 and IMB1 to IMB4 | Groundwater Levels or Pressures (artesian bores) Groundwater Quality: pH, EC, TDS (artesian bores) | Monthly. |

Table 36 (continued)

| Monitoring | Parameters | Monitoring Frequency |
|------------------|--|---|
| Sump-pumps | Abstraction Volumes Pump Operating Hours Collation of Cumulative Discharge Groundwater Quality: pH, EC, TDS Groundwater Quality: pH, EC, TDS, Total Alkalinity, Total Hardness, Cl, CO ₃ /HCO ₃ , SO ₄ , NO ₃ , NO ₂ , Na, K, Ca, Mg, Fe, SiO ₂ , Al, Mn, As, Cd, Cu, Pb, Se and Zn. | Weekly Weekly Monthly Monthly Quarterly |
| Reporting | Preparation of Aquifer Reviews that detail the operational and technical aspects of the project. It is important that the Aquifer Reviews provide definitive assessments and reviews of: <ul style="list-style-type: none"> • New information on baseline groundwater environments • Residual mound characteristics • Residual mound distributions • Rates of tailings water recovery • Findings of risk assessments associated with propagation of the mounds to within vegetation root zones • Refinements on the fate of the residual tailings waters • Forecasts of consumptive process water uses • Lateral drawdown impacts within the confined aquifer systems • Impacts of drawdown on other groundwater users • Vertical propagation of drawdown within the Alinga Formation and Toolonga Calcilutite. These assessments should subsequently be applied to refine the water resources monitoring and management programmes. | Annual |
| Production Bores | Abstraction Volumes Groundwater Levels Groundwater Quality: pH, EC, TDS Groundwater Quality: pH, EC, TDS, Total Alkalinity, Total Hardness, Cl, CO ₃ /HCO ₃ , SO ₄ , NO ₃ , NO ₂ , Na, K, Ca, Mg, Fe, SiO ₂ , Al, Mn, As, Cd, Cu, Pb, Se and Zn. | Weekly Weekly Monthly Quarterly |

Table 36 (continued)

| Monitoring | Parameters | Monitoring Frequency |
|--|---|---|
| POST-MINING SAMPLING | | |
| <p>Local Superficial Formations Multipiezometers</p> <ul style="list-style-type: none"> • SMB2 to SMB4. • Additional Long-Term Multipiezometers SMB5 to SMB12 • Additional Vegetation Monitoring Multipiezometers VMB1 to VMB19 Adjacent to The Active Pits. • Nilemah Embayment Monitoring Multipiezometers NMB1 to NMB13 to the north of the project area. | <p>Groundwater Levels</p> <p>Groundwater Quality: pH, EC, TDS.</p> <p>Groundwater Quality: pH, EC, TDS, Total Alkalinity, Total Hardness, Cl, CO₃/HCO₃, SO₄, NO₃, NO₂, Na, K, Ca, Mg, Fe, SiO₂, Al, Mn, As, Cd, Cu, Pb, Se and Zn.</p> | <p>Monthly</p> <p>Quarterly</p> <p>Annually</p> |
| <p>Regional Piezometers</p> <ul style="list-style-type: none"> • Existing Nilemah Artesian No.1A, Coburn No.4, Hamelin MRD Bore, Hamelin 26 (SB1), and Meadow 5(old). • Additional Multipiezometers DMB2 to DMB7 and IMB1 to IMB4 | <p>Groundwater Levels or Pressures (artesian bores)</p> <p>Groundwater Quality: pH, EC, TDS (artesian bores)</p> | <p>Monthly.</p> <p>Quarterly</p> |
| <p>Reporting</p> | <p>Preparation of Aquifer Reviews that detail the operational and technical aspects of the project. It is important that the Aquifer Reviews provide definitive assessments and reviews of:</p> <ul style="list-style-type: none"> • Residual mound distributions • Refinements on the fate and potential impacts of the residual tailings waters • Recovery of the confined aquifer systems • Impacts of drawdown on other groundwater users | <p>Annual for at least 5 years after mining</p> |

Note: 1 The duration of post-mining monitoring is not closely defined. It is linked to, and dependent on the need to manage rehabilitation programme schedules and rates of water table recovery. The minimum duration would be three years.

The Amy Zone mineral sand resource is located adjacent to the eastern limits of the Shark World Heritage Property, south of Hamelin Pool; on the Hamelin and Coburn stations. Development of the mineral sand resource is proposed over a 20-year period, using conventional dry strip mining and wet gravity concentrators. Development is proposed to commence in the southern Amy Zone and progress to the north.

The Amy Zone is predominantly comprised of reworked Peron Sandstone, has typical slimes contents less than 1% by weight and is dry except in localised northern areas. Mined ore would be mixed with groundwater and processed in slurry form to extract ilmenite and zircon sands. Once mined, the developed pits would be backfilled with slurried sand tailings. Groundwater is proposed to be abstracted from regional confined aquifer systems formed by the Birdrong Sandstone and Kopke Sandstone for meeting of process water supply demands. Process water supply demands up to about 18 GL/annum are forecast.

The known groundwater resources issues linked to the proposed Amy Zone developments include:

- Recovery and reuse of process water from the disposed sand and slimes tailings, limiting consumptive groundwater use.
- Mounding of the water table in the superficial formations, due to disposal of sand and slimes tailings in slurry form, to within the root zones of vegetation stands.
- The transport and fate within the superficial formations of residual process waters not recovered from the disposed sand and slimes tailings, given the water table aquifer would discharge in part into Nilemah Embayment and Hamelin Pool.
- Salinisation of the process water supplies due to recycling and cumulative effects of evaporative losses.
- Drawdown impacts within the superficial formations resulting from pit dewatering in the northern project area.
- Drawdown impacts within the confined aquifer systems due to large-scale abstractions from the Birdrong Sandstone and Kopke Sandstone for process water supplies.
- Potential for propagation of drawdown impacts from the regional confined aquifer systems vertically upwards into the water table aquifer.
- Removal from storage of groundwater in the regional confined aquifer systems due to rates of forecast abstractions exceeding the estimated recharge and throughflow beneath the project area.

Each of these known groundwater resources issues has been specifically addressed in order to frame the potential environmental impacts and effects on existing groundwater supply amenities and use. The hydrogeology of the Carnarvon Basin is comparatively poorly defined. Consequently, there is uncertainty in the interpreted hydrogeology. The findings of hydrogeological site investigations and geo-biology

research in the vicinity of Hamelin Pool have been applied in order to understand and manage the outlined issues.

The findings of the site investigations and research literature have initially been consolidated to develop conceptual hydrogeological models of the superficial formations and the regional confined aquifer systems. Key elements of these models include:

- **Superficial Formations Conceptual Hydrogeological Model**

The water table occurs in the northern superficial formations, in areas proximal to Hamelin Pool, and the underlying predominantly silty or sand clay beds of the Toolonga Calcilutite. The water table is recharged by both rainfall infiltration and upward leakage from the regional confined aquifer systems. Where saturated, the Peron Sandstone forms a comparatively homogeneous and transmissive aquifer system. Conversely, the Toolonga Calcilutite typically forms a low-transmissivity low-flow groundwater environment. Groundwater flow is towards the northwest, north, with discharge into Nilemah Embayment and Hamelin Pool.

On a local scale, groundwater flow is controlled by palaeodrainage features on the Toolonga Calcilutite contact and marine clay deposits in foreshore areas of Hamelin Pool. Both influence the location and mechanisms for discharge of groundwater. Subcrop or outcrop zones of the marine clay deposits are characterised by topographic depressions, clay pans and saline. These zones overlie a shallow water table, hypersaline groundwater and are interpreted to form groundwater discharge (by evaporation) zones.

Groundwater in the superficial formations and shallow Toolonga Calcilutite is saline to hypersaline, slightly acidic and a sodium-chloride type. Salinities increase along the flow paths, being highest beneath the saline discharge zones.

Localised aquifer systems occur beneath the shell coquina beach ridges that support flow of groundwater and chemical nutrients to stromatolite and algal mat colonies within the intertidal zone of Hamelin Pool.

- **Confined Aquifer Conceptual Hydrogeological Model**

The predominant confined aquifer zones are formed by the Windalia Radiolarite, Windalia Sand Member, Birdrong Sandstone, Kopke Sandstone and Tumblagooda Sandstone. Each aquifer is regional in extent, with recharge zones occurring where they subcrop beneath the Ajana Ridge and along the southern and southeastern catchment divides. Regional groundwater flow is westwards, with discharge into Hamelin Pool, Freycinet Reach and the Indian Ocean. Upwards hydraulic gradients are interpreted between the confined aquifer systems, with resultant discharge through the overlying argillaceous deposits of the Alinga Formation and Toolonga Calcilutite.

The aquifer formed by the Birdrong Sandstone and Kopke Sandstone are characterised by hydraulic conductivities in the range from 5 to 13 and 2 to 4 m/day beneath the project area. The salinity of mixed groundwater abstracted from these aquifer systems is 8,900 mg/L TDS in DTB1.

Recharge to the confined aquifer systems is estimated to be 0.5% of annual average rainfall, equivalent to about 4.5 GL/annum. Long-term historical abstractions from uncontrolled artesian bores are understood to exceed the annual rates of recharge.

Assessments of the known groundwater resources issues linked to the proposed Amy Zone developments have been undertaken using representative groundwater flow models of the superficial formations and regional confined aquifer systems. These models have been applied to determine:

Superficial Formations

- Proactive sand tailings water recovery strategies. Outcomes show an average annual recovery rate of between 43 to 68%. The differences in recoveries are predominantly linked to the numbers and locations of pit-floor drains to intercept the tailings water and the length of flow paths to the drains. Maximum recoveries occur where more rather than fewer drains are employed and the lengths of the flow paths are comparatively short.
- Consumptive process water supply demands that range from 11 to 15 GL/annum, to service two 2,200 tph concentrators. Differences in the consumptive use are directly linked to the sand tailing water recoveries. Under extremely adverse operating conditions the consumptive water use might reach 18 GL/annum.
- The magnitude, extent and propagation of water table mounding within the superficial formations are due to sand tailings water that is not recovered. Mounds up to 15 to 20 m in height are predicted in the immediate vicinity of active sand-stackers. Individual mounds would occur in each pit during backfilling with sand tailings, with characteristics dependent on the thickness of the superficial formations beneath the pit floor and rates of sand-stacker advance. In broad terms, the typical mounds are forecast to propagate during the mining operations distances up to 900 m behind the initial sand-stacking area, 500 m beyond the pit sides and 400 m beyond the end of individual pits.
- The fate of tailings waters that contribute to residual mounds, given that discharge in part would ultimately be into Hamelin Pool. The groundwater flow models show that the residual mounds progressively decay in height after cessation of sand-stacker operations. Also, the mounds migrate down gradient along regional flow paths and gradually dissipate within the water table environment. Rates of mound dissipation would be linked to the local water table environment and transmissivity of the saturated superficial formations and shallow Toolonga Calcilutite profiles.
- The outcomes of the predictive groundwater flow modelling indicate residual mounds remain evident after a 50-year duration.
- Salinisation of the process water supplies, due to cumulative effects of evaporation losses, in forecast to progressively increase salt loadings by about 40%. Over the 20-year mining period, the salinity of the process water would increase from 8,900 to 12,600 mg/L TDS.
- Pit dewatering in the northern project area. Typically, the saturated thickness of the superficial formations to be mined in less than one to two metres, representing a low-transmissivity, limited-

extent aquifer setting. Abstractions to facilitate dry mining would be small-scale (<500 kL/day) and would not impose any adverse impacts on the water table environment in areas adjoining the northern pit.

The findings of the superficial formations groundwater resources impact assessments indicate that the predominant environmental issues and potential risks linked to the Amy Zone development include:

- recovery of sand tailings waters and limiting the potentials for mounding of the water table, within both the southern and northern project areas, propagating into the root zones of vegetation stands; and
- potentials for discharge from the northern water table mounds into salina domains within the Nilemah Embayment and the Shark Bay World Heritage Property.

The proposed mining developments would temporarily alter the water table environment. Mounding of the water table due to tailings processes has the potential to invade the root zones of vegetation. This may occur in several locations adjacent to the proposed pits where the thickness of the superficial formations is less than 10 m. These areas occur both west and north of the proposed pits, in the Shark Bay World Heritage Property, and further east. Residual tailings waters may rise close to the surface near the base of the Peron Sandstone dunes around the fringes of the Nilemah Embayment. The residual water table mounding due to sand tailings disposal is predicted to remain within about 3 km of the project area. Throughflow would be towards the Nilemah Embayment, with discharge being controlled in part by evaporation-dominated hydro-cycle in salinas, presence of marine clay beds and rates of groundwater throughflow.

These assessments also indicate that the potentials for adverse environmental impacts linked to the outlined issues is low and broadly acceptable in the south, but medium in the north and requiring the identification of further risk reduction options. Within the superficial formations, the predictive modelling results show that:

- water table mounding within the southern project areas that potentially threatens vegetation root zones can be mitigated by the dedicated operation of in-pit trench drains that intercept and enhance recovery of tailings waters;
- water table mounding within the northern project areas that potentially threatens vegetation root zones can be mitigated by refining knowledge of salina water table and groundwater discharge environments and reviewing mining plans to reduce the rate of northern pit development, the number of sand-stackers in operation and the magnitudes of the residual mounds; and
- the simulated mounds do not actually have a surface expression within the salinas.

The mitigation of potential risks to stands of vegetation in perimeter areas of the proposed pits should be approached in a staged manner. This staged approach includes:

- mapping of the vegetation and typical depths of root penetration;
- the installation of multipiezometers to characterise thickness of the superficial formations and depths to the water table;
- use of the additional knowledge to refine the potential risks;
- monitoring of actual water table mounding;
- where appropriate, maintain active drains in the pit(s) adjacent to areas at risk in order to intercept and abstract tailings water locally contributing to the mounding; and
- where appropriate review the mining plans to increase the duration of mining and reduce the residual mounding.

No groundwater-dependent flora or fauna are known in the project area. No stygofauna were found following a survey conducted on all shallow groundwater bores in and near the project area (UWA, 2005). The nearest groundwater dependent ecosystem is likely to be the estuarine ecology associated with Hamelin Pool and the Nilemah Embayment. Both are groundwater discharge areas. The stromatolites along the shoreline of Hamelin Pool, near the old Hamelin Telegraph Station, are located in groundwater discharge zones about 12 km from the northern project area. The groundwater discharge is from a different catchment than the project area and Nilemah Embayment. There are no predicted impacts on the Hamelin Pool ecosystem due to occurrence of residual tailings waters in the superficial formations and water table environment.

Additional investigations are required to refine the understanding of the local vegetation systems and water table environment. Results of these investigations would be applied to refine the potential environmental risks and develop appropriate and practical mitigation strategies. These aspects might be aligned with reviews of the mine plans for the northern pit that consider options for scheduling and/or staging of the developments to lengthen the mining period, minimise the number of sand-stackers in use and consequently reduce the volumes of tailings waters in residual mounds.

Regional Confined Aquifers

- Drawdown impacts due to forecast abstractions of 11 to 15 GL/annum. Abstractions in this range have been simulated from three and four production bores, with pumping rates of 15,060 to 18,500 kL/day.
- Predicted drawdowns in the Windalia Radiolarite, Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone will radially propagate 60 to 75 km from the project area. The magnitudes of the predicted drawdowns would vary from about 9 m beneath the project area to <1.0 m in a regional context.

-
- The predicted drawdowns would impact on private bores. Impacts on private bores that intersect only the Windalia Radiolarite and Windalia Sand Member are expected to be less than those intersecting the Birdrong Sandstone and Kopke Sandstone. Predicted impacts on about 60 private bores have been quantified, together with proposed remedial actions (if required) to enable the monitoring of existing supplies and amenity. In most bores, remedial actions are linked to lowering of pump inlets to maintain sufficient submergence and available drawdown. The pumping infrastructure in bores closest to the project area may also require upgrading. Spinifex Bore is the only artesian bore expected to stop flowing. A decrease in the artesian pressure at the Hamelin Homestead may adversely impact on the ability of the existing equipment to generate local electricity supplies.
 - The predicted drawdowns due to abstractions from the confined aquifer systems would propagate vertically upwards in the stratigraphic profile, being manifest in decreasing magnitudes in the Alinga Formation, Toolonga Calcilutite and superficial formations. No measurable drawdowns are forecast in the superficial formations beneath the northern project area. Within the Toolonga Calcilutite, the predicted drawdowns range up to 3 m beneath the project area and 1 m at distances of 12 km. The predicted drawdowns in the Toolonga Calcilutite propagate beneath Hamelin Pool.
 - Almost complete recovery of the confined aquifer systems is predicted within five years of the cessation of process water supply abstractions.
 - The developed and calibrated regional confined aquifer groundwater flow model is characterised by a predominance of vertical upward groundwater flow throughout the stratigraphic profile. Outcomes from the predictive modelling are sensitive to the simulated vertical hydraulic conductivity values.

The findings of the groundwater resources impact assessments indicate that the predominant environmental issues and potential risks linked to the large-scale abstractions from the confined aquifer systems for process water supplies include:

- potentials for propagation of drawdown impacts from the regional confined aquifer systems into the water table aquifer systems; and
- temporary deficits in recharge compared to abstraction and consequent removal of groundwater from storage in unconfined zones of the regional aquifer systems.

These assessments also indicate that the potentials for adverse environmental impacts linked to the outlined issues are low. For the confined aquifer systems, the predictive simulations show drawdowns of up to 4.0 m within the Toolonga Calcilutite and that the superficial formations are not affected. Also, there are no known adverse impacts from long-term deficits in recharge compared to abstraction due the uncontrolled flows from artesian bores.

Notwithstanding these predictive outcomes, there is uncertainty in the understanding of the regional hydrogeology and confined aquifer flow systems and, the environmental impacts already imposed on both local and regional groundwater resources by uncontrolled artesian abstractions. As such, the conceptual hydrogeological model of the confined aquifer systems and predictive drawdown outcomes due to long

term abstraction need to be validated during the early operational phase of the project and the potential environmental risks refined.

A reasonable estimate for recharge to the domain of the confined aquifer systems in the hinterland of the project area is 4.5 GL/annum. Historical abstractions from uncontrolled artesian bores are understood to have exceeded the rates of annual recharge. In a regional context, the aggregate recharge over a 20-year period is 90 GL. Proposed abstraction is up to 360 GL over the same period, equating to a 270 GL temporary deficit in available groundwater resources. This temporary deficit would be enlarged by continuance in the future of uncontrolled abstractions from artesian bores, perhaps by another 100 GL. As such, the aggregate temporary deficit would be in the order of 370 GL during the project period. A deficit of this magnitude is interpreted to represent <0.03% of the groundwater volumes in storage within the Birdrong Sandstone and Kopke Sandstone in the recharge domain. The deficit in recharge compared to abstraction would be predominantly manifest as drawdown in unconfined aquifer zones.

An Operating Strategy has been developed to facilitate appropriate monitoring and management both local and regional groundwater resources and associated potential impacts. Key elements of the Operating Strategy include:

- The establishment of investigation and monitoring facilities linked to:
 - characterising tailings water recovery and residual water table mound magnitudes and distributions;
 - characterising the baseline groundwater environment in areas of potential risk due to water table mounding invading the root zones of overlying vegetation;
 - refining the understanding of the hydrogeology of the superficial formations in areas between the northern pit and Hamelin Pool;
 - improving the quantitative and qualitative water table baseline and relationships, in terms of groundwater levels and groundwater flow, between the superficial formations and Toolonga Calcilutite;
 - characterising the vertical potentiometric level distributions within the Alinga Formation, Toolonga Calcilutite and superficial formations;
 - measurement of drawdown magnitudes and distributions in the superficial formations (if any), Toolonga Calcilutite, Alinga Formation, Windalia Sand Member, Birdrong Sandstone and Kopke Sandstone due to the process water supply abstractions; and
 - assessment of vertical hydraulic conductivities in the groundwater flow systems.
- Establishment of monitoring programmes that provides both quantitative and qualitative baseline, operating phase and post-mining data on the relevant groundwater environments and aquifer systems.

-
- Specification of reporting schedules whereby measured actual impacts are compared with those predicted and the implications of differences can be investigated and assessed.

Development of the Coburn Mineral Sand Project would result in both local and regional impacts on the groundwater resources, groundwater environments and other users. The developed conceptual hydrogeological models and several input parameters to the predictive groundwater flow models used in the reported groundwater resources impact assessments incorporate uncertainty. As such, there are requirements to verify, through investigation, monitoring and operational practises, several of these aspects in order to refine the understanding of the aquifer systems and potential risks to the environment and existing groundwater users. The following recommendations are made on this basis:

- Use of this report in support of the Public Environmental Review for the project and Groundwater Well Licence applications for abstractions of up to 18 GL/annum from the confined aquifer systems for process water supplies.
- Trial and implement robust, practical and secure tailings water recovery strategies that strongly promote and demonstrate groundwater conservation principles. Such strategies are fundamental to limiting the environmental risks associated with the project. Sustained recovery rates would be predominantly linked to implementation of effective drain systems in proximity to the operational sand-stackers and limiting the length of the flow paths from the deposited sand tailings and drain systems.
- Implement monitoring programmes, particularly in the initial three years of the project, that enable the magnitudes and dimensions of the water table mounding beneath the sand-stackers to be characterised. The monitoring data are fundamental to demonstrating actual fates of the residual sand tailings waters and the refinement of potential environmental risks.
- Implement investigation and monitoring programmes in known areas of potential environmental risk due to water table mounding encroaching on the root zones of vegetation stands. These programmes are forecast to include:
 - mapping of vegetation and typical depths of root penetration;
 - installation of multipiezometers to characterise ground surface elevations, thickness of the superficial formations, shallow Toolonga Calcilutite lithologies and water table elevations;
 - use of the additional data to refine the potential environmental risks;
 - monitoring of actual water table mounding;
 - where appropriate, maintain active drains in the pit(s) in order to intercept and abstract tailings waters locally contributing to the water table mounding; and
 - Where appropriate review the mining plans to increase the duration of mining and reduce the residual mounding.
- Develop practical operating strategies linked to the sand-stackers that would facilitate the retention and tailing waters abstraction from localised in-pit drains required to limit environmental risks to nearby vegetation stands. The mitigation of all risks associated with mounding of the water table

beneath woodland areas is considered to be best and most practicably achieved through the localised retention and use of drains in the developed pits. This approach seeks to intercept the tailings waters nearer their source, promote recovery by reducing the lengths of flow paths and avoid access and intrusive activities within the Shark Bay World Heritage Property.

- Implement investigation and monitoring programmes within the Nilemah Embayment to refine the understanding of the stratigraphy hydrogeology and shallow groundwater environments. The Nilemah Embayment and adjoining Hamelin Pool would form discharge zones for the residual tailings water mounds. The understanding of potential impacts in shallow water table settings needs refinement given small-scale changes in water table elevations might promote direct impacts on salinas in the Nilemah Embayment. The investigation programmes should involve the installation of multipiezometers that enable characterisation of the lateral and vertical groundwater gradients and flow paths and, aquifer tests that enable interpretation of the hydraulic conductivity of the predominant stratigraphic units. Data from these investigations would be applied to demonstrate baseline groundwater environments.
- Review mining plans to reduce the rate of northern pit development, the number of sand-stackers in operation and the magnitudes of the residual mounds.
- Investigate and monitor the vertical hydraulic gradients and hydraulic conductivities within the Alinga Formation and Toolonga Calcilutite. Refinement in the understanding of these parameters is integral to quantifying, in both a local and regional context, the propagation of drawdown impacts from the confined aquifer systems to the water table environment.
- Establish a multipiezometer network in the confined aquifer systems that provide a robust pre-development baseline and subsequently enables an accurate assessment of local and regional drawdown impacts.

Existing bores identified in the monitoring programmes should be assessed to ensure construction details, screened intervals and datum elevation are known. Otherwise alternative bores might be used.

Regional multipiezometers specifically installed in the predominant aquifer zones should be lithologically and geophysically logged and constructed similar to DMB1.

- Develop and implement a communication strategy to broadcast to individual pastoralists the predicted drawdown impacts on their production bores. Subsequently, agreed monitoring and remediation (if required) strategies need to be framed in terms of responsibilities and commitments.
- Process water supply production bore designs should be reviewed in context of the use of corrosion-resistant casings and the use of finer aperture screens or a gravel-pack construction.

-
- Allen, A.D., 1987 Groundwater contributions to the Geology of the Carnarvon Basin, Western Australia, pp 237-244. Bulletin 133 of the Geological Survey of Western Australia, Department of Mines Western Australia, Perth 1987.2” edited by P. G. Purcell and R.R. Purcell: Petroleum Exploration Society of Australia Symposium, Perth, W.A., 1998, Proceedings, pp 599-611.
- Astill, W., Baston K., and Shepherd, R. Carnarvon Artesian Basin: 90% Saved, What Now? Paper presented at the GAB Fest 2002 Conference held by the Great Artesian Basin Consultative Council, 11 March 2002.
- Blandford, D.C., Coburn Mineral Sands Project, Soils and Landforms of the Amy Zone Ore Body. Unpublished report prepared for URS Australia. May 2004.
- Bureau of Mineral Resources (BMR), 1990. The Geobiology of Hamelin Pool, Research Reports of the Baas Becking Geobiological Laboratory’s Shark Bay Project. Record 1990/89, Compiled by RV Burne and G Hunt.
- Department of Environment, 2004. Drillhole data extract derived from the WINS database held at Plain St, East Perth.
- Geo-Eng Australia Pty. Ltd., 1999. Carnarvon Basin Rehabilitation Project – Stage 1. Geophysical Logging and Bore Assessment, Report No. 3 of 38 – Nanga No. 1 Bore. Report 1700/9518/103, October 1999.
- Geo-Eng Australia Pty. Ltd., 1999. Carnarvon Basin Rehabilitation Project – Stage 1. Geophysical Logging and Bore Assessment, Report No. 32 of 38 – Hamelin Station – Homestead No. 2 Bore. Report 1700/9518/132, November 1999.
- Geo-Eng Australia Pty. Ltd., 1999. Carnarvon Basin Rehabilitation Project – Stage 1. Geophysical Logging and Bore Assessment, Report No. 37 of 38 – Hamelin Spinifex No. 2 Bore. Report 1700/9518/137, November 1999.
- Hiller, B.T. Dogramaci S, Clement P, & Wills R. Solutes, Stable Isotopes and Radiocarbon Isotopes as Tracers of Groundwater Flow, Carnarvon Basin, Western Australia. Paper presented to IAH Conference “Balancing the Budget, Darwin, May 2002.
- Hocking, R.M. and Moors, H.T. and Van De Graaff, W.J.E., 1987. Geology of the Carnarvon Basin, Western Australia, Bulletin 133 of the Geological Survey of Western Australia, Department of Mines Western Australia, Perth 1987.
- Iasky, R.P., Ercole, C.D., Ghori, K.A.R., Mory, A.J., and Lockwood, A.M., 2003. Structure and Petroleum Prospectivity of the Gascoyne Platform, Western Australia. Report 87, Geological Survey of Western Australia, Perth, 2003.
- Kempin, E., and Fujioka, N., 1973. Tamala No. 1 Well, Western Australia, Well Completion Report for Oceania Petroleum Pty Ltd. September 1973.

-
- Knott, B & Goater, S., 2005. Coburn Mineral Sand Project Amy Zone Operation - Stygofauna Pilot Survey. Unpublished draft report prepared for Gunson Resources Ltd. M092 Zoology, The University of Western Australia, January 2005.
- Mattiske, pers. comm. 2005. Key Issues related to the Potential Impacts of proposed mine water mounding on the Gunson Project Area. Undated document No. URS0501r5.doc.
- McWhae, J.R.H., 1958. Hydrodynamic and Salinity Studies of the Chief Aquifers of the Carnarvon Basin. Unpublished report to West Australian Petroleum Pty Ltd.
- Mory, A.J., Iasky, R.P., and Shechenko, S.I., 1998, The Coolcalalaya Sub-Basin: A Forgotten Frontier 'between' the Perth and Carnarvon Basins, WA. In "The sedimentary basins of Western Australia.
- Ninox, 2005. Vertebrate Fauna Survey, Coburn Mineral Sands Project. Unpublished report to URS Australia Pty Ltd. And Gunson Resources Limited by Ninox Wildlife Consulting, January 2005.
- Playford, P.E., and Chase, R.E., 1955. Carnarvon Basin Water Bores: Unpublished report to West Australian Petroleum Pty Ltd.
- URS, 2003. Environmental Referral Submitted Under Chapter 4 of the Environment Protection and Biodiversity Conservation Act, 1999 for the Coburn Mineral Sands Project. Unpublished report prepared for Gunson Resources Limited, 9 September 2003. Report No. 52830-001-562/552-F5940.0
- URS, 2003. Environmental Referral Submitted Under Section 38(1) of the Environmental Protection Act, 1986 for the Coburn Mineral Sands Project. Unpublished report prepared for Gunson Resources Limited, 16 September 2003. Report No. 52830-001-562/552-F5941.2
- URS, 2004. Preliminary Water Resources Study, Coburn Project. Unpublished report to Gunson Resources Limited. 1 April 2004. Report No. 52830-001-562/580-F6240.1.doc.
- Water & Rivers Commission, 1996. Gascoyne Region Water Resources Review and Development Plan. Vols. I and II. Water and Rivers Commission Report, Water Resource Allocation and Planning Series, 1996.
- Wills, R and Dogramaci S, Hydrogeology Report No. 170, Carnarvon Basin, Hydrogeology and Hydrochemistry of the Confined Groundwater Systems, WA. Water & Rivers Commission, Perth, 2000.
- Yasin, A.R. and Mory, A.J., 1999. Coburn 1 Well Completion Report, Gascoyne Platform, Southern Carnarvon Basin, Western Australia. Record No. 1995/5 of the Geological Survey of Western Australia, Department of Minerals and Energy, Perth 1999.

URS Australia Pty Ltd (URS) has prepared this report for the use of Gunson Resources Limited in accordance with the usual care and thoroughness of the consulting profession. It is based on generally accepted practices and standards at the time it was prepared. No other warranty, expressed or implied, is made as to the professional advice included in this report. It is prepared in accordance with the scope of work and for the purpose outlined in the Proposal dated 10 March 2004.

The methodology adopted and sources of information used by URS are outlined in this report. URS has made no independent verification of this information beyond the agreed scope of works and URS assumes no responsibility for any inaccuracies or omissions. No indications were found during our investigations that information contained in this report as provided to URS was false.


This report was prepared between 23 July 2004 and 14 January 2005 and is based on the conditions encountered and information reviewed at the time of preparation. URS disclaims responsibility for any changes that may have occurred after this time.

This report should be read in full. No responsibility is accepted for use of any part of this report in any other context or for any other purpose or by third parties. This report does not purport to give legal advice. Legal advice can only be given by qualified legal practitioners.

This report contains information obtained by inspection, sampling, testing or other means of investigation. This information is directly relevant only to the points in the ground where they were obtained at the time of the assessment. The borehole logs indicate the inferred ground conditions only at the specific locations tested. The precision with which conditions are indicated depends largely on the frequency and method of sampling, and the uniformity of conditions as constrained by the project budget limitations. The behaviour of groundwater and some aspects of contaminants in soil and groundwater are complex. Our conclusions are based upon the analytical data presented in this report and our experience. Future advances in regard to the understanding of chemicals and their behaviour, and changes in regulations affecting their management, could impact on our conclusions and recommendations regarding their potential presence on this site.

Where conditions encountered at the site are subsequently found to differ significantly from those anticipated in this report, URS must be notified of any such findings and be provided with an opportunity to review the recommendations of this report.

Whilst to the best of our knowledge information contained in this report is accurate at the date of issue, subsurface conditions, including groundwater levels can change in a limited time. Therefore this document and the information contained herein should only be regarded as valid at the time of the investigation unless otherwise explicitly stated in this report.





| | | |
|--------------|----------|----------|
| Job No. | 42905541 | |
| Prep. By | RW | 3 Mar 05 |
| Chk'd By | RW | 3 Mar 05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT


REGIONAL SETTING

Figure 1





URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630




| | | |
|--------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | RBW | 31 Mar '05 |
| Chk'd By | RBW | 31 Mar '05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, CORURN PROJECT
**PROXIMITY OF NILEMAH EMBAYMENT
AND HAMELIN POOL**

Figure 3

URS



URS Australia Pty Ltd. Perth Office +61 89221 1630

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 27 Feb 05 |
| Chk'd By | RBW | 27 Feb 05 |
| Revision Indicator | 1 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
PLANNED MINE LAYOUT

Figure 4

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 3 Dec '04 |
| Chkd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
PROPOSED OPERATIONAL LAYOUT





Figure 5





| | |
|--------------|----------|
| Job No. | 42905541 |
| Prep. By | RBW |
| 20 Oct 04 | |
| Chk'd By | RBW |
| 20 Oct 04 | |
| Revision No. | 0 |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
METEOROLOGICAL DATA

Figure 6



LEGEND

| | |
|--|--|
| | Hamelin Pool |
| | Hamelin Coquina |
| | Holocene Dunes |
| | Marine Sediments |
| | Marine Clay |
| | Calcrete (palaeosol) |
| | Peron Sandstone (with coastal equivalents) |
| | Sandy and Silty Horizon (?reworked) |
| | Tooolonga Calcilutite |
| | Water Table (approx.) |

| | | |
|--------------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | DL | 4 April 05 |
| Chk'd By | RBW | 4 April 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**LOCAL GEOLOGICAL CROSS-SECTION
OF THE SUPERFICIAL FORMATIONS**




Figure 7

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

Near coastal geology from Bureau of Mineral Resources, 1990.
Local Geological Cross-section.srf

WEST

EAST



Reference: Carnarvon Basin, Hydrogeology and Hydrogeochemistry of the Confined Groundwater Systems, WA (Willis and Dogramaci, 2000)

| | | |
|--------------|----------|----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 3 Mar 05 |
| Chk'd By | IGB | 3 Mar 05 |
| Revision No. | 1 | |




Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**GASCOYNE PLATFORM
 WEST- EAST STRATIGRAPHY PROFILE**

URS

Figure 8a

SOUTH

NORTH




Reference: Carnarvon Basin, Hydrogeology and Hydrogeochemistry of the Confined Groundwater Systems, WA (Willis and Dogramaci, 2000)

| | | |
|--------------|----------|----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 3 Mar 05 |
| Chk'd By | IGB | 3 Mar 05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
GASCOYNE PLATFORM
SOUTH - NORTH
STRATIGRAPHY PROFILE

URS

Figure 8b



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 2 Dec '04 |
| Chk'd By | RBW | 2 Dec '04 |
| Revision No. | 2 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
LOCATIONS OF SITE INVESTIGATION BORES

Figure 9

URS

URS Australia Pty Ltd
 20 Terrace Rd, East Perth, 6004
 Phone 08 92211630
 Fax 08 92211639

 PROJECT NAME: **Coburn Mineral Sands Project**
 PROJECT NUMBER: **42905541.1841**


 DRILLING CO: **Aquatech Drilling**
 DRILL METHOD: **Mud-rotary**

 CLIENT: **Gunson Resources Ltd**
 LOCATION: **Hamelin Station, Shark Bay**

| SHALLOW PIEZOMETER | INTERMEDIATE PIEZOMETER | DEEP PIEZOMETER | GENERAL DATA |
|------------------------------------|-----------------------------|------------------------------------|--|
| RL of Collar (S): 41.71 | RL of Collar (I): N/A | RL of Collar (D): 41.71 | Total Drilled Depth: 40m |
| Total Cased Depth (S): 24 | Total Cased Depth (I): N/A | Total Cased Depth (D): 40 | Coordinates Datum: GDA 94 Easting (mE): 211125.3 mE Northing (mN): 7060717.7 mN |
| Casing/Screen Dia (S): 54mmID | Casing/Screen Dia (I): N/A | Casing/Screen Dia (D): 54mmID | |
| Screen Interval (S): 18 - 24 | Screen Interval (I): N/A | Screen Interval (D): 34 - 40 | |
| Static Water Level (S): 23.36 mbgl | Static Water Level (I): N/A | Static Water Level (D): 23.16 mbgl | |
| Final Salinity (S): 14,052 mg/l | Final Salinity (I): N/A | Final Salinity (D): 34,500 mg/l | |
| Final pH (S): 6.3 | Final pH (I): N/A | Final pH (D): 6.7 | |
| Pump Test: bailed | Pump Test: N/A | Pump Test: 13.8 kL/d, 40min | |

 START DATE: **4/8/04**

 FINISH DATE: **5/8/04**

 LOGGED BY: **RBW**


URS Australia Pty Ltd
 20 Terrace Rd, East Perth, 6004
 Phone 08 92211630
 Fax 08 92211639

 PROJECT NAME: **Coburn Mineral Sands Project**
 PROJECT NUMBER: **42905541.1841**


 DRILLING CO: **Aquatech Drilling**
 DRILL METHOD: **Mud-rotary**

 CLIENT: **Gunson Resources Ltd**
 LOCATION: **Hamelin Station, Shark Bay**

| SHALLOW PIEZOMETER | | INTERMEDIATE PIEZOMETER | | DEEP PIEZOMETER | | GENERAL DATA | |
|-------------------------|-----------|-------------------------|-----|-------------------------|-------------|--------------------------|--|
| RL of Collar (S): | 33.50mAHD | RL of Collar (I): | N/A | RL of Collar (D): | 33.50mAHD | Total Drilled Depth: 43m | |
| Total Cased Depth (S): | 30m | Total Cased Depth (I): | N/A | Total Cased Depth (D): | 43m | Coordinates | |
| Casing/Screen Dia (S): | 54mm ID | Casing/Screen Dia (I): | N/A | Casing/Screen Dia (D): | 54mm ID | Datum: GDA 94 | |
| Screen Interval (S): | 24 - 30 | Screen Interval (I): | N/A | Screen Interval (D): | 37 - 43 | Easting (mE): 208683.0 | |
| Static Water Level (S): | Dry | Static Water Level (I): | N/A | Static Water Level (D): | 30.12 mbtoc | Northing (mN): 7065001.0 | |
| Final Salinity (S): | N/A | Final Salinity (I): | N/A | Final Salinity (D): | 34,476mg/l | Pump Test: Not pumped | |
| Final pH (S): | N/A | Final pH (I): | N/A | Final pH (D): | 6.2 | | |
| Pump Test: | N/A | Pump Test: | N/A | Pump Test: | Not pumped | | |

 START DATE: **1/8/04**

 FINISH DATE: **2/8/04**

 LOGGED BY: **RBW**


URS Australia Pty Ltd
 20 Terrace Rd, East Perth, 6004
 Phone 08 92211630
 Fax 08 92211639

 PROJECT NAME: **Coburn Mineral Sands**
 PROJECT NUMBER: **42905541**


 DRILLING CO: **Aquatech Drilling**
 DRILL METHOD: **Mud-rotary**

 CLIENT: **Gunson Resources Ltd**
 LOCATION: **Hamelin Station, Shark Bay**

| SHALLOW PIEZOMETER | | INTERMEDIATE PIEZOMETER | | DEEP PIEZOMETER | | GENERAL DATA | |
|-------------------------|------------|-------------------------|-----|-------------------------|---------------|---------------------------|--|
| RL of Collar (S): | 67.22m AHD | RL of Collar (I): | N/A | RL of Collar (D): | 67.76m AHD | Total Drilled Depth: 42m | |
| Total Cased Depth (S): | 30m | Total Cased Depth (I): | N/A | Total Cased Depth (D): | 42m | Coordinates | |
| Casing/Screen Dia (S): | 54mm ID | Casing/Screen Dia (I): | N/A | Casing/Screen Dia (D): | 54mm ID | Datum: GDA 94 | |
| Screen Interval (S): | 24-30 | Screen Interval (I): | N/A | Screen Interval (D): | 36-42m | Easting (mE): 212594.1mE | |
| Static Water Level (S): | Dry | Static Water Level (I): | N/A | Static Water Level (D): | 37.11mbgl | Northing (mN): 705527.1mN | |
| Final Salinity (S): | N/A | Final Salinity (I): | N/A | Final Salinity (D): | 11,172 | | |
| Final pH (S): | N/A | Final pH (I): | N/A | Final pH (D): | 6.2 | | |
| Pump Test: | N/A | Pump Test: | N/A | Pump Test: | 2.4kL/d,25min | | |

 START DATE: **2/8/04**

 FINISH DATE: **3/8/04**

 LOGGED BY: **RBW**



URS Australia Pty Ltd
 20 Terrace Rd, East Perth, 6004
 Phone 08 92211630
 Fax 08 92211639

 PROJECT NAME: **Coburn Mineral Sands Project**
 PROJECT NUMBER: **42905541.1841**

 DRILLING CO: **Aquatech Drilling**
 DRILL METHOD: **Mud-rotary**

 CLIENT: **Gunson Resources Ltd**
 LOCATION: **Hamelin Station, Shark Bay**


| | | |
|----------------------------------|---|---------------------------------|
| TOTAL DRILLED DEPTH: 43m | OPEN INTERVAL: 16-43m | R.L OF COLLAR: 33.76 |
| TOTAL CASSED DEPTH: 43m | STATIC WATER LEVEL (mbgs): 30.22mbgl | COORDINATES: 208698.5 mE |
| CASING DIAMETER: 154mm ID | DATE OF MEASUREMENT: 10/8/04 | 7065001.6 mN |
| SCREEN DIAMETER: 154mm ID | PUMPING TEST: 7.5kL/d for 3hrs | DATUM: GDA 94 |
| | FINAL SALINITY: mg/L | |


 START DATE: **28/7/04** FINISH DATE: **31/7/04** LOGGED BY: **RBW**


| | | |
|--------------|---------------|-----------|
| Job No. | 42905541.1841 | |
| Prep. By | RBW | 20 Aug 04 |
| Chk'd By | RBW | 20 Aug 04 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
SMB2d PUMPING TEST RESULTS

Figure 14



Gunson Resources Limited

Figure 15

GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

SMB2s AND SMB2d, FALLING HEAD TESTS



| | | |
|--------------|---------------|-----------|
| Job No. | 42905541.1841 | |
| Prep. By | RBW | 20 Aug 04 |
| Chk'd By | RBW | 20 Aug 04 |
| Revision No. | 0 | |




| | | |
|--------------|---------------|-----------|
| Job No. | 42905541.1841 | |
| Prep. By | RBW | 20 Aug 04 |
| Chk'd By | RBW | 20 Aug 04 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
STB3 PUMPING TEST
DRAWDOWN IN STB3 and SMB3d

Figure 16



● SMB3d - S.W.L. = 30.20 m brp
 + SMB3s - S.W.L = >29.94 m brp (below base)

| | | |
|--------------|---------------|-----------|
| Job No. | 42905541.1841 | |
| Prep. By | RBW | 20 Aug 04 |
| Chk'd By | RBW | 20 Aug 04 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

SMB3S AND SMB3d FALLING HEAD TESTS


Figure 17




| | | |
|--------------|---------------|-----------|
| Job No. | 42905541.1841 | |
| Prep. By | RBW | 20 Aug 04 |
| Chk'd By | RBW | 20 Aug 04 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT
SMB4d PUMPING TEST RESULTS

Figure 18



| | | |
|--------------|---------------|-----------|
| Job No. | 42905541.1841 | |
| Prep. By | RBW | 20 Aug 04 |
| Chk'd By | RBW | 20 Aug 04 |
| Revision No. | 0 | |


Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

SMB4s AND SMB4d FALLING HEAD TESTS


Figure 19



START DATE: 12 Sept 2004 FINISH DATE: 11 Nov 2004 LOGGED BY: RW




| COMPLETION REPORT | | BOREHOLE: | | DMB1 (Monitoring Bore) | |
|---|----------------------------------|--------------------------|------------------------------|--|------------------------------|
| DRILLING CO: Drilling Contractors of Australia | DRILL METHOD: Mud Rotary | WINDALIA Sand Piezometer | BIRDRONG Piezometer | KOPKE Piezometer | General Data |
| RL of Collar: 85.9 | Casing/screen Dia. (mm): 40 mmND | Total Depth: 190 m | Screen Interval: 184 - 190 m | Static Water Level (mbtoc): 36.41 (16/12/04) | Final Salinity: 7.0 |
| RL of Collar: 85.9 | Casing/screen Dia. (mm): 40 mmND | Total Depth: 216 m | Screen Interval: 210 - 216 m | Static Water Level (mbtoc): 36.20 (16/12/04) | Final pH: 6.8 |
| RL of Collar: 85.9 | Casing/screen Dia. (mm): 40 mmND | Total Depth: 400 m | Screen Interval: 392 - 398 m | Static Water Level (mbtoc): 35.74 (16/12/04) | Final pH: 7.0 |
| | | | | Total Drilled depth (m): 400 | Coordinates: GDA94 |
| | | | | | Eastings (mE): 216,734 mE |
| | | | | | Northings (mN): 7,042,678 mN |
| START DATE: 12 Nov 2004 | | FINISH DATE: 9 Dec 2004 | | LOGGED BY: RW | |



DTB1 Gamma Log


DMB1 Gamma Log

Coburn 1 Gamma Log



| | |
|----------|------------|
| Job No. | 42905541 |
| Prep By. | RBW |
| Date | 23 Dec '04 |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
Geophysical Log Correlations DTB1, DMB1 & Coburn 1

Figure 22


| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 18 Jan 05 |
| Chk'd By | RBW | 18 Jan 05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**DTB1 STEP AND CONSTANT RATE PUMPING TEST
DRAWDOWN IN DTB1**


Figure 23a



| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 18 Jan 05 |
| Chk'd By | RBW | 18 Jan 05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**DTB1 CONSTANT RATE PUMPING TEST
 DRAWDOWN IN DMB1b and DMB1k**

Figure 23b




- DMB1b - S.W.L = 36.16 m brp (+0.20 m agl)
- + DMB1k - S.W.L = 36.59 m brp (+0.20 m agl), r = 1,040 m

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 18 Jan 05 |
| Chk'd By | RBW | 18 Jan 05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
DTB1 RECOVERY TEST
RESIDUAL DRAWDOWN IN DTB1

Figure 24a



| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 18 Jan 05 |
| Chk'd By | RBW | 18 Jan 05 |
| Revision No. | 0 | |

Gunson Resources Limited

GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**DTB1 RECOVERY TEST
RESIDUAL DRAWDOWN IN DMB1b and DMB1k**






Figure 24b






| LEGEND | |
|--------|-------------------------------------|
| ● | Existing Active Private Water Bore |
| + | Inactive Private Water Bore or Site |
| - - - | Nominal Bore Census Coverage |
| ■ | Amy Zone |
| □ | Mining Leases |
| □ | Shark Bay World Heritage Property |



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 24 Dec 04 |
| Chk'd By | RBW | 24 Dec 04 |
| Revision Indicator | 2 | |


| | |
|---|--|
| Gunson Resources Limited | |
| GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT | |
| REGIONAL PRIVATE BORE LOCALITY MAP | |

Figure 25



LEGEND

- Superficial Formations Site Investigation
- ◆ Confined Aquifer Site Investigations
- ✱ Private Bore
- Interpreted Elevations of the Superficial Formations




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESMENT, COBURN PROJECT
**INTERPRETED BASAL ELEVATIONS OF
 THE SUPERFICIAL FORMATIONS**

Figure 26






URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630



| | | | |
|--------------|----------------|--|---|
| Job No. | 42905541 | Gunson Resources Limited GROUNDWATER IMPACT ASSESSMENT, CORURN PROJECT BASELINE SUPERFICIAL FORMATIONS AND TOOLONGA CALCILUTITE WATER TABLE ELEVATIONS | Figure 27 |
| Prep. By | RBW 15 Oct '04 | |  |
| Chk'd By | RBW 15 Oct '04 | | |
| Revision No. | 1 | | |

Shallow Water Level Map.srf



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | | | |
|--------------|----------|------------|--|------------------|
| Job No. | 42905541 | | Gunson Resources Limited | Figure 28 |
| Prep. By | RBW | 15 Oct '04 | | |
| Chk'd By | RBW | 15 Oct '04 | SATURATED AREAS OF SUPERFICIAL FORMATIONS IN CONTEXT WITH REGIONAL FLOW | URS |
| Revision No. | 0 | | | |



LEGEND

- Hamelin Pool
- Coastal Shell Coquina
- Holocene Dunes
- Marine Sediments
- Marine Clay
- Peron Sandstone (with coastal equivalents)
- Toolonga Calcilutite
- Water Table (approx.)
- Inferred Groundwater Flow Path


| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
WATER TABLE ELEVATIONS IN CROSS SECTION

Figure 29

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

Near coastal geology from Bureau of Mineral Resources, 1990.
 Unconfined Water Level Cross Sections.srf





| | | |
|--------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | RBW | 04 Feb '05 |
| Chk'd By | RBW | 04 Feb '05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT
PIPER DIAGRAM OF GROUNDWATER CHEMISTRY

Figure 30





LEGEND


| | |
|--|--|
| | Hamelin Pool |
| | Coastal Shell Coquina |
| | Holocene Dunes |
| | Marine Sediments |
| | Marine Clay |
| | Peron Sandstone (with coastal equivalents) |
| | Toolonga Calcilutite |
| | Water Table (approx.) |
| | Inferred Groundwater Flow Path |

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**CONCEPTUAL HYDROGEOLOGICAL MODEL
 WITH HYDRAULIC AND WATER QUALITY PARAMETERS**

Figure 31


URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 03 Dec 04 |
| Chk'd By | RBW | 03 Dec 04 |
| Revision Indicator | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**INTERPRETED GROUNDWATER LEVELS
 WINDALIA SAND MEMBER**


Figure 32



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 1 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**INTERPRETED GROUNDWATER LEVELS
 BIRDRONG SANDSTONE**

Figure 33




LEGEND

| | |
|---|-------------------------------------|
|  | Superficial Formations |
|  | Toolonga Calcilutite |
|  | Alinga Formation (Gearle Siltstone) |
|  | Windalia Radiolarite |
|  | Windalia Sand Member |
|  | Muderong Shale |
|  | Birdrong Sandstone |
|  | Sweeney Mia Formation |
|  | Kopke Sandstone |
|  | Faure Formation |
|  | Dirk Hartog Group |
|  | Tumblagooda Sandstone |




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**CONFINED AQUIFER CONCEPTUAL
 HYDROGEOLOGICAL MODEL**

Figure 34



5 m/day



15 m/day



10 m/day




— Modelled Drain Cells

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Generic Model Domains for Sand Stacker Advances
 of 5 m/day, 10 m/day and 15 m/day**

Figure 35a


80 m/day



50 m/day



35 m/day




— Modelled Drain Cells

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 23 Feb 05 |
| Chk'd By | RBW | 23 Feb 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Generic Model Domains for Sand Stacker Advances
 of 35 m/day, 50 m/day and 80 m/day**

Figure 35b




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 3 Mar '05 |
| Chk'd By | RBW | 3 Mar '05 |
| Revision No. | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**TYPICAL MINE PROFILE WITHIN
 THE SUPERFICIAL FORMATIONS**

Figure 36

Plan View



Elevation View



(Not to Scale)


URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630





| | | |
|--------------|---------------|------------|
| Job No. | 42905541-1841 | |
| Prep. By | RBW | 15 Oct '04 |
| Chk'd By | RBW | 15 Oct '04 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Development of the Conceptual Sand Tailings
 Water Recovery Systems
 Initial Plan**


Figure 37a







| LEGEND | |
|---|----------------------|
|  | Local Collector Pump |
|  | Main Transfer Pump |
|  | Mine Water Seepage |
|  | Collector Pipeline |


URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | | | |
|--------------|----------|------------|--|---|
| Job No. | 42905541 | | Gunson Resources Limited GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT Development of the Conceptual Sand Tailings Water Recovery Systems Second Plan | Figure 37b |
| Prep. By | RBW | 24 Nov '04 | |  |
| Chk'd By | RBW | 24 Nov '04 | | |
| Revision No. | 1 | | | |



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | | | |
|--------------|----------|------------|--|-------------------|
| Job No. | 42905541 | | Gunson Resources Limited GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT FINAL CONCEPTUAL SAND TAILS WATER RECOVERY PLAN (START OF PIT) | Figure 38a |
| Prep. By | RBW | 24 Nov '04 | | URS |
| Chk'd By | RBW | 24 Nov '04 | | |
| Revision No. | 1 | | | |



LEGEND


- Local Collector Pump
- Main Transfer Pump
- Mine Water Seepage
- Collector Pipeline

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|---------------|------------|
| Job No. | 42905541-1841 | |
| Prep. By | RBW | 24 Nov '04 |
| Chk'd By | RBW | 24 Nov '04 |
| Revision No. | 1 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
FINAL CONCEPTUAL SAND TAILS WATER
RECOVERY PLAN
(MIDDLE OF SAND-STACKER TRAVERSE)

Figure 38b








URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|---------------|------------|
| Job No. | 42905541-1841 | |
| Prep. By | RBW | 24 Nov '04 |
| Chk'd By | RBW | 24 Nov '04 |
| Revision No. | 1 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
FINAL CONCEPTUAL SAND TAILS WATER RECOVERY PLAN
(SAND-STACKER CHANGEOVER)

Figure 38c

| LEGEND | |
|---|----------------------|
|  | Local Collector Pump |
|  | Main Transfer Pump |
|  | Mine Water Seepage |
|  | Collector Pipeline |




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | RBW | 24 Nov '04 |
| Chk'd By | RBW | 24 Nov '04 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**FINAL CONCEPTUAL SAND TAILS WATER
 RECOVERY PLAN
 (END OF PIT)**

Figure 38d







URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
SIMULATED SAND MOUNDING
5m/day Sand-Stacker Advance and No Sand
Beneath Pit Floor

Figure 39

figure32 Simulated mounding beneath tails mine.srf



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630


figure33 RECOVERY RATE CALCULATIONS.srf

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 22 Feb 05 |
| Chk'd By | RBW | 22 Feb 05 |
| Revision Indicator | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**RECOVERY RATE CALCULATIONS:
 5 m/day Sand-Stacker Advance and
 2m Sand Beneath Pit Floor**

Figure 40


5m/day



10m/day




15m/day




| | |
|--------------------|-----------|
| Job No. | 42905541 |
| Prep. By | ECPL |
| Chkd By | RBW |
| Revision Indicator | 0 |
| | 21 Feb 05 |
| | 21 Feb 05 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
 Simulated Upper-Bound Tailings Water Recovery Rates
 5 to 15 m/day Advance With All Active Drains


35m/day



55m/day




80m/day



| | |
|--------------------|-----------|
| Job No. | 42905541 |
| Prep. By | ECPL |
| Chkd By | RBW |
| Revision Indicator | 0 |
| | 21 Feb 05 |
| | 21 Feb 05 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
 Simulated Upper-Bound Tailings Water Recovery Rates
 35 to 80 m/day Advance Rate With All Active Drains


Figure 41b




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 26 Feb 05 |
| Chk'd By | RBW | 26 Feb 05 |
| Revision No. | 1 | |


Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
ALTERNATIVE CONCEPTUAL SAND TAILINGS WATER
RECOVERY PLAN
2 DRAINS ONLY

Figure 42


5m/day



10m/day




15m/day




| | |
|--------------------|-----------|
| Job No. | 42905541 |
| Prep. By | ECPL |
| Chkd By | RBW |
| Revision Indicator | 0 |
| | 21 Feb 05 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
 Simulated Lower-Bound Tailings Water Recovery Rates
 5 to 15 m/day Advance Rate, With 2 Active Drains


35m/day



55m/day







80m/day



| | |
|--------------------|-----------|
| Job No. | 42905541 |
| Prep. By | ECPL |
| Chkd By | RBW |
| Revision Indicator | 0 |
| | 21 Feb 05 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
 Simulated Lower-Bound Tailings Water Recovery Rates
 35 to 80 m/day Advance Rate, with 2 Active Drains


Figure 43b




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED LOWER-BOUND MOUNDING WITH
 0, 2, 5, 10 m SAND BENEATH PIT FLOOR
 @ 5m/day ADVANCE RATE**

Figure 44a


0 m sand




2 m sand



5 m sand



10 m sand







| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
SIMULATED LOWER-BOUND MOUNDING WITH 0, 2, 5, 10 m SAND BENEATH PIT FLOOR @ 10 m/day ADVANCE RATE

Figure 44b









| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED LOWER-BOUND MOUNDING WITH 0, 2, 5, 10 m
 SAND PIT FLOOR @ 15m/day ADVANCE RATE**

Figure 44c




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 23 Feb 05 |
| Chk'd By | RBW | 23 Feb 05 |
| Revision Indicator | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT
SIMULATED LOWER BOUND MOUNDING WITH 0, 2, 5 & 10 m SAND BENEATH PIT FLOOR AT 35 m/day ADVANCE RATE

Figure 44d


0 m Sand Thickness




2 m Sand Thickness



5 m Sand Thickness



10 m Sand Thickness




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 23 Feb 05 |
| Chk'd By | RBW | 23 Feb 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
SIMULATED LOWER-BOUND MOUNDING WITH 0, 2, 5 & 10 m SAND BENEATH PIT FLOOR AT 55 m/day ADVANCE RATE


Figure 44e




0 m Sand Thickness




2 m Sand Thickness



5 m Sand Thickness







10 m Sand Thickness



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 23 Feb 05 |
| Chk'd By | RBW | 23 Feb 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
SIMULATED LOWER-BOUND MOUNDING WITH 0, 2, 5 & 10 m SAND BENEATH PIT FLOOR AT 80 m/day ADVANCE RATE

Figure 44f




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 28 Feb 05 |
| Chk'd By | RBW | 28 Feb 05 |
| Revision Indicator | 0 | |


Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED UPPER-BOUND MOUNDING WITH 0, 2, 5, 10 m SAND
BENEATH PIT FLOOR @ 5m/day ADVANCE RATE**

Figure 45a


0 m sand




2 m sand



5 m sand







10 m sand




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 28 Feb 05 |
| Chk'd By | RBW | 28 Feb 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED UPPER-BOUND MOUNDING WITH 0, 2, 5, 10 m SAND
 BENEATH PIT FLOOR @ 10m/day ADVANCE RATE**




| | | | | |
|--------------------|----------|-----------|---|-------------------|
| Job No. | 42905541 | | Gunson Resources Limited GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT SIMULATED UPPER-BOUND MOUNDING WITH 0, 2, 5, 10 m SAND BENEATH PIT FLOOR @ 15 m/day ADVANCE RATE | Figure 45c |
| Prep. By | ECPL | 28 Feb 05 | | |
| Chk'd By | RBW | 28 Feb 05 | | |
| Revision Indicator | 0 | | | |
| | | | URS | |


0 m Sand Thickness




2 m Sand Thickness



5 m Sand Thickness



10 m Sand Thickness




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 28 Feb 05 |
| Chk'd By | RBW | 28 Feb 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED UPPER-BOUND MOUNDING WITH 0, 2, 5, 10 m SAND
 BENEATH PIT FLOOR @ 55 m/day ADVANCE RATE**

Figure 45e






| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 1 Apr '05 |
| Chk'd By | RBW | 1 Apr '05 |
| Revision Indicator | 0 | |

| | |
|--|--|
| Gunson Resources Limited | |
| GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT | |
| Areas of Potential Risk Due to Mounding Encroachment Within Vegetation Root Zones | |

Figure 46




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar '05 |
| Chk'd By | RWC | 31 Mar '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
NORTHERN PIT MODEL DOMAIN

Figure 47





URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar '05 |
| Chk'd By | RWC | 31 Mar '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**FORM OF THE NORTHERN PIT MODEL
 PLAN VIEW OF SUB-CROP GEOLOGY**

Figure 48a




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**FORM OF THE NORTHERN PIT MODEL
NORTH-SOUTH SECTION VIEW
A - A'**

Figure 48b





URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

Fig48c.srf

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**FORM OF THE NORTHERN PIT MODEL
 EAST-WEST SECTION VIEW
 B - B'**

Figure 48c



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

Fig48d.srf


| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**FORM OF THE NORTHERN PIT MODEL
EAST-WEST SECTION VIEW
C - C'**

Figure 48d







URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar '05 |
| Chk'd By | RWC | 31 Mar '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**SIMULATED WATER TABLE ENVIRONMENT
 PLAN VIEW**

Figure 49a



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630


Fig49b.srf

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**SIMULATED WATER TABLE ENVIRONMENT
NORTH-SOUTH SECTION VIEW : A - A'**


Figure 49b



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
SIMULATED DEPTHS TO STEADY-STATE WATER TABLE

Figure 49c






Model Easting (m)

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED WATER TABLE ENVIRONMENT
 SATURATED THICKNESS
 OF SUPERFICIAL FORMATIONS**

Figure 49d







| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT WATER TABLE MOUNDING
 AFTER 374 DAYS OF MINING**




Figure 50a



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT WATER TABLE MOUNDING
 AFTER 748 DAYS OF MINING**





Figure 50b



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT WATER TABLE MOUNDING
 AFTER 1105 DAYS OF MINING**





Figure 50c



| | | |
|--------------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 21 Mar '05 |
| Chk'd By | RBW | 21 Mar '05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED TRANSIENT MOUND DISTRIBUTIONS
 5 TO 20 YEARS AFTER MINING**

Figure 51a




| | | |
|--------------------|----------|------------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 21 Mar '05 |
| Chk'd By | RBW | 21 Mar '05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED TRANSIENT MOUND DISTRIBUTIONS
 25 to 50 YEARS AFTER MINING**

Figure 51b

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630



Planned Mine Layout and Profile Locations

Topography (m AHD)

Basement Contours (m AHD)





Superficial Formation Isopachs (m)

| | | | |
|--------------------|----------|------------|---|
| Job No. | 42905541 | | Gunson Resources Limited GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT |
| Prep. By | ECPL | 21 Mar '05 | |
| Chk'd By | RBW | 21 Mar '05 | DATA USED TO DEFINE PREDICTED MOUNDED WATER TABLE PROFILES BENEATH THE SHARK BAY WORLD HERITAGE AREA |
| Revision Indicator | 0 | | |

Figure 52a



Note: Digital Terrain Model topographic elevations south of 7,040,000 mN may be between 3 and 6 m too low.
Southern WHA Boundary Mounding.srf



| LEGEND | |
|--------|---|
| — | Predicted profile 5 years after mining |
| — | Predicted profile 10 years after mining |
| — | Predicted profile 15 years after mining |
| — | Predicted profile 20 years after mining |
| — | Predicted profile 30 years after mining |
| — | Predicted profile 40 years after mining |
| — | Predicted profile 50 years after mining |


URS AUSTRALIA PTY LTD, Perth Office +61 8922 11630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 18 Jan 05 |
| Chk'd By | RBW | 18 Jan 05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**SECTION VIEWS OF PREDICTED MOUNDED WATER TABLE PROFILES BENEATH
THE SHARK BAY WORLD HERITAGE PROPERTY**




Figure 52b



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT RESIDUAL WATER TABLE
 MOUNDING - 1 YEAR AFTER MINING**


Figure 53a



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT RESIDUAL WATER TABLE
 MOUNDING - 5 YEARS AFTER MINING**



Figure 53b



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT RESIDUAL WATER TABLE
 MOUNDING - 10 YEARS AFTER MINING**


Figure 53c



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT RESIDUAL WATER TABLE
 MOUNDING - 15 YEARS AFTER MINING**

Figure 53d




Model Easting (m)

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT RESIDUAL WATER TABLE
 MOUNDING - 20 YEARS AFTER MINING**

Figure 53e





| | | | |
|--------------------|----------------|---|-------------------|
| Job No. | 42905541 | Gunson Resources Limited | Figure 53f |
| Prep. By | ECPL 31 Mar 05 | GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT | |
| Chk'd By | RBW 31 Mar 05 | PREDICTED NORTHERN PIT RESIDUAL WATER TABLE MOUNDING - 30 YEARS AFTER MINING | |
| Revision Indicator | 0 | | |








Simulated
Depths to
Water Table (m)



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT RESIDUAL WATER TABLE
MOUNDING - 40 YEARS AFTER MINING**


Figure 53g
URS



| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT RESIDUAL WATER TABLE
 MOUNDING - 50 YEARS AFTER MINING**

Figure 53h




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

Fig54a.srf

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
PREDICTED NORTHERN PIT WATER TABLE MOUNDING
NORTH-SOUTH SECTION VIEW : A - A'
1 YEAR AFTER MINING

Figure 54a








URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

Fig54b.srf

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RBW | 31 Mar 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**PREDICTED NORTHERN PIT WATER TABLE MOUNDING
 NORTH-SOUTH SECTION VIEW : A - A'
 50 YEARS AFTER MINING**

Figure 54b




| | | |
|--------------------|----------|----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 5 Apr 05 |
| Chk'd By | RBW | 5 Apr 05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
PREDICTED NORTHERN PIT FLUXES



Figure 54c

figure55 Deep aquifer model domain.tif



| | |
|--------------------|-----------|
| Job No. | 42905541 |
| Prep. By | ECPL |
| CHK'd By | RBW |
| Revision Indicator | 0 |
| | 3 Dec '04 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
CONFINED AQUIFER MODEL DOMAIN




| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 3 Dec '04 |
| Chk'd By | RBW | 3 Dec '04 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
FORM OF THE CONFINED AQUIFER MODEL

Figure 56


Figure 57 Confined aquifer model boundary conditions.tif



| | |
|--------------------|-----------|
| Job No. | 42905541 |
| Prep. By | ECPL |
| CHK'd By | RBW |
| Revision Indicator | 0 |
| | 3 Dec '04 |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**CONFINED AQUIFER MODEL
 BOUNDARY CONDITIONS**

Figure 57



LEGEND

- Existing Active Private Water Bore
- ✚ Deep Test Bores
- ▭ Amy Zone
- ▭ World Heritage Area
- Piezometric Head Contour (m AHD)




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RWC | 31 Mar 05 |
| Revision No. | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED STEADY-STATE POTENTIOMETRIC
 LEVELS WINDALIA RADIOLARITE**

Figure 58a



LEGEND

- Existing Active Private Water Bore
- ✚ Deep Test Bores
- ▭ Amy Zone
- ▭ World Heritage Area
- Piezometric Head Contour (m AHD)




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630


| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RWC | 31 Mar 05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED STEADY-STATE POTENTIOMETRIC
 LEVELS WINDALIA SAND MEMBER**

Figure 58b



| LEGEND | |
|--------|------------------------------------|
| ● | Existing Active Private Water Bore |
| + | Deep Test Bores |
| □ | Amy Zone |
| □ | World Heritage Area |
| — | Piezometric Head Contour (m AHD) |




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RWC | 31 Mar 05 |
| Revision No. | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED STEADY-STATE POTENTIOMETRIC
 LEVELS BIRDRONG SANDSTONE**

Figure 58c



LEGEND

- Existing Active Private Water Bore
- ✚ Deep Test Bores
- ▭ Amy Zone
- ▭ World Heritage Area
- Piezometric Head Contour (m AHD)




URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 31 Mar 05 |
| Chk'd By | RWC | 31 Mar 05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED STEADY-STATE POTENTIOMETRIC
 LEVELS KOPKE SANDSTONE**

Figure 58d




LEGEND

| | |
|--|------------------------|
| | Superficial Formations |
| | Toolonga Calcilutite |
| | Alinga Formation |
| | Windalia Radiolarite |
| | Windalia Sand Member |
| | Muderong Shale |
| | Birdrong Sandstone |
| | Sweeney Mia Formation |
| | Kopke Sandstone |
| | Faure Formation |
| | Dirk Hartog Group |
| | Tumblagooda Sandstone |

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Apr '05 |
| Chk'd By | RBW | 3 Apr '05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED CONFINED AQUIFER
 NORTH TO SOUTH FLOW PATHS
 POTENTIOMETRIC LEVELS**

Figure 59a




LEGEND

| | |
|--------------|------------------------|
| Dark Blue | Superficial Formations |
| Dark Green | Toolonga Calcilutite |
| Light Blue | Alinga Formation |
| Black | Windalia Radiolarite |
| Red | Windalia Sand Member |
| Magenta | Muderong Shale |
| Olive Green | Birdrong Sandstone |
| Grey | Sweeney Mia Formation |
| Dark Grey | Kopke Sandstone |
| Blue | Faure Formation |
| Bright Green | Dirk Hartog Group |
| Cyan | Tumblagooda Sandstone |

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Apr '05 |
| Chk'd By | RBW | 3 Apr '05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED CONFINED AQUIFER
 WEST TO EAST FLOW PATHS
 POTENTIOMETRIC LEVELS**

Figure 59b




LEGEND

| | |
|--|------------------------|
| | Superficial Formations |
| | Toolonga Calcilutite |
| | Alinga Formation |
| | Windalia Radiolarite |
| | Windalia Sand Member |
| | Muderong Shale |
| | Birdrong Sandstone |
| | Sweeney Mia Formation |
| | Kopke Sandstone |
| | Faure Formation |
| | Dirk Hartog Group |
| | Tumblagooda Sandstone |

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Apr '05 |
| Chk'd By | RBW | 3 Apr '05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED CONFINED AQUIFER
 WEST TO EAST FLOW PATHS
 POTENTIOMETRIC LEVELS**

Figure 59c




LEGEND

- Superficial Formations
- Toolonga Calcilutite
- Alinga Formation
- Windalia Radiolarite
- Windalia Sand Member
- Muderong Shale
- Birdrong Sandstone
- Sweeney Mia Formation
- Kopke Sandstone
- Faure Formation
- Dirk Hartog Group
- Tumblagooda Sandstone

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Apr '05 |
| Chk'd By | RBW | 3 Apr '05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED CONFINED AQUIFER
 NORTH TO SOUTH FLOW PATHS
 FLOW VECTORS**

Figure 60a




LEGEND

| | |
|--|------------------------|
| | Superficial Formations |
| | Toolonga Calcilutite |
| | Alinga Formation |
| | Windalia Radiolarite |
| | Windalia Sand Member |
| | Muderong Shale |
| | Birdrong Sandstone |
| | Sweeney Mia Formation |
| | Kopke Sandstone |
| | Faure Formation |
| | Dirk Hartog Group |
| | Tumblagooda Sandstone |

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Apr '05 |
| Chk'd By | RBW | 3 Apr '05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED CONFINED AQUIFER
 WEST TO EAST FLOW PATHS
 FLOW VECTORS**

Figure 60b




LEGEND

| | |
|--|------------------------|
| | Superficial Formations |
| | Toolonga Calcilutite |
| | Alinga Formation |
| | Windalia Radiolarite |
| | Windalia Sand Member |
| | Muderong Shale |
| | Birdrong Sandstone |
| | Sweeney Mia Formation |
| | Kopke Sandstone |
| | Faure Formation |
| | Dirk Hartog Group |
| | Tumblagooda Sandstone |

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 3 Apr '05 |
| Chk'd By | RBW | 3 Apr '05 |
| Revision Indicator | 0 | |


Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**SIMULATED CONFINED AQUIFER
 WEST TO EAST FLOW PATHS
 FLOW VECTORS**

Figure 60c



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | | | |
|--------------|----------|-----------|---|------------------|
| Job No. | 42905541 | | Gunson Resources Limited GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT | Figure 61 |
| Prep. By | RBW | 1 Apr '05 | | |
| Chk'd By | RBW | 1 Apr '05 | Layout of Conceptual Process Water Borefield and Proposed Superficial Monitoring Bores | URS |
| Revision No. | 0 | | | |




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| — Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 1 Year Of 11 GL/annum Abstraction**

Figure 62a



0 10,000 20,000 30,000 40,000 50,000m
 Scale 1 : 75,000


| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 2 Years Of 11 GL/annum Abstraction**

Figure 62b




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 5 Years Of 11 GL/annum Abstraction**

Figure 62c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 10 Years Of 11 GL/annum Abstraction**

Figure 62d



| LEGEND | |
|--------|------------------------------------|
| ● | Existing Active Private Water Bore |
| + | Deep Test Bores |
| — | Drawdown Contour |
| □ | Amy Zone |
| □ | Shark Bay World Heritage Property |


URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | |
|--------------|----------------|
| Job No. | 42905541 |
| Prep. By | ECPL 1 Apr '05 |
| Chk'd By | RWC 1 Apr '05 |
| Revision No. | 0 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**Predicted Drawdowns
 in Windalia Radiolarite
 After 20 Years Of 11 GL/annum Abstraction**

Figure 62e




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 1 Year Of 11 GL/annum Abstraction**

Figure 63a




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✦ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 2 Years Of 11 GL/annum Abstraction**

Figure 63b




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✦ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 5 Years Of 11 GL/annum Abstraction**

Figure 63c





| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 10 Years Of 11 GL/annum Abstraction**

Figure 63d



Scale 1 : 75,000



| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 20 Years Of 11 GL/annum Abstraction**

Figure 63e



Scale 1 : 75,000


| LEGEND | | | |
|--------|------------------------------------|---|-----------------------------------|
| ● | Existing Active Private Water Bore | □ | Amy Zone |
| + | Deep Test Bores | □ | Shark Bay World Heritage Property |
| 2 | Drawdown Contour | | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 1 Year Of 11 GL/annum Abstraction**

Figure 64a





| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 2 Years Of 11 GL/annum Abstraction**

Figure 64b




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 / Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 5 Years Of 11 GL/annum Abstraction**

Figure 64c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 / Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 10 Years Of 11 GL/annum Abstraction**

Figure 64d




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | |
|--------------|----------------|
| Job No. | 42905541 |
| Prep. By | ECPL 1 Apr '05 |
| Chk'd By | RWC 1 Apr '05 |
| Revision No. | 0 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 20 Years Of 11 GL/annum Abstraction**

Figure 64e





| LEGEND | | | |
|--------|------------------------------------|---|-----------------------------------|
| ● | Existing Active Private Water Bore | □ | Amy Zone |
| + | Deep Test Bores | □ | Shark Bay World Heritage Property |
| 2 | Drawdown Contour | | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Kopke Sandstone
 After 1 Year Of 11 GL/annum Abstraction**

Figure 65a



Scale 1 : 75,000


| LEGEND | | | |
|--------|------------------------------------|---|-----------------------------------|
| ● | Existing Active Private Water Bore | □ | Amy Zone |
| + | Deep Test Bores | □ | Shark Bay World Heritage Property |
| 2 | Drawdown Contour | | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Kopke Sandstone
 After 2 Years Of 11 GL/annum Abstraction**

Figure 65b



0 10,000 20,000 30,000 40,000 50,000m
 Scale 1 : 75,000

| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**Predicted Drawdowns
 in Kopke Sandstone
 After 5 Years Of 11 GL/annum Abstraction**

Figure 65c



Scale 1 : 75,000


| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | |
|--------------|----------------|
| Job No. | 42905541 |
| Prep. By | ECPL 1 Apr '05 |
| Chk'd By | RWC 1 Apr '05 |
| Revision No. | 0 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Kopke Sandstone
 After 10 Years Of 11 GL/annum Abstraction**

Figure 65d



LEGEND


| | |
|---|---|
| <ul style="list-style-type: none"> ● Existing Active Private Water Bore ✚ Deep Test Bores 2 Drawdown Contour | <ul style="list-style-type: none"> □ Amy Zone □ Shark Bay World Heritage Property |
|---|---|

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Kopke Sandstone
 After 20 Years Of 11 GL/annum Abstraction**

Figure 65e





| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Alinga Formation
 After 20 Years Of 11 GL/annum Abstraction**

Figure 66a





| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| — Drawdown Contour | |

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 7 Mar '05 |
| Chk'd By | RBW | 7 Mar '05 |
| Revision Indicator | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns in Toolonga Calcilutite
 After 20 Years of 11 GL/annum Abstraction**

Figure 66b



Scale 1 : 75,000


| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in the Superficial Formations
 After 20 Years Of 11 GL/annum Abstraction**

Figure 66c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 1 Year Of 15 GL/annum Abstraction**

Figure 67a




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 / Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 2 Years Of 15 GL/annum Abstraction**

Figure 67b




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 5 Years Of 15 GL/annum Abstraction**

Figure 67c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | |
|--------------|----------------|
| Job No. | 42905541 |
| Prep. By | ECPL 1 Apr '05 |
| Chk'd By | RWC 1 Apr '05 |
| Revision No. | 0 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 10 Years Of 15 GL/annum Abstraction**

Figure 67d




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Radiolarite
 After 20 Years Of 15 GL/annum Abstraction**

Figure 67e




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 1 Year Of 15 GL/annum Abstraction**

Figure 68a




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 2 Years Of 15 GL/annum Abstraction**

Figure 68b



0 10,000 20,000 30,000 40,000 50,000m
 Scale 1 : 75,000

| LEGEND | | | |
|--------|------------------------------------|---|-----------------------------------|
| ● | Existing Active Private Water Bore | □ | Amy Zone |
| + | Deep Test Bores | □ | Shark Bay World Heritage Property |
| 2 | Drawdown Contour | | |


URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**Predicted Drawdowns
 in Windalia Sand Member
 After 5 Years Of 15 GL/annum Abstraction**

Figure 68c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 10 Years Of 15 GL/annum Abstraction**

Figure 68d



LEGEND


| | |
|--|---|
| <ul style="list-style-type: none"> ● Existing Active Private Water Bore ✚ Deep Test Bores 2/ Drawdown Contour | <ul style="list-style-type: none"> □ Amy Zone □ Shark Bay World Heritage Property |
|--|---|

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Windalia Sand Member
 After 20 Years Of 15 GL/annum Abstraction**

Figure 68e



0 10,000 20,000 30,000 40,000 50,000m

Scale 1 : 75,000

LEGEND



| | |
|--|---|
| <ul style="list-style-type: none"> ● Existing Active Private Water Bore ✚ Deep Test Bores 2/ Drawdown Contour | <ul style="list-style-type: none"> □ Amy Zone □ Shark Bay World Heritage Property |
|--|---|

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 1 Year Of 15 GL/annum Abstraction**

Figure 69a



Scale 1 : 75,000



| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 2 Years Of 15 GL/annum Abstraction**

Figure 69b




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 / Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 5 Years Of 15 GL/annum Abstraction**

Figure 69c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 10 Years Of 15 GL/annum Abstraction**

Figure 69d



LEGEND


| | |
|---|---|
| <ul style="list-style-type: none"> ● Existing Active Private Water Bore ✚ Deep Test Bores 2 Drawdown Contour | <ul style="list-style-type: none"> □ Amy Zone □ Shark Bay World Heritage Property |
|---|---|

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Birdrong Sandstone
 After 20 Years Of 15 GL/annum Abstraction**

Figure 69e



0 10,000 20,000 30,000 40,000 50,000m
 Scale 1 : 75,000

| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |


URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**Predicted Drawdowns
 in Kopke Sandstone
 After 1 Year Of 15 GL/annum Abstraction**

Figure 70a



0 10,000 20,000 30,000 40,000 50,000m
 Scale 1 : 75,000

| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |


URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**Predicted Drawdowns
 in Kopke Sandstone
 After 2 Years Of 15 GL/annum Abstraction**

Figure 70b




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | |
|--------------|----------------|
| Job No. | 42905541 |
| Prep. By | ECPL 1 Apr '05 |
| Chk'd By | RWC 1 Apr '05 |
| Revision No. | 0 |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Kopke Sandstone
 After 5 Years Of 15 GL/annum Abstraction**

Figure 70c



LEGEND

| | |
|---|---|
| <ul style="list-style-type: none"> ● Existing Active Private Water Bore ✚ Deep Test Bores 2 Drawdown Contour | <ul style="list-style-type: none"> □ Amy Zone □ Shark Bay World Heritage Property |
|---|---|



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT

**Predicted Drawdowns
 in Kopke Sandstone
 After 10 Years Of 15 GL/annum Abstraction**

Figure 70d



Scale 1 : 75,000

| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Drawdowns
 in Kopke Sandstone
 After 20 Years Of 15 GL/annum Abstraction**

Figure 70e





Figure 71a

Gunsong Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT
PREDICTED DRAWDOWN IMPACTS OF 11GL/ANNUM
ABSTRACTION ON NANGA RESORT, CARBLA STATION AND
SWEENEY MIA 2001 BORES




| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | BM | 28-Feb-05 |
| CHK'D By | RBW | 28-Feb-05 |
| Revision No. | 0 | |




| | |
|--------------|----------|
| Job No. | 42905541 |
| Prep. By | BM |
| 28-Feb-05 | |
| CHK'd By | RBW |
| 28-Feb-05 | |
| Revision No. | 0 |


Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT
PREDICTED DRAWDOWN IMPACTS OF 11 GLANNUM
ABSTRACTION ON NORTHERN HAMELIN STATION,
TELEGRAPH STATION AND OVERLANDER ROADHOUSE
BORES


Figure 71b


| | |
|--------------|----------|
| Job No. | 42905541 |
| Prep. By | BM |
| 28-Feb-05 | |
| CHK'D By | RBW |
| 28-Feb-05 | |
| Revision No. | 0 |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT
PREDICTED DRAWDOWN IMPACTS OF 11 GL/ANNUM
ABSTRACTION ON SOUTHERN HAMELIN AND COBURN
STATIONS BORES

Figure 71c






| | |
|--------------|-----------|
| Job No. | 42905541 |
| Prep. By | BM |
| Revision No. | 0 |
| Chk'd By | RBW |
| | 28-Feb-05 |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
PREDICTED DRAWDOWN IMPACTS OF 11 GL/ANNUM ABSTRACTION ON EASTERN HAMELIN, MEADOW AND NERREN NERREN STATIONS AND BILLABONG ROADHOUSE BORES

Figure 71d







Figure 72a

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT
PREDICTED DRAWDOWN IMPACTS OF 15GL/ANNUM
ABSTRACTION ON NANGA RESORT, CARBLA STATION AND
SWEENEY MIA 2001 BORES

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | BM | 28-Feb-05 |
| CHK'D By | RBW | 28-Feb-05 |
| Revision No. | 0 | |






| | |
|--------------|----------|
| Job No. | 42905541 |
| Prep. By | BM |
| CHK'd By | RBW |
| Revision No. | 0 |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT
PREDICTED DRAWDOWN IMPACTS OF 15 GLANNUM
ABSTRACTION ON NORTHERN HAMELIN STATION,
TELEGRAPH STATION AND OVERLANDER ROADHOUSE
BORES



Figure 72b




| | |
|--------------|----------|
| Job No. | 42905541 |
| Prep. By | BM |
| CHK'D By | RBW |
| Revision No. | 0 |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT

**PREDICTED DRAWDOWN IMPACTS OF 15GL/ANNUM
ABSTRACTION ON SOUTHERN HAMELIN AND COBURN
STATIONS BORES**






| | |
|--------------|---------------|
| Job No. | 42905541.1895 |
| Prep. By | BM |
| 28-Feb-05 | |
| Chk'd By | RBW |
| 28-Feb-05 | |
| Revision No. | 0 |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT
PREDICTED DRAWDOWN IMPACTS OF 15GL/ANNUM
ABSTRACTION ON EASTERN HAMELIN, MEADOW AND
NERREN NERREN STATIONS AND BILLABONG ROADHOUSE
BORES

Figure 72d






| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Windalia Radiolarite, 1 Year
 After Abstraction of 11 GI/annum Has Stopped**

Figure 73a





| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| — Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Windalia Radiolarite, 2 Years
 After Abstraction of 11 GI/annum Has Stopped**

Figure 73b



Scale 1 : 75,000

LEGEND


| | |
|---|---|
| <ul style="list-style-type: none"> ● Existing Active Private Water Bore ✚ Deep Test Bores Residual Drawdown Contour | <ul style="list-style-type: none"> Amy Zone Shark Bay World Heritage Property |
|---|---|

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
Predicted Residual Drawdown
in Windalia Radiolarite, 5 Years
After Abstraction of 11 GL/annum Has Stopped

Figure 73c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Windalia Radiolarite, 10 Years
 After Abstraction of 11 GL/annum Has Stopped**

Figure 73d



0 10,000 20,000 30,000 40,000 50,000m
 Scale 1 : 75,000

LEGEND


| | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Windalia Sand Member, 1 Year
 After Abstraction of 11 GI/annum Has Stopped**

Figure 74a




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| — Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Windalia Sand Member, 2 Years
 After Abstraction of 11 GI/annum Has Stopped**

Figure 74b



0 10,000 20,000 30,000 40,000 50,000m
 Scale 1 : 75,000


| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Windalia Sand Member, 5 Years
 After Abstraction of 11 GI/annum Has Stopped**

Figure 74c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2/ Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Windalia Sand Member, 10 Years
 After Abstraction of 11 GL/annum Has Stopped**

Figure 74d




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Birdrong Sandstone, 1 Year
 After Abstraction of 11 Gl/annum Has Stopped**

Figure 75a




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| + Deep Test Bores | □ Shark Bay World Heritage Property |
| — Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Birdrong Sandstone, 2 Year
 After Abstraction of 11 G/annum Has Stopped**

Figure 75b




| LEGEND | | | |
|--------|------------------------------------|---|-----------------------------------|
| ● | Existing Active Private Water Bore | □ | Amy Zone |
| + | Deep Test Bores | □ | Shark Bay World Heritage Property |
| 2 | Residual Drawdown Contour | | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Birdrong Sandstone, 5 Years
 After Abstraction of 11 GL/annum Has Stopped**

Figure 75c




| LEGEND | |
|--------|------------------------------------|
| ● | Existing Active Private Water Bore |
| + | Deep Test Bores |
| — | Residual Drawdown Contour |
| □ | Amy Zone |
| □ | Shark Bay World Heritage Property |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Birdrong Sandstone, 10 Years
 After Abstraction of 11 GL/annum Has Stopped**

Figure 75d



LEGEND


- Existing Active Private Water Bore
- ✚ Deep Test Bores
- Residual Drawdown Contour
- ▭ Amy Zone
- ▭ Shark Bay World Heritage Property

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Kopke Sandstone, 1 Year
 After Abstraction of 11 GI/annum Has Stopped**

Figure 76a




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Kopke Sandstone, 2 Years
 After Abstraction of 11 GL/annum Has Stopped**

Figure 76b



0 10,000 20,000 30,000 40,000 50,000m
 Scale 1 : 75,000


| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| — Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Kopke Sandstone, 5 Years
 After Abstraction of 11 GL/annum Has Stopped**

Figure 76c




| LEGEND | |
|--------------------------------------|-------------------------------------|
| ● Existing Active Private Water Bore | □ Amy Zone |
| ✚ Deep Test Bores | □ Shark Bay World Heritage Property |
| 2 Residual Drawdown Contour | |

URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**Predicted Residual Drawdown
 in Kopke Sandstone, 10 Years
 After Abstraction of 11 GL/annum Has Stopped**

Figure 76d



Job No. 42905541

Prep. By BM 28-Feb-05

CHK'd By RBW 28-Feb-05

Revision No. 0

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT



PREDICTED TRANSIENT RESIDUAL DRAWDOWNS AFTER
ABSTRACTION OF 11GL/ANNUM - NANGA RESORT, CARBLA
STATION AND SWEENEY MIA 2001 BORES

Figure 77a




| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | BM | 28-Feb-05 |
| CHK'd By | RBW | 28-Feb-05 |
| Revision No. | 0 | |


Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT
PREDICTED TRANSIENT RESIDUAL DRAWDOWNS AFTER
ABSTRACTION OF 11GL/ANNUM - NORTHERN HAMELIN
STATION, TELEGRAPH STATION AND OVERLANDER
ROADHOUSE BORES




| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | BM | 28-Feb-05 |
| CHK'd By | RBW | 28-Feb-05 |
| Revision No. | 0 | |

Gunson Resources Limited
GROUNDWATER IMPACT ASSESSMENT, COBURN
PROJECT
PREDICTED TRANSIENT RESIDUAL DRAWDOWNS AFTER
ABSTRACTION OF 11GL/ANNUM - SOUTHERN HAMELIN AND
COBURN STATIONS BORES

Figure 77c







| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | BM | 28-Feb-05 |
| CHK'd By | RBW | 28-Feb-05 |
| Revision No. | 0 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN
 PROJECT
 PREDICTED TRANSIENT RESIDUAL DRAWDOWNS AFTER
 ABSTRACTION OF 11GL/ANNUM - EASTERN HAMELIN
 STATION, MEADOW AND NERREN NERREN STATIONS AND
 BILLABONG ROADHOUSE BORES

Figure 77d



Legend

- Area of Disturbance
- Concentrator Location
- Pit Outline
- Mine access road
- Services corridor & access road
- Future main access road & services corridor
- Site office, workshops and accomodation camp
- Waste Disposal Sites
- Construction site and initial concentrator location
- Existing Fence Line
- World Heritage Boundary
- World Heritage Area

Mounding Definition Piezometers

- Out of Pit
- In Pit

Vegetation Risk Piezometers

- Long-Term Shallow Piezometers

Stockpiles


- Initial Tailings Stockpiles
- Initial Overburden Stockpile
- Initial Topsoil/Vegetation Stockpile

| | | |
|--------------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | RBW | 27 Feb 05 |
| Chk'd By | RBW | 27 Feb 05 |
| Revision Indicator | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
LOCATIONS OF ADDITIONAL SUPERFICIAL FORMATIONS MONITORING BORES


Figure 78a

URS Australia Pty Ltd. Perth Office +61 89221 1630



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | | | |
|--------------|----------|------------|---|-------------------|
| Job No. | 42905541 | | Gunson Resources Limited | Figure 78b |
| Prep. By | RBW | 15 Oct '04 | | |
| Chk'd By | RBW | 15 Oct '04 | LOCATIONS OF ADDITIONAL SUPERFICIAL FORMATIONS PIEZOMETERS IN THE NORTHERN MINE AND NILEMAH EMBAYMENT AREA | URS |
| Revision No. | 1 | | | |



URS AUSTRALIA PTY LTD Perth Office +61 8 9221 1630

| | | |
|--------------|----------|-----------|
| Job No. | 42905541 | |
| Prep. By | ECPL | 1 Apr '05 |
| Chk'd By | RWC | 1 Apr '05 |
| Revision No. | 1 | |

Gunson Resources Limited
 GROUNDWATER IMPACT ASSESSMENT, COBURN PROJECT
**LOCATIONS OF CONFINED AQUIFER
 MULTIPIEZOMETERS**

Figure 79

URS

Appendix A
Copy of Licence to Construct or Alter Well Nos.
CAW155919(1) & CAW155924(1)



LICENCE TO CONSTRUCT OR ALTER WELL

Granted by the Commission under section 26D of the Rights in Water and Irrigation Act 1914

| | | |
|--------------------------------------|------------------------------------|--------------------------------|
| Licensee(s) | Gunson Resources Ltd | |
| Description of Water Resource | Gascoyne Camarvon - Superficial | |
| Location of Well(s) | E9/939 E9/940, E9/941 & E9/996 | |
| Authorised Activities | Activity | Location of Activity |
| | Construct 4 exploratory well(s). | E9/939 E9/940, E9/941 & E9/996 |
| Duration of Licence | From 14 June 2004 to 14 June 2005 | |

This Licence is subject to the following terms, conditions and restrictions:

- 1 The well must be constructed by a driller having a current class 1 water well drillers certificate issued by the Western Australian branch of the Australian Drilling Industry Association or other certification approved by the Water and Rivers Commission as equivalent.
- 2 That no well shall be sunk within 200 metres of an existing well without the written permission of the owner of that well.
- 3 That the depth of the bore/s shall be limited to the superficial aquifer.
- 4 That the licensee install a monitoring device, approved by the Water and Rivers Commission, on the bore for the measurement of water levels.
- 5 The licensee is required to provide to the Water and Rivers Commission a geophysical log of the bore.
- 6 The licensee is required to provide to the Water and Rivers Commission a completed 'Particulars of Completed Bore Hole Form' on completion of the approved drilling programme.
- 7 That on completion of the exploratory drilling programme the licensee shall submit two copies of a hydrogeological assessment of the groundwater source, prepared by a competent hydrogeologist.
- 8 The Hydrological and Monitoring report should be compiled in accordance with the Water and Rivers Commission publication "Guidelines for Hydrogeological and Monitoring Reports Associated with Groundwater Licensing".
- 9 That prior to a production bore licence being issued the licensee demonstrates that the required groundwater will be available for abstraction without causing harmful effects on the aquifer or other users.
- 10 The water drawn from the bore shall be limited to well development, test pumping and sampling
- 11 That water discharged during the pump test, is to be disposed of in such a manner as to cause no undesirable environmental impact
- 12 That a plan is provided showing the exact locations of all wells or shafts and indicating those designated as production, monitoring or abandoned.
- 13 Approval by the Water and Rivers Commission is to be obtained prior to the construction of additional and replacement wells and the modification or refurbishment of existing wells.

This Licence is granted subject to the Rights in Water and Irrigation Regulations 2000.



LICENCE TO CONSTRUCT OR ALTER WELL

Granted by the Commission under section 26D of the Rights in Water and Irrigation Act 1914

This Licence is subject to the following terms, conditions and restrictions:

- 14 That the licensee shall allow access, in an agreed manner, by Water And Rivers Commission personnel for the purposes of inspection at any time.
- 15 This licence is not renewable.

End of terms, conditions and restrictions

This Licence is granted subject to the Rights in Water and Irrigation Regulations 2000.



LICENCE TO CONSTRUCT OR ALTER WELL

Granted by the Commission under section 26D of the Rights in Water and Irrigation Act 1914

| | | |
|--------------------------------------|-----------------------------------|--------------------------------|
| Licensee(s) | Gunson Resources Ltd | |
| Description of Water Resource | Gascoyne Carnarvon - Birdrong. | |
| Location of Well(s) | E9/939 E9/940, E9/941 & E9/996 | |
| Authorised Activities | Activity | Location of Activity |
| | Construct 2 exploratory well(s). | E9/939 E9/940, E9/941 & E9/996 |
| Duration of Licence | From 14 June 2004 to 14 June 2005 | |

This Licence is subject to the following terms, conditions and restrictions:

- 1 The well must be constructed by a driller having a current class 3 water well drillers certificate issued by the Western Australian branch of the Australian Drilling Industry Association or other certification approved by the Water and Rivers Commission as equivalent.
- 2 That no well shall be sunk within 1000 metres of an existing well without the written permission of the owner of that well.
- 3 That bore construction is limited to the screening of one discrete aquifer interval per bore.
- 4 That the casing or casings are equipped with centralisers not less than one per casing length and are inserted in a hole providing an annulus of not less than 30mm and that the annulus is pressure cement grouted from the top of the screen to the surface.
- 5 That the bore is adequately capped and if it flows at the surface, equipped with a valve to control the flow.
- 6 The licensee is required to provide to the Water and Rivers Commission a geophysical log of the bore.
- 7 The licensee is required to provide to the Water and Rivers Commission a completed 'Particulars of Completed Bore Hole Form' on completion of the approved drilling programme.
- 8 That on completion of the exploratory drilling programme the licensee shall submit two copies of a hydrogeological assessment of the groundwater source, prepared by a competent hydrogeologist.
- 9 The Hydrological and Monitoring report should be compiled in accordance with the Water and Rivers Commission publication "Guidelines for Hydrogeological and Monitoring Reports Associated with Groundwater Licensing".
- 10 That prior to a production bore licence being issued the licensee demonstrates that the required groundwater will be available for abstraction without causing harmful effects on the aquifer or other users.
- 11 The water drawn from the bore shall be limited to well development, test pumping and sampling
- 12 That the bore is not permitted to run to waste.
- 13 That should the bore/s be abandoned it/they shall be sealed off to the satisfaction of the Water and Rivers Commission.

This Licence is granted subject to the Rights in Water and Irrigation Regulations 2000.



LICENCE TO CONSTRUCT OR ALTER WELL

Granted by the Commission under section 26D of the Rights in Water and Irrigation Act 1914

This Licence is subject to the following terms, conditions and restrictions:

- 14 That water discharged during the pump test, is to be disposed of in such a manner as to cause no undesirable environmental impact
- 15 That a plan is provided showing the exact locations of all wells or shafts and indicating those designated as production, monitoring or abandoned.
- 16 Approval by the Water and Rivers Commission is to be obtained prior to the construction of additional and replacement wells and the modification or refurbishment of existing wells.
- 17 That the licensee shall allow access, in an agreed manner, by Water And Rivers Commission personnel for the purposes of inspection at any time.
- 18 This licence is not renewable.

End of terms, conditions and restrictions

This Licence is granted subject to the Rights in Water and Irrigation Regulations 2000.

Appendix B
Summary of Aquifer Testing and
Calculated Parameters

APPENDIX B. Summary of Aquifer Parameters - Shallow Bores

| Bore No. | Ref. Point (m agl) | SWL | | Depth (m bgl) | Saturated Thickness (m) | Slotted Interval | | Pumping Rate (kL/d) | Inflow rate (kL/d) | Const. Head (m) | Hydraulic Conductivity (m/d) | | | | Storage Coeff. Jacob |
|----------|-----------------------|---------|---------|------------------|-------------------------------|------------------|---------------|------------------------|-----------------------|--------------------|------------------------------|-----------------|-------------|----------|-------------------------|
| | | (m brp) | (m bgl) | | | From (m bgl) | To (m bgl) | | | | Jacob | Bower & Rice | Summerville | Hvorslev | |
| SMB2s | 0.51 | 23.74 | 23.23 | 24 | 0.77 | 18 | 24 | N/A | >360 | abt. 23.5 | - | - | >13 | >2.5 | - |
| SMB2d | 0.51 | 23.76 | 23.25 | 40 | 16.75 | 34 | 40 | 13.8 | 13 | 23.8 | - | 0.13 | - | 0.08 | - |
| STB3 | 0.41 | 30.63 | 30.22 | 43 | 12.78 | 16 | 43 | 7.5 | - | - | 0.2 | - | - | - | - |
| SMB3s | 0.49 | >30.2 | >29.7 | 30 | 0 | 24 | 30 | N/A | ~440 | 25.0 | - | - | 5.6 | 2.6 | - |
| SMB3d | 0.49 | 30.2 | 29.71 | 43 | 13.29 | 37 | 43 | N/A | 35 | 30.2 | 0.4 | 0.1 | - | 0.17 | 2.2E-05 |
| SMB4s | 0.54 | >30.0 | >30.0 | 30 | 0 | 24 | 30 | N/A | >345 | 30.0 | - | - | >5.3 | - | - |
| SMB4d | 0.54 | 37.63 | 37.09 | 42 | 4.91 | 36 | 42 | 2.4 | >410 | 30.0 | 0.05 | 0.5* | - | >2.0* | - |

APPENDIX B. Derivation of Formation Yields Based on Salinities and Formation Resistivities

| Groundwater | | | | Formation | | | |
|----------------------|-----------|------------|---------------------|---------------------|------------------|------------------------|---------------|
| Salinity (mg/L) TDS | EC (mS/m) | EC (mho/m) | Resistivity (ohm m) | Resistivity (ohm m) | Formation Factor | Depth Interval (m bgl) | Material Type |
| Windalia Sand Member | | | | | | | |
| 9,100 | 1,400 | 1.4 | 0.714 | 3.0 | 4.2 | 170 - 195 | Sand(stone) |
| Birdrong Sandstone | | | | | | | |
| 7,750 | 1,100 | 1.1 | 0.909 | 3.5 | 3.9 | 205 - 230 | Sand(stone) |
| Kopke Sandstone | | | | | | | |
| 12,000 | 1,700 | 1.7 | 0.588 | 4.5 | 7.7 | 380 - 387 | Sandstone |

Kopke Sandstone Salinities from DTB1 Geophysical Log

| Interval Details | | | | Formation | | Groundwater | | | |
|------------------|--------------|--------------------|----------------------|---------------------|------------------|---------------------|-----------|--------------------------------|-----------------------------|
| Depth From (m) | Depth To (m) | Interval Thickness | Cumulative Thickness | Resistivity (ohm m) | Formation Factor | Resistivity (ohm m) | EC (mS/m) | Interval Salinity * (mg/L TDS) | Average Salinity (mg/L TDS) |
| 228 | 240 | 12 | 12 | 3.5 | 7.7 | 0.455 | 2,200 | 14,300 | 14300 |
| 240 | 245 | 5 | 17 | 4 | 7.7 | 0.519 | 1,925 | 12,513 | 13774 |
| 245 | 280 | 35 | 52 | 5.5 | 7.7 | 0.714 | 1,400 | 9,100 | 10628 |
| 280 | 285 | 5 | 57 | 5 | 7.7 | 0.649 | 1,540 | 10,010 | 10574 |
| 285 | 317 | 32 | 89 | 4.5 | 7.7 | 0.584 | 1,711 | 11,122 | 10771 |
| 317 | 370 | 53 | 142 | 6 | 7.7 | 0.779 | 1,283 | 8,342 | 9864 |
| 370 | 415 | 45 | 187 | 5 | 7.7 | 0.649 | 1,540 | 10,010 | 9899 |

Note: * - EC to TDS conversion based on an average of four Kopke groundwater samples to arrive at a ratio of 0.65.

0.65

DTB1 Salinity = 8900 mg/L TDS
 Kopke Proportion = 54%
 Birdrong Proportion = 46%
 Derived Combined Salinity = 8911 mg/L TDS

Appendix C
Laboratory Certificates and Chemical Analyses of
Regional (Private) Bores



LABORATORY REPORT COVERSHEET

DATE: 3 September 2004

TO: URS Corporation
Level 3, The Hyatt Centre
20 Terrace Road
EAST PERTH WA 6004

ATTENTION: Mr Rob Wallis

YOUR REFERENCE: 52830-005-562 0108

OUR REFERENCE: 83127

SAMPLES RECEIVED: 16/08/04

SAMPLES/QUANTITY: 5 Waters

The above samples were received intact and analysed according to your written instructions. Unless otherwise stated, solid samples are reported on a dry weight basis and liquid samples as received.

JANICE VENNING
Manager, Perth

LIEN TANG
Manager Reporting Systems

***This report supersedes preliminary results that were reported by E-Mail.
This report must not be reproduced except in full.***



CLIENT: URS Corporation

OUR REFERENCE: 83127

PROJECT: 52830-005-562 0108

LABORATORY REPORT

| Your Reference Our Reference Date Sampled Type of Sample | Units | SMB 2 (shall) 83127-1 13/08/2004 Water | SMB 2 (deep) 83127-2 12/08/2004 Water | STB 3 83127-3 12/08/2004 Water | SMB 4 (deep) 83127-4 12/08/2004 Water | STB 1 83127-5 13/08/2004 Water |
|---|----------|---|--|---|--|---|
| pH | pH Units | 6.3 | 6.7 | 6.2 | 6.2 | 6.6 |
| Electrical Conductivity @ 25 oC | µS/cm | 18,000 | 34,000 | 47,000 | 17,000 | 92,000 |
| Total Dissolved Solids (grav) @ 180°C | mg/L | 14,000 | 25,000 | 34,000 | 11,000 | 68,000 |
| Total Alkalinity as CaCO ₃ | mg/L | 750 | 260 | 130 | 280 | 230 |
| True Colour | PCU | 60 | 10 | 10 | 35 | 10 |
| Hardness (equivalent CaCO ₃) | mg/L | 430 | 4,300 | 6,000 | 880 | 12,000 |
| Iron (Total), Fe | mg/L | 8.6 | 0.25 | 0.15 | 10 | <0.5 |
| Sodium, Na | mg/L | 4,200 | 8,100 | 10,000 | 3,700 | 21,000 |
| Potassium, K | mg/L | 72 | 210 | 280 | 99 | 560 |
| Calcium, Ca | mg/L | 56 | 420 | 590 | 88 | 1,200 |
| Magnesium, Mg | mg/L | 72 | 780 | 1,100 | 160 | 2,200 |
| Chloride, Cl | mg/L | 5,100 | 13,000 | 17,000 | 4,900 | 37,000 |
| Carbonate, CO ₃ | mg/L | <1 | <1 | <1 | <1 | <1 |
| Bicarbonate, HCO ₃ | mg/L | 920 | 320 | 160 | 350 | 280 |
| Sulphate, SO ₄ | mg/L | 1,100 | 2,200 | 1,400 | 1,000 | 4,800 |
| Nitrate, NO ₃ | mg/L | 1.0 | 6.9 | 15 | <0.2 | 34 |
| Nitrite, NO ₂ | mg/L | <0.05 | <0.05 | <0.05 | <0.05 | <0.05 |
| Fluoride, F | mg/L | 0.5 | 0.6 | 1.0 | 0.1 | 0.6 |
| Manganese, Mn | mg/L | 0.50 | 0.85 | 0.10 | 1.1 | <0.5 |
| Silica, SiO ₂ | mg/L | 190 | 41 | 60 | 140 | 21 |
| Sum of Ions (calc.) | mg/L | 11,521 | 25,041 | 30,543 | 10,295 | 67,072 |
| Cation/Anion balance | % | 3.04 | 2.89 | 4.71 | 4.71 | 0.86 |



CLIENT: URS Corporation
 PROJECT: 52830-005-562 0108

OUR REFERENCE: 83127

LABORATORY REPORT

| Your Reference Our Reference Date Sampled Type of Sample | Units | SMB 2 (shall) 83127-1 13/08/2004 Water | SMB 2 (deep) 83127-2 12/08/2004 Water | STB 3 83127-3 12/08/2004 Water | SMB 4 (deep) 83127-4 12/08/2004 Water | STB 1 83127-5 13/08/2004 Water |
|---|-------|---|--|---|--|---|
| Aluminium, Al | mg/L | 12 | <0.1 | 0.2 | 4.4 | <1 |
| Arsenic, As | mg/L | 0.090 | 0.005 | 0.010 | 0.065 | <0.005 |
| Cadmium, Cd | mg/L | <0.001 | <0.001 | <0.001 | <0.001 | <0.01 |
| Copper, Cu | mg/L | <0.05 | <0.05 | 0.05 | <0.05 | <0.5 |
| Mercury, Hg | mg/L | <0.0005 | <0.0005 | <0.0005 | <0.0005 | <0.0005 |
| Lead, Pb | mg/L | <0.005 | <0.005 | <0.005 | <0.005 | <0.05 |
| Selenium, Se | mg/L | <0.01 | <0.01 | <0.01 | <0.01 | <0.01 |
| Zinc, Zn | mg/L | 0.10 | 0.05 | 0.10 | 0.05 | <0.5 |

| TEST PARAMETERS | UNITS | LOR | METHOD |
|--|----------|------|--------------------|
| Standard 2 | | | |
| pH | pH Units | 0.1 | PEI-001 |
| Electrical Conductivity @ 25°C | µS/cm | 1 | PEI-032 |
| Total Dissolved Solids (grav) @ 180°C | mg/L | 10 | PEI-002 |
| Total Alkalinity as CaCO ₃ | mg/L | 5 | PEI-006 |
| True Colour | PCU | 5 | PEI-004 |
| Hardness (equivalent CaCO ₃) | mg/L | 5 | PEI-043 |
| Iron (Total), Fe | mg/L | 0.05 | PEP-060/ PEM001 |
| Sodium, Na | mg/L | 0.5 | PEM-001 |
| Potassium, K | mg/L | 0.5 | PEM-001 |
| Calcium, Ca | mg/L | 0.5 | PEM-002 |
| Magnesium, Mg | mg/L | 0.5 | PEM-002 |
| Chloride, Cl | mg/L | 1 | PEI-020 |
| Carbonate, CO ₃ | mg/L | 1 | PEI-006 |
| Bicarbonate, HCO ₃ | mg/L | 5 | PEI-006 |



CLIENT: URS Corporation
PROJECT: 52830-005-562 0108

OUR REFERENCE: 83127

LABORATORY REPORT

| TEST PARAMETERS | UNITS | LOR | METHOD |
|------------------------------|-------|--------|---------|
| Sulphate, SO ₄ | mg/L | 1 | PEI-020 |
| Nitrate, NO ₃ | mg/L | 0.2 | PEI-020 |
| Nitrite, NO ₂ | mg/L | 0.05 | PEI-013 |
| Fluoride, F | mg/L | 0.1 | PEI-027 |
| Manganese, Mn | mg/L | 0.05 | PEM-001 |
| Silica, SiO ₂ | mg/L | 2 | PEM-002 |
| Sum of Ions (calc.) | mg/L | | Calc. |
| Cation/Anion balance | % | | Calc. |
| Drinking Water Metals | | | |
| Aluminium, Al | mg/L | 0.1 | PEM-002 |
| Arsenic, As | mg/L | 0.005 | PEM-004 |
| Cadmium, Cd | mg/L | 0.001 | PEM-003 |
| Copper, Cu | mg/L | 0.05 | PEM-001 |
| Mercury, Hg | mg/L | 0.0005 | PEM-005 |
| Lead, Pb | mg/L | 0.005 | PEM-003 |
| Selenium, Se | mg/L | 0.01 | PEM-004 |
| Zinc, Zn | mg/L | 0.05 | PEM-001 |



CLIENT: URS Corporation
 PROJECT: 52830-005-562 0108

OUR REFERENCE: 83127

LABORATORY REPORT

| QUALITY CONTROL | UNITS | Blank | Replicate Sm# | Replicate Sample Replicate | Spike Sm# | Matrix Spike |
|--|----------|-------|---------------|-----------------------------|-----------|--------------|
| pH | pH Units | - | [NT] | [NT] | Water | - |
| Electrical Conductivity @ 25°C | µS/cm | - | [NT] | [NT] | Water | - |
| Total Dissolved Solids (grav) @ 180°C | mg/L | <10 | [NT] | [NT] | Water | 129% |
| Total Alkalinity as CaCO ₃ | mg/L | <5 | [NT] | [NT] | Water | 107% |
| True Colour | PCU | <5 | [NT] | [NT] | Water | - |
| Hardness (equivalent CaCO ₃) | mg/L | <5 | [NT] | [NT] | Water | - |
| Iron (Total), Fe | mg/L | <0.05 | [NT] | [NT] | Water | 105% |
| Sodium, Na | mg/L | <0.5 | [NT] | [NT] | Water | 102% |
| Potassium, K | mg/L | <0.5 | [NT] | [NT] | Water | 102% |
| Calcium, Ca | mg/L | <0.5 | [NT] | [NT] | Water | 110% |
| Magnesium, Mg | mg/L | <0.5 | [NT] | [NT] | Water | 104% |
| Chloride, Cl | mg/L | <1 | [NT] | [NT] | Water | 94% |
| Carbonate, CO ₃ | mg/L | <1 | [NT] | [NT] | Water | - |
| Bicarbonate, HCO ₃ | mg/L | <5 | [NT] | [NT] | Water | - |
| Sulphate, SO ₄ | mg/L | <1 | [NT] | [NT] | Water | 106% |
| Nitrate, NO ₃ | mg/L | <0.2 | [NT] | [NT] | Water | 96% |
| Nitrite, NO ₂ | mg/L | <0.05 | [NT] | [NT] | Water | 103% |
| Fluoride, F | mg/L | <0.1 | [NT] | [NT] | Water | 88% |
| Manganese, Mn | mg/L | <0.05 | [NT] | [NT] | Water | 107% |
| Silica, SiO ₂ | mg/L | <2 | [NT] | [NT] | Water | - |
| Sum of Ions (calc.) | mg/L | - | [NT] | [NT] | Water | - |
| Cation/Anion balance | % | - | [NT] | [NT] | Water | - |



CLIENT: URS Corporation
PROJECT: 52830-005-562 0108

OUR REFERENCE: 83127

LABORATORY REPORT

| QUALITY CONTROL | UNITS | Blank | Replicate Sm# | Replicate | Spike Sm# | Matrix Spike |
|-----------------|-------|---------|---------------|-------------------|-----------|--------------|
| | | | | Sample Replicate | | |
| Aluminium, Al | mg/L | <0.1 | [NT] | [NT] | Water | - |
| Arsenic, As | mg/L | <0.005 | [NT] | [NT] | Water | 105% |
| Cadmium, Cd | mg/L | <0.001 | [NT] | [NT] | Water | 123% |
| Copper, Cu | mg/L | <0.05 | [NT] | [NT] | Water | 99% |
| Mercury, Hg | mg/L | <0.0005 | [NT] | [NT] | Water | 105% |
| Lead, Pb | mg/L | <0.005 | [NT] | [NT] | Water | 114% |
| Selenium, Se | mg/L | <0.01 | [NT] | [NT] | Water | 105% |
| Zinc, Zn | mg/L | <0.05 | [NT] | [NT] | Water | 101% |

NOTES:

LOR - Limit of Reporting.

CHAIN OF CUSTODY and
ANALYSIS REQUEST

SGS Environmental Services
52 Murray Road, Welshpool, WA 6106
Phone: 08 9458 7278
Facsimile: 08 9451 3505



FAKED

LAB QUOTE:
PURCHASE ORDER:

CLIENT: **URS**
PROJECT NAME: **Coburn Mineral Sands**

ANALYSIS REQUIRED

COLLECTORS NAME: **Rob Wallis**
PROJECT #: **52830-005 2-562 0108**

REPORTS
PRELIMINARY BY: / /
FINAL REPORT BY: / /
EMAIL REPORT (Y/N/O) **(Y)**

LAB REF: **83127**

MATRIX

PRESERVATION

| SAMPLE ID | LAB # | MATRIX | | | | PRESERVATION | | | | SAMPLING DATE | No of CONTAINERS | REMARKS |
|--------------|-------|--------|------|-----|-------|--------------|-----------|----------|---------|---------------|------------------|----------------------------|
| | | WATER | SOIL | AIR | OTHER | ICE | ACIDIFIED | ALKALINE | NONE | | | |
| SMB2 (shall) | 1 | X | | | | ✓ | ✓ | ✓ | ✓ | 13/8/04 | 3 | Refer to attached schedule |
| SMB2 (deep) | 2 | X | | | | ✓ | ✓ | ✓ | 12/8/04 | 3 | | |
| STB3 | 3 | X | | | | ✓ | ✓ | ✓ | 12/8/04 | 3 | | |
| SMB4 (deep) | 4 | X | | | | ✓ | ✓ | ✓ | 12/8/04 | 3 | | |
| STB1 | 5 | X | | | | ✓ | ✓ | ✓ | 13/8/04 | 3 | | |

Relinquished by: **RB Wallis** Date: **13/8/04** Time: **1730** Received by: **Tamara** Date: **10/8**

Condition of cooler:
Sealed: Yes / No
Temperature: Ambient / Chilled
(Please circle as appropriate)

Water Quality Report


Report Number : 00053071
Job Number : JP042570

Samples Received : 21/12/04

| Lab No. | Sample Description | Date Sampled |
|----------|--------------------|--------------|
| P0408761 | DMB1_392m-398m | 06/12/04 |
| P0408762 | DMB1_206m-212m | 07/12/04 |
| P0408763 | DMB1_184m-190m | 08/12/04 |

| | P0408761 | P0408762 | P0408763 |
|---------------------------------------|----------|----------|----------|
| Total Alkalinity as CaCO ₃ | 300 | 350 | 300 |
| Chloride | 5540 | 3210 | 4080 |
| Alkalinity as HCO ₃ | 371 | 425 | 371 |
| Conductivity at 25°C (mS/m) | 1700 | 1100 | 1400 |
| Fluoride | 0.60 | 0.80 | 0.70 |
| Calcium ICP | 360 | 220 | 200 |
| Hardness as CaCO ₃ | 2200 | 1280 | 1420 |
| Potassium ICP | 135 | 99 | 105 |
| Magnesium ICP | 320 | 180 | 220 |
| Sodium ICP | 3280 | 1960 | 2480 |
| Sulfate ICP | 1270 | 765 | 895 |
| Nitrate as Nitrogen | 0.095 | <0.05 | <0.05 |
| pH Lab (units) | 7.30 | 7.70 | 7.90 |
| Total Filt. Solids (by evap) | 12000 | 7750 | 9100 |

All units in mg/L (equivalent to g/m³) unless otherwise stated.

Approved Signatory 
Arash Shafizadeh
Senior Chemist



Job No: **032230B**
 Client: GUNSON RESOURCES
 Address: LEVEL 2
 33 RICHARDSON ST WEST PERTH
 WA 6005

Client Reference: Paid VISA
 Date Received: 2/09/2003
 Date Sampled: 21/08/2003
 Test Method: Water samples submitted by clients are analysed on an as received basis. Metals analysis on acidified samples as received. Analysis performed in accordance with MPL Laboratories WILAB 5, 6 and 8.

Sampled By: CLIENT

| IDENT UNITS | External ident | EC uS/cm | TDS mg/L | pH | CO3 mg/L | HCO3 mg/L | OH mg/L | Na mg/L | K mg/L | Ca mg/L | Mg mg/L |
|--------------|----------------|----------|----------|-------------|----------|-----------|----------|----------|----------|----------|----------|
| | | + | + | + | + | + | + | | | | |
| M001 | CP-Site1 | 11000 | 7300 | 7.15 | <1 | 230 | <1 | 2100 | 92 | 160 | 210 |
| M002 | CP-Site3 | 15000 | 10000 | 8.00 | <1 | 310 | <1 | 2900 | 120 | 200 | 340 |
| M003 | CP-Base1 | 630 | 400 | 7.95 | <1 | 140 | <1 | 70 | 5 | 38 | 12 |
| M004 | CP-Base2 | 170 | 110 | 6.50 | <1 | 3 | <1 | 25 | 2 | 3 | 4 |
| M001 Lab Dup | CP-Site1 | 11000 | 7000 | -- | -- | -- | -- | 2100 | 93 | 160 | 200 |
| LQL | | 1 | 1 | 0.05 | 1 | 1 | 1 | 5 | 1 | 1 | 1 |

| IDENT UNITS | External ident | Hard mg/L | Fe mg/L | Si mg/L | Mn mg/L | Cl mg/L | SO4 mg/L | NO3 mg/L | NO2 mg/L |
|--------------|----------------|-----------|-------------|----------|-------------|----------|----------|------------|------------|
| | | | | | | | | + | + |
| M001 | CP-Site1 | 1200 | <0.01 | 8 | <0.01 | 3600 | 880 | 0.8 | <0.1 |
| M002 | CP-Site3 | 1900 | <0.01 | 6 | 0.12 | 5200 | 1100 | <0.1 | <0.1 |
| M003 | CP-Base1 | 140 | <0.01 | 8 | <0.01 | 130 | 19 | 3.3 | <0.1 |
| M004 | CP-Base2 | 25 | 0.15 | 2 | <0.01 | 50 | 5 | 9.2 | <0.1 |
| M001 Lab Dup | CP-Site1 | 1200 | <0.01 | 8 | <0.01 | 3800 | 890 | 0.6 | <0.1 |
| LQL | | 5 | 0.01 | 2 | 0.01 | 1 | 1 | 0.1 | 0.1 |

+ indicates sample received outside holding time recommended by AS/NZ 5667.1:1998

Checked: _____

Approved Signatory: _____

Date: 4/02/2005
 Page 1 of 1



CLIENT: URS Corporation
PROJECT: 42905541

OUR REFERENCE: 86464

LABORATORY REPORT

| Your Reference Our Reference Date Sampled Type of Sample | Units | DTB1_45hrs 86464-1 17/01/2005 Water |
|---|------------|--|
| pH | pH Units | 7.3 |
| Electrical Conductivity @ 25 oC | μ S/cm | 15,000 |
| Total Dissolved Solids (grav) @ 180°C | mg/L | 8,900 |
| Total Alkalinity as CaCO ₃ | mg/L | 140 |
| True Colour | PCU | <5 |
| Hardness (equivalent CaCO ₃) | mg/L | 2,300 |
| Iron (Total), Fe | mg/L | 3.0 |
| Sodium, Na | mg/L | 3,000 |
| Potassium, K | mg/L | 120 |
| Calcium, Ca | mg/L | 330 |
| Magnesium, Mg | mg/L | 350 |
| Chloride, Cl | mg/L | 4,900 |
| Carbonate, CO ₃ | mg/L | <1 |
| Bicarbonate, HCO ₃ | mg/L | 160 |
| Sulphate, SO ₄ | mg/L | 1,100 |
| Nitrate, NO ₃ | mg/L | 0.2 |
| Nitrite, NO ₂ | mg/L | <0.2 |
| Fluoride, F | mg/L | 0.5 |
| Manganese, Mn | mg/L | 0.30 |
| Silica, SiO ₂ | mg/L | 17 |
| Sum of Ions (calc.) | mg/L | 9,885 |
| Cation/Anion balance | % | 4.96 |



CLIENT: URS Corporation
 PROJECT: 42905541

OUR REFERENCE: 86464

LABORATORY REPORT

| Your Reference Our Reference Date Sampled Type of Sample | Units | DTBI_45hrs 86464-1 17/01/2005 Water |
|---|-------|--|
| Aluminium, Al | mg/L | <0.1 |
| Arsenic, As | mg/L | <0.005 |
| Cadmium, Cd | mg/L | <0.005 |
| Copper, Cu | mg/L | <0.05 |
| Lead, Pb | mg/L | <0.05 |
| Zinc, Zn | mg/L | 0.05 |
| Mercury, Hg | mg/L | <0.0005 |
| Selenium, Se | mg/L | <0.005 |

| TEST PARAMETERS | UNITS | LOR | METHOD |
|--|----------|------|--------------------|
| Standard 2 | | | |
| pH | pH Units | 0.1 | PEI-001 |
| Electrical Conductivity @ 25°C | µS/cm | 1 | PEI-032 |
| Total Dissolved Solids (grav) @ 180°C | mg/L | 10 | PEI-002 |
| Total Alkalinity as CaCO ₃ | mg/L | 5 | PEI-006 |
| True Colour | PCU | 5 | PEI-004 |
| Hardness (equivalent CaCO ₃) | mg/L | 5 | PEI-043 |
| Iron (Total), Fe | mg/L | 0.05 | PEP-060/ PEM001 |
| Sodium, Na | mg/L | 0.5 | PEM-001 |
| Potassium, K | mg/L | 0.5 | PEM-001 |
| Calcium, Ca | mg/L | 0.5 | PEM-002 |
| Magnesium, Mg | mg/L | 0.5 | PEM-002 |
| Chloride, Cl | mg/L | 1 | PEI-020 |
| Carbonate, CO ₃ | mg/L | 1 | PEI-006 |
| Bicarbonate, HCO ₃ | mg/L | 5 | PEI-006 |



CLIENT: URS Corporation
PROJECT: 42905541

OUR REFERENCE: 86464

LABORATORY REPORT

| TEST PARAMETERS | UNITS | LOR | METHOD |
|---------------------------|-------|--------|---------|
| Sulphate, SO ₄ | mg/L | 1 | PEI-020 |
| Nitrate, NO ₃ | mg/L | 0.2 | PEI-020 |
| Nitrite, NO ₂ | mg/L | 0.2 | PEI-020 |
| Fluoride, F | mg/L | 0.1 | PEI-027 |
| Manganese, Mn | mg/L | 0.05 | PEM-001 |
| Silica, SiO ₂ | mg/L | 2 | PEM-002 |
| Sum of Ions (calc.) | mg/L | | Calc. |
| Cation/Anion balance | % | | Calc. |
| Metals in water | | | |
| Aluminium, Al | mg/L | 0.1 | PEM-002 |
| Arsenic, As | mg/L | 0.005 | PEM-004 |
| Cadmium, Cd | mg/L | 0.005 | PEM-001 |
| Copper, Cu | mg/L | 0.05 | PEM-001 |
| Lead, Pb | mg/L | 0.05 | PEM-001 |
| Zinc, Zn | mg/L | 0.05 | PEM-001 |
| Mercury, Hg | mg/L | 0.0005 | PEM-005 |
| Selenium, Se | mg/L | 0.005 | PEM-004 |



CLIENT: URS Corporation
PROJECT: 42905541

OUR REFERENCE: 86464

LABORATORY REPORT

| QUALTY CONTROL | UNITS | Blank | Replicate Sm# | Replicate Sample Replicate | Spike Sm# | Matrix Spike |
|--|----------|-------|---------------|-----------------------------|-----------|--------------|
| pH | pH Units | - | [NT] | [NT] | Water | - |
| Electrical Conductivity @ 25°C | µS/cm | - | [NT] | [NT] | Water | - |
| Total Dissolved Solids (grav) @ 180°C | mg/L | <10 | [NT] | [NT] | Water | 97% |
| Total Alkalinity as CaCO ₃ | mg/L | <5 | [NT] | [NT] | Water | 109% |
| True Colour | PCU | <5 | [NT] | [NT] | Water | - |
| Hardness (equivalent CaCO ₃) | mg/L | <5 | [NT] | [NT] | Water | - |
| Iron (Total), Fe | mg/L | <0.05 | [NT] | [NT] | Water | 78% |
| Sodium, Na | mg/L | <0.5 | [NT] | [NT] | Water | 106% |
| Potassium, K | mg/L | <0.5 | [NT] | [NT] | Water | 106% |
| Calcium, Ca | mg/L | <0.5 | [NT] | [NT] | Water | 101% |
| Magnesium, Mg | mg/L | <0.5 | [NT] | [NT] | Water | 101% |
| Chloride, Cl | mg/L | <1 | [NT] | [NT] | Water | 93% |
| Carbonate, CO ₃ | mg/L | <1 | [NT] | [NT] | Water | - |
| Bicarbonate, HCO ₃ | mg/L | <5 | [NT] | [NT] | Water | - |
| Sulphate, SO ₄ | mg/L | <1 | [NT] | [NT] | Water | 98% |
| Nitrate, NO ₃ | mg/L | <0.2 | [NT] | [NT] | Water | 98% |
| Nitrite, NO ₂ | mg/L | <0.2 | [NT] | [NT] | Water | 95% |
| Fluoride, F | mg/L | <0.1 | [NT] | [NT] | Water | 74% |
| Manganese, Mn | mg/L | <0.05 | [NT] | [NT] | Water | 107% |
| Silica, SiO ₂ | mg/L | <2 | [NT] | [NT] | Water | 85% |
| Sum of Ions (calc.) | mg/L | - | [NT] | [NT] | Water | - |
| Cation/Anion balance | % | - | [NT] | [NT] | Water | - |



CLIENT: URS Corporation
PROJECT: 42905541

OUR REFERENCE: 86464

LABORATORY REPORT

| QUALITY CONTROL | UNITS | Blank | Replicate Sm# | Replicate Sample Replicate | Spike Sm# | Matrix Spike |
|-----------------|-------|---------|---------------|-----------------------------|-----------|--------------|
| Aluminium, Al | mg/L | <0.1 | [NT] | [NT] | Water | - |
| Arsenic, As | mg/L | <0.005 | [NT] | [NT] | Water | 105% |
| Cadmium, Cd | mg/L | <0.005 | [NT] | [NT] | Water | 95% |
| Copper, Cu | mg/L | <0.05 | [NT] | [NT] | Water | 116% |
| Lead, Pb | mg/L | <0.05 | [NT] | [NT] | Water | 115% |
| Zinc, Zn | mg/L | <0.05 | [NT] | [NT] | Water | 101% |
| Mercury, Hg | mg/L | <0.0005 | [NT] | [NT] | Water | - |
| Selenium, Se | mg/L | <0.005 | [NT] | [NT] | Water | 84% |

NOTES:

LOR - Limit of Reporting.

FOXES

CHAIN OF CUSTODY FORM

Sheet of

THIS COLUMN FOR LAB USE ONLY

FROM: URS (AUSTRALIA)
ACN 000 691 690
Project office address here
20 Terrace Rd, East Perth 6004
Ph: _____
Fax: _____

Container Size, Type, Preservative and Analysis

DATE: 18/1/05 TO: SES Environmental
52 Murray Rd,
Welshpool, WA, 6106
Ph: 08 9458 7278

Due Date: _____
Project No: 42405541
Project Manager: Rob Willis
Signature(s): _____
Agreement No: _____
Checked: _____

Custody seal intact?
YES NO
Sample cold?
YES NO
Released for URS by: Bob Willis - Somen
Date: 18/1/05 Time: _____
Received for Laboratory by: Tamarica
Date: 18/1/05 Time: 1:20pm

| Lab Identification | Date | Time | Matrix | Sample Number | Comments | Total no | Tick required analyses | Container Identification |
|-------------------------------|------|------|--------|---------------|--------------------------|-----------|--|---|
| 17/1/05 17/1/05 | | | water | OT82-45hrs | UBN ^o 86464-1 | 3 bottles | <input checked="" type="checkbox"/> pH, EC, TDS (grnd) <input checked="" type="checkbox"/> Alkalinity <input checked="" type="checkbox"/> Colour, hardness <input checked="" type="checkbox"/> NO ₃ , NO ₂ , F <input checked="" type="checkbox"/> NH ₄ , CO ₃ <input checked="" type="checkbox"/> HCO ₃ <input checked="" type="checkbox"/> Cd, Cu, Pb, Ni, Mn <input checked="" type="checkbox"/> Total Fe, Se, Zn, Sc | 500ml P Non-Filtered 500ml P 250ml N 100ml * |
| TOTAL | | | | | | | | |

Remarks: * Potassium permanganate preservation / nitric preservation

* Container Type and Preservative Codes: P = Neutral Plastic; N = Nitric Acid Preserved; C = Sodium Hydroxide Preserved; J = Solvent Washed Acid Rinsed Jar; S = Solvent Washed Acid Rinsed Glass Bottle; VC = Hydrochloric Acid Preserved Vial; VS = Sulfuric Acid Preserved Vial; BS = Sulfuric Acid Preserved Glass Bottle; Z = Zinc Acetate Preserved Bottle; E = EDTA Preserved Bottles; ST = Sterile Bottle

Courier Job No: _____ Specify Turnaround Time: _____

NOTE: SAMPLES MAY CONTAIN DANGEROUS AND HAZARDOUS SUBSTANCES



| | |
|----------|------------|
| REG NO | 162005-143 |
| DATE | 4-2-05 |
| NAME | Rob Wallis |
| FILE NO. | |

LABORATORY REPORT COVERSHEET

DATE: 3 February 2005

TO: URS Corporation

Level 3, The Hyatt Centre
20 Terrace Road

EAST PERTH WA 6004

ATTENTION: Mr Rob Wallis


YOUR REFERENCE: 42905541


OUR REFERENCE: 86464

SAMPLES RECEIVED: 18/01/05

SAMPLES/QUANTITY: 1 Water

The above samples were received intact and analysed according to your written instructions. Unless otherwise stated, solid samples are reported on a dry weight basis and liquid samples as received.


JANICE VENNING
Manager, Perth


LIEN TANG
Manager Reporting Systems

***This report supersedes our preliminary results that were reported by facsimile.
This report must not be reproduced except in full.***

APPENDIX D. Chemical Analyses from Regional (Private) Bores

| Bore Name | Nanga Homestead | Spinifex Bore | Hamelin Old Homestead Bore | Meadow No. 1 | | Coburn 7 | Carbla New Homestead Bore | Homestead Tamala No. 1 | | Sweeney Mia 2001 | Yaringa No. 6 | Brickhouse Stn Boodalia Bore | Wooramel Woorla Bore | Marron Stn New Homestead Bore |
|--|-----------------|---------------|----------------------------|--------------|-------------|-------------------|---------------------------|------------------------|-------------|------------------|---------------|------------------------------|----------------------|-------------------------------|
| WIN ID No. | 2000069 | 20000916 | 20000958 | 20003960 | | 20000919 | 23002263 | 20000058 | | 23000421 | 20000970 | 20000096 | 6907 | 23000382 |
| Sampled Date | 1999* | 21-Aug-2003 | 1999* | 18-May-1977 | 30-May-1977 | 21-Aug-2003 | 1999* | 8-Jul-1966 | 20-Sep-1967 | 8-Aug-2001 | 1999* | 1999* | 1999* | 1999* |
| pH | 7.4 | 7.15 | 7.1 | 6.1 | 7.2 | 8.0 | 7.2 | 7.3 | 7.8 | 6.9 | 7.0 | 7.6 | 7.2 | 7.4 |
| EC | uS/cm | 7,200 | 11,000 | 10,000 | 20,300 | 9,400 | 15,000 | 6,400 | 3,449 | 6,656 | 7,600 | 5,200 | 6,800 | 2,700 |
| TDS | mg/L | 4,490 | 7,300 | 6,410 | 13,500 | 5,720 | 10,000 | 3,880 | 2,150 | 4,540 | 6,930 | 4,510 | 3,460 | 1,590 |
| Na | mg/L | 1,300 | 2,100 | 1,700 | 3,800 | 1,730 | 2,900 | 1,200 | 478 | 1,100 | 1,600 | 1,100 | 860 | 320 |
| K | mg/L | 68 | 92 | 85 | 177 | 84 | 120 | 63 | 29 | 49 | 61 | 65 | 44 | 31 |
| Ca | mg/L | 140 | 160 | 170 | 240 | 150 | 200 | 68 | 144 | 210 | 160 | 140 | 100 | 92 |
| Mg | mg/L | 92 | 210 | 140 | 465 | 147 | 340 | 62 | 86 | 158 | 140 | 100 | 72 | 65 |
| Cl | mg/L | 1,800 | 3,600 | 2,700 | 6,610 | 2,760 | 5,200 | 1,700 | 753 | 1,940 | 2,400 | 2,100 | <1 | 550 |
| CO ₃ | mg/L | <1 | <1 | <1 | | | <1 | <1 | | | <1 | | <1 | <1 |
| HCO ₃ | mg/L | 250 | 230 | 230 | | | 310 | 200 | | | 180 | 210 | 210 | 230 |
| OH | mg/L | | <1 | | | | <1 | | | | | | | |
| SO ₄ | mg/L | 540 | 880 | 690 | 1,590 | 732 | 1,100 | 360 | 398 | 558 | 650 | 450 | 540 | 320 |
| NO ₃ | mg/L | | 0.8 | | 3 | 5 | <0.1 | | 77 | 88 | | | | |
| NO ₂ | mg/L | | <0.1 | | | | <0.1 | | | | | | | |
| F (sol) | mg/L | 0.6 | | 0.8 | 0.2 | 0.8 | | 0.7 | | | 0.032 | 0.8 | 0.7 | 0.5 |
| Fe | mg/L | <0.1 | <0.01 | <0.1 | | | <0.01 | <0.01 | 0.1 | 0.1 | 0.8 | <0.1 | <0.1 | <0.1 |
| Si | mg/L | 28 | 8 | 16 | 13 | 29 | 6 | 12 | 8 | 15 | 7.8 | 8.1 | 11 | 8.9 |
| Mn | mg/L | | <0.01 | | | | 0.12 | | | | 0.18 | | | |
| Colour | (TCU) | | | | 5 | | | | | | | | | |
| Hardness | mg/L | 730 | 1,200 | 1,000 | 2,509 | 979 | 1,900 | 430 | 713 | 1,174 | | 790 | 540 | 500 |
| Alkalinity (HCO ₃ -HCO ₃) | mg/L | | | | 27 | 238 | | | 305 | 302 | | | | |
| Alkalinity (total) (CaCO ₃) | mg/L | | | | 22 | 195 | | | 250 | 248 | 160 | | | |
| Aquifer Sampled | Windalia | Windalia | Windalia | Windalia | | Windalia/Birdrong | Birdrong | Birdrong | | Birdrong | Birdrong | Kopke | Kopke | Kopke |

Data Sources: Gunson Resources Ltd, (2003)

WIN Database - Department of Environment (2004)

Wills and Dogramaci, Water & Rivers Commission Hydrogeology Report No. 170, (2000) - These results have a sampled date of 1999.

Appendix D
Results of Bore Census

Census of Bores within 50 km of the Coburn Project

| Name / No. | Also Known As | WIN ID No. | Station / Loc | Completion Date | Status | Eastings | Northings | Datum Elevation | Depth | Screened | Aquifer | Formation(s) | Equipped With | Original Flow Rate | | Current Flow Rate | | Original SWL | | | Current SWL | | | Original Water Quality | | | Current Water Quality | | | | |
|------------------------|-------------------------------------|---------------|---------------|-----------------|---------------|-------------|-----------|-----------------|--------|--------------------|---------------|--------------------------------|--------------------------|--------------------|-------------------|-------------------|------------|--------------|-------|---------------|---------------|------|-------------|------------------------|--------|------|-----------------------|------------|---------|-------------|-------------|
| | | | | | | m MGA (250) | m MGA | m AHD | m bgl | m bgl | m bgl | | m ³ /d | date | m ³ /d | date | m brp* | mAHD | date | m brp* | Collar height | mAHD | date | mg/L | pH | date | mg/L | E.C. mS/cm | pH | date | |
| Hamelin Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Hamelin Homestead No.3 | Hamelin Homestead No.1c | 20000962 | Hamelin | 3/09/1990 | Active | 219,899 | 7,073,849 | 21.94 | 115 | open | 112-115 | ?Birdrong | Artesian Headworks | N.D. | N.D. | -1000 | Aug-04 | -24.1 | 46.04 | 3-Sep-1990 | -22.06 | 0.65 | 44.00 | 3-Jun-2004 | 5,260 | N.D. | Nov-1999 | 6,930 | N.D. | N.D. | 3/08/2001 |
| Hamelin MRD Bore | | N.D. | Hamelin | N.D. | Decomm. | 253,842 | 7,056,239 | N.D. | N.D. | N.D. | N.D. | N.D. | Not Equipped | S/A | - | S/A | - | N.D. | N.D. | N.D. | 45.89 | 0.20 | N.D. | 15-Dec-2004 | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 15-Dec-2004 |
| Hamelin No. 4 | Boolagoorda No. 4 | 20000944 | Hamelin | 1928 | Active | 250,068 | 7,077,631 | 61.45 | 67.36 | N.D. | 60.6 - 67.4 | Alinga | Windmill | S/A | - | S/A | - | 11.6 | 49.9 | N.D. | N.D. | N.D. | 18-Dec-2004 | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 18-Dec-2004 | |
| Hamelin No. 5 | Boolagoorda No. 5, or Stone Tank | 20000951 | Hamelin | 1928 | Active | 229,315 | 7,067,593 | 74.79 | 128.02 | N.D. | 122.5 - 127.7 | ?Birdrong | Windmill | S/A | - | S/A | - | 25.5 | 49.3 | 30-Jun-1921 | 25.84 | 0.28 | 48.95 | 11-Aug-2004 | 6,063 | 6.9 | N.D. | 8,380 | 13.20 | 6.8 | 11-Aug-2004 |
| Outcamp Bore | Hamelin No.7, or 23 Mile Bore | 20000946 | Hamelin | N.D. | Active | 250,564 | 7,069,042 | 67.95 | 137.46 | N.D. | N.D. | Windalia Radiolarite ?Birdrong | Windmill | S/A | - | S/A | - | 18.2 | 49.75 | 1967 | 21.1(P) | 0.30 | 46.85 | 18-Dec-2004 | N.D. | N.D. | N.D. | 9,450 | 14.77 | 6.7 | 18-Dec-2004 |
| Hamelin No. 8 | | 20000901 | Hamelin | 13/05/1926 | Active | 230,010 | 7,059,746 | 84.52 | 117.65 | N.D. | 112.5 - 117.3 | Windalia Sand Mbr | Windmill | S/A | - | 32.91m | 1926 | 32.8 | 51.7 | 1967 | 34.12 | 0.40 | 50.40 | 11-Aug-2004 | 6,564 | 7.0 | 1926 | 12,350 | 19.00 | 6.6 | 11-Aug-2004 |
| Hamelin No 9 | | 20003952 | Hamelin | 9/07/1926 | Active | 243,443 | 7,060,644 | 76.45 | 65.53 | ND | 215.0 - 218.0 | ?Windalia Sand Mbr | Windmill | S/A | - | 22.5m | 1926 | 30.4 | 46.05 | 1967 | 25.60 | 0.31 | 50.85 | 11-Aug-2004 | ND | ND | ND | 8,250 | 13.00 | 6.6 | 11/08/2004 |
| Hamelin No. 11 | | 20000952 | Hamelin | 26/03/1927 | Active | 237,465 | 7,068,143 | 80.09 | 105.46 | N.D. | 102.1 - 105.1 | Windalia Sand Mbr | Windmill | S/A | - | 28.95m | 1927.0 | 29.0 | 51.1 | 1927 | 30.60 | 0.18 | 50.30 | 11-Aug-2004 | 5,000 | ND | 1985 | 5,970 | 9.60 | 7.1 | 11-Aug-2004 |
| Hamelin No. 13 | | | Hamelin | N.D. | Active | 258,120 | 7,078,104 | 68.20 | 46.9 | open | 37.8-46.9 | Windalia Radiolarite | Windmill | S/A | - | S/A | - | 12.8 | 55.4 | N.D. | 19.40(P) | 0.25 | N.D. | 15-Dec-2004 | ND | ND | ND | 7,420 | 11.77 | 6.5 | 15-Dec-2004 |
| Hamelin No. 14 | | 20003954 | Hamelin | 4/08/1928 | Active | 251,468 | 7,061,391 | 78.92 | 67.36 | N.D. | 67.5 - 79.0 | ?Birdrong | Windmill | S/A | - | S/A | - | 25.5 | 53.4 | 1967 | 27.70(P) | 0.35 | 51.22 | 15-Dec-2004 | 12,200 | 7.1 | N.D. | 11,900 | 18.34 | 6.7 | 15-Dec-2004 |
| Hamelin No. 16 | | 20003976 | Hamelin | 1959 | Active | 258,894 | 7,069,508 | 68.99 | 35.97 | N.D. | 30.8 - 36.0 | Windalia Radiolarite | Windmill | S/A | - | S/A | - | 13.7 | 55.3 | 10-Nov-1928 | 15.50 | 0.20 | 53.49 | 15-Dec-2004 | N.D. | N.D. | N.D. | 7,650 | 12.12 | 6.5 | 15-Dec-2004 |
| Hamelin No. 17 New | | 20000900(old) | Hamelin | 5/09/1953 | Not yet comm. | 236,848 | 7,055,518 | 86.87 | 93.57 | 90-93 | 88.7-93.6 | Windalia Sand Mbr | Not Equipped | S/A | - | S/A | - | 36.3 | 50.6 | Sep-2003 | 36.45 | 0.36 | 50.42 | 11-Aug-2004 | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 11-Aug-2004 |
| Hamelin No. 18 | | 20003955 | Hamelin | Aug-35 | Active | 251,540 | 7,056,232 | 91.94 | 65.53 | N.D. | 58.7 - 65.4 | ?Windalia Sand Mbr | Windmill | S/A | - | S/A | - | 38.6 | 53.3 | 1967 | 41.75(P) | 0.45 | 50.19 | 15/12/2004 | 10,480 | 8.3 | Jun-35 | 9,420 | 1473.00 | 6.9 | 15-Dec-2004 |
| Hamelin No. 20B | | 20003956 | Hamelin | Nov-20 | Active | 259,755 | 7,056,124 | 122.92 | 76.5 | N.D. | 76.0 - 76.3 | ?Windalia / ?Alinga | Windmill | S/A | - | S/A | - | 68.7 | 54.2 | February 1950 | 63.60 | 0.30 | 59.32 | 15/12/2004 | 15,115 | N.D. | Jan-50 | 10,550 | 16.38 | 6.5 | 15-Dec-2004 |
| Hamelin No. 23 | Hamelin No. 19 (replaced) | N.D. | Hamelin | 1959 | Active | 236,790 | 7,060,395 | 83.90 | 90.83 | N.D. | 68.1 - 90.6 | Windalia Sand Mbr | Windmill | S/A | - | S/A | - | 71.4 | 12.5 | 1967 | 33.00 | 0.26 | 50.90 | 11/08/2004 | 6,000 | N.D. | 1985 | 5,970 | 9.60 | 7.1 | 11-Aug-2004 |
| Hamelin No. 24 | North Bore | N.D. | Hamelin | 1962 | U/S | 259,263 | 7,089,876 | N.D. | 89.3 | N.D. | N.D. | N.D. | Not Equipped | S/A | - | S/A | - | 45.7 | N.D. | 1967 | Blocked | 0.47 | N.D. | 18/12/2004 | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 18-Dec-2004 |
| Hamelin No 26 | SB1 | 20003959 | Hamelin | N.D. | Decomm | 266,050 | 7,051,196 | 138.20 | 184 | 80.1-184.0 | 80-184 | ?Windalia Sand Mbr | Not Equipped | S/A | - | S/A | - | 80.8 | 57.40 | 11-Nov-1987 | 81.63 | 0.26 | 56.57 | 14-Dec-2004 | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 14-Dec-2004 |
| Hamelin Spinifex 1 | Hamelin No. 6 | 20000916 | Hamelin | 1921 | Flowing | 220,276 | 7,063,497 | 46.63 | 158.49 | 153.1 - 158.1 | 128 - 158 | Windalia Sand Mbr | Flowing | 378.54 | 1921 | -10 | 11/08/2004 | N.D. | >46.6 | 1921 | Flowing | None | >46 | 11/08/2004 | 7,659 | N.D. | 4/11/1997 | N.D. | N.D. | N.D. | 11-Aug-2004 |
| Hamelin Spinifex 2 | South Bore | 20000917 | | 1964 | Flowing | 220,278 | 7,063,508 | -46.6 | 159.71 | No Screen | N.D. | Windalia Sand Mbr | Flowing | 11.35 | 1967 | -10 | 11/08/2004 | N.D. | N.D. | N.D. | Flowing | 0.65 | >46.6 | 11/08/2004 | 6,786 | N.D. | 4/11/1997 | 5,840 | 9.40 | 7.1 | 11-Aug-2004 |
| Hamelin Kevins Bore | Hamelin No. 25 | 20000955 | Hamelin | 1965 | Active | 241,846 | 7,077,532 | 71.42 | 116.4 | N.D. | 101.8 - 116.4 | ?Birdrong | Windmill | S/A | - | S/A | - | 32.0 | 39.42 | 10-May-1965 | 22.35 | 0.28 | 49.07 | 15-Dec-2004 | 8,000 | N.D. | 1985 | 8,480 | 13.35 | 7.3 | 15-Dec-2004 |
| Hamelin Five Mile Bore | Hamelin No. 12 (1928) | 20000947 | Hamelin | 1965 | Active | 228,633 | 7,074,650 | 59.78 | 127.1 | N.D. | 122.5-126.7 | ?Windalia Sand Mbr | Windmill | S/A | - | S/A | - | 6.4 | 53.4 | 1967 | 13.50 | 0.16 | 46.28 | 11-Aug-2004 | 6,000 | N.D. | 1985 | 6,100 | 9.80 | 6.8 | 11-Aug-2004 |
| Hamelin Ten Mile Bore | Hamelin No. 6, or Boolagoorda No. 3 | 20000954 | Hamelin | N.D. | Active | 237,198 | 7,076,015 | 71.96 | 184.7 | N.D. | 137.1-184.7 | ?Birdrong | Windmill | S/A | - | S/A | - | 23.2 | 48.4 | 1967 | N.D. | 0.40 | N.D. | 11-Aug-2004 | 7,000 | N.D. | 1985 | 8,180 | 12.90 | N.D. | 11-Aug-2004 |
| Sweeney Mia Bore 2001 | | 23000421 | Hamelin | 15-Jun-01 | Active | 236,347 | 7,104,862 | 25.60 | 177.5 | 147-159 165-171 | 137.0-177.5 | Birdrong | Nil - Artesian Headworks | 733 | 37091 | N.D. | - | -24.1 | 49.1 | 19-Jul-2001 | Artesian | N.D. | N.D. | 15-Dec-2004 | 5,000 | N.D. | 7/06/1905 | 5,430 | 8.78 | 6.8 | 15-Dec-2004 |

Census of Bores within 50 km of the Coburn Project

| Name / No. | Also Known As | WIN ID No. | Station / Loc | Completion Date | Status | Eastings | Northings | Datum Elevation | Depth | Screened | Aquifer | Formation(s) | Equipped With | Original Flow Rate | | Current Flow Rate | | Original SWL | | | Current SWL | | | Original Water Quality | | | Current Water Quality | | | | | |
|---|----------------------|------------|------------------|----------------------|--------|-------------|-----------|-----------------|--------|-------------------|---------------|----------------------|----------------------|--------------------|-------------------|-------------------|--------|--------------|--------|-------------|---------------|------|-------|------------------------|----------------|------|-----------------------|------------|-------|------|-------------|-------------|
| | | | | | | m MGA (250) | m MGA | m AHD | m bgl | m bgl | m bgl | | m ³ /d | date | m ³ /d | date | m brp* | mAHD | date | m brp* | Collar height | mAHD | date | mg/L | pH | date | mg/L | E.C. mS/cm | pH | date | | |
| Coburn Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Coburn No. 4 | | 20000904 | Coburn | 1926 (Deepened 1935) | Decomm | 249,216 | 7,045,002 | 110.89 | 116.43 | 110 - 116 | >60 | Windalia Sand Mbr | Not Equipped | S/A | - | S/A | - | 56.1 | 54.809 | 30-Jun-1920 | 56.90 | 0.14 | 53.99 | 11-Aug-2004 | 8,610 - 11,690 | N.D. | 1926 | N.D. | N.D. | N.D. | N.D. | 11-Aug-2004 |
| Coburn No. 7 | | 20000919 | Coburn | N.D. | Active | 226,396 | 7,044,054 | 79.50 | 184.1 | Open below 98.8 m | 107.0 - 164.7 | Windalia / Birdrong | Mono Pump 54.8m | S/A | - | S/A | - | 42.7? | 36.83? | N.D. | N.D. | N.D. | N.D. | 11-Aug-2004 | 8,660 | 7 | 30/06/1936 | 8,250 | 13.00 | 6.5 | 16-Dec-2004 | |
| Coburn No. 8 | | N.D. | Coburn | N.D. | Active | 241,162 | 7,049,691 | 99.45 | 79.9 | N.D. | N.D. | N.D. | Mono Pump 60.96m | S/A | - | S/A | - | N.D. | N.D. | N.D. | N.D. | 0.35 | N.D. | 11-Aug-2004 | N.D. | N.D. | N.D. | 7,240 | 11.50 | 7.5 | 11-Aug-2004 | |
| Coburn No. 9 B | | N.D. | Coburn | 16/07/1988 | Active | 225,080 | 7,048,971 | 84.69 | 129 | 117-129 | 117-129 | Windalia Sand Mbr | Mono Pump 60.96m | S/A | - | S/A | - | 36.0 | 48.7 | 1-Jul-1988 | N.D. | 0.45 | N.D. | 11-Aug-2004 | 9,415 | N.D. | Jul-88 | 6,240 | 10.00 | 7.5 | 11-Aug-2004 | |
| Coburn No. 11 B | | 20000905 | Coburn | 6/08/1988 | Active | 249,224 | 7,048,552 | 103.06 | 69 | 57-69 | 54-69 | Windalia Sand Mbr | Mono Pump 60.96m | S/A | - | S/A | - | 50.0 | 53.06 | 1-Aug-1988 | N.D. | 0.40 | N.D. | 11-Aug-2004 | 10,750 | N.D. | N.D. | 7,170 | 11.40 | 7.8 | 11-Aug-2004 | |
| Coburn No. 14 | | 20000907 | Coburn | N.D. | Active | 232,169 | 7,044,243 | 87.82 | 91.44 | N.D. | N.D. | N.D. | Mono Pump 60.96m | S/A | - | S/A | - | 39.6 | 48.22 | N.D. | N.D. | 0.25 | N.D. | 11-Aug-2004 | 9,200 | N.D. | N.D. | 7,910 | 12.50 | 7.1 | 11-Aug-2004 | |
| Overlander Roadhouse (Main Roads Bore) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Overlander Roadhouse | MRD Overlander | 20000945 | Hamelin | Jan-80 | Active | 246,846 | 7,076,254 | 63.59 | 150 | 114-149 | 85 - 149 | Windalia Sand Mbr | Electric Submersible | S/A | - | S/A | - | 21.35 | 48.7 | 11-Nov-1997 | N.D. | N.D. | N.D. | 12-Dec-2004 | 9,510 | N.D. | Jan-80 | 8,740 | 13.73 | 6.7 | 12-Dec-2004 | |
| Billabong Roadhouse | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Billabong Roadhouse | | 20003946 | Meadow | N.D. | Active | 262,732 | 7,031,518 | 130.44 | N.D. | N.D. | N.D. | ?Windalia Sand Mbr | Electric Submersible | S/A | - | S/A | - | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 14-Dec-2004 | 11,680 | N.D. | N.D. | 11,520 | 17.80 | 6.0 | 14-Dec-2004 | |
| Hamelin Telegraph Station & Caravan park | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Hamelin Telegraph Station | Hamelin Caravan Park | 20000961 | Lot 161, Hamelin | 18-Nov-88 | Active | 217,201 | 7,076,870 | 4.14 | 106 | N.D. | N.D. | Windalia Radiolarite | Artesian Headworks | N.D. | - | N.D. | N.D. | -42 | 46.14 | 18-Nov-1998 | N.D. | 0.35 | N.D. | 11-Aug-2004 | 5,970 | N.D. | N.D. | 4,890 | 7.95 | 6.9 | 11-Aug-2004 | |

Census of Bores within 50 km of the Coburn Project

| Name / No. | Also Known As | WIN ID No. | Station / Loc | Completion Date | Status | Eastings | Northings | Datum Elevation | Depth | Screened | Aquifer | Formation(s) | Equipped With | Original Flow Rate | | Current Flow Rate | | Original SWL | | | Current SWL | | | Original Water Quality | | | Current Water Quality | | | | |
|------------------------------|---|------------|---------------|-----------------|-------------|----------------|-----------|-----------------|--------|---------------|---------------|--|---------------------------------|--------------------|-------------------|-------------------|-------------|--------------|--------|-------------|---------------|------|-------|------------------------|--------|------|-----------------------|------------|-------|------|-------------|
| | | | | | | m MGA (250) | m MGA | m AHD | m bgl | m bgl | m bgl | | m ³ /d | date | m ³ /d | date | m brp* | mAHD | date | m brp* | Collar height | mAHD | date | mg/L | pH | date | mg/L | E.C. mS/cm | pH | date | |
| Meadow Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Meadow No. 1 | | 20003960 | Meadow | 1988 | Active | 263,366 | 7,044,424 | 135.46 | 87.8 | 86.2-87.8 | 76.6 - 87.6 | Windalia Sand Mbr | Mono Pump | S/A | - | S/A | - | 76.6 | 58.9 | May 1951 | N.D. | N.D. | N.D. | 16-Dec-2004 | 16,913 | 5.4 | May-51 | N.D. | N.D. | N.D. | 16-Dec-2004 |
| Meadow No. 3 | Billabong Hotel | 20003947 | Meadow | 1980 | Active | 262,798 | 7,031,657 | 130.35 | 78.6 | 75.6-78.6 | 74.4 - 78.6 | ?Windalia Sand Mbr | Electric Submersible | S/A | - | S/A | - | 74.4 | 56.0 | 1950 | N.D. | N.D. | N.D. | 14-Dec-2004 | N.D. | N.D. | N.D. | 11,390 | 17.61 | 5.7 | 14-Dec-2004 |
| Meadow No. 4 | | 20003944 | Meadow | Abt 1951-52 | Active | 268,465 | 7,031,136 | 139.29 | 88.2 | N.D. | 82.3-88.2 | Tumblagooda Sandstone | Windmill | S/A | - | S/A | - | Est 76 | Est 63 | 1951-52 | N.D. | 0.30 | N.D. | 15-Dec-2004 | 9,928 | 7.6 | 1951-52 | 8,900 | 13.98 | 9.2 | 14-Dec-2004 |
| Meadow No. 5 | | 20003945 | Meadow | 1990-91 | Active | 267,779 | 7,038,527 | 134.87 | 106.7 | 100.7-106.7 | 78.3-106.7 | Windalia Sand? Tumblagooda Sandstone | Windmill | S/A | - | S/A | - | 77.4 | 57.5 | 1952-53 | 78.12 | 0.38 | 56.75 | 15/12/2004 (old bore) | 11,000 | N.D. | 18/05/1977 | 12,000 | 18.53 | 4.5 | 15-Dec-2004 |
| Meadow No. 6 | Relined 1988 | 20003949 | Meadow | 1950 | Pump U/S | 268,580 | 7,023,695 | 141.67 | 95.1 | N.D. | 86.3-95.1 | ?Tumblagooda Sandstone | Mono Pump | S/A | - | S/A | - | Est 86.3 | N.D. | 1950 | N.D. | N.D. | N.D. | 16-Dec-2004 | 8,800 | 7.1 | 1950 | N.D. | N.D. | N.D. | 16-Dec-2004 |
| Meadow No. 7 | | 20003948 | Meadow | 1946 | Active | 262,288 | 7,038,384 | 128.07 | 86.6 | N.D. | 57.9 - 86.6 | Windalia Sand Mbr / ?Birdrong / ?Tumblagooda | Windmill | S/A | - | S/A | - | 72.4 | 55.7 | 1946 | N.D. | N.D. | N.D. | 14-Dec-2004 | N.D. | N.D. | N.D. | 13,460 | 20.60 | 4.0 | 14-Dec-2004 |
| Meadow No. 8 (New) | | N.D. | Meadow | 2000 | Not Equiped | 256,460 | 7,044,452 | 118.90 | 109.7 | 103.7-109.7 | 75.6-109.7 | ?Windalia Sand Mbr | Not Equiped | S/A | - | S/A | - | N.D. | N.D. | N.D. | 72.96 | 0.53 | 45.94 | 14-Dec-2004 | 13,330 | 6.4 | Jun 1950 (old bore) | N.D. | N.D. | N.D. | 14-Dec-2004 |
| Nerren Nerren Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Nerren Nerren 1A | Cooloomia | 20000913 | Nerren Nerren | N.D. | Active | 255,991 | 7,017,901 | 147.07 | 109.7 | 103.7-109.7 | N.D. | ?Tumblagooda Sandstone | Mono Pump | S/A | - | S/A | - | 92.0 | 55.07 | N.D. | N.D. | N.D. | N.D. | 18-Dec-2004 | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 16-Dec-2004 |
| Nerren Nerren 5A | Nerren Nerren 5 | 20003942 | Nerren Nerren | N.D. | Active | 256,752 | 6,996,877 | 172.39 | 167.6 | pen 152.4-167 | 152.4-167.6 | ?Tumblagooda Sandstone | Mono Pump | S/A | - | S/A | - | 109.7 | 62.69 | N.D. | N.D. | N.D. | N.D. | 18-Dec-2004 | N.D. | N.D. | N.D. | 14,570 | 22.20 | 6.8 | 18-Dec-2004 |
| Carbla Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Carbla Homestead | Replaced Milyila No. 11 / Carbla 11 | 23002263 | Carbla | 22/08/2001 | Active | 228,800 | 7,099,500 | Abt. 32 | 156.59 | 138.3 - 150.3 | 140.0 - 156.6 | Birdrong | Artesian Headworks | N.D. | - | N.D | N.D | 17.56 | 49.56 | 22-Aug-2001 | N.D. | 0.60 | N.D. | 17-Dec-04 | 4,739 | N.D. | Jun-68 | 4,740 | 7.73 | 6.5 | 17-Dec-2004 |
| Carbla No. 12 | | N.D. | Carbla | N.D. | Active | 245,705 | 7,094,785 | N.D. | N.D. | N.D. | N.D. | N.D. | Windmill | S/A | - | S/A | - | N.D. | N.D. | N.D. | 16.19 | 0.25 | N.D. | 17-Dec-2004 | N.D. | N.D. | N.D. | 5,210 | 8.45 | N.D. | 17-Dec-2004 |
| Carbla No. 13 | | 20000936 | Carbla | 1935 | Active | 228,838 | 7,089,056 | 13.32 | 113.39 | 107 - 113.1 | N.D. | ?Windalia Radiolarite | Windmill | Sml flow | - | S/A | N.D | 9.14 | 10.98 | 30-Jun-1935 | 5.15 | 0.45 | 8.17 | 17-Dec-2004 | N.D. | N.D. | N.D. | 6,160 | 9.89 | 6.9 | 17-Dec-2004 |
| Carbla No. 14 | | 20000934 | Carbla | 1935 | Active | 245,973 | 7,089,500 | 57.09 | 101.5 | N.D. | N.D. | ?Birdrong | Windmill | S/A | - | S/A | N.D | 1.83 | 71.32 | 30-Jun-1935 | 10.25 | 0.32 | 46.84 | 17-Dec-2004 | N.D. | N.D. | N.D. | 5,680 | 9.16 | 6.5 | 17-Dec-2004 |
| Carbla No. 16 | | 20000941 | Carbla | N.D. | Active | 237,358 | 7,088,357 | 50.91 | N.D. | N.D. | N.D. | ?Windalia Radiolarite | Windmill | S/A | - | S/A | - | N.D. | N.D. | N.D. | 7.03 | 0.32 | 43.88 | 17-Dec-2004 | N.D. | N.D. | N.D. | 5,260 | 8.52 | 6.9 | 17-Dec-2004 |
| Carbla No. 17 | | N.D. | Carbla | N.D. | Active | 237,073 | 7,099,858 | N.D. | N.D. | N.D. | N.D. | N.D. | Windmill | N.D. | N.D. | S/A | - | N.D. | N.D. | N.D. | N.D. | 0.10 | N.D. | 17-Dec-2004 | N.D. | N.D. | N.D. | 5,460 | 8.33 | 6.5 | 17-Dec-2004 |
| Six Mile Well | Hamelin Pool No.2 | 20000931 | Carbla | Jun-68 | Active | 236,347 | 7,104,862 | 25.60 | 130.4 | 127.4 - 130.4 | 127.4 - 130.4 | Nannyarra Sandstone | Leaking Artesian Headworks | 3182 | Jun-68 | N.D. | 17/12/2004 | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 17-Dec-2004 | 3,968 | N.D. | 6-Nov-1997 | 3,760 | 6.21 | 6.4 | 17-Dec-2004 |
| SEC Bore | | N.D. | Carbla | N.D. | Active | 245,926 | 7,100,986 | N.D. | N.D. | N.D. | N.D. | N.D. | Windmill | S/A | - | S/A | - | N.D. | N.D. | N.D. | 4.07 | 0.29 | N.D. | 17-Dec-2004 | N.D. | N.D. | N.D. | 5,640 | 9.09 | 6.5 | 17-Dec-2004 |
| Nanga Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Nanga Homestead | Nanga No.2 Homestead Nanga View Homestead | 20000069 | Nanga | 12-Aug-90 | Active | <u>181,513</u> | 7,093,023 | N.D. | 349.5 | 312-349.5 | 330-349.5 | Windalia Radiolarite | Artesian Headworks | N.D. | 12-Aug-90 | N.D. | 13/12/2004 | >-20 | >30 | 12-Aug-1990 | >20 | 0.45 | >30 | 13-Dec-2004 | N.D. | N.D. | 12/08/1990 | 4,680 | 7.64 | 7.1 | Dec-04 |
| Nilemah Artesian No. 1A | | 20000963 | Nanga | 26/11/1992 | Active | 205,888 | 7,073,900 | 5.37 | 164 | 161-164 | 154-164 | Birdrong | Artesian Headworks | 5,680 | 1921 | N.D | 12-Aug-2004 | N.D. | >30.5 | 1955 | -40.00 | 0.46 | 45.37 | 12-Aug-2004 | 6,829 | N.D. | 1921 (old bore) | 6,300 | 10.10 | 6.9 | 12-Aug-2004 |
| Tamala Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cape Well Bore | Cape Camp Bore | 20000050 | Tamala | Bef. 1972 | Active | <u>175,645</u> | 7,029,550 | N.D | 100.0 | N.D. | N.D. | ?Tamala Limestone | Mono Pump | S/A | - | S/A | - | N.D | N.D | N.D | N.D | N.D | N.D | 12-Dec-2004 | 688 | N.D. | 12/03/1993 | N.D | N.D | N.D | 12-Dec-2004 |
| Beethen Outcamp Well | Beethan Well (South) | 20000051 | Tamala | Bef 1977 | Active | <u>174,195</u> | 7,031,900 | N.D | 9.0 | N.D. | N.D. | ?Tamala Limestone | Mono Pump & Windmill | S/A | - | S/A | - | N.D | N.D | N.D | N.D | N.D | N.D | 12-Dec-2004 | 2,943 | N.D. | 12/03/1993 | N.D | N.D | N.D | 12-Dec-2004 |
| Natta Outcamp Bore | | 20000048 | Tamala | N.D. | Active | <u>181,145</u> | 7,033,000 | N.D | 30 | N.D. | N.D. | ?Tamala Limestone | Windmill & Electric Submersible | S/A | - | S/A | - | N.D | N.D | N.D | N.D | N.D | N.D | 12-Dec-2004 | 1,694 | N.D. | 12/03/1993 | N.D | N.D | N.D | 12-Dec-2004 |
| Woodleigh Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Woodleigh No 10C | | | Woodleigh | N.D. | Active | 265,980 | 7,099,940 | N.D. | N.D. | N.D. | N.D. | N.D. | Electric Submersible | S/A | - | S/A | - | N.D | N.D | N.D | 60.92 | 0.19 | N.D. | 14-Dec-2004 | N.D. | N.D. | N.D. | 11,000 | 17.05 | N.D. | 14-Dec-2004 |
| Woodleigh No 11 | | | Woodleigh | N.D. | Active | 255,281 | 7,101,004 | N.D. | N.D. | N.D. | N.D. | N.D. | Windmill | S/A | - | S/A | - | 5.49 | N.D. | N.D. | N.D. | N.D. | N.D. | 17-Dec-2004 | 8,812 | 7.2 | 1948 | 5,790 | 9.32 | N.D. | 18-Dec-2004 |
| Woodleigh No 22 | | | Woodleigh | N.D. | Active | 273,765 | 7,092,651 | N.D. | N.D. | N.D. | N.D. | N.D. | Electric Submersible | S/A | - | S/A | - | N.D | N.D | N.D | N.D. | 0.05 | N.D. | 14-Dec-2004 | N.D. | N.D. | N.D. | 4,330 | 7.09 | N.D. | 14-Dec-2004 |
| Woodleigh No 25 | BHP Camp Bore | | Woodleigh | N.D. | Active | 270,223 | 7,078,696 | N.D. | N.D. | N.D. | N.D. | N.D. | Electric Submersible | S/A | - | S/A | - | N.D | N.D | N.D | N.D. | 0.20 | N.D. | 14-Dec-2004 | N.D. | N.D. | N.D. | 8,280 | 13.05 | 6.5 | 14-Dec-2004 |
| Toolonga Station | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SB2 | | 20003943 | Toolonga | N.D. | Not in use | 294,721 | 7,044,156 | 201.34 | 190 | 87.3-190 | 87-190 | ?Tumblagooda Sandstone | Not Equiped | S/A | - | S/A | - | 110.7 | 90.64 | 16-Nov-1981 | N.D. | 0.13 | N.D. | 14-Dec-2004 | N.D. | N.D. | N.D. | N.D. | N.D. | N.D. | 14-Dec-2004 |

Data Sources:

McWhae, Hydrodynamic and Salinity Study of the Chief Aquifers of the Carnarvon Basin, (1958)
 Playford & Chase, Carnarvon Basin Water Bores: West Australian Petroleum Dept. (1955)
 WIN Database - Department of Environment (2004)
 Wills and Dogramaci, Water & Rivers Commission Hydrogeology Report No. 170, (2000)

Abbreviations: m AHD - metres above the Australian Height Datum
 m bgl - metres below ground level
 m brp - metres below the reference point (usually top of bore casing)
 N.D. - Not Determined

mg/L TDS - milligrams per litre Total Dissolved Solids
 m³/d - cubic metres (or kilolitres)
 S/A - Sub artesian water level, i.e. not flowing

Appendix E
Mine Water Balance Detail

Appendix E. Summary Calculations for Life-of-Mine Water Balance

| Year | Inputs | Outputs* | Period Balance Required from Bores | Annual Bore Water Require ment |
|--------------------------------------|--------|------------|---|--------------------------------------|
| | kL | kL | kL | kL |
| 1 | 10,595 | 5,942,564 | 5,931,969 | 5,931,969 |
| 2 | 10,595 | 5,942,564 | 5,931,969 | 5,931,969 |
| 3 | 10,595 | 9,917,228 | 9,906,633 | 9,906,633 |
| 4 | 10,595 | 9,917,228 | 9,906,633 | 9,906,633 |
| 5 | 10,595 | 11,267,228 | 11,256,633 | 11,256,633 |
| 5 - 10 | 52,975 | 53,185,085 | 53,132,110 | 10,626,422 |
| 10 - 15 | 52,975 | 52,285,085 | 52,232,110 | 10,446,422 |
| 15 - 20 | 52,975 | 51,385,085 | 51,332,110 | 10,266,422 |
| Average Water Requirement (1 plant) | | | | 5,931,969 |
| Average Water Requirement (2 plants) | | | | 10,401,528 |

APPENDIX E. Annual Water Balance Calculations

| | | | Water In | | Water Out | | | | | | | | | | Balance | | |
|--------------------------------|----------------------|------------------|--------------------------|-------------------------|--------------------|----------------------|---------------|---------------------------|-------------------|---------------------------|---------------|------------------------|--------------------|-----------------------|------------------------|--|---|
| Source | | | Direct Rainfall Recharge | Process Water Dams | Evaporation Losses | | | Evapora-tion Losses Total | Dust Suppress-ion | Concen-trate Water Losses | Process Bores | Seepage Losses | | | Seepage Losses (Total) | Total Make-up Process Water Pumpage Required | Estimated Annual Licenced Water Requirement |
| Location | | | Water Dams | Initial Plant Start-ups | Process Water Dam | Slimes Settling Area | Stacker Areas | | | | | Tailings Not Recovered | Process Water Dams | Slimes Settling Areas | | | |
| Notes | | | 1 | 2 | 3 | 4 | 5 | 3 - 5 | 6 | 7 | 8 | 9 | 10 | 11 | 9 - 11 | 12 | 13 |
| Year No. | Operating time (yrs) | Plants Operating | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL |
| 1 | 0.81 | 1 | 10,595 | 900,000 | 224,458 | 26,935 | 11,223 | 262,616 | 182,500 | 170,400 | 131,400 | 2,662,784 | 0 | 1,632,864 | 4,295,648 | 5,931,969 | 5,931,969 |
| 2 | 0.81 | 1 | 10,595 | 900,000 | 224,458 | 26,935 | 11,223 | 262,616 | 182,500 | 170,400 | 131,400 | 2,662,784 | 0 | 1,632,864 | 4,295,648 | 5,931,969 | 5,931,969 |
| 3 | 0.81 | 2 | 10,595 | 0 | 448,916 | 53,870 | 22,446 | 525,232 | 365,000 | 340,800 | 94,900 | 5,325,568 | 0 | 3,265,728 | 8,591,296 | 9,906,633 | 9,906,633 |
| 4 | 0.81 | 2 | 10,595 | 0 | 448,916 | 53,870 | 22,446 | 525,232 | 365,000 | 340,800 | 94,900 | 5,325,568 | 0 | 3,265,728 | 8,591,296 | 9,906,633 | 9,906,633 |
| 5 | 0.81 | 2 | 10,595 | 1,350,000 | 448,916 | 53,870 | 22,446 | 525,232 | 365,000 | 340,800 | 94,900 | 5,325,568 | 0 | 3,265,728 | 8,591,296 | 11,256,633 | 11,256,633 |
| 10 | 4.05 | 2 | 52,975 | 3,600,000 | 2,244,582 | 269,350 | 112,229 | 2,626,161 | 1,825,000 | 1,702,944 | 474,500 | 26,627,840 | 0 | 16,328,640 | 42,956,480 | 53,132,110 | 10,626,422 |
| 15 | 4.05 | 2 | 52,975 | 2,700,000 | 2,244,582 | 269,350 | 112,229 | 2,626,161 | 1,825,000 | 1,702,944 | 474,500 | 26,627,840 | 0 | 16,328,640 | 42,956,480 | 52,232,110 | 10,446,422 |
| 20 | 4.05 | 2 | 52,975 | 1,800,000 | 2,244,582 | 269,350 | 112,229 | 2,626,161 | 1,825,000 | 1,702,944 | 474,500 | 26,627,840 | 0 | 16,328,640 | 42,956,480 | 51,332,110 | 10,266,422 |
| Project Lifetime Totals | | | 211,900 | 11,250,000 | 8,529,412 | 1,023,529 | 426,471 | 9,979,412 | 6,935,000 | 6,472,032 | 1,971,000 | 101,185,792 | 0 | 62,048,832 | 163,234,624 | 199,630,168 | |

- Key Assumptions:
- Tailings discharge cyclones recover 47% of water used for each 2,000 tonnes/hr of ore processed reaching an average solids content of 65%.
 - On average, 68% of the tailings water is recovered
 - Process water bores each yield 3.1 GL/annum (100 L/sec) but only pumped at an average of 75 L.sec (75% up-time) for 2.37 GL/year
 - Processing occurs for 7,100 hrs/year

- Notes:
- 1 Based on the annual mean rainfall data for Hamelin Pool (BoM Stn. No. 006025, Jan 1886-Jul 2004) and annual evaporation data from Hamelin pool (BoM Stn. No. 006025, May 1978-Apr 1980), Nanga Stn. (BoM Stn. No. 006080, May 1980-Apr 1988) and Brickhouse Stn (BoM Stn. No. 6087, Sep 1966-Mar 1977).
Dam surface areas based on there being 1 Ha of water in the process water dam and 4 Ha in the slimes settling area.
 - 2 This value based on filling process water dams (450 ML each) for each plant site move. (Does not include plant recommissioning requirements)
 - 3 Surface area of the process water dams are based on 320 x 320 m dams for each plant. One new dam is allowed for for each new plant site.
Evaporation calculated as 0.72 x pan evaporation figures from BoM as per Ag. Dpet tech Report 65, 1988.
 - 4 Surface area of the slimes dams are based on 2 dams (1 active and 1 inactive) of average size of 200 x 30 m dams for each plant. Two for years 1 and 2, and four dams for years 3 onwards.
Evaporation calculated as 0.72 x pan evaporation figures from BoM as per Ag. Dpet tech Report 65, 1988.
 - 5 It is assumed that the active stacker site will be approx. 50 x 100 m per plant.
 - 6 Dust suppression losses based on half the nominated area of 30,000 m² of watered roads (mine access and internal roads) being constantly wet and subjected to evaporative losses.
An additional average of 500 kL/d has been allowed for dust suppression that is assumed as a total loss.
 - 7 Losses are expected from the system via the concentrate stockpiles at a rate of 24 kL/hr.
 - 8 Camp supply based on nominated number of people as 100 construction personnel, 80 mining personnel in years 1-2 and 130 in years 3 onwards. An average consumption is calculated on the basis of 0.75 kL perperson per day of potable water and that 1.5 kL of raw water required to produce this.
 - 9 Non-recovered tailings seepage is the difference between the hydrocyclone underflow discharge and calculated seepage recovery.
This value calculated from modelling water recovery from the re-deposited and/or underlying Superficial sand for the tailings water.
It is assumed that processing occurs for 7,100 hrs per year and that only 20% of the slimes water is recovered..
 - 10 All process water dams are nominated to be lined.
 - 11 Assume that all slimes water is not recovered, and that which is not evaporated is retained or lost to seepage. Quantity of water discharged based on the consumption of 233 kL/hr of water per plant and that 20 % of this is recovered by decant, and no seepage water is recovered.
 - 12 Difference between the water in (or recovered) and losses from the system.
 - 13 Water requirements for the make-up supply re-calculated on an annual basis to include a 20% factor of safety for hydrogeological and operational uncertainties.

APPENDIX E. Detailed Mine Water Balance Calculations, 1,172 kL/hr With Optimal Drain Configuration

| Mine Northing | Mining Year | Mining Year | Tails Year (approx.) | Duration | Pit Base | Pit Width (or sum) | Floor Sand Thickness | Overall Mine Advance Rate | Tailing Rate | Recovery Rate | Cyclone Underflow | Mine Water Recovered | Make-up Water Lost | Average Make-up Rate | Cumulative Annual Requirements | Average Recovery Rate | Annual Losses | Cumulative Annual Losses | Cumulative Average Annual Recovery | Cumulative Average Annual Losses |
|---------------|-------------|-------------|----------------------|----------|------------|--------------------|----------------------|---------------------------|--------------|----------------|-------------------|----------------------|--------------------|----------------------|--------------------------------|-----------------------|---------------|--------------------------|------------------------------------|----------------------------------|
| | (years) | (calendar) | (years) | Days | (av. m RL) | (m) | (m) | (m/d) | (m/d) | % | (kL/d) | (kL) | (kL) | (kL/d) | (kL) | % | (kL) | (kL) | % | (kL) |
| | Formulae: | B | C | D | E | F | G | H = diff A / D | I = F / D | J = (modelled) | K = D x 19,680 | L = J x K | M = K - L | N = M / D | O = sum N | P = ann. average | | | | |
| 7,033,000 | 0.11 | 2,006.91 | 2,007.41 | 182.5 | 72.3 | 700 | 0 | 0.7 | | | | | | | | | | | | |
| 7,033,125 | 0.18 | 2,006.98 | 2,007.48 | 26.4 | 69.0 | 70 | 0 | 4.7 | 2.6 | 93% | 520,434 | 484,004 | 36,430 | 1,378 | 36,430 | | | | | |
| 7,033,250 | 0.21 | 2,007.01 | 2,007.51 | 10.3 | 69.5 | 750 | 0 | 12.1 | 72.6 | 59% | 203,350 | 120,221 | 83,129 | 8,045 | 119,559 | | | | | |
| 7,033,375 | 0.26 | 2,007.06 | 2,007.56 | 20.8 | 69.0 | 750 | 0 | 6.0 | 36.0 | 65% | 410,313 | 268,637 | 141,676 | 6,795 | 261,235 | | | | | |
| 7,033,500 | 0.31 | 2,007.11 | 2,007.61 | 18.5 | 69.5 | 800 | 0 | 6.8 | 43.3 | 65% | 363,970 | 238,296 | 125,674 | 6,795 | 386,909 | | | | | |
| 7,033,625 | 0.37 | 2,007.17 | 2,007.67 | 22.0 | 67.0 | 800 | 0 | 5.7 | 36.4 | 65% | 432,446 | 283,128 | 149,318 | 6,795 | 536,227 | | | | | |
| 7,033,750 | 0.37 | 2,007.17 | 2,007.67 | 0.0 | | | | | | | | | | | 536,227 | | | | | |
| 7,033,875 | 0.37 | 2,007.17 | 2,007.67 | 0.0 | | | | | | | | | | | 536,227 | | | | | |
| 7,034,000 | 0.41 | 2,007.21 | 2,007.71 | 11.6 | 75.0 | 1,100 | 0 | 10.8 | 94.8 | 59% | 228,464 | 135,068 | 93,396 | 8,045 | 629,623 | | | | | |
| 7,034,125 | 0.49 | 2,007.29 | 2,007.79 | 31.6 | 70.7 | 1,000 | 0 | 4.0 | 31.6 | 73% | 622,154 | 454,456 | 167,698 | 5,305 | 797,321 | | | | | |
| 7,034,250 | 0.55 | 2,007.35 | 2,007.85 | 19.8 | 71.5 | 900 | 0 | 6.3 | 45.5 | 65% | 388,903 | 254,620 | 134,283 | 6,795 | 931,604 | | | | | |
| 7,034,375 | 0.63 | 2,007.43 | 2,007.93 | 29.0 | 70.0 | 800 | 0 | 4.3 | 27.6 | 73% | 570,662 | 416,843 | 153,819 | 5,305 | 1,085,423 | | | | | |
| 7,034,500 | 0.71 | 2,007.51 | 2,008.01 | 31.9 | 71.3 | 600 | 0 | 3.9 | 18.8 | 73% | 627,575 | 458,416 | 169,159 | 5,305 | 1,254,582 | | | | | |
| 7,034,625 | 0.76 | 2,007.56 | 2,008.06 | 16.5 | 71.3 | 550 | 0 | 7.6 | 33.3 | 73% | 325,034 | 237,423 | 87,611 | 5,305 | 1,342,193 | | | | | |
| 7,034,750 | 0.76 | 2,007.56 | 2,008.06 | 0.0 | | | | | | | | | | | 1,342,193 | | | | | |
| 7,034,875 | 0.82 | 2,007.62 | 2,008.12 | 23.7 | 67.0 | 450 | 1 | 5.3 | 19.0 | 70% | 465,509 | 325,142 | 140,367 | 5,934 | 1,482,561 | | | | | |
| 7,035,000 | 0.86 | 2,007.66 | 2,008.16 | 14.5 | 71.3 | 450 | 1 | 8.6 | 31.1 | 70% | 285,015 | 199,073 | 85,942 | 5,934 | 1,568,502 | | | | | |
| 7,035,125 | 0.90 | 2,007.70 | 2,008.20 | 14.9 | 68.5 | 450 | 1 | 8.4 | 30.2 | 70% | 293,416 | 204,941 | 88,475 | 5,934 | 1,656,978 | | | | | |
| 7,035,250 | 0.92 | 2,007.72 | 2,008.22 | 7.2 | 69.0 | 450 | 1 | 17.2 | 62.1 | 53% | 142,643 | 74,895 | 67,748 | 9,347 | 1,724,726 | | | | | |
| 7,035,375 | 0.95 | 2,007.75 | 2,008.25 | 8.1 | 72.0 | 450 | 1 | 15.4 | 55.6 | 53% | 159,265 | 83,622 | 75,643 | 9,347 | 1,800,369 | | | | | |
| 7,035,500 | 0.99 | 2,007.79 | 2,008.29 | 17.2 | 71.3 | 450 | 1 | 7.3 | 26.2 | 70% | 338,495 | 236,427 | 102,068 | 5,934 | 1,902,437 | | | | | |
| 7,035,625 | 1.03 | 2,007.83 | 2,008.33 | 12.9 | 70.5 | 500 | 1 | 9.7 | 38.8 | 61% | 253,577 | 153,995 | 99,582 | 7,728 | 2,002,019 | 67% | 2,002,019 | 2,002,019 | 67% | 2,002,019 |
| 7,035,750 | 1.06 | 2,007.86 | 2,008.36 | 12.4 | 72.0 | 700 | 1 | 10.1 | 56.6 | 53% | 243,279 | 127,734 | 115,545 | 9,347 | 115,545 | | | | | |
| 7,035,875 | 1.10 | 2,007.90 | 2,008.40 | 12.8 | 75.0 | 900 | 1 | 9.7 | 70.1 | 53% | 252,493 | 132,572 | 119,922 | 9,347 | 235,467 | | | | | |
| 7,036,000 | 1.17 | 2,007.97 | 2,008.47 | 26.6 | 71.5 | 1,100 | 1 | 4.7 | 41.4 | 61% | 522,602 | 317,372 | 205,230 | 7,728 | 440,697 | | | | | |
| 7,036,125 | 1.24 | 2,008.04 | 2,008.54 | 26.0 | 74.3 | 2,400 | 1 | 4.8 | 92.5 | 53% | 510,768 | 268,179 | 242,589 | 9,347 | 683,287 | | | | | |
| 7,036,250 | 1.57 | 2,008.37 | 2,008.87 | 119.3 | 68.5 | 2,500 | 1 | 1.0 | 20.9 | 70% | 2,348,594 | 1,640,411 | 708,184 | 5,934 | 1,391,470 | | | | | |
| 7,036,375 | 2.01 | 2,008.81 | 2,009.31 | 162.1 | 70.0 | 2,600 | 1 | 0.8 | 16.0 | 70% | 3,190,811 | 2,228,669 | 962,141 | 5,934 | 2,353,612 | 60% | 2,353,612 | 4,355,631 | 63% | 2,177,815 |
| 7,036,500 | 2.28 | 2,009.08 | 2,009.58 | 98.7 | 69.0 | 2,650 | 1 | 1.3 | 13.4 | 84% | 3,886,256 | 3,253,178 | 633,078 | 6,412 | 633,078 | | | | | |
| 7,036,625 | 2.53 | 2,009.33 | 2,009.83 | 91.3 | 69.5 | 2,650 | 1 | 1.4 | 14.5 | 84% | 3,591,638 | 3,006,554 | 585,084 | 6,412 | 1,218,162 | | | | | |
| 7,036,750 | 2.74 | 2,009.54 | 2,010.04 | 76.9 | 69.3 | 2,700 | 1 | 1.6 | 17.6 | 70% | 3,027,481 | 2,114,589 | 912,892 | 11,868 | 2,131,054 | | | | | |
| 7,036,875 | 2.88 | 2,009.68 | 2,010.18 | 48.4 | 72.0 | 2,700 | 1 | 2.6 | 27.9 | 70% | 1,904,405 | 1,330,160 | 574,245 | 11,868 | 2,705,299 | | | | | |
| 7,037,000 | 3.08 | 2,009.88 | 2,010.38 | 75.9 | 71.3 | 2,700 | 1 | 1.6 | 17.8 | 70% | 2,985,745 | 2,085,438 | 900,307 | 11,868 | 3,605,606 | 75% | 3,605,606 | 7,961,236 | 67% | 2,653,745 |
| 7,037,125 | 3.25 | 2,010.05 | 2,010.55 | 58.7 | 71.5 | 2,600 | 1 | 2.1 | 22.1 | 70% | 2,311,646 | 1,614,604 | 697,042 | 11,868 | 697,042 | | | | | |
| 7,037,250 | 3.42 | 2,010.22 | 2,010.72 | 64.2 | 71.8 | 2,500 | 1 | 1.9 | 19.5 | 70% | 2,527,914 | 1,765,659 | 762,255 | 11,868 | 1,459,297 | | | | | |
| 7,037,375 | 3.60 | 2,010.40 | 2,010.90 | 64.8 | 66.0 | 2,400 | 1 | 1.9 | 18.5 | 70% | 2,549,866 | 1,780,992 | 768,874 | 11,868 | 2,228,172 | | | | | |
| 7,037,500 | 3.75 | 2,010.55 | 2,011.05 | 56.2 | 67.3 | 2,300 | 1 | 2.2 | 20.4 | 70% | 2,213,901 | 1,546,332 | 667,569 | 11,868 | 2,895,740 | | | | | |
| 7,037,625 | 3.91 | 2,010.71 | 2,011.21 | 56.3 | 66.7 | 2,200 | 2 | 2.2 | 19.5 | 67% | 2,216,069 | 1,476,953 | 739,117 | 13,128 | 3,634,857 | | | | | |
| 7,037,750 | 3.98 | 2,010.78 | 2,011.28 | 26.0 | 65.5 | 2,100 | 2 | 4.8 | 40.5 | 56% | 1,021,627 | 571,979 | 449,648 | 17,323 | 4,084,505 | 67% | 4,084,505 | 12,045,741 | 67% | 3,011,435 |
| 7,037,875 | 4.12 | 2,010.92 | 2,011.42 | 51.6 | 65.0 | 2,000 | 3 | 2.4 | 19.4 | 62% | 2,029,974 | 1,250,347 | 779,627 | 15,117 | 779,627 | | | | | |
| 7,038,000 | 4.16 | 2,010.96 | 2,011.46 | 15.9 | 61.0 | 1,950 | 3 | 7.9 | 61.3 | 37% | 626,129 | 230,643 | 395,486 | 24,861 | 1,175,113 | | | | | |
| 7,038,125 | 4.21 | 2,011.01 | 2,011.51 | 16.8 | 69.0 | 2,000 | 3 | 7.4 | 59.4 | 37% | 662,987 | 244,220 | 418,767 | 24,861 | 1,593,880 | | | | | |
| 7,038,250 | 4.28 | 2,011.08 | 2,011.58 | 25.6 | 69.3 | 2,100 | 3 | 4.9 | 41.0 | 49% | 1,008,167 | 491,826 | 516,341 | 20,159 | 2,110,220 | | | | | |
| 7,038,375 | 4.39 | 2,011.19 | 2,011.69 | 40.5 | 67.3 | 2,200 | 2 | 3.1 | 27.2 | 67% | 1,592,921 | 1,061,641 | 531,281 | 13,128 | 2,641,501 | | | | | |
| 7,038,500 | 4.52 | 2,011.32 | 2,011.82 | 45.7 | 66.3 | 2,250 | 2 | 2.7 | 24.6 | 67% | 1,796,813 | 1,197,529 | 599,284 | 13,128 | 3,240,785 | | | | | |
| 7,038,625 | 4.57 | 2,011.37 | 2,011.87 | 19.0 | 67.5 | 2,100 | 2 | 6.6 | 55.1 | 46% | 749,711 | 344,041 | 405,670 | 21,298 | 3,646,454 | | | | | |
| 7,038,750 | 4.62 | 2,011.42 | 2,011.92 | 20.7 | 65.0 | 2,000 | 1 | 6.0 | 48.4 | 61% | 813,760 | 494,190 | 319,570 | 15,457 | 3,966,025 | | | | | |
| 7,038,875 | 4.67 | 2,011.47 | 2,011.97 | 16.3 | 66.5 | 1,900 | 1 | 7.7 | 58.4 | 53% | 640,403 | 336,243 | 304,159 | 18,694 | 4,270,184 | | | | | |
| 7,039,000 | 4.67 | 2,011.47 | 2,011.97 | 0.0 | | | | | | | | | | | 4,270,184 | | | | | |
| 7,039,125 | 4.68 | 2,011.48 | 2,011.98 | 3.7 | 71.0 | 350 | 0 | 33.6 | 47.0 | 65% | 146,527 | 95,933 | 50,594 | 13,591 | 4,320,778 | | | | | |
| 7,039,250 | 4.75 | 2,011.55 | 2,012.05 | 24.5 | 64.0 | 400 | 0 | 5.1 | 8.2 | 89% | 965,527 | 859,328 | 106,199 | 4,329 | 4,426,977 | | | | | |
| 7,039,375 | 4.85 | 2,011.65 | 2,012.15 | 38.2 | 64.0 | 400 | 0 | 3.3 | 5.2 | 89% | 1,503,035 | 1,337,715 | 165,320 | 4,329 | 4,592,297 | | | | | |
| 7,039,500 | 4.92 | 2,011.72 | 2,012.22 | 24.5 | 67.0 | 450 | 0 | 5.1 | 9.2 | 89% | 963,991 | 857,961 | 106,030 | 4,329 | 4,698,327 | | | | | |
| 7,039,625 | 5.00 | 2,011.80 | 2,012.30 | 31.6 | 67.7 | 500 | 0 | 4.0 | 7.9 | 89% | 1,241,870 | 1,105,275 | 136,594 | 4,329 | 4,834,922 | 64% | 4,834,922 | 16,880,663 | 67% | 3,376,133 |
| 7,039,750 | 5.12 | 2,011.92 | 2,012.42 | 41.9 | 64.0 | 600 | 0 | 3.0 | 7.2 | 89% | 1,647,937 | 1,466,679 | 181,258 | 4,329 | 181,258 | | | | | |
| 7,039,875 | 5.23 | 2,012.03 | 2,012.53 | 40.8 | 70.5 | 700 | 0 | 3.1 | 8.6 | 89% | 1,604,755 | 1,428,247 | 176,509 | 4,329 | 357,767 | | | | | |
| 7,040,000 | 5.35 | 2,012.15 | 2,012.65 | 42.8 | 66.7 | 850 | 0 | 2.9 | 9.9 | 89% | 1,685,517 | 1,500,126 | 185,392 | 4,329 | 543,158 | | | | | |
| 7,040,125 | 5.52 | 2,012.32 | 2,012.82 | 61.8 | 65.7 | 850 | 2 | 2.0 | 6.9 | 87% | 2,432,337 | 2,107,976 | 324,362 | 5,249 | 867,520 | | | | | |
| 7,040,250 | 5.61 | 2,012.41 | 2,012.91 | 33.8 | 66.0 | 850 | 4 | 3.7 | 12.6 | 77% | 1,331,755 | 1,025,845 | 305,910 | 9,041 | 1,173,430 | | | | | |
| 7,040,375 | 5.70 | 2,012.50 | 2,013.00 | 33.7 | 76.0 | 850 | 6 | 3.7 | 12.6 | 74% | 1,326,245 | 987,867 | 338,377 | 10,042 | 1,511,807 | | | | | |
| 7,040,500 | 5.80 | 2,012.60 | 2,013.10 | 35.8 | 76.5 | 850 | 8 | 3.5 | 11.9 | 74% | 1,410,168 | 1,050,379 | 359,790 | 10,042 | 1,871,597 | | | | | |
| 7,040,625 | 5.89 | 2,012.69 | 2,013.19 | 32.8 | 85.3 | 840 | 8 | 3.8 | 12.8 | 66% | 1,291,013 | | | | | | | | | |

APPENDIX E. Detailed Mine Water Balance Calculations, 1,172 kL/hr With Optimal Drain Configuration

| Mine Northing | Mining Year | Mining Year | Tails Year (approx.) | Duration | Pit Base | Pit Width (or sum) | Floor Sand Thickness | Overall Mine Advance Rate | Tailing Rate | Recovery Rate | Cyclone Underflow | Mine Water Recovered | Make-up Water Lost | Average Make-up Rate | Cumulative Annual Requirements | Average Recovery Rate | Annual Losses | Cumulative Annual Losses | Cumulative Average Annual Recovery | Cumulative Average Annual Losses |
|---------------|-------------|-------------|----------------------|----------|------------|--------------------|----------------------|---------------------------|----------------|---------------|-------------------|----------------------|--------------------|----------------------|--------------------------------|-----------------------|------------------|--------------------------|------------------------------------|----------------------------------|
| | (years) | (calendar) | (years) | Days | (av. m RL) | (m) | (m) | (m/d) | (m/d) | % | (kL/d) | (kL) | (kL) | (kL/d) | (kL) | % | (kL) | (kL) | % | (kL) |
| | A | Formulae: | B | C | D | E | F | G | H = diff A / D | I = F / D | J = (modelled) | K = D x 19,680 | L = J x K | M = K - L | N = M / D | O = sum N | P = ann. average | | | |
| 7,041,000 | 6.05 | 2,012.85 | 2,013.35 | 17.8 | 79.0 | 810 | 8 | 7.0 | 22.8 | 51% | 699,032 | 359,916 | 339,115 | 19,094 | 339,115 | | | | | |
| 7,041,125 | 6.11 | 2,012.91 | 2,013.41 | 21.1 | 80.0 | 780 | 8 | 5.9 | 18.5 | 38% | 831,286 | 312,342 | 518,944 | 24,571 | 858,059 | | | | | |
| 7,041,250 | 6.18 | 2,012.98 | 2,013.48 | 26.4 | 69.7 | 750 | 8 | 4.7 | 14.2 | 66% | 1,038,610 | 684,164 | 354,446 | 13,432 | 1,212,505 | | | | | |
| 7,041,375 | 6.25 | 2,013.05 | 2,013.55 | 25.9 | 73.7 | 700 | 9 | 4.8 | 13.5 | 63% | 1,019,188 | 642,109 | 377,079 | 14,562 | 1,589,583 | | | | | |
| 7,041,500 | 6.30 | 2,013.10 | 2,013.60 | 16.3 | 75.3 | 650 | 9 | 7.7 | 20.0 | 38% | 640,854 | 240,790 | 400,064 | 24,571 | 1,989,647 | | | | | |
| 7,041,625 | 6.33 | 2,013.13 | 2,013.63 | 11.2 | 81.5 | 700 | 9 | 11.2 | 31.2 | 33% | 440,847 | 145,194 | 295,653 | 26,397 | 2,285,300 | | | | | |
| 7,041,750 | 6.35 | 2,013.15 | 2,013.65 | 9.0 | 79.0 | 750 | 9 | 14.0 | 41.9 | 14% | 352,678 | 51,046 | 301,631 | 33,663 | 2,586,932 | | | | | |
| 7,041,875 | 6.39 | 2,013.19 | 2,013.69 | 15.1 | 82.0 | 800 | 9 | 8.3 | 26.5 | 33% | 593,788 | 195,565 | 398,223 | 26,397 | 2,985,155 | | | | | |
| 7,042,000 | 6.46 | 2,013.26 | 2,013.76 | 24.0 | 79.5 | 850 | 9 | 5.2 | 17.7 | 38% | 945,382 | 355,212 | 590,170 | 24,571 | 3,575,325 | | | | | |
| 7,042,125 | 6.50 | 2,013.30 | 2,013.80 | 15.7 | 78.5 | 650 | 7 | 8.0 | 20.8 | 51% | 616,373 | 317,357 | 299,016 | 19,094 | 3,874,341 | | | | | |
| 7,042,250 | 6.53 | 2,013.33 | 2,013.83 | 9.9 | 72.7 | 450 | 5 | 12.7 | 22.8 | 51% | 388,722 | 200,145 | 188,577 | 19,094 | 4,062,918 | | | | | |
| 7,042,375 | 6.55 | 2,013.35 | 2,013.85 | 7.2 | 72.0 | 300 | 4 | 17.4 | 20.9 | 57% | 282,847 | 159,924 | 122,922 | 17,105 | 4,185,840 | | | | | |
| 7,042,500 | 6.59 | 2,013.39 | 2,013.89 | 13.2 | 65.0 | 250 | 4 | 9.5 | 9.5 | 83% | 518,537 | 429,642 | 88,895 | 6,748 | 4,274,736 | | | | | |
| 7,042,625 | 6.62 | 2,013.42 | 2,013.92 | 10.9 | 73.3 | 300 | 4 | 11.5 | 13.8 | 77% | 427,838 | 329,562 | 98,276 | 9,041 | 4,373,012 | | | | | |
| 7,042,750 | 6.71 | 2,013.51 | 2,014.01 | 35.6 | 69.6 | 500 | 4 | 3.5 | 7.0 | 83% | 1,401,044 | 1,160,856 | 240,188 | 6,748 | 4,613,200 | | | | | |
| 7,042,875 | 6.83 | 2,013.63 | 2,014.13 | 42.0 | 69.3 | 1,500 | 3 | 3.0 | 17.9 | 62% | 1,653,447 | 1,018,428 | 635,019 | 15,117 | 5,248,220 | | | | | |
| 7,043,000 | 6.94 | 2,013.74 | 2,014.24 | 42.0 | 68.3 | 1,500 | 3 | 3.0 | 17.9 | 62% | 1,651,460 | 1,017,204 | 634,256 | 15,117 | 5,882,476 | 53% | 5,882,476 | 26,088,055 | 65% | 3,726,865 |
| 7,043,125 | 7.09 | 2,013.89 | 2,014.39 | 55.0 | 68.7 | 1,500 | 3 | 2.3 | 13.6 | 80% | 2,165,209 | 1,722,923 | 442,286 | 8,040 | 442,286 | | | | | |
| 7,043,250 | 7.17 | 2,013.97 | 2,014.47 | 28.8 | 71.8 | 500 | 2 | 4.3 | 8.7 | 87% | 1,134,549 | 983,252 | 151,296 | 5,249 | 593,583 | | | | | |
| 7,043,375 | 7.22 | 2,014.02 | 2,014.52 | 15.6 | 74.0 | 300 | 1 | 8.0 | 9.6 | 88% | 615,650 | 540,742 | 74,908 | 4,789 | 668,490 | | | | | |
| 7,043,500 | 7.22 | 2,014.02 | 2,014.52 | 0.0 | | | | | | | | | | | 668,490 | | | | | |
| 7,043,625 | 7.22 | 2,014.02 | 2,014.52 | 0.0 | | | | | | | | | | | 668,490 | | | | | |
| 7,043,750 | 7.25 | 2,014.05 | 2,014.55 | 12.6 | 75.0 | 300 | 0 | 9.9 | 11.9 | 85% | 495,682 | 422,832 | 72,850 | 5,785 | 741,340 | | | | | |
| 7,043,875 | 7.25 | 2,014.05 | 2,014.55 | 0.0 | | | | | | | | | | | 741,340 | | | | | |
| 7,044,000 | 7.30 | 2,014.10 | 2,014.60 | 16.3 | 71.3 | 350 | 0 | 7.7 | 10.7 | 85% | 642,390 | 547,978 | 94,412 | 5,785 | 835,752 | | | | | |
| 7,044,125 | 7.33 | 2,014.13 | 2,014.63 | 13.3 | 72.3 | 400 | 0 | 9.4 | 15.0 | 85% | 525,042 | 447,877 | 77,165 | 5,785 | 912,917 | | | | | |
| 7,044,250 | 7.35 | 2,014.15 | 2,014.65 | 8.1 | 73.5 | 450 | 0 | 15.4 | 27.7 | 73% | 319,253 | 233,200 | 86,053 | 10,609 | 998,969 | | | | | |
| 7,044,375 | 7.39 | 2,014.19 | 2,014.69 | 12.8 | 61.0 | 500 | 1 | 9.8 | 19.6 | 70% | 502,457 | 350,949 | 151,508 | 11,868 | 1,150,478 | | | | | |
| 7,044,500 | 7.40 | 2,014.20 | 2,014.70 | 3.1 | 70.0 | 500 | 1 | 40.9 | 81.9 | 53% | 120,149 | 63,084 | 57,065 | 18,694 | 1,207,542 | | | | | |
| 7,044,625 | 7.46 | 2,014.26 | 2,014.76 | 23.1 | 64.0 | 500 | 1 | 5.4 | 10.8 | 84% | 908,253 | 760,297 | 147,956 | 6,412 | 1,355,499 | | | | | |
| 7,044,750 | 7.50 | 2,014.30 | 2,014.80 | 13.0 | 62.0 | 500 | 1 | 9.6 | 19.2 | 70% | 511,220 | 357,069 | 154,151 | 11,868 | 1,509,649 | | | | | |
| 7,044,875 | 7.52 | 2,014.32 | 2,014.82 | 8.4 | 75.0 | 550 | 1 | 14.8 | 32.6 | 70% | 331,629 | 231,631 | 99,998 | 11,868 | 1,609,647 | | | | | |
| 7,045,000 | 7.55 | 2,014.35 | 2,014.85 | 9.6 | 81.3 | 550 | 1 | 13.0 | 28.6 | 73% | 378,604 | 276,554 | 102,051 | 10,609 | 1,711,698 | | | | | |
| 7,045,125 | 7.56 | 2,014.36 | 2,014.86 | 7.0 | 81.3 | 550 | 1 | 17.8 | 39.1 | 61% | 276,794 | 168,095 | 108,699 | 15,457 | 1,820,397 | | | | | |
| 7,045,250 | 7.62 | 2,014.42 | 2,014.92 | 20.7 | 69.5 | 500 | 1 | 6.0 | 12.1 | 84% | 816,380 | 683,390 | 132,990 | 6,412 | 1,953,387 | | | | | |
| 7,045,375 | 7.68 | 2,014.48 | 2,014.98 | 22.9 | 69.5 | 450 | 0 | 5.5 | 9.8 | 89% | 900,033 | 801,037 | 98,995 | 4,329 | 2,052,382 | | | | | |
| 7,045,500 | 7.76 | 2,014.56 | 2,015.06 | 26.0 | 68.3 | 400 | 0 | 4.8 | 7.7 | 89% | 1,022,982 | 910,463 | 112,519 | 4,329 | 2,164,901 | | | | | |
| 7,045,625 | 7.83 | 2,014.63 | 2,015.13 | 26.1 | 68.0 | 350 | 0 | 4.8 | 6.7 | 89% | 1,026,415 | 913,518 | 112,896 | 4,329 | 2,277,797 | | | | | |
| 7,045,750 | 7.83 | 2,014.63 | 2,015.13 | 0.0 | | | | | | | | | | | 2,277,797 | | | | | |
| 7,045,875 | 7.83 | 2,014.63 | 2,015.13 | 0.0 | | | | | | | | | | | 2,277,797 | | | | | |
| 7,046,000 | 7.88 | 2,014.68 | 2,015.18 | 18.6 | 65.1 | 200 | 1 | 6.7 | 5.4 | 88% | 731,734 | 642,702 | 89,032 | 4,789 | 2,366,829 | | | | | |
| 7,046,125 | 7.88 | 2,014.68 | 2,015.18 | 0.0 | | | | | | | | | | | 2,366,829 | | | | | |
| 7,046,250 | 7.88 | 2,014.68 | 2,015.18 | 0.0 | | | | | | | | | | | 2,366,829 | | | | | |
| 7,046,375 | 7.88 | 2,014.68 | 2,015.18 | 0.0 | | | | | | | | | | | 2,366,829 | | | | | |
| 7,046,500 | 7.92 | 2,014.72 | 2,015.22 | 16.5 | 62.2 | 300 | 0 | 7.6 | 9.1 | 89% | 650,430 | 578,889 | 71,541 | 4,329 | 2,438,370 | | | | | |
| 7,046,625 | 7.92 | 2,014.72 | 2,015.22 | 0.0 | | | | | | | | | | | 2,438,370 | | | | | |
| 7,046,750 | 7.92 | 2,014.72 | 2,015.22 | 0.0 | | | | | | | | | | | 2,438,370 | | | | | |
| 7,046,875 | 7.92 | 2,014.72 | 2,015.22 | 0.0 | | | | | | | | | | | 2,438,370 | | | | | |
| 7,047,000 | 7.96 | 2,014.76 | 2,015.26 | 14.7 | 59.1 | 700 | 0 | 8.5 | 23.8 | 73% | 578,160 | 422,320 | 155,840 | 10,609 | 2,594,210 | | | | | |
| 7,047,125 | 7.96 | 2,014.76 | 2,015.26 | 0.0 | | | | | | | | | | | 2,594,210 | | | | | |
| 7,047,250 | 7.96 | 2,014.76 | 2,015.26 | 0.0 | | | | | | | | | | | 2,594,210 | | | | | |
| 7,047,375 | 7.96 | 2,014.76 | 2,015.26 | 0.0 | | | | | | | | | | | 2,594,210 | | | | | |
| 7,047,500 | 7.99 | 2,014.79 | 2,015.29 | 10.3 | 56.2 | 650 | 0 | 12.1 | 31.5 | 73% | 406,519 | 296,944 | 109,575 | 10,609 | 2,703,785 | | | | | |
| 7,047,625 | 7.99 | 2,014.79 | 2,015.29 | 0.0 | | | | | | | | | | | 2,703,785 | | | | | |
| 7,047,750 | 7.99 | 2,014.79 | 2,015.29 | 0.0 | | | | | | | | | | | 2,703,785 | | | | | |
| 7,047,875 | 7.99 | 2,014.79 | 2,015.29 | 0.0 | | | | | | | | | | | 2,703,785 | | | | | |
| 7,048,000 | 8.03 | 2,014.83 | 2,015.33 | 12.4 | 64.8 | 1,550 | 3 | 10.1 | 62.5 | 37% | 487,823 | 179,696 | 308,126 | 24,861 | 3,011,911 | 77% | 3,011,911 | 29,099,966 | 67% | 3,637,496 |

APPENDIX E. Detailed Mine Water Balance Calculations, 1,172 kL/hr With Optimal Drain Configuration

| Mine Northing | Mining Year | Mining Year | Tails Year (approx.) | Duration | Pit Base | Pit Width (or sum) | Floor Sand Thickness | Overall Mine Advance Rate | Tailing Rate | Recovery Rate | Cyclone Underflow | Mine Water Recovered | Make-up Water Lost | Average Make-up Rate | Cumulative Annual Requirements | Average Recovery Rate | Annual Losses | Cumulative Annual Losses | Cumulative Average Annual Recovery | Cumulative Average Annual Losses |
|---------------|-------------|-------------|----------------------|----------|------------|--------------------|----------------------|---------------------------|--------------|----------------|-------------------|----------------------|--------------------|----------------------|--------------------------------|-----------------------|---------------|--------------------------|------------------------------------|----------------------------------|
| | (years) | (calendar) | (years) | Days | (av. m RL) | (m) | (m) | (m/d) | (m/d) | % | (kL/d) | (kL) | (kL) | (kL/d) | (kL) | % | (kL) | (kL) | % | (kL) |
| | Formulae: | B | C | D | E | F | G | H = diff A / D | I = F / D | J = (modelled) | K = D x 19,680 | L = J x K | M = K - L | N = M / D | O = sum N | P = ann. average | | | | |
| 7,048,125 | 8.03 | 2,014.83 | 2,015.33 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,048,250 | 8.03 | 2,014.83 | 2,015.33 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,048,375 | 8.03 | 2,014.83 | 2,015.33 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,048,500 | 8.07 | 2,014.87 | 2,015.37 | 15.6 | 64.0 | 1,650 | 4 | 8.0 | 52.9 | 42% | 614,295 | 255,432 | 358,863 | 22,994 | 358,863 | | | | | |
| 7,048,625 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 358,863 | | | | | |
| 7,048,750 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 358,863 | | | | | |
| 7,048,875 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 358,863 | | | | | |
| 7,049,000 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 358,863 | | | | | |
| 7,049,125 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 358,863 | | | | | |
| 7,049,250 | 9.01 | 2,015.81 | 2,016.31 | 344.6 | 66.0 | 1,700 | 5 | 0.4 | 2.5 | 88% | 13,563,761 | 11,898,690 | 1,665,071 | 4,832 | 2,023,934 | 65% | 2,023,934 | 31,123,900 | 67% | 3,458,211 |
| 7,049,375 | 9.01 | 2,015.81 | 2,016.31 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,049,500 | 9.01 | 2,015.81 | 2,016.31 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,049,625 | 9.01 | 2,015.81 | 2,016.31 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,049,750 | 9.75 | 2,016.55 | 2,017.05 | 269.4 | 64.9 | 1,650 | 5 | 0.5 | 3.1 | 88% | 10,601,867 | 9,300,395 | 1,301,473 | 4,832 | 1,301,473 | | | | | |
| 7,049,875 | 9.75 | 2,016.55 | 2,017.05 | 0.0 | | | | | | | | | | | 1,301,473 | | | | | |
| 7,050,000 | 9.75 | 2,016.55 | 2,017.05 | 0.0 | | | | | | | | | | | 1,301,473 | | | | | |
| 7,050,125 | 9.75 | 2,016.55 | 2,017.05 | 0.0 | | | | | | | | | | | 1,301,473 | | | | | |
| 7,050,250 | 10.16 | 2,016.96 | 2,017.46 | 151.0 | 54.6 | 1,300 | 4 | 0.8 | 4.3 | 89% | 5,943,168 | 5,288,815 | 654,353 | 4,334 | 1,955,826 | 78% | 1,955,826 | 33,079,726 | 68% | 3,307,973 |
| Max | | | | | 85.8 | 2,700 | 9 | 40.9 | 94.8 | 93% | | | | 33,663 | | 78% | 5,882,476 | | | |
| Min | | | | | 54.6 | 70 | 0 | 0.4 | 2.5 | 14% | | | | 1,378 | | 53% | 1,955,826 | | | |
| Average | | | | | 70.1 | 1,052 | 2 | 6.9 | 26.5 | 67% | | | | 11,236 | | 68% | 3,307,973 | | | |

Notes: The recovery rates were derived from the numerical modelling using an underflow rate of 1,172 kL/hr.

The floor sand thicknesses were derived directly from the Gunson geological and mine database as at 11 Jan 2005 at 500 or 1,000 m centres. Data for line spacings between have been interpolated from the database or planned mine layout maps.

Appendix E. Summary Calculations for Life-of-Mine Water Balance, 2-Drains Scenario

| Year | Inputs | Outputs* | Period Balance Required from Bores | Annual Bore Water Require- ment |
|--------------------------------------|--------|------------|--|---------------------------------------|
| | kL | kL | kL | kL |
| 1 | 10,595 | 7,939,652 | 7,929,057 | 7,929,057 |
| 2 | 10,595 | 7,939,652 | 7,929,057 | 7,929,057 |
| 3 | 10,595 | 13,911,404 | 13,900,809 | 13,900,809 |
| 4 | 10,595 | 13,911,404 | 13,900,809 | 13,900,809 |
| 5 | 10,595 | 15,261,404 | 15,250,809 | 15,250,809 |
| 5 - 10 | 52,975 | 73,155,965 | 73,102,990 | 14,620,598 |
| 10 - 15 | 52,975 | 72,255,965 | 72,202,990 | 14,440,598 |
| 15 - 20 | 52,975 | 71,355,965 | 71,302,990 | 14,260,598 |
| Average Water Requirement (1 plant) | | | | 7,929,057 |
| Average Water Requirement (2 plants) | | | | 14,395,704 |

APPENDIX E. Annual Water Balance Calculations, 2-Drains Scenario

| | | | Water In | | Water Out | | | | | | | | | | Balance | | |
|--------------------------------|----------------------|------------------|--------------------------|-------------------------|--------------------|----------------------|---------------|---------------------------|-------------------|---------------------------|---------------|------------------------|--------------------|-----------------------|------------------------|--|---|
| Source | | | Direct Rainfall Recharge | Process Water Dams | Evaporation Losses | | | Evapora-tion Losses Total | Dust Suppress-ion | Concen-trate Water Losses | Process Bores | Seepage Losses | | | Seepage Losses (Total) | Total Make-up Process Water Pumpage Required | Estimated Annual Licenced Water Requirement |
| Location | | | Water Dams | Initial Plant Start-ups | Process Water Dam | Slimes Settling Area | Stacker Areas | | | | Camp Supply | Tailings Not Recovered | Process Water Dams | Slimes Settling Areas | | | |
| Notes | | | 1 | 2 | 3 | 4 | 5 | 3 - 5 | 6 | 7 | 8 | 9 | 10 | 11 | 9 - 11 | 12 | 13 |
| Year No. | Operating time (yrs) | Plants Operating | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL | kL |
| 1 | 0.81 | 1 | 10,595 | 900,000 | 224,458 | 26,935 | 11,223 | 262,616 | 182,500 | 170,400 | 131,400 | 4,659,872 | 0 | 1,632,864 | 6,292,736 | 7,929,057 | 7,929,057 |
| 2 | 0.81 | 1 | 10,595 | 900,000 | 224,458 | 26,935 | 11,223 | 262,616 | 182,500 | 170,400 | 131,400 | 4,659,872 | 0 | 1,632,864 | 6,292,736 | 7,929,057 | 7,929,057 |
| 3 | 0.81 | 2 | 10,595 | 0 | 448,916 | 53,870 | 22,446 | 525,232 | 365,000 | 340,800 | 94,900 | 9,319,744 | 0 | 3,265,728 | 12,585,472 | 13,900,809 | 13,900,809 |
| 4 | 0.81 | 2 | 10,595 | 0 | 448,916 | 53,870 | 22,446 | 525,232 | 365,000 | 340,800 | 94,900 | 9,319,744 | 0 | 3,265,728 | 12,585,472 | 13,900,809 | 13,900,809 |
| 5 | 0.81 | 2 | 10,595 | 1,350,000 | 448,916 | 53,870 | 22,446 | 525,232 | 365,000 | 340,800 | 94,900 | 9,319,744 | 0 | 3,265,728 | 12,585,472 | 15,250,809 | 15,250,809 |
| 10 | 4.05 | 2 | 52,975 | 3,600,000 | 2,244,582 | 269,350 | 112,229 | 2,626,161 | 1,825,000 | 1,702,944 | 474,500 | 46,598,720 | 0 | 16,328,640 | 62,927,360 | 73,102,990 | 14,620,598 |
| 15 | 4.05 | 2 | 52,975 | 2,700,000 | 2,244,582 | 269,350 | 112,229 | 2,626,161 | 1,825,000 | 1,702,944 | 474,500 | 46,598,720 | 0 | 16,328,640 | 62,927,360 | 72,202,990 | 14,440,598 |
| 20 | 4.05 | 2 | 52,975 | 1,800,000 | 2,244,582 | 269,350 | 112,229 | 2,626,161 | 1,825,000 | 1,702,944 | 474,500 | 46,598,720 | 0 | 16,328,640 | 62,927,360 | 71,302,990 | 14,260,598 |
| Project Lifetime Totals | | | 211,900 | 11,250,000 | 8,529,412 | 1,023,529 | 426,471 | 9,979,412 | 6,935,000 | 6,472,032 | 1,971,000 | 177,075,136 | 0 | 62,048,832 | 239,123,968 | 275,519,512 | |

- Key Assumptions:
- Tailings discharge cyclones recover 47% of water used for each 2,000 tonnes/hr of ore processed reaching an average solids content of 65%.
 - On average, 44% of the tailings water is recovered
 - Process water bores each yield 3.1 GL/annum (100 L/sec) but only pumped at an average of 75 L.sec (75% up-time) for 2.37 GL/year
 - Processing occurs for 7,100 hrs/year

- Notes:
- 1 Based on the annual mean rainfall data for Hamelin Pool (BoM Stn. No. 006025, Jan 1886-Jul 2004) and annual evaporation data from Hamelin pool (BoM Stn. No. 006025, May 1978-Apr 1980), Nanga Stn. (BoM Stn. No. 006080, May 1980-Apr 1988) and Brickhouse Stn (BoM Stn. No. 6087, Sep 1966-Mar 1977).
Dam surface areas based on there being 1 Ha of water in the process water dam and 4 Ha in the slimes settling area.
 - 2 This value based on filling process water dams (450 ML each) for each plant site move. (Does not include plant recommissioning requirements)
 - 3 Surface area of the process water dams are based on 320 x 320 m dams for each plant. One new dam is allowed for for each new plant site.
Evaporation calculated as 0.72 x pan evaporation figures from BoM as per Ag. Dpet tech Report 65, 1988.
 - 4 Surface area of the slimes dams are based on 2 dams (1 active and 1 inactive) of average size of 200 x 30 m dams for each plant. Two for years 1 and 2, and four dams for years 3 onwards.
Evaporation calculated as 0.72 x pan evaporation figures from BoM as per Ag. Dpet tech Report 65, 1988.
 - 5 It is assumed that the active stacker site will be approx. 50 x 100 m per plant.
 - 6 Dust suppression losses based on half the nominated area of 30,000 m² of watered roads (mine access and internal roads) being constantly wet and subjected to evaporative losses.
An additional average of 500 kL/d has been allowed for dust suppression that is assumed as a total loss.
 - 7 Losses are expected from the system via the concentrate stockpiles at a rate of 24 kL/hr.
 - 8 Camp supply based on nominated number of people as 100 construction personnel, 80 mining personnel in years 1-2 and 130 in years 3 onwards. An average consumption is calculated on the basis of 0.75 kL perperson per day of potable water and that 1.5 kL of raw water required to produce this.
 - 9 Non-recovered tailings seepage is the difference between the hydrocyclone underflow discharge and calculated seepage recovery.
This value calculated from modelling water recovery from the re-deposited and/or underlying Superficial sand for the tailings water.
It is assumed that processing occurs for 7,100 hrs per year and that only 20% of the slimes water is recovered..
 - 10 All process water dams are nominated to be lined.
 - 11 Assume that all slimes water is not recovered, and that which is not evaporated is retained or lost to seepage. Quantity of water discharged based on the consumption of 233 kL/hr of water per plant and that 20 % of this is recovered by decant, and no seepage water is recovered.
 - 12 Difference between the water in (or recovered) and losses from the system.
 - 13 Water requirements for the make-up supply re-calculated on an annual basis to include a 20% factor of safety for hydrogeological and operational uncertainties.

APPENDIX E. Detailed Mine Water Balance Calculations, 1,172 kL/hr With Only 2 Active Drains

| Mine Northing | Mining Year | Mining Year | Tails Year (approx.) | Duration | Pit Base | Pit Width (or sum) | Floor Sand Thickness | Overall Mine Advance Rate | Tailing Rate | Recovery Rate | Cyclone Underflow | Mine Water Recovered | Make-up Water Lost | Average Make-up Rate | Cumulative Annual Requirements | Average Recovery Rate | Annual Losses | Cumulative Annual Losses | Cumulative Average Annual Recovery | Cumulative Average Annual Losses | |
|---------------|-------------|-------------|----------------------|----------|------------|--------------------|----------------------|---------------------------|----------------|---------------|-------------------|----------------------|--------------------|----------------------|--------------------------------|-----------------------|------------------|--------------------------|------------------------------------|----------------------------------|--|
| | (years) | (calendar) | (years) | Days | (av. m RL) | (m) | (m) | (m/d) | (m/d) | % | (kL/d) | (kL) | (kL) | (kL/d) | (kL) | % | (kL) | (kL) | % | (kL) | |
| | A | Formulae: | B | C | D | E | F | G | H = diff A / D | I = F / D | J = (modelled) | K = D x 19,680 | L = J x K | M = K - L | N = M / D | O = sum N | P = ann. average | | | | |
| 7,033,000 | 0.11 | 2,006.91 | 2,007.41 | 182.5 | 72.3 | 700 | 0 | 0.7 | | | | | | | | | | | | | |
| 7,033,125 | 0.18 | 2,006.98 | 2,007.48 | 26.4 | 69.0 | 70 | 0 | 4.7 | 2.6 | 81% | 520,434 | 421,552 | 98,883 | 3,739 | 98,883 | | | | | | |
| 7,033,250 | 0.21 | 2,007.01 | 2,007.51 | 10.3 | 69.5 | 750 | 0 | 12.1 | 72.6 | 30% | 203,350 | 61,005 | 142,345 | 13,776 | 241,227 | | | | | | |
| 7,033,375 | 0.26 | 2,007.06 | 2,007.56 | 20.8 | 69.0 | 750 | 0 | 6.0 | 36.0 | 33% | 410,313 | 135,403 | 274,910 | 13,186 | 516,137 | | | | | | |
| 7,033,500 | 0.31 | 2,007.11 | 2,007.61 | 18.5 | 69.5 | 800 | 0 | 6.8 | 43.3 | 33% | 363,970 | 120,110 | 243,860 | 13,186 | 759,997 | | | | | | |
| 7,033,625 | 0.37 | 2,007.17 | 2,007.67 | 22.0 | 67.0 | 800 | 0 | 5.7 | 36.4 | 33% | 432,446 | 142,707 | 289,739 | 13,186 | 1,049,735 | | | | | | |
| 7,033,750 | 0.37 | 2,007.17 | 2,007.67 | 0.0 | | | | | | | | | | | 1,049,735 | | | | | | |
| 7,033,875 | 0.37 | 2,007.17 | 2,007.67 | 0.0 | | | | | | | | | | | 1,049,735 | | | | | | |
| 7,034,000 | 0.41 | 2,007.21 | 2,007.71 | 11.6 | 75.0 | 1,100 | 0 | 10.8 | 94.8 | 30% | 228,464 | 68,539 | 159,924 | 13,776 | 1,209,660 | | | | | | |
| 7,034,125 | 0.49 | 2,007.29 | 2,007.79 | 31.6 | 70.7 | 1,000 | 0 | 4.0 | 31.6 | 42% | 622,154 | 261,305 | 360,850 | 11,414 | 1,570,509 | | | | | | |
| 7,034,250 | 0.55 | 2,007.35 | 2,007.85 | 19.8 | 71.5 | 900 | 0 | 6.3 | 45.5 | 33% | 388,903 | 128,338 | 260,565 | 13,186 | 1,831,074 | | | | | | |
| 7,034,375 | 0.63 | 2,007.43 | 2,007.93 | 29.0 | 70.0 | 800 | 0 | 4.3 | 27.6 | 42% | 570,662 | 239,678 | 330,984 | 11,414 | 2,162,058 | | | | | | |
| 7,034,500 | 0.71 | 2,007.51 | 2,008.01 | 31.9 | 71.3 | 600 | 0 | 3.9 | 18.8 | 42% | 627,575 | 263,581 | 363,993 | 11,414 | 2,526,052 | | | | | | |
| 7,034,625 | 0.76 | 2,007.56 | 2,008.06 | 16.5 | 71.3 | 550 | 0 | 7.6 | 33.3 | 42% | 325,034 | 136,514 | 188,520 | 11,414 | 2,714,571 | | | | | | |
| 7,034,750 | 0.76 | 2,007.56 | 2,008.06 | 0.0 | | | | | | | | | | | 2,714,571 | | | | | | |
| 7,034,875 | 0.82 | 2,007.62 | 2,008.12 | 23.7 | 67.0 | 450 | 1 | 5.3 | 19.0 | 40% | 465,509 | 183,876 | 281,633 | 11,906 | 2,996,204 | | | | | | |
| 7,035,000 | 0.86 | 2,007.66 | 2,008.16 | 14.5 | 71.3 | 450 | 1 | 8.6 | 31.1 | 40% | 285,015 | 112,581 | 172,434 | 11,906 | 3,168,638 | | | | | | |
| 7,035,125 | 0.90 | 2,007.70 | 2,008.20 | 14.9 | 68.5 | 450 | 1 | 8.4 | 30.2 | 40% | 293,416 | 115,899 | 177,517 | 11,906 | 3,346,155 | | | | | | |
| 7,035,250 | 0.92 | 2,007.72 | 2,008.22 | 7.2 | 69.0 | 450 | 1 | 17.2 | 62.1 | 26% | 142,643 | 36,374 | 106,269 | 14,662 | 3,452,424 | | | | | | |
| 7,035,375 | 0.95 | 2,007.75 | 2,008.25 | 8.1 | 72.0 | 450 | 1 | 15.4 | 55.6 | 26% | 159,265 | 40,613 | 118,652 | 14,662 | 3,571,077 | | | | | | |
| 7,035,500 | 0.99 | 2,007.79 | 2,008.29 | 17.2 | 71.3 | 450 | 1 | 7.3 | 26.2 | 40% | 338,495 | 133,705 | 204,789 | 11,906 | 3,775,866 | | | | | | |
| 7,035,625 | 1.03 | 2,007.83 | 2,008.33 | 12.9 | 70.5 | 500 | 1 | 9.7 | 38.8 | 30% | 253,577 | 74,805 | 178,772 | 13,874 | 3,954,638 | 38% | 3,954,638 | 3,954,638 | 38% | 3,954,638 | |
| 7,035,750 | 1.06 | 2,007.86 | 2,008.36 | 12.4 | 72.0 | 700 | 1 | 10.1 | 56.6 | 26% | 243,279 | 62,036 | 181,243 | 14,662 | 181,243 | | | | | | |
| 7,035,875 | 1.10 | 2,007.90 | 2,008.40 | 12.8 | 75.0 | 900 | 1 | 9.7 | 70.1 | 26% | 252,493 | 64,386 | 188,108 | 14,662 | 369,350 | | | | | | |
| 7,036,000 | 1.17 | 2,007.97 | 2,008.47 | 26.6 | 71.5 | 1,100 | 1 | 4.7 | 41.4 | 30% | 522,602 | 154,168 | 368,435 | 13,874 | 737,785 | | | | | | |
| 7,036,125 | 1.24 | 2,008.04 | 2,008.54 | 26.0 | 74.3 | 2,400 | 1 | 4.8 | 92.5 | 26% | 510,768 | 130,246 | 380,522 | 14,662 | 1,118,307 | | | | | | |
| 7,036,250 | 1.57 | 2,008.37 | 2,008.87 | 119.3 | 68.5 | 2,500 | 1 | 1.0 | 20.9 | 40% | 2,348,594 | 927,695 | 1,420,900 | 11,906 | 2,539,207 | | | | | | |
| 7,036,375 | 2.01 | 2,008.81 | 2,009.31 | 162.1 | 70.0 | 2,600 | 1 | 0.8 | 16.0 | 40% | 3,190,811 | 1,260,370 | 1,930,441 | 11,906 | 4,469,647 | 31% | 4,469,647 | 8,424,285 | 34% | 4,212,143 | |
| 7,036,500 | 2.28 | 2,009.08 | 2,009.58 | 98.7 | 69.0 | 2,650 | 1 | 1.3 | 13.4 | 64% | 3,886,256 | 2,487,204 | 1,399,052 | 14,170 | 1,399,052 | | | | | | |
| 7,036,625 | 2.53 | 2,009.33 | 2,009.83 | 91.3 | 69.5 | 2,650 | 1 | 1.4 | 14.5 | 64% | 3,591,638 | 2,298,649 | 1,292,990 | 14,170 | 2,692,042 | | | | | | |
| 7,036,750 | 2.74 | 2,009.54 | 2,010.04 | 76.9 | 69.3 | 2,700 | 1 | 1.6 | 17.6 | 40% | 3,027,481 | 1,195,855 | 1,831,626 | 23,813 | 4,523,668 | | | | | | |
| 7,036,875 | 2.88 | 2,009.68 | 2,010.18 | 48.4 | 72.0 | 2,700 | 1 | 2.6 | 27.9 | 40% | 1,904,405 | 752,240 | 1,152,165 | 23,813 | 5,675,833 | | | | | | |
| 7,037,000 | 3.08 | 2,009.88 | 2,010.38 | 75.9 | 71.3 | 2,700 | 1 | 1.6 | 17.8 | 40% | 2,985,745 | 1,179,369 | 1,806,376 | 23,813 | 7,482,208 | 49% | 7,482,208 | 15,906,494 | 39% | 5,302,165 | |
| 7,037,125 | 3.25 | 2,010.05 | 2,010.55 | 58.7 | 71.5 | 2,600 | 1 | 2.1 | 22.1 | 40% | 2,311,646 | 913,100 | 1,398,546 | 23,813 | 1,398,546 | | | | | | |
| 7,037,250 | 3.42 | 2,010.22 | 2,010.72 | 64.2 | 71.8 | 2,500 | 1 | 1.9 | 19.5 | 40% | 2,527,914 | 998,526 | 1,529,388 | 23,813 | 2,927,934 | | | | | | |
| 7,037,375 | 3.60 | 2,010.40 | 2,010.90 | 64.8 | 66.0 | 2,400 | 1 | 1.9 | 18.5 | 40% | 2,549,866 | 1,007,197 | 1,542,669 | 23,813 | 4,470,603 | | | | | | |
| 7,037,500 | 3.75 | 2,010.55 | 2,011.05 | 56.2 | 67.3 | 2,300 | 1 | 2.2 | 20.4 | 40% | 2,213,901 | 874,491 | 1,339,410 | 23,813 | 5,810,013 | | | | | | |
| 7,037,625 | 3.91 | 2,010.71 | 2,011.21 | 56.3 | 66.7 | 2,200 | 2 | 2.2 | 19.5 | 37% | 2,216,069 | 819,946 | 1,396,124 | 24,797 | 7,206,137 | | | | | | |
| 7,037,750 | 3.98 | 2,010.78 | 2,011.28 | 26.0 | 65.5 | 2,100 | 2 | 4.8 | 40.5 | 26% | 1,021,627 | 265,623 | 756,004 | 29,126 | 7,962,141 | 37% | 7,962,141 | 23,868,634 | 39% | 5,967,159 | |
| 7,037,875 | 4.12 | 2,010.92 | 2,011.42 | 51.6 | 65.0 | 2,000 | 3 | 2.4 | 19.4 | 34% | 2,029,974 | 683,425 | 1,346,549 | 26,109 | 1,346,549 | | | | | | |
| 7,038,000 | 4.16 | 2,010.96 | 2,011.46 | 15.9 | 61.0 | 1,950 | 3 | 7.9 | 61.3 | 16% | 626,129 | 100,181 | 525,949 | 33,062 | 1,872,498 | | | | | | |
| 7,038,125 | 4.21 | 2,011.01 | 2,011.51 | 16.8 | 69.0 | 2,000 | 3 | 7.4 | 59.4 | 16% | 662,987 | 106,078 | 556,909 | 33,062 | 2,429,407 | | | | | | |
| 7,038,250 | 4.28 | 2,011.08 | 2,011.58 | 25.6 | 69.3 | 2,100 | 3 | 4.9 | 41.0 | 22% | 1,008,167 | 218,436 | 789,730 | 30,832 | 3,219,137 | | | | | | |
| 7,038,375 | 4.39 | 2,011.19 | 2,011.69 | 40.5 | 67.3 | 2,200 | 2 | 3.1 | 27.2 | 37% | 1,592,921 | 589,381 | 1,003,540 | 24,797 | 4,222,678 | | | | | | |
| 7,038,500 | 4.52 | 2,011.32 | 2,011.82 | 45.7 | 66.3 | 2,250 | 2 | 2.7 | 24.6 | 37% | 1,796,813 | 664,821 | 1,131,992 | 24,797 | 5,354,670 | | | | | | |
| 7,038,625 | 4.57 | 2,011.37 | 2,011.87 | 19.0 | 67.5 | 2,100 | 2 | 6.6 | 55.1 | 21% | 749,711 | 157,439 | 592,272 | 31,094 | 5,946,941 | | | | | | |
| 7,038,750 | 4.62 | 2,011.42 | 2,011.92 | 20.7 | 65.0 | 2,000 | 1 | 6.0 | 48.4 | 30% | 813,760 | 240,059 | 573,701 | 27,749 | 6,520,642 | | | | | | |
| 7,038,875 | 4.67 | 2,011.47 | 2,011.97 | 16.3 | 66.5 | 1,900 | 1 | 7.7 | 58.4 | 26% | 640,403 | 163,303 | 477,100 | 29,323 | 6,997,742 | | | | | | |
| 7,039,000 | 4.67 | 2,011.47 | 2,011.97 | 0.0 | | | | | | | | | | | 6,997,742 | | | | | | |
| 7,039,125 | 4.68 | 2,011.48 | 2,011.98 | 3.7 | 71.0 | 350 | 0 | 33.6 | 47.0 | 33% | 146,527 | 48,354 | 98,173 | 26,371 | 7,095,916 | | | | | | |
| 7,039,250 | 4.75 | 2,011.55 | 2,012.05 | 24.5 | 64.0 | 400 | 0 | 5.1 | 8.2 | 73% | 965,527 | 704,835 | 260,692 | 10,627 | 7,356,608 | | | | | | |
| 7,039,375 | 4.85 | 2,011.65 | 2,012.15 | 38.2 | 64.0 | 400 | 0 | 3.3 | 5.2 | 73% | 1,503,035 | 1,097,216 | 405,820 | 10,627 | 7,762,428 | | | | | | |
| 7,039,500 | 4.92 | 2,011.72 | 2,012.22 | 24.5 | 67.0 | 450 | 0 | 5.1 | 9.2 | 73% | 963,991 | 703,714 | 260,278 | 10,627 | 8,022,705 | | | | | | |
| 7,039,625 | 5.00 | 2,011.80 | 2,012.30 | 31.6 | 67.7 | 500 | 0 | 4.0 | 7.9 | 73% | 1,241,870 | 906,565 | 335,305 | 10,627 | 8,358,010 | 40% | 8,358,010 | 32,226,644 | 39% | 6,445,329 | |
| 7,039,750 | 5.12 | 2,011.92 | 2,012.42 | 41.9 | 64.0 | 600 | 0 | 3.0 | 7.2 | 73% | 1,647,937 | 1,202,994 | 444,943 | 10,627 | 444,943 | | | | | | |
| 7,039,875 | 5.23 | 2,012.03 | 2,012.53 | 40.8 | 70.5 | 700 | 0 | 3.1 | 8.6 | 73% | 1,604,755 | 1,171,471 | 433,284 | 10,627 | 878,227 | | | | | | |
| 7,040,000 | 5.35 | 2,012.15 | 2,012.65 | 42.8 | 66.7 | 850 | 0 | 2.9 | 9.9 | 73% | 1,685,517 | 1,230,427 | 455,090 | 10,627 | 1,333,316 | | | | | | |
| 7,040,125 | 5.52 | 2,012.32 | 2,012.82 | 61.8 | 65.7 | 850 | 2 | 2.0 | 6.9 | 71% | 2,432,337 | 1,726,959 | 705,378 | 11,414 | 2,038,694 | | | | | | |
| 7,040,250 | 5.61 | 2,012.41 | 2,012.91 | 33.8 | 66.0 | 850 | 4 | 3.7 | 12.6 | 60% | 1,331,755 | 794,614 | 537,141 | 15,875 | 2,575,836 | | | | | | |
| 7,040,375 | 5.70 | 2,012.50 | 2,013.00 | 33.7 | 76.0 | 850 | 6 | 3.7 | 12.6 | 58% | 1,326,245 | 769,222 | 557,023 | 16,531 | 3,132,858 | | | | | | |

APPENDIX E. Detailed Mine Water Balance Calculations, 1,172 kL/hr With Only 2 Active Drains

| Mine Northing | Mining Year | Mining Year | Tails Year (approx.) | Duration | Pit Base | Pit Width (or sum) | Floor Sand Thickness | Overall Mine Advance Rate | Tailing Rate | Recovery Rate | Cyclone Underflow | Mine Water Recovered | Make-up Water Lost | Average Make-up Rate | Cumulative Annual Requirements | Average Recovery Rate | Annual Losses | Cumulative Annual Losses | Cumulative Average Annual Recovery | Cumulative Average Annual Losses |
|---------------|-------------|-------------|----------------------|----------|------------|--------------------|----------------------|---------------------------|----------------|---------------|-------------------|----------------------|--------------------|----------------------|--------------------------------|-----------------------|------------------|--------------------------|------------------------------------|----------------------------------|
| | (years) | (calendar) | (years) | Days | (av. m RL) | (m) | (m) | (m/d) | (m/d) | % | (kL/d) | (kL) | (kL) | (kL/d) | (kL) | % | (kL) | (kL) | % | (kL) |
| | A | Formulae: | B | C | D | E | F | G | H = diff A / D | I = F / D | J = (modelled) | K = D x 19,680 | L = J x K | M = K - L | N = M / D | O = sum N | P = ann. average | | | |
| 7,041,000 | 6.05 | 2,012.85 | 2,013.35 | 17.8 | 79.0 | 810 | 8 | 7.0 | 22.8 | 27% | 699,032 | 188,739 | 510,293 | 28,733 | 510,293 | | | | | |
| 7,041,125 | 6.11 | 2,012.91 | 2,013.41 | 21.1 | 80.0 | 780 | 8 | 5.9 | 18.5 | 18% | 831,286 | 149,631 | 681,654 | 32,275 | 1,191,947 | | | | | |
| 7,041,250 | 6.18 | 2,012.98 | 2,013.48 | 26.4 | 69.7 | 750 | 8 | 4.7 | 14.2 | 52% | 1,038,610 | 540,077 | 498,533 | 18,893 | 1,690,480 | | | | | |
| 7,041,375 | 6.25 | 2,013.05 | 2,013.55 | 25.9 | 73.7 | 700 | 9 | 4.8 | 13.5 | 50% | 1,019,188 | 509,594 | 509,594 | 19,680 | 2,200,074 | | | | | |
| 7,041,500 | 6.30 | 2,013.10 | 2,013.60 | 16.3 | 75.3 | 650 | 9 | 7.7 | 20.0 | 18% | 640,854 | 115,354 | 525,500 | 32,275 | 2,725,575 | | | | | |
| 7,041,625 | 6.33 | 2,013.13 | 2,013.63 | 11.2 | 81.5 | 700 | 9 | 11.2 | 31.2 | 15% | 440,847 | 66,127 | 374,720 | 33,456 | 3,100,294 | | | | | |
| 7,041,750 | 6.35 | 2,013.15 | 2,013.65 | 9.0 | 79.0 | 750 | 9 | 14.0 | 41.9 | 3% | 352,678 | 11,991 | 340,687 | 38,022 | 3,440,981 | | | | | |
| 7,041,875 | 6.39 | 2,013.19 | 2,013.69 | 15.1 | 82.0 | 800 | 9 | 8.3 | 26.5 | 15% | 593,788 | 89,068 | 504,720 | 33,456 | 3,945,701 | | | | | |
| 7,042,000 | 6.46 | 2,013.26 | 2,013.76 | 24.0 | 79.5 | 850 | 9 | 5.2 | 17.7 | 18% | 945,382 | 170,169 | 775,213 | 32,275 | 4,720,914 | | | | | |
| 7,042,125 | 6.50 | 2,013.30 | 2,013.80 | 15.7 | 78.5 | 650 | 7 | 8.0 | 20.8 | 27% | 616,373 | 166,421 | 449,952 | 28,733 | 5,170,866 | | | | | |
| 7,042,250 | 6.53 | 2,013.33 | 2,013.83 | 9.9 | 72.7 | 450 | 5 | 12.7 | 22.8 | 27% | 388,722 | 104,955 | 283,767 | 28,733 | 5,454,634 | | | | | |
| 7,042,375 | 6.55 | 2,013.35 | 2,013.85 | 7.2 | 72.0 | 300 | 4 | 17.4 | 20.9 | 30% | 282,847 | 85,797 | 197,050 | 27,421 | 5,651,684 | | | | | |
| 7,042,500 | 6.59 | 2,013.39 | 2,013.89 | 13.2 | 65.0 | 250 | 4 | 9.5 | 9.5 | 69% | 518,537 | 357,791 | 160,747 | 12,202 | 5,812,430 | | | | | |
| 7,042,625 | 6.62 | 2,013.42 | 2,013.92 | 10.9 | 73.3 | 300 | 4 | 11.5 | 13.8 | 60% | 427,838 | 255,277 | 172,561 | 15,875 | 5,984,992 | | | | | |
| 7,042,750 | 6.71 | 2,013.51 | 2,014.01 | 35.6 | 69.6 | 500 | 4 | 3.5 | 7.0 | 69% | 1,401,044 | 966,721 | 434,324 | 12,202 | 6,419,315 | | | | | |
| 7,042,875 | 6.83 | 2,013.63 | 2,014.13 | 42.0 | 69.3 | 1,500 | 3 | 3.0 | 17.9 | 34% | 1,653,447 | 556,661 | 1,096,787 | 26,109 | 7,516,102 | | | | | |
| 7,043,000 | 6.94 | 2,013.74 | 2,014.24 | 42.0 | 68.3 | 1,500 | 3 | 3.0 | 17.9 | 34% | 1,651,460 | 555,991 | 1,095,468 | 26,109 | 8,611,570 | 33% | 8,611,570 | 46,513,301 | 41% | 6,644,757 |
| 7,043,125 | 7.09 | 2,013.89 | 2,014.39 | 55.0 | 68.7 | 1,500 | 3 | 2.3 | 13.6 | 61% | 2,165,209 | 1,327,995 | 837,214 | 15,219 | 837,214 | | | | | |
| 7,043,250 | 7.17 | 2,013.97 | 2,014.47 | 28.8 | 71.8 | 500 | 2 | 4.3 | 8.7 | 71% | 1,134,549 | 805,530 | 329,019 | 11,414 | 1,166,233 | | | | | |
| 7,043,375 | 7.22 | 2,014.02 | 2,014.52 | 15.6 | 74.0 | 300 | 1 | 8.0 | 9.6 | 72% | 615,650 | 443,268 | 172,382 | 11,021 | 1,338,615 | | | | | |
| 7,043,500 | 7.22 | 2,014.02 | 2,014.52 | 0.0 | | | | | | | | | | | 1,338,615 | | | | | |
| 7,043,625 | 7.22 | 2,014.02 | 2,014.52 | 0.0 | | | | | | | | | | | 1,338,615 | | | | | |
| 7,043,750 | 7.25 | 2,014.05 | 2,014.55 | 12.6 | 75.0 | 300 | 0 | 9.9 | 11.9 | 65% | 495,682 | 322,193 | 173,489 | 13,776 | 1,512,104 | | | | | |
| 7,043,875 | 7.25 | 2,014.05 | 2,014.55 | 0.0 | | | | | | | | | | | 1,512,104 | | | | | |
| 7,044,000 | 7.30 | 2,014.10 | 2,014.60 | 16.3 | 71.3 | 350 | 0 | 7.7 | 10.7 | 65% | 642,390 | 417,553 | 224,836 | 13,776 | 1,736,940 | | | | | |
| 7,044,125 | 7.33 | 2,014.13 | 2,014.63 | 13.3 | 72.3 | 400 | 0 | 9.4 | 15.0 | 65% | 525,042 | 341,277 | 183,765 | 13,776 | 1,920,705 | | | | | |
| 7,044,250 | 7.35 | 2,014.15 | 2,014.65 | 8.1 | 73.5 | 450 | 0 | 15.4 | 27.7 | 42% | 319,253 | 134,086 | 185,167 | 22,829 | 2,105,872 | | | | | |
| 7,044,375 | 7.39 | 2,014.19 | 2,014.69 | 12.8 | 61.0 | 500 | 1 | 9.8 | 19.6 | 40% | 502,457 | 198,471 | 303,987 | 23,813 | 2,409,858 | | | | | |
| 7,044,500 | 7.40 | 2,014.20 | 2,014.70 | 3.1 | 70.0 | 500 | 1 | 40.9 | 81.9 | 26% | 120,149 | 30,638 | 89,511 | 29,323 | 2,499,369 | | | | | |
| 7,044,625 | 7.46 | 2,014.26 | 2,014.76 | 23.1 | 64.0 | 500 | 1 | 5.4 | 10.8 | 64% | 908,253 | 581,282 | 326,971 | 14,170 | 2,826,340 | | | | | |
| 7,044,750 | 7.50 | 2,014.30 | 2,014.80 | 13.0 | 62.0 | 500 | 1 | 9.6 | 19.2 | 40% | 511,220 | 201,932 | 309,288 | 23,813 | 3,135,628 | | | | | |
| 7,044,875 | 7.52 | 2,014.32 | 2,014.82 | 8.4 | 75.0 | 550 | 1 | 14.8 | 32.6 | 40% | 331,629 | 130,993 | 200,636 | 23,813 | 3,336,264 | | | | | |
| 7,045,000 | 7.55 | 2,014.35 | 2,014.85 | 9.6 | 81.3 | 550 | 1 | 13.0 | 28.6 | 42% | 378,604 | 159,014 | 219,591 | 22,829 | 3,555,854 | | | | | |
| 7,045,125 | 7.56 | 2,014.36 | 2,014.86 | 7.0 | 81.3 | 550 | 1 | 17.8 | 39.1 | 30% | 276,794 | 81,654 | 195,140 | 27,749 | 3,750,994 | | | | | |
| 7,045,250 | 7.62 | 2,014.42 | 2,014.92 | 20.7 | 69.5 | 500 | 1 | 6.0 | 12.1 | 64% | 816,380 | 522,483 | 293,897 | 14,170 | 4,044,891 | | | | | |
| 7,045,375 | 7.68 | 2,014.48 | 2,014.98 | 22.9 | 69.5 | 450 | 0 | 5.5 | 9.8 | 73% | 900,033 | 657,024 | 243,009 | 10,627 | 4,287,900 | | | | | |
| 7,045,500 | 7.76 | 2,014.56 | 2,015.06 | 26.0 | 68.3 | 400 | 0 | 4.8 | 7.7 | 73% | 1,022,982 | 746,777 | 276,205 | 10,627 | 4,564,105 | | | | | |
| 7,045,625 | 7.83 | 2,014.63 | 2,015.13 | 26.1 | 68.0 | 350 | 0 | 4.8 | 6.7 | 73% | 1,026,415 | 749,283 | 277,132 | 10,627 | 4,841,237 | | | | | |
| 7,045,750 | 7.83 | 2,014.63 | 2,015.13 | 0.0 | | | | | | | | | | | 4,841,237 | | | | | |
| 7,045,875 | 7.83 | 2,014.63 | 2,015.13 | 0.0 | | | | | | | | | | | 4,841,237 | | | | | |
| 7,046,000 | 7.88 | 2,014.68 | 2,015.18 | 18.6 | 65.1 | 200 | 1 | 6.7 | 5.4 | 72% | 731,734 | 526,848 | 204,885 | 11,021 | 5,046,122 | | | | | |
| 7,046,125 | 7.88 | 2,014.68 | 2,015.18 | 0.0 | | | | | | | | | | | 5,046,122 | | | | | |
| 7,046,250 | 7.88 | 2,014.68 | 2,015.18 | 0.0 | | | | | | | | | | | 5,046,122 | | | | | |
| 7,046,375 | 7.88 | 2,014.68 | 2,015.18 | 0.0 | | | | | | | | | | | 5,046,122 | | | | | |
| 7,046,500 | 7.92 | 2,014.72 | 2,015.22 | 16.5 | 62.2 | 300 | 0 | 7.6 | 9.1 | 73% | 650,430 | 474,814 | 175,616 | 10,627 | 5,221,738 | | | | | |
| 7,046,625 | 7.92 | 2,014.72 | 2,015.22 | 0.0 | | | | | | | | | | | 5,221,738 | | | | | |
| 7,046,750 | 7.92 | 2,014.72 | 2,015.22 | 0.0 | | | | | | | | | | | 5,221,738 | | | | | |
| 7,046,875 | 7.92 | 2,014.72 | 2,015.22 | 0.0 | | | | | | | | | | | 5,221,738 | | | | | |
| 7,047,000 | 7.96 | 2,014.76 | 2,015.26 | 14.7 | 59.1 | 700 | 0 | 8.5 | 23.8 | 42% | 578,160 | 242,827 | 335,333 | 22,829 | 5,557,071 | | | | | |
| 7,047,125 | 7.96 | 2,014.76 | 2,015.26 | 0.0 | | | | | | | | | | | 5,557,071 | | | | | |
| 7,047,250 | 7.96 | 2,014.76 | 2,015.26 | 0.0 | | | | | | | | | | | 5,557,071 | | | | | |
| 7,047,375 | 7.96 | 2,014.76 | 2,015.26 | 0.0 | | | | | | | | | | | 5,557,071 | | | | | |
| 7,047,500 | 7.99 | 2,014.79 | 2,015.29 | 10.3 | 56.2 | 650 | 0 | 12.1 | 31.5 | 42% | 406,519 | 170,738 | 235,781 | 22,829 | 5,792,852 | | | | | |
| 7,047,625 | 7.99 | 2,014.79 | 2,015.29 | 0.0 | | | | | | | | | | | 5,792,852 | | | | | |
| 7,047,750 | 7.99 | 2,014.79 | 2,015.29 | 0.0 | | | | | | | | | | | 5,792,852 | | | | | |
| 7,047,875 | 7.99 | 2,014.79 | 2,015.29 | 0.0 | | | | | | | | | | | 5,792,852 | | | | | |
| 7,048,000 | 8.03 | 2,014.83 | 2,015.33 | 12.4 | 64.8 | 1,550 | 3 | 10.1 | 62.5 | 16% | 487,823 | 78,052 | 409,771 | 33,062 | 6,202,623 | 54% | 6,202,623 | 52,715,924 | 42% | 6,589,490 |

APPENDIX E. Detailed Mine Water Balance Calculations, 1,172 kL/hr With Only 2 Active Drains

| Mine Northing | Mining Year | Mining Year | Tails Year (approx.) | Duration | Pit Base | Pit Width (or sum) | Floor Sand Thickness | Overall Mine Advance Rate | Tailing Rate | Recovery Rate | Cyclone Underflow | Mine Water Recovered | Make-up Water Lost | Average Make-up Rate | Cumulative Annual Requirements | Average Recovery Rate | Annual Losses | Cumulative Annual Losses | Cumulative Average Annual Recovery | Cumulative Average Annual Losses |
|---------------|-------------|-------------|----------------------|----------|------------|--------------------|----------------------|---------------------------|--------------|-------------------|-------------------|----------------------|--------------------|----------------------|--------------------------------|-----------------------|---------------|--------------------------|------------------------------------|----------------------------------|
| | (years) | (calendar) | (years) | Days | (av. m RL) | (m) | (m) | (m/d) | (m/d) | % | (kL/d) | (kL) | (kL) | (kL/d) | (kL) | % | (kL) | (kL) | % | (kL) |
| | Formulae: | B | C | D | E | F | G | H = diff A / D | I = F / D | J = (modelled) | K = D x 19,680 | L = J x K | M = K - L | N = M / D | O = sum N | P = ann. average | | | | |
| 7,048,125 | 8.03 | 2,014.83 | 2,015.33 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,048,250 | 8.03 | 2,014.83 | 2,015.33 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,048,375 | 8.03 | 2,014.83 | 2,015.33 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,048,500 | 8.07 | 2,014.87 | 2,015.37 | 15.6 | 64.0 | 1,650 | 4 | 8.0 | 52.9 | 17% | 614,295 | 106,478 | 507,817 | 32,538 | 507,817 | | | | | |
| 7,048,625 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 507,817 | | | | | |
| 7,048,750 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 507,817 | | | | | |
| 7,048,875 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 507,817 | | | | | |
| 7,049,000 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 507,817 | | | | | |
| 7,049,125 | 8.07 | 2,014.87 | 2,015.37 | 0.0 | | | | | | | | | | | 507,817 | | | | | |
| 7,049,250 | 9.01 | 2,015.81 | 2,016.31 | 344.6 | 66.0 | 1,700 | 5 | 0.4 | 2.5 | 77% | 13,563,761 | 10,444,096 | 3,119,665 | 9,053 | 3,627,482 | 47% | 3,627,482 | 56,343,406 | 43% | 6,260,378 |
| 7,049,375 | 9.01 | 2,015.81 | 2,016.31 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,049,500 | 9.01 | 2,015.81 | 2,016.31 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,049,625 | 9.01 | 2,015.81 | 2,016.31 | 0.0 | | | | | | | | | | | 0 | | | | | |
| 7,049,750 | 9.75 | 2,016.55 | 2,017.05 | 269.4 | 64.9 | 1,650 | 5 | 0.5 | 3.1 | 77% | 10,601,867 | 8,163,438 | 2,438,429 | 9,053 | 2,438,429 | | | | | |
| 7,049,875 | 9.75 | 2,016.55 | 2,017.05 | 0.0 | | | | | | | | | | | 2,438,429 | | | | | |
| 7,050,000 | 9.75 | 2,016.55 | 2,017.05 | 0.0 | | | | | | | | | | | 2,438,429 | | | | | |
| 7,050,125 | 9.75 | 2,016.55 | 2,017.05 | 0.0 | | | | | | | | | | | 2,438,429 | | | | | |
| 7,050,250 | 10.16 | 2,016.96 | 2,017.46 | 151.0 | 54.6 | 1,300 | 4 | 0.8 | 4.3 | 78% | 5,943,168 | 4,635,671 | 1,307,497 | 8,659 | 3,745,926 | 59% | 3,745,926 | 60,089,332 | 44% | 6,008,933 |
| Max | | | | | 85.8 | 2,700 | 9 | 40.9 | 94.8 | 81% | | | | 38,022 | | 59% | 8,611,570 | | | |
| Min | | | | | 54.6 | 70 | 0 | 0.4 | 2.5 | 3% | | | | 3,739 | | 31% | 3,627,482 | | | |
| Average | | | | | 70.1 | 1,052 | 2 | 6.9 | 26.5 | 44% | | | | 19,185 | | 44% | 6,008,933 | | | |

Notes: The recovery rates were derived from the numerical modelling using an underflow rate of 1,172 kL/hr.

The floor sand thicknesses were derived directly from the Gunson geological and mine database as at 11 Jan 2005 at 500 or 1,000 m centres. Data for line spacings between have been interpolated from the database or planned mine layout maps.

APPENDIX E. Derived Sand Thicknesses and Pit Widths from Mine Database for First 10 Years of Mining

| Northing (m AMG) | Year(s) | Pit 1* Sand Thickness | Adopted Thickness (m) | Pit 1 Width (m) | Pit 2 Sand Thickness | Adopted Thickness (m) | Pit 2 Width (m) | Pit 3 Sand Thickness | Adopted Thickness (m) | Pit 3 Width (m) | Pit 4 Sand Thickness | Adopted Thickness (m) | Pit 4 Width (m) | Pit 5 Sand Thickness | Adopted Thickness (m) | Pit 5 Width (m) | Pit 6 Sand Thickness | Adopted Thickness (m) | Pit 6 Width (m) | Pit 7 Sand Thickness | Adopted Thickness (m) | Pit 7 Width (m) | Pit 8 sand Thickness | Adopted Thickness (m) | Pit 8 Width (m) | Pit 9 Sand Thickness | Adopted Thickness (m) | Pit 9 Width (m) | Average Sand Thickness (m) | Combined Pit Width (m) | No. of Pits |
|------------------|---------|-----------------------|-----------------------|-----------------|----------------------|-----------------------|-----------------|----------------------|-----------------------|-----------------|----------------------|-----------------------|-----------------|----------------------|-----------------------|-----------------|----------------------|-----------------------|-----------------|----------------------|-----------------------|-----------------|----------------------|-----------------------|-----------------|--|-----------------------|-----------------|----------------------------|------------------------|-------------|
| 7,033,000 | 2007.41 | 0 | 0 | 700 | | | | | | | | | | | | | | | | | | | | | | | | 0 | 700 | 1 | |
| 7,033,500 | 2007.61 | 0 | 0 | 400 | 0 | 0 | 400 | | | | | | | | | | | | | | | | | | | | | 0 | 800 | 2 | |
| 7,034,000 | 2007.71 | 0 | 0 | 300 | 0 | 0 | 500 | 0 | 0 | 300 | | | | | | | | | | | | | | | | | | 0 | 1100 | 3 | |
| 7,034,500 | 2008.01 | 0 | 0 | 200 | 0 - 1 | 1 | 300 | 0 | 0 | 100 | | | | | | | | | | | | | | | | | | 0 | 600 | 3 | |
| 7,035,000 | 2008.16 | | | | 1 | 1 | 250 | 0 | 0 | 200 | | | | | | | | | | | | | | | | | | 1 | 450 | 2 | |
| 7,035,500 | 2008.29 | | | | 1 | 1 | 300 | 1 | 1 | 150 | | | | | | | | | | | | | | | | | | 1 | 450 | 2 | |
| 7,036,000 | 2008.47 | | | | 1 | 1 | 650 | 0 | 0 | 450 | | | | | | | | | | | | | | | | | | 1 | 1100 | 2 | |
| 7,036,500 | 2009.58 | | | | 1 | 1 | 450 | 0 | 0 | 2200 | | | | | | | | | | | | | | | | | | 1 | 2650 | 2 | |
| 7,037,000 | 2010.38 | | | | 0 | 0 | 700 | Av 1 - 2 | 2 | 2000 | | | | | | | | | | | | | | | | | | 1 | 2700 | 2 | |
| 7,037,500 | 2011.05 | | | | 0 | 0 | 350 | Av 1 - 2 | 2 | 1950 | | | | | | | | | | | | | | | | | | 1 | 2300 | 2 | |
| 7,038,000 | 2011.46 | | | | 2 | 2 | 150 | Av 3 - 4 | 4 | 1800 | | | | | | | | | | | | | | | | | | 3 | 1950 | 2 | |
| 7,038,500 | 2011.82 | | | | 0 | 0 | 750 | Av 4 | 4 | 1500 | | | | | | | | | | | | | | | | | | 2 | 2250 | 2 | |
| 7,039,000 | 2011.97 | | | | 0 | 0 | 350 | | | | | | | | | | | | | | | | | | | | | 0 | 350 | 1 | |
| 7,039,500 | 2012.22 | | | | | | | | | | 0 | 0 | 350 | 0 | 0 | 100 | | | | | | | | | | | | 0 | 450 | 2 | |
| 7,040,000 | 2012.65 | | | | | | | | | | 0 | 0 | 450 | 0 | 0 | 400 | | | | | | | | | | | | 0 | 850 | 2 | |
| 7,040,500 | 2013.10 | | | | | | | | | | (N.D) | 0 | 700 | 15 | 15 | 150 | | | | | | | | | | | | 8 | 850 | 2 | |
| 7,041,000 | 2013.35 | | | | | | | | | | 0 | 0 | 560 | | | | 10 - 15 | 15 | 250 | | | | | | | | | 8 | 810 | 2 | |
| 7,041,500 | 2013.60 | | | | | | | | | | Av 2 | 2 | 400 | | | | 10 - 15 | 15 | 250 | | | | | | | | | 9 | 650 | 2 | |
| 7,042,000 | 2013.76 | | | | | | | | | | 1 - 2 | 2 | 750 | | | | 15 | 15 | 100 | | | | | | | | | 9 | 850 | 2 | |
| 7,042,500 | 2013.89 | | | | | | | | | | 4 | 4 | 250 | | | | | | | | | | | | | | | 4 | 250 | 1 | |
| 7,043,000 | 2014.24 | | | | | | | | | | 3 | 3 | 1500 | | | | | | | | | | | | | | | 3 | 1500 | 1 | |
| 7,043,500 | 2014.52 | | | | | | | | | | 1 | 1 | 250 | | | | | | | | | | | | | | | 1 | 250 | 1 | |
| 7,044,000 | 2014.60 | | | | | | | | | | 0 | 0 | 350 | | | | | | | | | | | | | | | 0 | 350 | 1 | |
| 7,044,500 | 2014.70 | | | | | | | | | | Av 1 | 1 | 500 | | | | | | | | | | | | | | | 1 | 500 | 1 | |
| 7,045,000 | 2014.85 | | | | | | | | | | 1 | 1 | 400 | | | | | | | 0 | 0 | 150 | | | | | | 1 | 550 | 2 | |
| 7,045,500 | 2015.06 | | | | | | | | | | 0 | 0 | 250 | | | | | | | 0 | 0 | 150 | | | | | | 0 | 400 | 2 | |
| 7,046,000 | 2015.18 | | | | | | | | | | | | | | | | | | | 1 | 1 | 200 | | | | | | 1 | 200 | 1 | |
| 7,046,500 | 2015.22 | | | | | | | | | | | | | | | | | | | 0 | 0 | 300 | | | | | | 0 | 300 | 1 | |
| 7,047,000 | 2015.26 | | | | | | | | | | | | | | | | | | | 0 | 0 | 400 | 0 | 0 | 300 | | | 0 | 700 | 2 | |
| 7,047,500 | 2015.29 | | | | | | | | | | | | | | | | | | | (N.D) | 0 | 350 | (N.D) | 0 | 300 | | | 0 | 650 | 2 | |
| 7,048,000 | 2015.33 | | | | | | | | | | | | | | | | | | | 0 | 0 | 250 | 0 | 0 | 300 | ¹ / ₂ = 0; ¹ / ₂ - Av 15 | 10 | 1000 | 3 | 1550 | 3 |
| 7,048,500 | 2015.37 | | | | | | | | | | | | | | | | | | | (N.D) | 2 | 250 | (N.D) | 2 | 350 | (N.D) | 9 | 1050 | 4 | 1650 | 3 |
| 7,049,000 | 2015.37 | | | | | | | | | | | | | | | | | | | Av 4 | 4 | 250 | Av 4 | 4 | 400 | ¹ / ₂ = 0; ¹ / ₂ - Av 10 | 7 | 1100 | 5 | 1750 | 3 |
| 7,049,500 | 2016.31 | | | | | | | | | | | | | | | | | | | (N.D) | 4 | 200 | (N.D) | 4 | 400 | (N.D) | 6 | 1100 | 5 | 1700 | 3 |
| 7,050,000 | 2017.05 | | | | | | | | | | | | | | | | | | | Av 4 | 4 | 100 | Av 4 | 4 | 350 | ¹ / ₂ = 0; ¹ / ₂ - Av 4 | 4 | 1100 | 4 | 1550 | 3 |

Notes: * - Pit numbers nominal from South and West to North and East
 Av - Average thickness visually averaged off cross sections with 100 m spaced drillholes
 (N.D.) - Not determined. No drillhole data available.